INCH-POUND

A-A-60069
May 30, 2025

COMMERCIAL ITEM DESCRIPTION

JACKET, WELDING

The General Services Administration has authorized the use of this Commercial Item Description (CID) by all federal agencies.

1. SCOPE. This CID covers the requirements for jacket, welding that is part of the Welding Individual Protective Safety (WIPS) ensemble, used by welders across the Department of Defense, and are intended to be used in a shop and combat environment.

2. CLASSIFICATION.

2.1 Size. The Jacket shall be in the following five (5) sizes.

SIZE SCHEDULES

Medium (M), Large, (L), Extra Large, (XL), Extra, Extra Large, (2XL) Extra, Extra, Extra, Large, (3XL)

3. SALIENT CHARACTERISTICS.

3.1 Description. The welding jacket shall be a long-sleeved hoodless jacket with a collar. It shall have a front closure with a minimum of six (6) snaps. The snaps shall have an inner placket on the wearer's right for the male snaps, and the left side shall have female snaps. The placket shall cover the male snap caps, so the snaps do not make contact with the wearer. The item shall have dual layered sleeves with a heavy-duty outer layer for added protection. The sleeves shall utilize a two-piece design that gives the sleeve a natural bend. The sleeve cuffs shall be fitted at the wrist with at least one (1) metal snap closure on each cuff and the snaps shall be covered on the inside of the cuff, so it does not make contact with the wearer. The back side of the jacket shall have a mesh insert to improve ventilation.

Comments, suggestions, or questions on this document should be sent to trpsptctstandardiz@dla.mil. Since contact information can change, verify the currency of the address information using Acquisition Streamlining and Standardization Information System ASSIST online database https://assist.dla.mil.

AMSC N/A FSC 8415

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

3.2 Material.

3.2.1 Base material. The sleeve and body materials shall be in accordance with NFPA 2112 requirements as well as the test methods specified in Table I.

3.2.2 Mesh material. The mesh material shall meet the flame resistant (FR), requirement in Table I.

3.2.3 Color. The color shall be as specified in the contract or purchase order. No color shall be reflective, metallic, or neon.

3.3 Requirements. The finished jacket shall conform to the physical requirements specified in Table I when tested as specified in Table I and conform to the dimensional requirements provided in 3.6.

TABLE I. Physical requirements and test methods.

Characteristic	Requirement	Test Method
Flame resistant Melt/drip Average char length (inches) (maximum) After flame (seconds) (maximum)	 No 6 2	 ASTM D6413/D6413M 1/ 2/
Molten metals 3/ Class (minimum.)	 Class 1 PPE 4/	ISO 9150 5/

1/ Six (6) samples per material (three (3) lengthwise, three (3) widthwise)
2/ Requirement derived from ASTM F1506
3/ Required only for First Article Testing. If material has been previously tested this can be waived.
4/ Requirement derived from ISO 11611.
5/ 10 samples.

3.4 Components.

3.4.1 Thread. The thread used shall be a para-aramid or meta-aramid commercially acceptable thread.

3.4.2 Closures (snaps). The jacket shall fasten at the front with a minimum of six (6) snaps. The closures (snaps) shall be high temperature resistant and shall not become defective if exposed to welding slag.

3.4.3 Mesh. The mesh material shall meet the flame-resistant requirement described in Table I.

3.4.4 Identification label. All components shall have a commercial identification label sewn in. The label shall be in accordance with MIL-DTL-32075, Type VI Class 1. The commercial label shall contain the following information:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

NSN: XXXX-XX-XXX-XXXX
ITEM NAME:
CONTRACT NUMBER:
CONTRACTOR'S NAME:
SIZE:
PART NUMBER:

3.5 Construction.

3.5.1 Stitches, seams and stitching. Commercial standard stitching shall be used throughout the item.

3.6 Finished measurements. The finished jacket shall conform to measurements as specified in Table II.

TABLE II. Sizes and finished measurements, jacket (inches).

Sizes	Back Length 1/	Half Chest 2/	Sleeve Length 3/	Half Sweep 4/
M	30	24	19	24
L	31	25	19-1/2	25
XL	32	26	20	26
2XL	33	27	20-1/2	27
3XL	34	28	21	28
Tolerance	±0.5	±0.5	±0.25	±0.5

1/ Back length - Measure along center back from collar joining seam to bottom edge of jacket.
2/ Half chest - With front snaps fastened and bi-swing facing up and folded in, lay jacket flat on table and measure in line with arm pit of armhole from outside folded edge to opposite outside folded edge.
3/ Sleeve length - Measure along underarm seam from sleeve joining seam to bottom of sleeve (including cuff).
4/ Half sweep - With front snaps fastened and bi-swing facing up and folded in, lay jacket flat on table and measure across bottom outside folded edge to opposite outside folded edge.

3.7 Toxicity. Unless otherwise specified in the contract or procurement documents (see 7.4), the finished jacket shall not present a health hazard and shall show compatibility with prolonged, direct skin contact when tested as specified in 3.7.1.

3.7.1 Toxicity test. When the toxicity requirement (see 3.7) can be demonstrated with historical use data, on the finishing treatments used, toxicity testing may not be required (see 7.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

3.8 Workmanship. The finished jacket shall conform to the quality of the product established in this document. The welding jacket shall be free from defects which would affect serviceability, appearance, useability, uniformity and quality assurance standards defined by the technical data in the procurement documents.

4. REGULATORY REQUIREMENTS. Unless otherwise specified, the offeror/contractor is encouraged to use recovered, recycled, bio based, and environmentally preferable materials to the maximum extent practicable, in accordance with paragraph 23.403, 23.404(b) of the Federal Acquisition Regulation (FAR), or the sustainable acquisition of EO 13693; as applicable. (See 7.1.2 and 7.1.4).

5. PRODUCT CONFORMANCE PROVISIONS.

5.1 Product conformance. The jacket shall meet the salient characteristics of this CID conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance.

5.2 Market acceptability. The finished jacket offered must have been sold to the government or commercial market.

5.3 End item inspection procedures. Sampling for inspection shall be conducted in accordance with ASQ/ANSI Z1.4 - Sampling Procedures and Tables for Inspection of Attributes (see 7.2.1).

5.4 Visual examination. Each finished jacket shall be examined for the defects listed in Table III as defined in ASTM D3990. Defects shall not exceed the acceptance criteria (see 5.5).

TABLE III. Visual examination defects.

Material defects: Any hole, cut, tear, permanent fold, pleat, or crease; any spot or stain on outside, discoloration or color not as specified, any serious material defects or objectionable odor.
Closures: Non-functioning snaps/zippers, missing snaps
Stitches, seams and stitching: Loose or tight stitching tension, broken or skipped stitches, needle chew, any part caught in an unrelated operation or stitching, raw edge, thread ends not removed, any seam slippage, re-stitching, pleating or puckering; distorted, open, pulled or snagged stitches, twisted, ragged or inconsistent edge.
Labels: Label(s) missing, incorrect, or illegible.

5.5 Acceptance criteria. Acceptance criteria shall be as specified in the contract or procurement documents (see 7.4).

6. PACKAGING. The preservation, packing and marking shall be as specified in the contract or order (see 7.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

7. NOTES.

7.1 Source of Government documents:

7.1.1 Copies of Government documents are available online at https://quicksearch.dla.mil.

7.1.2 Federal Acquisition Regulations (FAR) are available online at https://acquisition.gov.

7.1.3 Toxicity testing is outlined in the following references:
Skin Sensitization 406 and Dermal Irritation 404 (https://www.oecd-ilibrary.org/environment/oecd-guidelines-for-the-testing-of-chemicals-section-4-health-effects_20745788?page=1).

Dermal Sensitization (https://www.law.cornell.edu/cfr/text/40/798.4100).
Dermal Toxicity (https://www.law.cornell.edu/cfr/text/40/798.2250).

7.1.4 EPA and EO 13693 information is available online at https://www.epa.gov.

7.2 Source of non-Government documents.

7.2.1 ASQ/ANSI Z1.4 – Sampling Procedures are available online at https://asq.org.

7.2.2 ASTM Standards are available for purchase online at https://www.astm.org.

7.2.3 ISO Standards are available for purchase online at https://www.iso.org.

7.2.4 NFPA 2112 Standards are available for purchase online at https://www.nfpa.org/codes-and-standards/nfpa-2112-standard-development/2112

7.3 Intended use. The jacket, welding is intended to be used by male and female welders across the Department of Defense. Components within the ensemble are intended to be configured in a shop environment.

7.4 Ordering data. Acquisition documents should specify the following

a. Title, number, and date of this CID.
b. Component sizes required (see 2.1).
c. Color required (see 3.2.3).
d. When toxicity testing is required (see 3.7).
e. Product conformance (see 5).
f. Acceptance criteria (see 5.5).
g. Packaging requirements (see 6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

7.5 Key words.

Coat
Combat environment
Protection
Shop environment

7.6 National Stock Number (NSNs) The following NSN and part number have been assigned that correspond to this jacket welding CID. This list may not be indicative of all possible NSNs associated with the CID and are provided for reference only.

NSNs #	Sizes
8415-01-721-8304	M
8415-01-721-8305	L
8415-01-721-8306	XL
8415-01-721-8308	2XL
8415-01-721-8307	3XL

MILITARY INTEREST

Custodians:
Army - GL

CIVIL AGENCY COORDINATING ACTVITY:
GSA-FAS

Preparing Activity
DLA-CT

(Project 8415-2025-008)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.