INCH-POUND

A-A-60070
May 27, 2025

COMMERCIAL ITEM DESCRIPTION

BOOT, SPATS

The General Services Administration has authorized the use of this Commercial Item Description (CID) by all federal agencies.

1. SCOPE. This CID covers the requirements for boot spats that is part of the Welding Individual Protective Safety (WIPS) ensemble, used by welders across the Department of Defense, and are intended to be used in a shop environment.

2. CLASSIFICATION.

2.1 Size. The Boot spats shall be in one size (OS) fits all.

3. SALIENT CHARACTERISTICS.

3.1 Description. The boot spats shall fit over the work boots. The spats shall be donned over the boot. The spats shall be donned with snaps around the ankles and a strap that goes under the sole of the boot and attaches on the other side via a removable connection such as a buckle. The boot spats are there to cover and protect the boot and laces.

3.2 Material.

3.2.1 Base material. The material shall be leather for the body of the boot spat. The strap shall be leather and must be durable. The materials shall be in accordance with the requirements and test methods specified in Table I. The ankle cover and strap of the boot spat shall be made from a 3.0 – 3.5 oz. per square foot split leather. The boot cover of the boot spat shall be made with a 5 – 6 oz. per square foot split leather.

3.2.2 Color. The color shall be as specified in the contract or purchase order. No color shall be reflective, metallic, or neon.

Comments, suggestions, or questions on this document should be sent to trpsptctstandardiz@dla.mil. Since contact information can change, verify the currency of the address information using Acquisition Streamlining and Standardization Information System ASSIST online database https://assist.dla.mil.

AMSC N/A FSC 8415

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

3.3 Requirements. The finished boot spats shall conform to the physical requirements specified in Table I.

TABLE I. Physical requirements and test methods.

Characteristic	Minimum Requirement	Test Method
Flame resistant Melt/drip Average char length (inches) (maximum)	 No 6	 ASTM D6413/D6413M 1/ 2/
Hot air heat resistance Average. dimensional change (%) (maximum.)	 7.6	ASTM F2894 3/
Molten metals 4/ Class (minimum.)	 Class 1 PPE 5/	ISO 9150 6/

1/ Six (6) samples per material (three (3) lengthwise, three (3) widthwise).
2/ Requirement derived from ASTM F1506.
3/ Temperature at 260°C for five (5) minutes. The boot spats will be tested with the modifications per NFPA 2112 Section 8.4.1.2.
4/ Required only for First Article Testing. If material has been previously tested this can be waived.
5/ Requirement derived from ISO 11611.
6/ 10 samples.

3.4 Components.

3.4.1 Thread. The thread used shall be a para-aramid (see 7.5) commercially acceptable thread.

3.4.2 Identification label. All components shall have a commercial identification label sewn in. The label shall be in accordance with MIL-DTL-32075, Type VI, Class 1. The commercial label shall contain the following information:

NSN: XXXX-XX-XXX-XXXX
ITEM NAME:
CONTRACT NUMBER:
CONTRACTOR'S NAME:
PART NUMBER:

3.5 Construction.

3.5.1 Stitches, seams and stitching. The boot spats shall be assembled with materials including but not limited to para-aramid thread (see 7.5) and staple reinforcement.

3.6 Toxicity. Unless otherwise specified in the contract or procurement documents (see 7.4), the finished boot spats shall not present a health hazard and shall show compatibility with prolonged, direct skin contact when tested as specified in 3.6.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

3.6.1 Toxicity test. When the toxicity requirement (see 3.6) can be demonstrated with historical use data, on the finishing treatments used, toxicity testing may not be required (see 7.4).

3.7 Workmanship. The finished boot spats shall conform to the quality of the product established in this document. The welding boot spats shall be free from defects which would affect serviceability, appearance, useability, uniformity and quality assurance standards defined by the technical data in the procurement documents.

4. REGULATORY REQUIREMENTS. Unless otherwise specified, the offeror/contractor is encouraged to use recovered, recycled, bio based, and environmentally preferable materials to the maximum extent practicable, in accordance with paragraph 23.403, 23.404(b) of the Federal Acquisition Regulation FAR, or the sustainable acquisition of EO 13693; as applicable. (See 7.1.2 and 7.1.4).

5. PRODUCT CONFORMANCE PROVISIONS.

5.1 Product conformance. The boot spats shall meet the salient characteristics of this CID conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance.

5.2 Market acceptability. The finished boot spats offered must have been sold to the government or commercial market.

5.3 End item inspection procedures. Sampling for inspection shall be conducted in accordance with ASQ/ANSI Z1.4 - Sampling Procedures and Tables for Inspection of Attributes (see 7.2.1).

5.4 Visual examination. Each finished boot spats shall be examined for the defects listed in Table II as defined in ASTM D3990. Defects shall not exceed the acceptance criteria (see 5.5).

TABLE II Visual examination defects.

Material defects: Any hole, cut, tear, permanent fold, pleat, or crease; any spot or stain on outside, discoloration or color not as specified, any serious material defects or objectionable odor.
Closures: Non-functioning snaps/zippers, missing snaps, wrong length zipper, damaged and not cut hook and loop,
Stitches, seams and stitching: Loose or tight stitching tension, broken or skipped stitches, needle chew, any part caught in an unrelated operation or stitching, raw edge, thread ends not removed, any seam slippage, re-stitching, pleating or puckering; distorted, open, pulled or snagged stitches, twisted, ragged or inconsistent edge.

5.5 Acceptance criteria. Acceptance criteria shall be as specified in the contract or procurement documents (see 7.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

6. PACKAGING. The preservation, packing and marking shall be as specified in the contract or order (see 7.4).

7. NOTES.

7.1 Source of Government documents.

7.1.1 Copies of Government documents are available online at https://quicksearch.dla.mil.

7.1.2 Federal Acquisition Regulations (FAR) are available online at https://acquisition.gov.

7.1.3 Toxicity testing is outlined in the following references:
Skin Sensitization 406 and Dermal Irritation 404 (https://www.oecd-ilibrary.org/environment/oecd-guidelines-for-the-testing-of-chemicals-section-4-health-effects_20745788?page=1).

Dermal Sensitization (https://www.law.cornell.edu/cfr/text/40/798.4100).
Dermal Toxicity (https://www.law.cornell.edu/cfr/text/40/798.2250).

7.1.4 EPA and EO 13834 information is available online at https://www.epa.gov and https://www.fedcenter.gov/programs/eo13693/.

7.2 Source of non-Government documents.

7.2.1 ASQ/ANSI Z1.4 – Sampling Procedures are available online at https://asq.org.

7.2.2 ASTM Standards are available for purchase online at https://www.astm.org.

7.2.3 ISO Standards are available for purchase online at https://www.iso.org.

7.2.4 NFPA Standards are available for purchase online at https://www.nfpa.org.

7.3 Intended use. The boot spats are intended to be used by male and female welders across the Department of Defense. Components within the ensemble are intended to be configured for shop environment.

7.4 Ordering data. Acquisition documents should specify the following

a. Title, number, and date of this CID.
b. Component sizes required (see 2.1).
c. Color required (see 3.2.2).
d. When toxicity testing is required (see 3.6).
e. Product conformance (see 5).
f. Acceptance criteria (see 5.5).
g. Packaging requirements (see 6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

7.5 For this requirement Kevlar® is the para-aramid thread.

7.6 Key words.

Footwear
Leather
Protection
Shop environment
Welding

7.7 National Stock Number (NSN) The following NSN and part number have been assigned that correspond to this boot spats CID. This list may not be indicative of all possible NSNs associated with the CID and are provided for reference only.

NSN #	Size
8415-01-720-7963	(OS)

MILITARY INTEREST

CIVIL AGENCY COORDINATING ACTVITY:
GSA-FAS

Custodians:
Army - GL

Preparing Activity
DLA-CT

(Project 8415-2025-011)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.