INCH-POUND

A-A-60071
May 27, 2025

COMMERCIAL ITEM DESCRIPTION

GLOVES, HEAVY-DUTY

The General Services Administration has authorized the use of this Commercial Item Description (CID) by all federal agencies.

1. SCOPE. This CID covers the requirements for the heavy-duty welding gloves, that is heat resistant and part of the Welding Individual Protective Safety (WIPS) ensemble, used across the Department of Defense, (DoD), and are intended to be used in a shop and combat environment.

2. CLASSIFICATION.

2.1 Size. The heavy-duty welding gloves shall be available in four (4) sizes.

SIZE SCHEDULES

Small - (S), Medium - (M), Large - (L), Extra Large - (XL)

3. SALIENT CHARACTERISTICS.

3.1 Description. The heavy-duty gloves shall be lined and use a Gunn Cut pattern design with a gauntlet cuff style. These gloves incorporate a soft split grain leather that is sewn together with para-aramid thread. The gauntlet shall range between 4.4-inches to 5.4-inches, depending on size when measured with a scientific ruler.

3.2 Materials.

3.2.1 Components. The materials for the heavy-duty welding gloves shall be in accordance with the requirements and test methods specified in Table I.

Comments, suggestions, or questions on this document should be sent to trpsptctstandardiz@dla.mil. Since contact information can change, verify the currency of the address information using Acquisition Streamlining and Standardization Information System ASSIST online database https://assist.dla.mil.

AMSC N/A FSC 8415

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

3.2.2 Main material. The materials for the main body of the heavy-duty glove shall be split cowhide leather or side split leather. The materials shall be in accordance with the requirements listed in Table I. The split cowhide leather shall be between 1.3mm – 1.5mm thick or 3.25 – 3.75 oz. per square foot. The side split leather shall be between 1.5mm – 1.7mm or 3.75 – 4.25 oz. per square foot.

3.2.3 Gauntlet material. The materials for the gauntlet of the heavy-duty gloves shall be split cowhide leather or side split leather. The materials shall be in accordance with the requirements listed in Table I. The split cowhide leather shall be between 2mm – 2.4mm thick or 5 – 6 oz. per square foot. The side split leather shall be between 1.0mm – 1.3mm or 2.5 – 3.25 oz. per square foot.

3.2.4 Heavy-duty liner. The finished insulating fabric liner shall not melt nor drip when exposed to flame or heat. It shall be in accordance with the flame resistance requirements listed in Table I.

3.2.5 Color. The color shall be as specified in the contract or purchase order. No color shall be reflective, metallic, or neon.

3.3 Requirements. The finished heavy-duty welding gloves shall conform to the physical requirements specified in Table I and conform to the dimensional requirements provided in 3.6 when tested as specified in Table I.

TABLE I. Physical requirements and test methods.

Characteristic	Minimum Requirement	Test Method
Main, cuff, and liner material Flame resistance Melt/drip Average char length (inches) (maximum)	 No 6	 ASTM D6413/D6413M 1/ 2/
Main and cuff material Molten metals 3/ Class (minimum.)	 Class 1 PPE 4/	 ISO 9150 5/
Main material Abrasion resistance 3/ Average cycles to failure (cycles) (minimum)	 9,000	 ASTM D3884 6/

1/ Six (6) samples per material (three (3) lengthwise, three (3) widthwise).
2/ Requirement derived from ASTM F1506.
3/ Required only for First Article Testing. If material has been previously tested this can be waived.
4/ Requirement derived from ISO 11611.
5/ 10 samples.
7/ Five (5) samples, no auxiliary weights, vacuum suction of 100, H-18, wheel abrasive wheel (subject to change based on availability), end point is two (2) or more yarns rupture for woven fabrics.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

3.4 Components.

3.4.1 Thread. The gloves heavy duty welding shall be sewn with a commercially acceptable para-aramid thread.

3.4.2 Identification label. All components shall have a commercial identification label sewn in. The label shall be in accordance with MIL-DTL-32075, Type VI, Class 1. The commercial label shall contain the following information:

NSN: XXXX-XX-XXX-XXXX
ITEM NAME:
CONTRACT NUMBER:
CONTRACTOR'S NAME:
SIZE:
PART NUMBER:

3.5 Construction.

3.5.1 Stitches, seams and stitching. The item shall be stitched securely throughout, with consistent stitch lengths.

3.6 Finished measurements. The finished heavy-duty welding gloves shall conform to measurements as provided by the manufacturer.

3.7 Toxicity. Unless otherwise specified in the contract or procurement documents (see 7.4), the finished heavy-duty gloves shall not present a health hazard and shall show compatibility with prolonged, direct skin contact when tested as specified in 3.7.1.

3.7.1 Toxicity test. When the toxicity requirement (see 3.7.) can be demonstrated with historical use data, on the finishing treatments used, toxicity testing may not be required (see 7.1.2 and 7.4).

3.8 Workmanship. The finished heavy-duty gloves shall conform to the quality of the product established in this document. The gloves shall be free from defects which would affect serviceability, appearance, uniformity and quality assurance standards defined by the technical data in the procurement documents.

4. REGULATORY REQUIREMENTS. Unless otherwise specified, the offeror/contractor is encouraged to use recovered, recycled, bio based, and environmentally preferable materials to the maximum extent practicable, in accordance with paragraph 23.403, 23.404(b) of the Federal Acquisition Regulation FAR, or the sustainable acquisition of EO 13693; as applicable. (See 7.1.2 and 7.1.4).

5. PRODUCT CONFORMANCE PROVISIONS.

5.1 Product conformance. The heavy-duty gloves shall meet the salient characteristics of this CID conform to the producer's own drawings, specifications, standards, and quality assurance practices,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

and be the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance.

5.2 Market acceptability. The finished heavy-duty gloves offered must have been sold to the government or commercial market.

5.3 End item inspection procedures. Sampling for inspection shall be conducted in accordance with ANSI/ASQ Z1.4 - Sampling Procedures and Tables for Inspection of Attributes (see 7.2.3).

5.4 Visual examination. Each finished heavy-duty gloves shall be examined for the defects listed in Table II as defined in ASTM D3990. Defects shall not exceed the acceptance criteria (see 5.5).

TABLE II. Visual examination defects.

Material defects: Any hole, cut, tear, permanent fold, pleat, or crease; any spot or stain on outside, discoloration or color not as specified, any serious material defects or objectionable odor.
Stitches, seams and stitching: Loose or heavy-duty gloves stitching tension, broken or skipped stitches, needle chew, any part caught in an unrelated operation or stitching, raw edge, thread ends not removed, any seam slippage, re-stitching, pleating or puckering; distorted, open, pulled or snagged stitches, twisted, ragged or inconsistent edge.
Labels: Label(s) missing, incorrect, or illegible.

5.5 Acceptance criteria. Acceptance criteria shall be as specified in the contract or procurement documents (see 7.4).

6. PACKAGING. The preservation, packing and marking shall be as specified in the contract or order (see 7.4).

7. NOTES.

7.1 Source of Government documents.

7.1.1 Copies of Government documents are available online at https://quicksearch.dla.mil.

7.1.2 Federal Acquisition Regulations (FAR) are available online at https://acquisition.gov.

7.1.3 Toxicity testing is outlined in the following references:
Skin Sensitization 406 and Dermal Irritation 404 (https://www.oecd-ilibrary.org/environment/oecd-guidelines-for-the-testing-of-chemicals-section-4-health-effects_20745788?page=1).

Dermal Sensitization (https://www.law.cornell.edu/cfr/text/40/798.4100).
Dermal Toxicity (https://www.law.cornell.edu/cfr/text/40/798.2250).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

7.1.4 EPA and EO 13834 information is available online at https://www.epa.gov and https://www.fedcenter.gov/programs/eo13693/.

7.2 Source of non-Government documents.

7.2.2 ASQ/ANSI Z1.4– – Sampling Procedures are available online at https://asq.org.

7.2.3 ASTM Standards are available for purchase online at https://www.astm.org.

7.2.4 ISO Standards are available for purchase online at https://www.iso.org.

7.2.5 NFPA 2112 Standards are available for purchase online at https://www.nfpa.org.

7.3 Intended use. The heavy-duty welding gloves are intended to be used by welders across the Department of Defense. Components within the ensemble are intended to be configured for two (2) use cases: shop environment and combat environment.

7.4 Ordering data. Acquisition documents should specify the following.

a. Title, number, and date of this CID.
b. Component sizes required (see 2.1).
c. Color required (see 3.2.3).
d. When toxicity testing is required (see 3.7).
e. Product conformance (see 5.1).
f. Acceptance criteria (see 5.5).
g. Packaging requirements (see 6.).

7.5 Key words.

Combat environment
Handwear
Protection
Shop environment

7.6 National Stock Number (NSNs). The following NSN and part number have been assigned that correspond to this Heavy-Duty Welding Gloves CID. This list may not be indicative of all possible NSNs associated with the CID and are provided for reference only.

NSNs #	Sizes
8415-01-721-2037	S
8415-01-721-2040	M
8415-01-721-2042	L
8415-01-721-2043	XL

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

MILITARY INTEREST

CIVIL AGENCY COORDINATING ACTVITY:
GSA-FAS

Custodians:
Army - GL

Preparing Activity
DLA-CT

(Project 8415-2025-007)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.