INCH-POUND

A-A-60075
May 27, 2025

COMMERCIAL ITEM DESCRIPTION

GLOVES, TUNGSTEN INERT, GAS (TIG), WELDERS GAUNTLET

The General Services Administration has authorized the use of this Commercial Item Description (CID) by all federal agencies.

1. SCOPE. This CID covers the requirements for the gloves, tungsten inert, gas (TIG), welders gauntlet that is part of the Welding Individual Protective Safety (WIPS) ensemble, used by across the Department of Defense, and are intended to be used in a shop or combat environment.

2. CLASSIFICATION.

2.1 Size. The TIG gloves shall be in the following four (4) sizes.

SIZE SCHEDULES

Small (S), Medium (M), Large (L), Extra Large (XL)

3. SALIENT CHARACTERISTICS.

3.1 Description. The TIG gloves shall use a Gunn Cut pattern design with a wing or keystone thumb and a gauntlet cuff style. This glove is based on the type of welding activity that shall be performed and is part of the WIPS ensemble.

3.2 Material.

3.2.1 Base material. The materials for the main body of the TIG gloves shall be light weight deerskin or goatskin, leather construction, heat resistant leather and shall be in accordance with the requirements and test methods specified in Table I. The goatskin leather shall be between 0.6mm – 1.0mm thick or 1.5 – 2.5 oz. per square foot. The deerskin leather shall be between 1.2mm – 1.4mm thick or 3 – 3.5 oz. per square foot.

Comments, suggestions, or questions on this document should be sent to trpsptctstandardiz@dla.mil. Since contact information can change, verify the currency of the address information using Acquisition Streamlining and Standardization Information System ASSIST online database https://assist.dla.mil.

AMSC N/A FSC 8415

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

3.2.2 Gauntlet material. The materials for the gauntlet of the TIG gloves shall be shoulder leather, deerskin leather, goatskin, or pigskin leather. The materials shall be in accordance with the requirements listed in Table I. The shoulder leather shall be between 1.3mm – 1.5mm thick or 3.25 – 3.75 oz. per square foot. The deerskin leather shall be between 1.2mm – 1.4mm thick or 3 – 3.5 oz. per square foot. The goatskin leather shall be between 0.8mm – 0.9mm thick or 2 – 2.25 oz. per square foot. The pigskin leather shall be between 1.4mm – 1.6mm thick or 3.5 – 4 oz. per square foot.

3.2.3 Color. The color shall be as specified in the contract or purchase order. No color shall be reflective, metallic, or neon.

3.3 Requirements. The finished TIG gloves shall conform to the physical requirements and test methods specified in Table I and conform to the dimensional requirements provided in 3.6.

TABLE I. Physical requirements and test methods.

Characteristic	Minimum Requirement	Test Method
Main & gauntlet leather material Flame resistant - Melt/drip - Average char length (inches) (maximum)	 No 6	 ASTM D6413/D6413M 1/ 2/
Main material Molten metals 3/ Class (minimum.)	 Class 1 PPE 4/	 ISO 9150 5/
Dexterity 6/ Average mean time to complete (sec) (maximum)	 60	 ASTM F2010/F2010M

1/ Six (6) samples per material (three (3) lengthwise, three (3) widthwise).
2/ Requirement derived from ASTM F1506.
3/ Required only for First Article Testing. If material has been previously tested this can be waived.
4/ Requirement derived from ISO 11611.
5/ 10 samples.
6/ Only required for First Article Testing.

3.4 Components.

3.4.1 Thread. The thread used shall be sewn with a para-aramid commercially acceptable thread.

3.4.2 Identification label. All components shall have a commercial identification label. The label shall be in accordance with MIL-DTL-32075, Type IV or Type VI and Class 4. The commercial label shall contain the following information:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

- Item description (item name)
- Contract number
- National stock numbers (NSNs)
- Fur, wool or fiber Products Act information
- Contractor's name (bottom label)
- Size

3.5 Construction.

3.5.1 Stitches, seams and stitching. The item shall be stitched securely throughout, with consistent stitch lengths.

3.6 Finished measurements. The finished TIG gloves shall conform to measurements as provided by the manufacturer.

3.7 Toxicity. Unless otherwise specified in the contract or procurement documents (see 7.4), the finished TIG gloves shall not present a health hazard and shall show compatibility with prolonged, direct skin contact when tested as specified in 3.7.1.

3.7.1 Toxicity test. When the toxicity requirement (see 3.7) can be demonstrated with historical use data, on the finishing treatments used, toxicity testing may not be required (see 7.4).

3.8 Workmanship. The finished TIG gloves shall conform to the quality of the product established in this document. The TIG gloves shall be free from defects which would affect serviceability, appearance, uniformity and quality assurance standards defined by the technical data in the procurement documents.

4. REGULATORY REQUIREMENTS. Unless otherwise specified, the offeror/contractor is encouraged to use recovered, recycled, bio based, and environmentally preferable materials to the maximum extent practicable, in accordance with paragraph 23.403, 23.404(b) of the Federal Acquisition Regulation FAR, or the sustainable acquisition of EO 13693; as applicable. (See 7.1.2 and 7.1.4).

5. PRODUCT CONFORMANCE PROVISIONS.

5.1 Product conformance. The TIG gloves shall meet the salient characteristics of this CID conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance.

5.2 Market acceptability. The finished TIG gloves offered must have been sold to the government or commercial market.

5.3 End item inspection procedures. Sampling for inspection shall be conducted in accordance with ASQ/ ANSI Z1.4 - Sampling Procedures and Tables for Inspection of Attributes (see 7.2.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

5.4 Visual examination. Each finished TIG gloves shall be examined for the defects listed in Table II as defined in ASTM D3990. Defects shall not exceed the acceptance criteria (see 5.5).

TABLE II. Visual examination defects.

Material defects: Any hole, cut, tear, permanent fold, crease; any spot or stain on outside, discoloration or color not as specified, any serious material defects or objectionable odor.
Stitches, seams and stitching: Loose or tight stitching tension, broken or skipped stitches, needle chew, any part caught in an unrelated operation or stitching, raw edge, thread ends not removed, any seam slippage, re-stitching, pleating or puckering; distorted, open, pulled or snagged stitches, twisted, ragged or inconsistent edge.
Labels: Label(s) missing, incorrect, or illegible.

5.5 Acceptance criteria. Acceptance criteria shall be as specified in the contract or procurement documents (see 7.4).

6. PACKAGING. The preservation, packing and marking shall be as specified in the contract or order (see 7.4).

7. NOTES.

7.1 Source of Government documents.

7.1.1 Copies of Government documents are available online at https://quicksearch.dla.mil.

7.1.2 Federal Acquisition Regulations (FAR) are available online at https://acquisition.gov.

7.1.3 Toxicity testing is outlined in the following references:
Skin Sensitization 406 and Dermal Irritation 404 (https://www.oecd-ilibrary.org/environment/oecd-guidelines-for-the-testing-of-chemicals-section-4-health-effects_20745788?page=1).

Dermal Sensitization (https://www.law.cornell.edu/cfr/text/40/798.4100).
Dermal Toxicity (https://www.law.cornell.edu/cfr/text/40/798.2250).

7.1.4 EPA and EO 13834 information is available online at https://www.epa.gov and https://www.fedcenter.gov/programs/eo13693/.

7.2 Source of non-Government documents.

7.2.1 ASQ/ANSI Z1.4– Sampling Procedures are available online at https://asq.org.

7.2.2 ASTM Standards are available for purchase online at https://www.astm.org.

7.2.3 ISO Standards are available for purchase online at https://www.iso.org.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

7.2.4 NFPA 2112 Standards are available for purchase online at https://www.nfpa.org/codes-and-standards/nfpa-2112-standard-development/2112

7.3 Intended use. The TIG gloves are intended to be used by welders across the Department of Defense. Components within the ensemble are intended to be configured for a shop and combat environment.

7.4 Ordering data. Acquisition documents should specify the following.

a. Title, number, and date of this CID.
b. Component sizes required (see 2.1).
c. Color required (see 3.2.3).
d. When toxicity testing is required (see 3.7).
e. Product conformance (see 5).
f. Acceptance criteria (see 5.5).
g. Packaging requirements (see 6).

7.5 Key words.
Combat environment
Protection
Shop environment
WIPS

7.6 National Stock Number (NSNs) The following NSNs and part numbers have been assigned that correspond to this TIG gloves CID. This list may not be indicative of all possible NSNs associated with the CID and are provided for reference only.

NSNs #	Sizes
8415-01-721-1140	S
8415-01-721-1141	M
8415-01-721-1142	L
8415-01-721-1143	XL

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

MILITARY INTEREST

CIVIL AGENCY COORDINATING ACTVITY:
GSA-FAS

Custodians:
Army - GL

Preparing Activity
DLA-CT

(Project 8415-2025-013)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.