INCH-POUND
A-A-60082
September 23, 2025

COMMERCIAL ITEM DESCRIPTION

BLAST CLEANING MACHINES – STATIONARY BLAST CLEANING CABINETS AND PORTABLE EXTERNAL VACUUM-BLAST CLEANING

The General Services Administration has authorized the use of this commercial item description by all federal agencies.

1. SCOPE. This specification covers two types of dry Blast Cleaning Machines (BCM) for surface cleaning, conditioning, and peening of ferrous and nonferrous metals using blast media.

2. CLASSIFICATION. The types of machines covered by this specification are of the following types and sizes in Table I:

Table I: BCM Types and Sizes.

Type I	Type II
Blast Cleaning Cabinets, Stationary	External Vacuum-Blast Cleaning, Portable (see 3.2.2 and 3.3.2)
Size A (see 3.2.1 and 3.3.1)	
Size B (see 3.2.1 and 3.3.1)	
Size C (see 3.2.1 and 3.3.1)	

3. SALIENT CHARACTERISTICS.

3.1 BCM description. The BCM is a self-contained, mechanical device consisting of a blast media container and recovery system, filtration system, valves, and attachments. When connected to a reserve volume of air under pressure, a mix of air and blast media may be discharged through a hose and nozzle at high speed against a surface to perform surface cleaning.

3.2 BCM operational requirements. The BCM shall be designed for simplicity of operation and safety to operating personnel and permit easy accessibility of components for normal maintenance and servicing. A pressurized feed shall supply blast media to the blast gun where high pressure air under controlled conditions propels the blast media at high velocity in a uniform and consistent stream to the parts being cleaned. The BCM shall be capable of blasting continuously for a minimum of 7 minutes. Blasting shut-off time required for automatic recharging of the hopper

Beneficial comments, recommendations, additions, deletions, clarifications, and any data that may improve this document should be sent to: AFLCMC/EZSS, 2145 Monahan Way, Area B, Wright-Patterson AFB, OH 45433-7017 or email to engineering.standards@us.af.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

shall not exceed 30 seconds. The machine shall be designed to accommodate engineered media in accordance with MIL-DTL-85891, glass shot in accordance with SAE AMS2431/6, glass beads in accordance with MIL-PRF-9954, steel shot sizes S-110 to S-230 and steel grit sizes G-80 to G-40 in accordance with SAE J444, and aluminum oxide, silicon carbide, garnet, and emery in accordance with A-A-59316. The BCM shall be capable of regulating a pneumatic supply pressure of 125 pounds per square inch gauge (PSIG) to an operating pressure between 20 to 100 PSIG.

3.2.1 Type I BCM operational requirements. The Type I BCM shall allow the operator to direct blast media upon a work piece inside a cabinet, while standing outside the cabinet with arms extended into the cabinet through protective port openings without loss of blast media to the atmosphere.

3.2.2 Type II BCM operational requirements. The Type II BCM shall allow the operator to direct blast media upon a work piece not suitable for cleaning inside a cabinet-type BCM. The Type II BCM shall allow the operator to clean flat, round, cylindrical, and square objects without loss of blast media to the atmosphere.

3.3 Design and construction. The BCM shall be designed and constructed to promote cost-effective, life-cycle sustainability by addressing considerations such as incorporating open standards, while satisfying system performance requirements. The BCM shall be designed and constructed so that subcomponents do not work loose during operation, and able to withstand the strains, jars, vibrations, and other conditions incident to shipping, installation, and service, and prevent the intrusion of blast media and dust into critical operating components.

3.3.1 Type I BCM design requirements. The Type I BCM shall be an enclosed-cabinet design with a recovery system and hopper for removing reusable blast media from the air stream and returning to the hopper, and a pressure vessel in accordance with American Society of Mechanical Engineers (ASME) Boiler & Pressure Vessel Code (BPVC). The recovery system shall consist of an exhaust, filtration, and dust collector system for maintaining a dust-free climate within the cabinet, with dust collection channeled into an enclosed metal dust collector with a High Efficiency Particulate Air (HEPA) filtration system, and reusable blast media channeled into the hopper. The hopper shall support a minimum of 40 pounds of blast media and include a provision for draining the media. The hopper shall automatically gravity feed reusable blast media to the pressure vessel when its pressure is released, which occurs when blasting operation ceases. A magnetic separator shall be included between the hopper and pressure vessel to remove ferrous materials from the reusable media. The pressure vessel shall include an easily accessible clean-out port, automatic sealing plunger, and pneumatic vibrator. The pressure vessel shall supply pressurized air volume and blast media to a blast nozzle when blasting operation begins. Media flow into the blast stream is controlled by a metering valve actuated by a foot pedal. A bypass hose shall remove abrasive from the abrasive feed hose and feed valve and into the hopper when blasting operation ceases. The Type I BCM shall also include a pressure blast nozzle, hose assemblies, and foot pedal with a normally-closed/manually-opened operating valve, built-in blow-off gun for displacing dust residue inside the cabinet, air and blast media operating controls, air pressure regulator and gauge, oil and water separators installed to supply clean and dry air to the regulator, and instructional panel. The cabinet shall be rigidly constructed from 10-gauge steel sheet metal and prevent escape of dust or blast media. The cabinet work floor shall be capable of supporting a 500-pound load

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

with a maximum allowable deflection of ¼ inch. The floor shall be supported within the cabinet in a manner that it is easily removed and replaced. The cabinet shall have two side-loading doors, one on each side, with size and shape maximized to the side profile of the cabinet. An observation window to include safety glass with minimum size of 12-inches x 24-inches shall be located above the arm port openings at a height to permit the operator full view of the area covered by the blast media discharge. The observation window shall tilt outward for quick, tool-free glass changes. The interior of the cabinet shall be illuminated by light-emitting diode (LED) lights. The lights shall provide a light intensity of 2100 to 3200 lumens along the width and center of the cabinet at the work level. The Type I BCM cabinets shall be provided in three optional sizes in Table II:

Table II: Type I BCM Sizes.

	Cabinet Width (feet)	Cabinet Depth (feet)	Cabinet Height (feet)	Door Opening Depth (inches)	Door Opening Height (inches)
Size A	4	3	3	>/= 32	>/= 24
Size B	5	4	3	>/= 42	>/= 30
Size C	6	6	5	>/= 68	>/= 56

3.3.2 Type II BCM design requirements. The Type II BCM shall be a vacuum-blast design to include a recovery system and hopper for removing reusable blast media from the air stream and returning to the hopper, and a pressure vessel in accordance with ASME BPVC. A recovery system shall consist of an exhaust, filtration, and dust collector system for maintaining a dust-free climate, with dust collection channeled into an enclosed metal dust collector with a HEPA filtration system. The hopper shall support a minimum of 5 pounds of media with provision for draining the media. The hopper shall automatically gravity feed reusable blast media to the pressure vessel when its pressure is released, which occurs when blasting operation ceases. A magnetic separator shall be included between the hopper and pressure vessel to remove ferrous materials from the reusable media. The pressure vessel shall include an easily accessible clean-out port, automatic sealing plunger, and pneumatic vibrator. The pressure vessel shall supply pressurized air volume and blast media to a blast gun when blasting operation begins. Media flow into the blast stream is controlled by a metering valve actuated by a foot pedal. A bypass hose shall remove abrasive from the abrasive feed hose and feed valve and into the hopper when blasting operation ceases. The Type II BCM shall include a pressure blast gun with a normally-closed/manually-opened operating valve, easily interchangeable vacuum brush attachments at quantities of 5 each for flat surfaces, inside and outside corners, and small and large diameter pipes; hose assemblies of 20 feet in length, air and blast media operating controls, air pressure regulator and gauge, oil and water separators installed to supply clean and dry air to the regulator, instructional panel, storage location and/or compartment for spare vacuum brush attachments, and mounted on industrial-type casters with safety brake for maneuverability.

3.3.3 Power input.

3.3.3.1 Type I BCM power input. The Type I BCM shall be operable from a 208-230 or 460-volt, 3 phase, 60 Hz power outlet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

3.3.3.2 Type II BCM power input. The Type II BCM shall be operable from a 110/220-volt, single phase, 60 Hz power outlet.

3.3.4 Plugs and connectors. The BCM shall be designed and manufactured to use National Electrical Manufacturers Association (NEMA) plugs and connectors, if applicable, in accordance with NEMA WD 6; covered male inlet plugs are generally preferred. An extension cord of 20 feet in length rated for the current draw shall be included with the BCM.

3.3.5 Finish. The machine shall be finished in accordance with the manufacturer's commercial practice.

3.3.6 Identification and information plates.

3.3.6.1 Identification plate. An identification plate in accordance with MIL-STD-130 shall be securely attached to the BCM in a readily accessible location. The identification plate shall contain the following information:

a. Nomenclature
b. Part identification number (PIN) (see 7.2.1)
c. Manufacturer's name
d. Commercial and Government Entity (CAGE) code
e. Part number
f. In-use (asset) National Stock Number (NSN)
g. Serial number
h. Date of manufacture
i. Date of warranty expiration

3.3.6.2 Item Unique Identification (IUID). The BCM shall have IUID information permanently affixed on or near the respective identification plate(s), marked in accordance with MIL-STD-130. UID information shall be included as both a 2D Data Matrix and human readable markings.

3.3.7 Environment, Safety, and Occupational Health (ESOH).

3.3.7.1 Hazardous material. The design shall minimize and control hazards associated with the inclusion or use of hazardous or toxic materials and the generation of toxic or noxious gases. The BCM shall not generate or use Class I or Class II Ozone Depleting Substances (ODS) during operation, maintenance, or disposal. Class I ODS and hazardous materials shall not be used in any system, component, or process. Hazardous materials are defined in AFI 32-7086; Class I and Class II ODS are defined in 40CFR82.

3.3.7.2 Component protection. All space in which work is performed during operation, service, and maintenance shall be free of hazardous protrusions, sharp edges, or other features which may cause injury to personnel.

3.3.7.3 Noise. The design shall ensure that noise created by the BCM is compatible with the environment and minimize exposure of personnel to noise hazards during operation and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

maintenance activities. The noise level exposure to the operator shall not exceed 84 A-weighted decibels (dB(A)). Where steady-state noise levels are 85 dB(A) or greater at locations specified in A.5.5.4.4.4 of MIL-STD-1474, the contractor shall provide a hazardous noise warning plate stating that operator's hearing protection is required when operating the BCM. The plate shall be made of corrosion-resistant material and shall measure a minimum of 4.00 inches x 4.00 inches. It shall have black lettering on a yellow background and shall be located in an area visible to the operator.

3.3.7.4 Electrostatic discharge (ESD). The design of the BCM shall preclude equipment damage due to ESD, protect personnel from electrical shock due to static charging, and prevent ignition of explosive atmospheres due to sparking.

3.3.8 Human systems integration. The BCM shall be designed in accordance with MIL-STD-1472 for ease of operation, inspection, and maintenance.

3.3.9 Fastening devices. All screws, bolts, nuts, pins, and other fastening devices shall be properly designed, manufactured, and installed with adequate means of preventing loss of torque or adjustment. Cotter pins, lock washers, or nylon patches shall not be used for this purpose, except for the attachment of trim items or as provided in commercial components (see 7.3.1). Tapped threads shall have a minimum thread engagement in accordance with Table III.

TABLE III. Minimum thread engagement.

Material	Minimum Thread Engagement
Steel	1.0 times the nominal fastener diameter
Cast iron, brass, or bronze	1.5 times the nominal fastener diameter
Aluminum, zinc, or plastic	2.0 times the nominal fastener diameter

3.3.10 Welders and welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface parts to be welded shall be free from rust, scale, paint, grease, and other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the welded parts. Welds shall transmit stress without cracking or permanent distortion when the parts connected by the welds are subjected to test, proof, and service loadings.

3.4 Environmental conditions.

3.4.1 Operating environment. The Class I BCM shall be operated inside a building and protected from outside environmental elements. The Class II BCM shall be operated both inside and outside.

3.4.2 Storage environment. The Class I and II BCMs shall be stored inside a building and protected from outside environmental elements.

3.5 Weight and dimensions. Overall weight and dimensions in air transport configuration (see 3.6.2) shall not exceed the values in Table IV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

TABLE IV. Max weight and dimensions.

	Type I	Type II
Length	88 inches.	88 inches.
Width	108 inches.	108 inches.
Height	90 inches.	90 inches.

3.6 Transportability.

3.6.1 Surface transportability. The BCM shall be transportable via all modes of surface shipment (highway, rail, and water) in accordance with MIL-STD-1366, and shall be capable of withstanding the mechanical shock and vibration characteristics of highway, rail, and water transport, except that design for rail impact testing (see 5.2.5 of MIL-STD-1366) is not required.

3.6.2 Air transportability. The BCM shall be transportable as palletized cargo in accordance with MIL-STD-1791. In all air transport configurations, the BCM shall be capable of being restrained and withstanding, without loss of serviceability, 2.0 G up and 4.5 G down accelerations, and shall be capable of being restrained and withstanding, without loss of structural integrity, 3.0 G forward, 1.5 G aft, and 1.5 G lateral accelerations. The BCM shall be equipped with pressure relief devices or configured for air transport to prevent any part from becoming a projectile in the event of catastrophic loss of aircraft cabin pressure.

3.7 Maintainability. The BCM shall be designed for maintainability in accordance with 5.9 through 5.9.22.9 of MIL-STD-1472; forces shall not exceed those specified for both males and females.

3.7.1 Inspection and servicing provisions. The BCM shall be designed for serviceability in accordance with 5.9 through 5.9.22.9 of MIL-STD-1472; forces shall not exceed those specified for both males and females. All prior-to-use inspection and servicing shall be accomplishable by one person in a time period not to exceed 30 minutes.

a. Pre-use inspection tasks shall not require tools.
b. Routine service and maintenance shall not require special tools (see 7.3.2).
c. Drain plugs and filters shall be directly accessible from the ground and oriented to have unimpeded drainage to a catch pan.
d. All fill ports shall be accessible from a ground level and offer easy access.

3.7.2 Special tools. The BCM shall be designed to minimize the requirement for special tools (see 7.3.2). All special tools shall be provided with, and stored on, the BCM.

3.8 Service life. The BCM structure, cabinet, and major system components with exception to high-wear expendable items shall be designed for a minimum service life of 15 years. Accomplishment of manufacturer's recommended and defined service tasks and intervals shall maintain output performance in excess of 90% of design through the entire service life.

3.9 Workmanship. The BCM, including all parts and accessories, shall be constructed and finished in a thoroughly workmanlike manner. Workmanship objectives shall include freedom from

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

blemishes, defects, burrs and sharp corners and edges; accuracy of dimensions, surface finish, and radii of fillets; thoroughness of welding, painting, and riveting; marking of parts and assemblies; and proper alignment of parts and tightness of assembly fasteners.

3.9.1 Bolted connections. Bolt holes shall be accurately punched or drilled and shall be deburred. Threaded fasteners shall be tight and shall not work loose during testing or service usage.

3.9.2 Riveted connections. Rivet holes shall be accurately punched or drilled and shall be deburred. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the component.

3.9.3 Gear and lever assemblies. Gear and lever assemblies shall be properly aligned and meshed and shall be operable without interference, tight spots, loose spots, or other irregularities. Where required for accurate adjustment, gear assemblies shall be free of excessive backlash.

3.9.4 Cleaning. The BCM shall be thoroughly cleaned. Loose, spattered, or excess solder; welding slag; stray bolts, nuts, and washers; rust; metal particles; pipe compound; and other foreign matter shall be removed during and after final assembly.

3.10 Equipment training video and material. A complete overview of the BCM controls and function, and BCM operation shall be provided in video format. Training shall provide the necessary skills and knowledge to operate the BCM safely, and include how to properly service and maintain the BCM. Redundant training materials shall be accessible to training participants for a minimum of three (3) years after receipt of the BCM at the installation location.

3.11 Warranty. A minimum one (1) year warranty shall be provided to protect against defects, breaks, or component failures during normal operation. The warranty shall include the replacement and installation of components/assemblies at the installation location by an Original Equipment Manufacturer (OEM)-certified technician. The warranty does not cover consumable items. For equipment located in austere operating environments, an OEM-certified technician may remotely oversee the repair by a Government representative; however, replacement components shall still be provided as part of the warranty.

3.12 Support. Technical support for the BCM shall be provided for a period of three (3) years after the date of purchase. Technical support shall be accessible, at a minimum, via phone and email.

3.13 Technical data.

3.13.1 Technical manuals. The contractor shall supply one (1) electronic copy of the technical manuals containing information necessary for the operation, maintenance, and illustrated parts breakdown (O&M and IPB) for the BCM to the Technical Order Management Office (TOMA) at:

406 SCMS/GUEE
235 BYRON ST BLDG 300 STE 19A
ROBINS AFB GA 31098-1670

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

The contractor shall supply one (1) paper copy of the technical manuals (O&M and IPB) for the BCM to the receiving activity concurrent with BCM delivery.

4. REGULATORY REQUIREMENTS.

4.1 Recycled, recovered, environmentally preferable, or biobased materials. Recycled, recovered, environmentally preferable, or biobased materials should be used to the maximum extent possible, provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with 23.403 of the Federal Acquisition Regulation (FAR). However, used, rebuilt, or refurbished items shall not be provided.

4.2 Green Procurement Program. Green Procurement Program (GPP) is a mandatory federal acquisition program that focuses on the purchase and use of environmentally preferable products and services. GPP requirements apply to all acquisitions using appropriated funds, including services and new requirements. FAR 23.404(b) applies and states the GPP requires 100% of EPA designated product purchase that are included in the Comprehensive Procurement Guidelines list that contains recovered materials, unless the item cannot be acquired: a) competitively within a reasonable timeframe; b) meet appropriate performance standards, or c) at a reasonable price. The prime contractor is responsible for ensuring that all subcontractors comply with this requirement.

5. PRODUCT CONFORMANCE PROVISIONS.

The products provided shall meet the salient characteristics of this Commercial Item Description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace, modified as necessary to comply with the requirements herein. The Government reserves the right to require proof of such conformance.

5.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First production inspection (see 5.2).
b. Conformance inspection (see 5.3).

5.2 First production inspection. The first production BCM shall be subjected to the analyses, certifications, demonstrations, examinations, and tests described in 5.5.1 through 5.5.5. The contractor shall provide or arrange for all test equipment and facilities.

5.3 Conformance inspection. Each production BCM shall be subjected to the examination described in 5.5.1.

5.4 Inspection requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

5.4.1 General inspection requirements. Apparatus used in conjunction with the inspections specified herein shall be laboratory precision type, calibrated at proper intervals to ensure laboratory accuracy.

5.4.2 Data. During all testing specified herein, at least the following data, unless not applicable, shall be recorded at intervals not to exceed 30 minutes. Additional data or shorter intervals shall be provided as appropriate for any specific test.

a. Date.
b. Time started.
c. Time finished.
d. Ambient temperature.
e. Ambient humidity.

5.4.3 Test rejection criteria. Throughout all tests specified herein, the BCM shall be closely observed for the following conditions, which shall be cause for rejection.

a. Failure to conform to design or performance requirements specified herein.
b. Evidence of excessive wear. If excessive wear is suspected, the OEM's specifications or tolerances shall be utilized for making a determination.
c. Evidence of corrosion or deterioration.
d. Misalignment of components.
e. Conditions that present a safety hazard to personnel during operation, servicing, or maintenance.
f. Interference between the BCM components.

5.5 Test methods.

5.5.1 Examination of product. Each BCM shall be examined to verify compliance with the requirements herein prior to accomplishing any other demonstrations or tests listed in 5.5. A contractor-generated, Government-approved checklist (part of the test procedure) shall be used to identify each requirement not verified by an analysis, certification, demonstration, or test, and shall be used to document the examination results. Particular attention shall be given to materials, workmanship, dimensions, surface finishes, protective coatings and sealants and their application, welding, fastening, and markings. Proper operation of each BCM function shall be verified. Certifications and analyses shall be provided in accordance with Table V. Each production BCM shall be inspected to a Government-approved reduced version of the checklist.

TABLE V. Certifications and analyses.

Section 3 Requirement	Verification Method	Section 5 Verification
3.2 BCM operational requirements.	Test.	5.5.2 BCM operational tests.
3.2.1 Type I operational requirements.	Test.	5.5.2.1 Type I BCM operational tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

TABLE V. Certifications and analyses – Continued.

3.2.2 Type II operational requirements.	Test.	5.5.2.2 Type II BCM operational tests.
3.3 Design and construction.	Examination	5.5.1 Examination of product.
3.3.1 Type I design requirements.	Examination.	5.5.1 Examination of product.
3.3.2 Type II design requirements.	Examination.	5.5.1 Examination of product.
3.3.3 Power input.	Examination.	5.5.1 Examination of product.
3.3.3.1 Type I BCM power input.	Examination.	5.5.1 Examination of product.
3.3.3.2 Type II BCM power input.	Examination.	5.5.1 Examination of product.
3.3.4 Plugs and connectors.	Examination.	5.5.1 Examination of product.
3.3.5 Finish.	Examination.	5.5.1 Examination of product.
3.3.6 Identification and information plates.		
3.3.6.1 Identification plate.	Examination.	5.5.1 Examination of product.
3.3.6.2 Item Unique Identification (IUID).	Examination.	5.5.1 Examination of product.
3.3.7 Environment, Safety, and Occupational Health (ESOH).		
3.3.7.1 Hazardous material.	Certification.	5.5.1 Examination of product.
3.3.7.2 Component protection.	Examination.	5.5.1 Examination of product.
3.3.7.3 Noise.	Test.	5.5.3 Noise test.
3.3.7.4 Electrostatic discharge (ESD).	Examination.	5.5.1 Examination of product.
3.3.8 Human systems integration.	Certification.	
3.3.9 Fastening devices.	Examination.	5.5.1 Examination of product.
3.3.10 Welders and welding.	Examination.	5.5.1 Examination of product.
3.4 Environmental conditions.		
3.4.1 Operating environment.	Certification.	5.5.1 Examination of product.
3.4.2 Storage environment.	Certification.	5.5.1 Examination of product.
3.5 Weight and dimensions.	Test and examination.	5.5.4 Weight test.
3.6 Transportability.		
3.6.1 Surface transportability.	Certification.	5.5.1 Examination of product.
3.6.2 Air transportability.	Analysis.	5.5.1 Examination of product.
3.7 Maintainability.	Certification.	5.5.1 Examination of product.
3.7.1 Inspection and servicing provisions.	Certification and demonstration.	5.5.1 Examination of product. 5.5.5 Inspection and servicing demonstration.
3.7.2 Special tools.	Examination.	5.5.1 Examination of product.
3.8 Service life.	Certification.	
3.9 Workmanship.	Examination.	5.5.1 Examination of product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

TABLE V. Certifications and analyses – Continued.

3.9.1 Bolted connections.	Examination.	5.5.1 Examination of product.
3.9.2 Riveted connections.	Examination.	5.5.1 Examination of product.
3.9.3 Gear and lever assemblies.	Examination.	5.5.1 Examination of product.
3.9.4 Cleaning.	Examination.	5.5.1 Examination of product.
3.10 Equipment training video and material.	Examination.	5.5.1 Examination of product.
3.11 Warranty.	Certification.	5.5.1 Examination of product.
3.12 Support.	Certification.	5.5.1 Examination of product.
3.13 Technical data.		
3.13.1 Technical manuals.	Examination.	5.5.1 Examination of product.

5.5.2 BCM operational tests. The first production BCM shall be operationally tested with various blast media as specified in 3.2 and corroded steel test coupons for verification of the requirements in 3.2.

5.5.2.1 Type I BCM operational tests. The first production Type I, Size A, B, and C BCM shall be operationally tested with various blast media as specified in 3.2 and corroded steel test coupons for verification of the requirements in 3.2.1.

5.5.2.2 Type II BCM operational tests. The first production Type II BCM shall be operationally tested with various blast media as specified in 3.2 and corroded steel test coupons for verification of the requirements in 3.2.2.

5.5.3 Noise test. The first production Type I, Size A, B, and C, and Type II BCM shall be tested by measuring the noise level at the operator's ear while operating the BCM (see 3.3.7.3).

5.5.4 Weight test. The first production Type I, Size A, B, and C, and Type II BCM shall be weighed (see 3.5).

5.5.5 Inspection and servicing demonstration. All recommended maintenance tasks shall be performed and the task times shall be recorded. It shall be demonstrated that the forces required do not exceed those allowed in MIL-STD-1472 (see 3.7.1).

6. PACKAGING. Preservation, packing, and marking shall be as specified in the contract or order.

7. NOTES.

7.1 Source of documents.

7.1.1 Department of Defense and Federal documents. Department of Defense and Federal documents are available online at https://quicksearch.dla.mil/.

7.1.2 Air Force Instructions (AFI). Copies of AFIs are available online at https://www.e-publishing.af.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

7.13 American Society of Mechanical Engineers (ASME). Copies of ASME documents may be obtained online at https://www.asme.org/.

7.1.5 Code of Federal Regulations (CFR). Copies of CFR's are available online at https://www.ecfr.gov/.

7.1.6 Federal Acquisition Regulation (FAR). Copies of FAR's are available online at https://www.acquisition.gov/.

7.1.7 National Electrical Manufactures Association (NEMA) documents. Copies of NEMA documents may be obtained online at https://www.nema.org.

7.1.8 SAE International documents. Copies of SAE standards may be obtained online at https://www.sae.org/.

7.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this CID.

b. Packaging requirements (see 6.).

c. BCM, Type I, Size A.

d. BCM, Type I, Size B.

e. BCM, Type I, Size C.

f. BCM, Type II.

7.2.1 Part identification number (PIN). The following part identification numbering procedure in Table VI is for Government purposes and does not constitute a requirement for the contractor.

Table VI: BCM PINs and Master NSNs.

PIN	Type	Size	Master NSN
A-A-60081-I-A	I	A	4940-##-###-####
A-A-60081-I-B	I	B	4940-##-###-####
A-A-60081-I-C	I	C	4940-##-###-####
A-A-60081-II	II		4940-##-###-####

7.3 Definitions.

7.3.1 Commercial item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

(1) Any item, other than real property, that is of a type customarily used by the general public or by non-Governmental entities for purposes other than Governmental purposes, and—

(i) Has been sold, leased, or licensed to the general public; or

(ii) Has been offered for sale, lease, or license to the general public;

(2) Any item that evolved from an item described in paragraph (1) of this definition through advances in technology or performance and that is not yet available in the commercial marketplace, but will be available in the commercial marketplace in time to satisfy the delivery requirements under a Government solicitation;

(3) Any item that would satisfy a criterion expressed in paragraphs (1) or (2) of this definition, but for—

(i) Modifications of a type customarily available in the commercial marketplace; or

(ii) Minor modifications of a type not customarily available in the commercial marketplace made to meet Federal Government requirements. Minor modifications means modifications that do not significantly alter the non-Governmental function or essential physical characteristics of an item or component, or change the purpose of a process. Factors to be considered in determining whether a modification is minor include the value and size of the modification and the comparative value and size of the final product. Dollar values and percentages may be used as guideposts, but are not conclusive evidence that a modification is minor;

(4) Any combination of items meeting the requirements of paragraphs (1), (2), (3), or (5) of this definition that are of a type customarily combined and sold in combination to the general public;

(5) Installation services, maintenance services, repair services, training services, and other services if—

(i) Such services are procured for support of an item referred to in paragraph (1), (2), (3), or (4) of this definition, regardless of whether such services are provided by the same source or at the same time as the item; and

(ii) The source of such services provides similar services contemporaneously to the general public under terms and conditions similar to those offered to the Federal Government;

(6) Services of a type offered and sold competitively in substantial quantities in the commercial marketplace based on established catalog or market prices for specific tasks performed or specific outcomes to be achieved and under standard commercial terms and conditions. For purposes of these services—

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

(i) “Catalog price” means a price included in a catalog, price list, schedule, or other form that is regularly maintained by the manufacturer or vendor, is either published or otherwise available for inspection by customers, and states prices at which sales are currently, or were last, made to a significant number of buyers constituting the general public; and

(ii) “Market prices” means current prices that are established in the course of ordinary trade between buyers and sellers free to bargain and that can be substantiated through competition or from sources independent of the offerors.

(7) Any item, combination of items, or service referred to in paragraphs (1) through (6) of this definition, notwithstanding the fact that the item, combination of items, or service is transferred between or among separate divisions, subsidiaries, or affiliates of a contractor; or

(8) A nondevelopmental item, if the procuring agency determines the item was developed exclusively at private expense and sold in substantial quantities, on a competitive basis, to multiple State and local Government. (Reference the Federal Acquisition Regulation (FAR) 2.101)

7.3.2 Special tool. A tool that is not commercially and readily available from a source other than the BCM contractor.

7.4 Key words.

Media
Sand

MILITARY INTERESTS:

Custodian:
Air Force – 184

Preparing Activity:
Air Force – 184

Agent:
Air Force – 110
(Project 4920-2025-012)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.