INCH-POUND

A-A-60088 (USAF)
30 JULY 2026

COMMERCIAL ITEM DESCRIPTION

TRUCK, AIRCRAFT FUELING-DEFUELING
C304 - 3000 GALLON COMMERCIAL REFUELER

The General Services Administration has authorized the use of this commercial item description by all federal agencies.

1. SCOPE. This commercial item description (CID) describes the general requirements for a commercial aviation refueling truck (herein referred to as the Refueling Vehicle) that will be used for fuel servicing of both military and commercial aircraft.

2. SALIENT CHARACTERISTICS.

2.1 Refueling Vehicle description. The Refueling Vehicle shall be a tank truck that will receive, transport, store, and pump jet fuels in accordance with ASTM D910, ASTM D1655, MIL-DTL-5624, MIL-DTL-25524, MIL-DTL-83133, GOST 10-227, MoD Def Stan 91-091, MoD Def Stan 91-087, ASTM D6615, and ASTM D7566. Excluding the 3% expansion space, the Refueling Vehicle shall have a 3,000 gallon capacity and shall be capable of the following:

a. Issuing fuel to aircrafts at volumetric flow rates of up to 300 gpm through a filtration system, a flow meter, a primary and secondary pressure control system, a ground servicing hose, and a single point nozzle.

b. Defueling aircraft into the cargo tank through the single point nozzle, ground servicing hose, the filtration system, and the flow meter at a minimum flow rate of 80 gpm without the assistance of aircraft boost pumps and at flow rates of at least 300 gpm with the assistance of aircraft boost pumps.

c. Bottom loading fuel into the cargo tank at flow rates up to 600 gpm with overfill protection.

Comments, suggestions, or questions on this document should be addressed to WR-ALC/LEEC, 295 Byron Street, Robins AFB, GA 31098-1611. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 1730

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2.2 Design and construction. The design shall promote cost effective, life-cycle sustainability by addressing considerations such as incorporating open standards, reducing pollutant emissions and wastes, and increasing fuel economy, while satisfying system performance requirements. It shall be designed and constructed so that no parts will work loose in service, and to withstand the strains, jars, vibrations, and other conditions incident to shipping, storage, installation, and service. It shall be weatherproof and designed to prevent the intrusion of water, sand, and dust into critical operating components.

2.2.1 Materials, protective coatings, and finish.

2.2.1.1 Protective coatings. Materials that deteriorate when exposed to sunlight, weather, or operational conditions normally encountered during the service life of the item shall not be used or shall have means of protection against such deterioration that does not prevent compliance with the performance requirements specified herein. Protective coatings that chip, crack, or scale with age or extremes of climatic conditions or when exposed to heat shall not be used. Exposed surfaces of fasteners, handles, and fittings shall also be primed and painted.

2.2.1.2 Finish. The exterior finish color of the Refueling Vehicle and the inner surfaces of compartments shall be the manufacturer's standard finish.

2.2.1.3 Exclusion of water. The design of the Refueling Vehicle shall be such as to prevent water leaking into, or being driven into, any part of the Refueling Vehicle interior when either in an operating or travelling configuration. All windows, doors, panels, covers, etc., shall be provided with sealing arrangements such that the entry of water is minimized when these items are correctly closed. Particular care shall be taken to prevent wetting of equipment and heat and sound proofing materials. Sharp corners and recesses shall be avoided so that moisture and solid matter cannot accumulate to initiate localized attack. Sealed floors with suitable drainage shall be provided for storage compartments, engine compartments, and other areas in the Refueling Vehicle that could collect and retain water.

2.2.1.3.1 Fluid traps and faying surfaces. There shall be no fluid traps on the Refueling Vehicle. Faying surfaces of all structural joints, except welded joints, shall be sealed to preclude fluid intrusion.

2.2.1.3.2 Ventilation. Ventilation shall be sufficient to prevent moisture retention and buildup.

2.2.1.3.3 Drainage. Drain holes shall be provided to prevent collection or entrapment of water or other unwanted fluid in areas where exclusion is impractical. All designs shall include considerations for the prevention of water or fluid entrapment and ensure that drain holes are located to effect maximum drainage of accumulated fluids. The number and location of drain holes shall be sufficient to permit drainage of all fluids when the Refueling Vehicle is on a 10-degree longitudinal slope facing both up and down and on a 10-degree side slope in each direction (right and left side facing up the slope). The minimum size of the drain holes shall be 0.375-inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2.2.2 Markings. The Refueling Vehicle shall be marked appropriately using MIL-HDBK-1223 for guidance. Four DOT hazardous material labels, number 1863, shall be mounted on the vehicle, one on each side of the forward 1/3 of the cargo tank, one on the upper right hand corner of the rear of the tank, and one on the front bumper of the truck. The Refueling Vehicle shall also be marked in accordance with 49 CFR 172.302 and National Fire Protection Association (NFPA) 407. Information/Caution markings shall be Lusterless Black, Color Number 37038 of SAE AMS-STD-595, and Warning/Danger markings shall be Lusterless Red, Color Number 31136 of SAE AMS-STD-595.

2.2.2.1 Flammable marking. "FLAMMABLE" in 6-inch letters shall be located on each side and the rear of the cargo tank. 4-inch letters may be used if there is not enough space.

2.2.2.2 No smoking marking. "NO SMOKING WITHIN 50 FEET" in 6-inch letters shall be located on each side and the rear of the cargo tank. 4-inch letters may be used if there is not enough space.

2.2.2.3 Avoid water marking. "CARGO FIRE - AVOID WATER" in 4-inch letters shall be located on each side and the rear of the cargo tank.

2.2.2.4 Emergency tank shutoff marking. "EMERGENCY TANK SHUTOFF" shall be marked in 2-inch letters near each emergency tank shutoff.

2.2.2.5 Jet fuel markings. Jet fuel product designation shall be marked on each side of the cargo tank in 6-inch letters. Jet fuel product designation shall be marked on the rear of the cargo tank in 4-inch letters. Markings shall be in accordance with the table below unless otherwise noted by the government. Base location will be specified in ordering data (see 4.2).

TABLE I. Product markings.

Refueling Vehicle Final Destination Location	Product Markings
CONUS locations ***except*** Grand Forks AFB ND, Edwards AFB CA, Beale AFB CA	"Jet Fuel Jet A" **and** "F-24"
All OCONUS locations ***and*** Grand Forks AFB ND, Edwards AFB CA, Beale AFB CA	"Jet Fuel JP-8" **and**"F-34

2.2.3 Identification and information plates.

2.2.3.1 The Refueling Vehicle shall be provided with a permanently-marked identification data plate constructed of a non-corroding metal permanently affixed to the exterior of the Refueling Vehicle in a readily accessible location in accordance with MIL-STD-130. The identification plate shall contain the following information:

a. Nomenclature.

b. Air Force vehicle registration number.

c. Part number.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

d. Serial number.

e. Date of manufacture.

f. Contract number.

g. Manufacturer's name.

h. Manufacturer's address and phone number.

i. Commercial and Government Entity (CAGE) code.

j. Date of warranty expiration (if applicable).

k. National Stock Number (NSN).

l. Vehicle weight, unloaded (pounds).

m. Gross vehicle weight (pounds).

n. Engine fuel type.

o. Engine oil viscosities for ambient temperatures ranging from -40 to +125 °F.

p. Cargo tank capacity (gallons).

2.2.3.2 Transportation data plate. A transportation data plate shall be securely attached to the Refueling Vehicle in a readily accessible location. The plate shall contain at least the following information:

a. Side and rear silhouette views of the Refueling Vehicle.

b. Horizontal and vertical location of the center of gravity of the Refueling Vehicle marked on the silhouette views.

c. Shipping weight.

d. Loading cubage.

e. Overall height, width, and length.

f. Front and rear axle loads.

g. Tie down information.

2.2.3.3 Lubrication data plate. The Refueling Vehicle shall be provided with a permanently-marked lubrication data plate constructed of a non-corroding metal, mounted on the exterior surface of the Refueling Vehicle that shall direct attention to all lubrication fittings and components that require lubrication. The plate shall identify the type and grade of lubricant required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2.2.4 Environment, Safety, and Occupational Health (ESOH).

2.2.4.1 Component protection. All space in which work is performed during operation, service, and maintenance shall be free of hazardous protrusions, sharp edges, or other features which may cause injury to personnel. All rotating and reciprocating parts and all parts subject to high operational temperatures or subject to being electrically energized, that are of such nature or so located as to be hazardous to personnel, shall be guarded or insulated to eliminate the hazard. All wires, cables, tubes, and hoses shall be supported and protected to minimize chafing and abrasion and shall be located so as to provide adequate clearance from moving parts and high operational temperatures. Grommets shall be provided wherever wires, cables, tubes, or hoses pass through bulkheads, partitions, or structural members.

2.2.4.2 Foreign object damage (FOD). All loose metal parts, such as pins or connector covers, shall be securely attached to the Refueling Vehicle with wire ropes or chains. “Dog tag" style beaded chains shall not be provided. Removable panels, if provided, shall be attached with captive fasteners. Tire valve stem caps shall be made of plastic.

2.2.4.3 Fire extinguisher. Two Type I, Class 2, Size 20 fire extinguishers, in accordance with A-A-393, shall be installed, one on each side of the truck. The fire extinguishers shall be accessible to personnel standing on the ground and shall be protected from tire splash.

2.2.4.4 Electrostatic discharge (ESD). The design of the Refueling Vehicle shall preclude equipment damage due to ESD, protect personnel from electrical shock due to static charging, and prevent ignition of explosive atmospheres due to sparking.

2.2.4.5 Grounding cables and reels. Two Type I, spring rewind, grounding reels with cables and cable guides shall be installed side by side on the driver’s side of the truck. The reels and cables shall be in accordance with A-A-50696. One cable shall have a welder style clamp, and the other cable shall have a grounding plug. The cables shall have cable stops to prevent the clip or plug from striking the cable guide. The cables shall be electrically bonded to the tanker chassis frame.

2.2.5 Cargo tank and related components.

2.2.5.1 Cargo tank. The Refueling Vehicle shall have single compartment cargo tank with a capacity of 3,000 gallons plus a minimum three percent expansion space. The cargo tank shall be in accordance with all requirements of NFPA 385, NFPA 407, and 49 CFR 178.346 (DOT 406). The cargo tank shall be constructed of aluminum. There shall be no metal-to-metal contact between the tank mounting brackets and the truck chassis mounting brackets.

2.2.5.2 Bottom loading system. The bottom loading system shall be capable of filling the cargo tank from a pressurized fuel source through a single point receptacle with the engine off. The system shall accept fuel flow up to 600 gpm.

2.2.5.3 Bottom loading internal valve. An air-operated bottom loading internal valve shall be interlocked so that it only opens after the truck parking brakes are set and the automatic vent system is open. The bottom loading internal valve shall automatically activate when a single point nozzle is connected to the bottom loading inlet receptacle. The valve must be equipped with a fusible link or a plug that closes the valve in the event of a fire.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2.2.5.4 Overfill prevention system. A dual, independent, automatic overfill prevention system shall be installed to stop fuel flow during bottom loading and defueling operations. The system used shall be a Scully Load Anywhere System or equivalent. The system shall be compatible with Scully ST-15 single point overfill prevention control unit, Scully Intelliltrol 2, or an equivalent system that uses a dual socket adapter and includes a pretest momentary-on push button located on the bottom loader control panel for test verification of the tank-level sensor. The socket adapter shall be equipped with ground verification. A mechanical jet level sensor shall not be used.

2.2.5.5 Cargo tank water drain. The water sump on the cargo tank shall have a 1-inch minimum self-closing drain valve. The drain valve shall be directed toward the ground, guarded from damage, accessible without crawling under the tank, and designed to prevent fuel contact with the operator.

2.2.5.6 Cargo tank vent system. The cargo tank vent system shall be a two part system. The primary system shall be an automatic vent system. The automatic vent system shall be interlocked and fail-safe during refueling, defueling, and bottom loading operations so that flow cannot commence unless the vent(s) are fully open. The automatic vent system shall be sized for a cargo tank fill rate of 600 gpm and a single-point nozzle discharge rate of 300 gpm. The secondary system shall be an emergency vent in accordance with 49 CFR 178 (DOT 406).

2.2.6 Pumping System.

2.2.6.1 Piping. All piping shall be aluminum or stainless steel with a minimum 150 psi working pressure.

2.2.6.2 Pump. The pump shall be a self-priming, centrifugal, aviation fuel dispensing pump. The pump shall be driven directly or hydraulically by the truck transmission PTO or by a split shaft gear box. A bypass system or relief valve shall be provided to protect the pump.

2.2.6.3 Pump inlet strainer. An in-line Y-style strainer shall be installed in the piping between the tank suction header and the pump. The strainer shall have a serviceable 10 to 20 mesh screen that is rated for flow up to 300 gpm. The strainer shall be positioned in an easily accessible location for servicing.

2.2.6.4 Pump maintenance shutoff valve. A pump maintenance shutoff valve shall be located both upstream and downstream of the pump. There shall be no devices, branch connections, or bypass/relief connections between the shutoff valves and the pump. The valves shall be a manual, quarter turn design and shall be operable while standing or kneeling on the left or right side of the truck.

2.2.6.5 Flow meter. All fuel flow through the pumping system shall be metered through a temperature compensated flow meter. The flow meter shall have a resettable totalizer capable of displaying the amount of fuel delivered in gallons. The flow meter shall be capable of capturing flow during both fueling and defueling operations.

2.2.6.6 Pressure control system. The pressure control system shall consist of an independent primary and secondary pressure control system. The pressure control system shall limit the single point nozzle pressure to a maximum peak surge pressure of 120 psi during a complete aircraft fueling operation. Valve(s) closure shall occur in a maximum timeframe of two seconds. Any surge pressure developed shall not exceed the pressure rating of any single component in the Refueling Vehicle pumping system. The pressure control system shall include a pump bypass

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

system or a relief valve. The pressure control system shall sense the single point nozzle pressure through a pressure sensing type component that consistently and repeatedly simulates the fuel pressure at the single point nozzle. Locked in pressure at the single point nozzle shall not exceed 55 psi for more than 15-seconds after flow stops. The system shall resume from an induced no-flow condition to primary pressure control system controlled flow within 15-seconds by disengaging and then re-engaging the dead man.

2.2.6.6.1 Primary pressure control system. The primary pressure control system shall be set to control and limit the single-point nozzle pressure 50 ±5 psi using a pressure control valve.

2.2.6.6.2 Secondary pressure control system. The secondary pressure control system shall be set to control and limit the single-point nozzle pressure to a maximum of 55 psig if the primary pressure control system should fail. The secondary pressure control system shall be a hose end pressure control valve.

2.2.7 Filtration System. The filtration system shall be rated for 300 gpm and 150 psi. The filter vessel and elements shall be qualified in accordance with the requirements of EI-1581 Specification and Qualification Procedures for Aviation Jet Fuel Filter Separators, Category M, Type S, Two Stage system configuration.

2.2.7.1 Filter vessel water drain. The water sump on the filter vessel shall be equipped with a one inch manually operable ball-type valve with a spring return handle that renders the valve normally closed. The drain valve shall be directed toward the ground, guarded from damage, accessible without crawling under the truck, and designed to prevent fuel contact with the operator.

2.2.7.2 Filter vessel maintenance shutoff valve. A filter vessel maintenance shutoff valve shall be located both upstream and downstream of the filter vessel. There shall be no devices, branch connections, or bypass/relief connections between the shutoff valves and the filter vessel. The valves shall be a manual, quarter turn design and shall be operable while standing or kneeling on the left or right side of the truck.

2.2.7.3 Differential pressure gauge. A non-calibrating differential pressure gauge shall be installed to continuously monitor the pressure drop across the filter coalesce stage during operation. The gauge shall register and hold the highest pressure drop achieved during operation. The gauge shall be resettable.

2.2.7.4 Fuel sampling. A fuel sampling valve shall be provided downstream of the filtration system and prior to the flow meter. The valve shall be easily accessible while standing at the operator control panel.

2.2.8 Hose assemblies.

2.2.8.1 Underwing hose. One 2” x 60’ aviation fueling hose shall be provided for underwing fueling operations.

2.2.8.2 Underwing hose reel. One single wrap hose reel sized for 2” x 60’ hose shall be provided. The reel shall have explosion proof electric rewind motor and switch with an auxiliary manual rewind.

2.2.8.3 Underwing nozzle. The underwing nozzle shall be D-3 universal single point nozzle. The nozzle shall have a 60 mesh stainless steel strainer and an automatic vacuum breaker.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2.2.8.4 Overwing hose. One 1.50” x 60’ aviation fueling hose shall be provided for overwing fueling operations.

2.2.8.5 Overwing hose reel. One single wrap hose reel or one drum hose reel sized for 1.50” x 60’ hose shall be provided. The reel shall have explosion proof electric rewind motor and switch with an auxiliary manual rewind.

2.2.8.6 Overwing nozzle. The overwing nozzle shall be a type I, size 2, class B, style 2 nozzle in accordance with A-A-52030 (such as an OPW model 295AF nozzle or equivalent). The overwing nozzle shall have a 100 or 60 mesh stainless steel strainer and the grounding wires shall be jacketed.

2.2.9 Night servicing lights. Two adjustable, vapor proof, service lights shall be installed to facilitate nighttime operations. One light shall be installed at the near the pumping compartment on the driver’s side. The other light shall be installed at the rear of the cargo tank on the driver’s side. The lights shall be approximately eight feet above the ground. Each light shall have its own on/off switch and be adjustable by a control handle that is within reach of a person standing on the ground. The combined light levels of these two lights shall illuminate the entire side of the vehicle.

2.2.10 Accessory lighting. Adequate lighting shall be provided at the control panel, bottom loading interface, and filter separator to facilitate nighttime operations.

2.3 Transportability.

2.3.1 Surface transportability. The Refueling Vehicle shall be transportable via all modes of surface shipment (highway, rail, and water) in accordance with MIL-STD-1366 and shall be capable of withstanding the mechanical shock and vibration characteristics of highway, rail, and water transport, except that design for rail impact testing (see 5.2.5 of MIL-STD-1366) is not required.

2.4 Maintainability.

2.4.1 Special tools. The design of the item shall minimize the requirement for special tools. All special tools shall be provided with, and stored on, the Refueling Vehicle.

2.4.2 Diagnostic software. A copy of any diagnostic software required or recommended for maintaining the Refueling Vehicle shall be provided with each Refueling Vehicle on CD-ROM or DVD-ROM.

2.5 Performance.

2.5.1 Underwing fuel servicing. When conducting underwing fuel servicing operations, the primary pressure control system shall maximize flow rate into the aircraft while limiting the single point nozzle pressure to no more than 50 ±5 psi. There shall also be an independent secondary pressure control system that will limit the nozzle pressure to 55 psi. In the event that the secondary pressure control system is activated, fuel flow shall continue. Stopping the fuel flow is not an acceptable secondary pressure control system. When operating in this mode, the pumping system shall be capable of issuing fuel to an aircraft from the cargo tank, through the filtration system, the flow meter, ground servicing hose, and the single point nozzle at a flow rate of 300 gpm.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2.5.2 Overwing fuel servicing. When conducting overwing fuel servicing operations, the throttle controller and overwing nozzle shall be used to control both flow rate and nozzle pressure. The pumping system shall be capable of delivering fuel at rates up to 100 gpm.

2.5.3 Defueling. When conducting defueling operations, the flow rate shall be maximized while preventing pump suction pressure from dropping below that required to maintain adequate NPSH. With the fuel level height at 10-feet above the ground, the pumping system shall be capable of defueling fuel from an aircraft through the single-point nozzle and hose, the filtration system, the flow meter, and into the cargo tank at a flow rate of at least 80 gpm without the assistance of aircraft boost pumps and at least 300 gpm with the assistance of aircraft boost pumps. Both hoses shall be capable of performing defueling operations.

2.5.4 Bottom loading. When bottom loading, the refueling vehicle shall be capable of filling the cargo tank from a pressurized fuel source through a single point receptacle at flow rates up to 600 gpm with the truck engine off.

2.5.5 Recirculation. When recirculating, the pumping system shall recirculate fuel form the cargo tank through the filtration system, flow meter, and internal piping and then back into the cargo tank. The fuel flow rate shall be controlled by the throttle controller. The control system shall not allow recirculation if the high-high level sensor is wet.

2.6 Mobility.

2.6.1 Transmission. The Refueling Vehicle shall be equipped with an automatic transmission which shall include a hydraulic torque converter and not less than five forward gear ratios. The net torque capacity and the net power rating of the transmission shall exceed the output ratings of the engine.

2.6.2 Axles. The Refueling Vehicle shall be equipped with axles rated at least equal to the load imposed on each axle, measured at the ground, with the Refueling Vehicle loaded to its GVWR.

2.6.3 Suspension. The Refueling Vehicle shall be equipped with a suspension system with components having a rated capacity at least equal to the load imposed on each member, measured at the ground, with the Refueling Vehicle loaded to its GVWR.

2.6.4 Steering. The Refueling Vehicle shall be equipped with a power assisted steering system, with manual steering available in the event of power assist failure.

2.6.5 Brakes. The Refueling Vehicle shall be equipped with an air brake system. A brake override shall be provided for maintenance or towing applications.

2.6.6 Spare tire and wheel assembly. When specified (see 4.2), a spare tire and wheel assembly (the tire mounted on the wheel) shall be shipped with the Refueling Vehicle; the wheel and tire shall be identical to the others provided. The assembly shall be securely stowed so that it does not come loose during transport.

2.6.7 Spare wheel. When specified (see 4.2), a spare wheel shall be shipped with the Refueling Vehicle; the wheel shall be identical to the others provided. The wheel shall be securely stowed so that it does not come loose during transport.

2.6.8 Engine. The Refueling Vehicle shall be equipped with a diesel engine.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2.7 Technical data.

2.7.1 Manufacturer's publications. The contractor shall provide the following manufacturer's publications in Indexed Portable Document Format (IPDF). All data shall be supplied in accordance with DFARS clause 252.227-7015. All manuals shall be delivered with either unlimited data rights or as a minimum, a Government Purpose License, to allow the Air Force to electronically store, print, distribute and update the manual. Manuals are subject to government review and approval in accordance with MIL-PRF-32216. Any changes or corrections noted by the Air Force shall be corrected and updated pages or manuals shall be submitted. Only one digital copy is required per order regardless of quantity of units.

2.7.1.1 Operator's manual. The operator's manual shall include all information required for the safe and efficient operation of the vehicle. The operator's manual shall include at least the following:

a. General description and step-by-step instructions for the operation of the vehicle and its auxiliary equipment.

b. Checklists, lubrication charts, and basic troubleshooting procedures for the daily maintenance inspection and mission readiness checks that the operator is expected to perform.

c. Schedules for required preventative maintenance and required periodic maintenance.

d. Full descriptions and illustrations for the location and function of all controls.

e. List of all checks and adjustments needed in preparation for placing the vehicle into service upon receipt from the contractor.

f. Preparation Instructions for shipment or storage.

g. Warranty information and a list that details the period of the warranty for the complete vehicle and for any component that exceeds the warranty of the complete vehicle. Addresses and telephone numbers shall be provided for all warranty providers listed.

2.7.1.2 Service and repair manuals. Service and repair manuals shall be provided for the chassis, engine, transmission, tanker body, and equipment. The service manuals shall identify any special tools and test equipment required and shall cover troubleshooting and maintenance as well as minor and major repair procedures. The text shall contain performance specifications, tolerances, fluid capacities, current data, voltage data, resistance data, test procedures, and any illustrations or exploded views that may be required to perform proper maintenance by qualified mechanics. The service and repair manuals shall contain an alphabetical subject index as well as a table of contents. The manual shall contain at least the following where applicable:

a. Pneumatic, electrical, and fuel schematics.

b. Schedules for required preventative maintenance and required periodic maintenance.

c. Troubleshooting, servicing, disassembly, repair, and assembly procedures.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2.7.1.3 Illustrated parts breakdown. An illustrated parts breakdown (IPB) manual shall be provided for the chassis, engine, transmission, tanker body, and equipment. IPB manuals shall include illustrations and exploded views as needed to properly identify all parts, assemblies, subassemblies, and special equipment. All components of assemblies shown in illustrations or exploded views shall be identified by reference numbers that correspond to the reference numbers in the parts list. All purchased parts shall be cross-referenced with the original manufacturer's name and part number. The IPB manual shall provide the description and quantity of each item used per vehicle. The size, thread dimensions, torque specifications, and special characteristics shall be provided for all nonstandard nuts, bolts, screws, washers, grease fittings, and similar items. The IPB manuals shall contain a numerical index. The manuals shall contain a list of all the component vendor names, addresses, and telephone numbers referenced in the parts list.

2.7.1.4 Manual delivery. Digital copies shall be provided via digital file transfer such as Department of Defense Secure Access File Exchange (DOD SAFE) and shall be furnished to AFLCMC/WROZ a minimum of 30 days prior to the first hardware delivery. Contact the appropriate Integrated Product Team Equipment Specialist for file delivery instructions.

2.7.2 Service bulletins. The contractor shall prepare service bulletins as required to notify the government of new maintenance problems and/or procedures to be implemented on the contractor's equipment prior to the issuance of permanent changes to the technical manuals. Service bulletins shall also be prepared when the program office has identified a trend of a potential problem or failure that has occurred at field level. The service bulletins shall identify any potential safety hazards and shall be submitted in a Microsoft Office digital format.

2.8 Cleaning. The Refueling Vehicle shall be thoroughly cleaned. Loose, spattered, or excess solder; welding slag; stray bolts, nuts, and washers; rust; metal particles; pipe compound; and other foreign matter shall be removed during and after final assembly.

3. PACKAGING. Preservation, packing, and marking shall be as specified in the contract or order.

4. NOTES.

4.1 Sources of documents.

4.1.1 Government Documents. Copies of Military Specifications, Standards, and Handbooks are available online at https://quicksearch.dla.mil.

4.1.2 Code of Federal regulations (CFR). Copies of the CFR are available online at https://www.ecfr.gov.

4.1.3 Advancing Standards Transforming Markets (ASTM). Copies of the ASTM may be obtained from https://www.astm.org.

4.1.4 Society of Automotive Engineers (SAE). Copies of the SAE may be obtained from https://www.sae.org.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

4.1.5 National Fire Protection Association (NFPA). Copies of the NFPA may be obtained from https://www.nfpa.org.

4.1.6 RussianGost (GOST). Copies of the GOST may be obtained from https://www.russiangost.com.

4.1.7 Defense Federal Acquisition Regulation Supplement (DFARS). Copies of the DFARS may be obtained from https://www.acquisition.gov/dfars.

4.1.8 Defense Gateway (MoD Def Stan). Copies of the MoD Def Stan may be obtained from https://www.dstan.mod.uk.

4.1.9 Energy Institiue (EI). Copies of the EI may be obtained from https://www.energyinst.org.

4.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this CID.

b. If a spare tire and wheel assembly is required (see 2.6.6).

c. If a spare wheel is required (see 2.6.7).

d. Base location for jet fuel markings (see 2.2.2.1).

4.3 Key words.

Batteries
Filtration
Jet Fuel
Recirculation
Refueling Vehicle

MILITARY INTEREST

Custodian:
Air Force - 184

Preparing activity:
Air Force - 184

(Project 1730-2026-005)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.