INCH-POUND

A-A-60091 (USAF)
30 JULY 2026

COMMERCIAL ITEM DESCRIPTION

TRUCK, TANK A/S32A-24, POTABLE WATER

The General Services Administration has authorized the use of this commercial item description by all federal agencies.

1. SCOPE. This commercial item description (CID) describes the general requirements for a 250 gallon Potable Water Truck.

2. SALIENT CHARACTERISTICS.

2.1 Potable Water Truck description. The Potable Water Tuck shall be capable of servicing military aircraft with potable water, demineralized water, or water/alcohol mixtures. The Potable Water Truck is based on a commercial truck chassis that has been modified for this use.

2.2 Design and construction. The design shall promote cost effective, life-cycle sustainability by addressing considerations such as incorporating open standards, reducing pollutant emissions and wastes, and increasing fuel economy, while satisfying system performance requirements. It shall be designed and constructed so that no parts will work loose in service, and to withstand the strains, jars, vibrations, and other conditions incident to shipping, storage, installation, and service. It shall be weatherproof and designed to prevent the intrusion of water, sand, and dust into critical operating components.

Comments, suggestions, or questions on this document should be addressed to WR-ALC/LEEC, 295 Byron Street, Robins AFB, GA 31098-1611. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 1730

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2.2.1 Materials, protective coatings, and finish.

2.2.1.1 Protective coatings. Materials that deteriorate when exposed to sunlight, weather, or operational conditions normally encountered during the service life of the item shall not be used or shall have means of protection against such deterioration that does not prevent compliance with the performance requirements specified herein. Protective coatings that chip, crack, or scale with age or extremes of climatic conditions or when exposed to heat shall not be used. Exposed surfaces of fasteners, handles, and fittings shall also be primed and painted. See 2.2.4.1 for prohibited hazardous materials.

2.2.1.2 Finish. Unless otherwise specified (see 6.2), the exterior finish color of the Potable Water Truck and the inner surfaces of compartments shall be semi-gloss green, Color Number 24052 of SAE AMS-STD-595. When specified, the exterior finish color shall be tan 686A, Color Number 33446 of SAE AMS-STD-595.

2.2.1.3 Exclusion of water. The design of the Potable Water Truck shall be such as to prevent water leaking into, or being driven into, any part of the Potable Water Truck interior when either in an operating or travelling configuration. All windows, doors, panels, covers, etc., shall be provided with sealing arrangements such that the entry of water is minimized when these items are correctly closed. Particular care shall be taken to prevent wetting of equipment and heat and sound proofing materials. Sharp corners and recesses shall be avoided so that moisture and solid matter cannot accumulate to initiate localized attack. Sealed floors with suitable drainage shall be provided for storage compartments, engine compartments, and other areas in the Potable Water Truck that could collect and retain water.

2.2.1.3.1 Fluid traps and faying surfaces. There shall be no fluid traps on the Potable Water Truck. Faying surfaces of all structural joints, except welded joints, shall be sealed to preclude fluid intrusion.

2.2.1.3.2 Ventilation. Ventilation shall be sufficient to prevent moisture retention and buildup.

2.2.1.3.3 Drainage. Drain holes shall be provided to prevent collection or entrapment of water or other unwanted fluid in areas where exclusion is impractical. All designs shall include considerations for the prevention of water or fluid entrapment and ensure that drain holes are located to effect maximum drainage of accumulated fluids. The number and location of drain holes shall be sufficient to permit drainage of all fluids when the Potable Water Truck is on a 10-degree longitudinal slope facing both up and down and on a 10 degree side slope in each direction (right and left side facing up the slope). The minimum size of the drain holes shall be 0.375-inch.

2.2.1.4 Elastomers. Materials used that are used inside the cargo tank, pumping system, and all other components that come into contact with water shall be compatible with potable water, de-mineralized water, water/alcohol mixtures, and 50/50 mixtures of propylene glycol (uninhibited) antifreeze with de-mineralized water.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2.2.2 Markings. All external devices which require an operational or maintenance interface shall be marked in accordance with MIL-STD-130. Markings shall be applied with decals and shall be 1-inch high block letters unless prohibited by the available space. In such cases, the markings shall be the largest size possible. Markings, Information/Caution shall be Lusterless Black, Color Number 37038 of SAE AMS-STD-595, and Markings, Warning/Danger shall be Lusterless Red, Color Number 31136 of SAE AMS-STD-595. The center of gravity of the Potable Water Truck shall be marked on the unit within 1-inch of the calculated center of gravity. Tire inflation pressure shall be marked as near to each tire as practicable.

2.2.3 Identification and information plates.

2.2.3.1 Identification plate. The Refueling Vehicle shall be provided with a permanently-marked identification data plate constructed of a non-corroding metal permanently affixed to the exterior of the Refueling Vehicle in a readily accessible location in accordance with MIL-STD-130. The identification plate shall contain the following:

a. Nomenclature.

b. Air Force vehicle registration number.

c. Part number.

d. Serial number.

e. Date of manufacture.

f. Contract number.

g. Manufacturer’s name.

h. Manufacturer’s address and phone number.

i. Commercial and Government Entity (CAGE) code.

j. Date of warranty expiration (if applicable).

k. National Stock Number (NSN).

l. Vehicle weight unloaded (pounds).

m. Gross vehicle weight (pounds).

n. Engine fuel type.

o. Engine oil viscosities for ambient temperatures ranging from -40 to +125°F.

p. Cargo tank capacity (gallons).

2.2.3.2 Transportation data plate. A transportation data plate shall be securely attached to the Potable Water Truck in a readily accessible location. The plate shall contain at least the following information:

a. Side and rear silhouette views of the Potable Water Truck.

b. Horizontal and vertical location of the center of gravity of the Potable Water Truck marked on the silhouette views.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

c. Shipping weight.

d. Loading cubage.

e. Overall height, width, and length.

f. Front and rear axle loads.

g. Tie down information.

2.2.3.3 Lubrication data plate. The Potable Water Truck shall be provided with a permanently-marked lubrication data plate constructed of a non-corroding metal, mounted on the exterior surface of the Potable Water Truck that shall direct attention to all lubrication fittings and components that require lubrication. The plate shall identify the type and grade of lubricant required for operational temperatures specified in 2.3.1.

2.2.3.4 Operating instruction plates. Brief operating and precautionary instructions shall be permanently affixed near appropriate controls. The instructions shall be clear, concise, and adequate to enable operation of the vehicle without damage to the equipment or injury to personnel. The instructions shall refer to components as identified by their nameplates (see 2.2.3.5).

2.2.3.5 Component name plates. All controls, valves, gauges, indicators, and any other relevant components used in the operation of the vehicle shall be identified by securely attached name plates. The name plates shall be constructed in a way that exposure to oil, dirt, light, etc. will not fade or erase them. Tags or decals shall not be used.

2.2.4 Environment, Safety, and Occupational Health (ESOH).

2.2.4.1 Hazardous material. The design shall minimize and control hazards associated with the inclusion or use of hazardous or toxic materials and the generation of toxic or noxious gases. The Potable Water Truck shall not generate or use Class I or Class II Ozone Depleting Substances (ODS) during operation, maintenance, or disposal. Class I ODS and hazardous materials shall not be used in any system, component, or process. The Potable Water Truck shall not contain or use either hexavalent chromium or cadmium without written approval by the procuring activity. Hazardous materials are defined in AFI 32-7086; Class I and Class II ODS are defined in 40 CFR 82.

2.2.4.2 Component protection. All space in which work is performed during operation, service, and maintenance shall be free of hazardous protrusions, sharp edges, or other features which may cause injury to personnel. All rotating and reciprocating parts and all parts subject to high operational temperatures or subject to being electrically energized, that are of such nature or so located as to be hazardous to personnel, shall be guarded or insulated to eliminate the hazard. All wires, cables, tubes, and hoses shall be supported and protected to minimize chafing and abrasion and shall be located so as to provide adequate clearance from moving parts and high operational temperatures. Grommets shall be provided wherever wires, cables, tubes, or hoses pass through bulkheads, partitions, or structural members.

2.2.4.3 Foreign object damage (FOD). All loose metal parts, such as pins or connector covers, shall be securely attached to the Potable Water Truck with wire ropes or chains. "Dog tag" style beaded chains shall not be provided. Removable panels, if provided, shall be attached with captive fasteners. Tire valve stem caps shall be made of plastic.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2.2.4.4 Fire extinguisher. A dry chemical fire extinguisher, Type 1, Class 1, Size 5 in accordance with A-A-393, shall be mounted in an easily accessible location on the driver's side of the vehicle.

2.2.4.5 Noise. The design shall ensure that noise created by the Potable Water Truck is compatible with the environment and minimize exposure of personnel to noise hazards during operations and maintenance activities. The maximum A-weighted Sound level produced by the vehicle during operations shall not exceed 85 dBA.

2.2.5 Electromagnetic interference (EMI). The Potable Water Truck shall be in accordance with the following radiated emission and susceptibility requirements of MIL-STD-461: RE102 and RS103.

2.2.6 Human systems integration. The Potable Water Truck shall be designed in accordance with MIL-STD-1472 for ease of operation, inspection, and maintenance, including the use of arctic mittens and Mission-Oriented Protective Posture (MOPP) Level 4 Chemical Warfare Gear. Chemical Warfare Gear is not required for preventive maintenance or major corrective maintenance.

2.2.7 Fastening devices. All screws, bolts, nuts, pins, and other fastening devices shall be properly designed, manufactured, and installed with adequate means of preventing loss of torque or adjustment. Cotter pins, lock washers, or nylon patches shall not be used for this purpose, except for the attachment of trim items or as provided in commercial (see 6.3.4) components. Tapped threads shall have a minimum thread engagement in accordance with Table I.

TABLE I. Minimum thread engagement.

Material	Minimum Thread Engagement
Steel	1.0 times the nominal fastener diameter
Cast iron, brass, or bronze	1.5 times the nominal fastener diameter
Aluminum, zinc, or plastic	2.0 times the nominal fastener diameter

2.2.8 Welders and welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface parts to be welded shall be free from rust, scale, paint, grease, and other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the welded parts. Welds shall transmit stress without cracking or permanent distortion when the parts connected by the welds are subjected to test, proof, and service loadings.

2.2.9 Cargo tank and related components.

2.2.9.1 Cargo Tank. The Potable water truck cargo tank shall have a 250 gallon liquid capacity. The tank shall use closed system filling, have baffles as needed, and include a 10% expansion space without reducing the stated minimum liquid capacity. The tank and all of its components that will come into contact with water shall be fabricated of 300 series stainless steel.

2.2.9.2 Manhole. A manhole of no less than 20-inches in diameter shall be provided to allow the entry of personnel within the tank for cleaning and/or inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2.2.9.3 Sight gauge. A sight gauge displaying tank product volume shall be located on the tank and shall be easily viewable when standing at the pumping compartment.

2.2.9.4 Access plates. Access plates shall be provided where necessary to allow easy access to the cargo tank for both maintenance and inspections.

2.2.9.5 Drain Valve. A drain valve shall be installed to allow for complete drainage of the cargo tank. The drain valve shall be located in a readily accessible location that does not require the operator to go beneath the Potable Water Truck.

2.2.9.6 Cargo tank servicing lights. The cargo tank shall be equipped with at least two adjustable lights to facilitate night servicing operations.

2.2.10 Pumping system and related components.

2.2.10.1 Pumping system. The Potable Water Truck shall be capable of delivering a minimum of 20 gpm at a maximum of 40 psi when the servicing nozzle is at least 35-feet above the pumping compartment floor. Then nozzle squeeze control valve shall be capable of throttling the liquid flow rate from 0 to 20 gpm without adjustment of the pumping system.

2.2.10.2 Flow meter. The pumping system shall contain a flow meter that has an LED display with at least 0.625-inch minimum characters. The display shall be readable from a minimum of 10-feet night or day. The flow meter shall be capable of displaying the totalized flow in gallons per minute and incorporate the use of a zero reset button. It shall be corrosion resistant and certified for use with potable drinking water.

2.2.10.3 Hose. The Potable Water Truck shall be equipped with a minimum of 25-feet of FDA approved potable drinking water service hose. The hose shall incorporate the use of camlock type or equivalent connections.

2.2.10.4 Hose reel. The hose reel for the Potable Water Truck shall have an electric rewind design. In the event of failure, the reel shall also be capable of manual rewind through the use of a hand powered crank.

2.2.10.5 Connections. All connections made within the pumping system shall be made with camlock type or equivalent connections. This applies to the tank to suction line, system relief valve, suction filtration line, etc.

2.2.10.6 Pumping compartment. The pumping system shall be housed in a completely enclosed compartment on the driver's side of the vehicle. The pumping controls, servicing hose, and nozzle storage box shall be easily accessible for both operation and maintenance. The pumping compartment shall have illumination capability to facilitate night servicing operations.

2.2.11 Rear bumper. A rear bumper shall be installed on the potable water truck.

2.2.12 Cab interior.

2.2.12.1 Cab lighting. The cab shall be equipped with an overhead interior light. The light(s) shall be of proper size, location, and intensity for reading manuals while seated in the cab or standing at the open driver's side door during night operations.

2.2.12.2 Air conditioning. The cab shall have a proper air conditioning system installed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2.3 Environmental conditions.

2.3.1 Operating temperature range. The Potable Water Truck shall be capable of starting and operating in ambient temperatures ranging from -40 to 125 °F.

2.3.2 Storage temperature range. The Potable Water Truck shall be capable of being stored in ambient temperatures ranging from -65 to 160 °F.

2.3.3 Precipitation.

2.3.3.1 Rain. The Potable Water Truck shall be capable of storage and operation during rainfall of 5-inches per hour for three consecutive hours and 10-inches per hour for 10 consecutive minutes, with winds of up to 35 knots; and with 6-inches of rain per hour impinging on the Potable Water Truck at angles from vertical to 45 degrees for 30 consecutive minutes.

2.3.3.2 Snow. The Potable Water Truck shall be capable of storage and operation during accretion of wet snow up to 2-inches per hour for at least 12 hours.

2.3.3.3 Ice. The Potable Water Truck shall be capable of storage and operation with ice accretion up to 1.5-inches on exposed horizontal surfaces. An operator may use an ice scraper for five minutes during the start-up process.

2.3.4 Solar radiation. The Potable Water Truck shall not be adversely affected by full time exposure to solar radiation, such as those conditions encountered in desert environments.

2.3.5 Fungus. All materials used in the Potable Water Truck shall be fungus resistant or shall be suitably treated to resist fungus. Materials treated for fungus resistance shall retain their original electronic and physical properties, shall not present toxic hazards, and treatment shall last for the entire service life of the part. The Potable Water Truck shall be suitable for operation and storage in conditions encountered in a tropical environment.

2.3.6 Salt fog. The Potable Water Truck shall be capable of storage and operation in high temperature, high humidity, salt laden, seacoast environments without damage or deterioration of performance.

2.3.7 Sand and dust. The Potable Water Truck shall be capable of storage and operation during exposure to wind-blown sand or dust without damage or deterioration of performance.

2.4 Dimensions. Dimensions for the Potable Water Truck shall not exceed:

Length	288-inches
Width	96-inches
Height	85-inches

2.5 Transportability.

2.5.1 Surface transportability. The Potable Water Truck shall be transportable via all modes of surface shipment (highway, rail, and water) in accordance with MIL-STD-1366 and shall be capable of withstanding the mechanical shock and vibration characteristics of highway, rail, and water transport, except that design for rail impact testing (see 5.2.5 of MIL-STD-1366) is not required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2.5.2 Tie downs. The Potable Water Truck shall be symmetrically restrained during ground transport. Tie down points shall be rated at a minimum of 25,000 pounds, marked for capacity, with a clear opening compatible with MIL-DTL-25959 and MIL-PRF-27260 tie down devices. Each end of each tie down device shall terminate at a tie down point and not pass through any other tie down point. There shall be no interference between tie down devices and the Potable Water Truck. The tie down provisions shall be in accordance with 4.1 through 4.12 of MIL-STD-209.

2.6 Maintainability. The Potable Water Truck shall be designed for maintainability in accordance with 5.9 through 5.9.18 of MIL-STD-1472; forces shall not exceed those specified for both males and females.

2.6.1 Inspection and servicing provisions.

a. Pre-use inspections and servicing tasks shall not require tools.

b. Routine service and preventive maintenance shall not require special tools (see 6.3.10).

c. Drain plugs and filters shall be directly accessible from the ground and oriented to have unimpeded drainage to a catch pan.

d. The Potable Water Truck shall be designed with maximum usage of sealed lifetime lubrication bearings.

2.6.2 Special tools. The design of the item shall minimize the requirement for special tools (see 6.3.10). All special tools shall be provided with, and stored on, the Potable Water Truck.

2.6.3 Diagnostic software. A copy of any diagnostic software required or recommended for maintaining the Potable Water Truck shall be provided with each Potable Water Truck on CD-ROM or DVD-ROM.

2.7 Performance. The Potable Water Truck shall be capable of meeting all performance requirements in 2.2.10.1.

2.8 Mobility. The fully equipped Potable Water Truck loaded to its gross vehicle weight rating (GVWR) shall:

a. Maximum speed. Maintain a speed of 60 miles per hour (mph) on a dry level paved road for at least 1-mile.

b. Gravel roads. Traverse a graded gravel road (see 6.3.8) at an average speed of 25 mph.

c. Belgian-block or cobblestone roads. Traverse a Belgian-block (see 6.3.2) or cobblestone (see 6.3.3) road at a speed of 20 mph.

d. Cross-country terrain. Traverse cross-country terrain (see 6.3.6) at an average speed of 20-mph.

e. Gradeability. Ascend and descend a 20 degree slope without spillage of any fluid.

f. Side slope negotiation. Negotiate an 11.5 degree side slope in each direction (right and left side facing up the slope) without spillage of any fluid.

g. Turning diameter. Have a wall-to-wall turning diameter, as defined by SAE J695, of 60-feet maximum in both directions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

h. Steering force. The force required to turn the wheels from lock to lock, with the Potable Water Truck loaded to its GVWR and the engine at low idle speed, shall not exceed 15 pounds when measured at the steering wheel rim.

i. Parking brakes. Hold the Potable Water Truck motionless on a 20 degree longitudinal grade in both upgrade and downgrade directions with the transmission in the neutral position. The grade surface shall be dry, hard, and free from loose material. The force required to set the brakes under these conditions shall not exceed 55 pounds.

j. Service brakes. Be in accordance with the performance requirements of Federal Motor Vehicle Safety Standard (FMVSS) Number 105 if equipped with hydraulic brakes or FMVSS Number 121 if equipped with air brakes.

2.8.1 Transmission. The Potable Water Truck shall be equipped with an automatic transmission which shall include a hydraulic torque converter and not less than five forward gear ratios. The net torque capacity and the net power rating of the transmission shall exceed the output ratings of the engine.

2.8.2 Axles. The Potable Water Truck shall be equipped with axles rated at least equal to the load imposed on each axle, measured at the ground, with the Potable Water Truck loaded to its GVWR.

2.8.3 Suspension. The Potable Water Truck shall be equipped with a suspension system with components having a rated capacity at least equal to the load imposed on each member, measured at the ground, with the Potable Water Truck loaded to its GVWR.

2.8.4 Steering. The Potable Water Truck shall be equipped with a power assisted steering system, with manual steering available in the event of power assist failure.

2.8.5 Brakes. The Potable Water Truck shall be equipped with hydraulic or full air brakes on all wheels. If hydraulic brakes are provided, they shall be power assisted, self-adjusting, with an antilock braking system (ABS), in accordance with FMVSS Number 105.

2.8.5.1 If air brakes are provided, the Potable Water Truck shall be equipped with full-air brakes, with an antilock braking system (ABS), that are in accordance with FMVSS Number 121. Brake linings shall be of non-asbestos material. The braking system, complete with all necessary components, shall include:

a. Air compressor, unloader-head type, engine driven and engine lubricated, air or water cooled, and having a capacity of not less than 340 L/min (12 cubic feet per minute (cfm)).

b. Air storage reservoir(s), each tank equipped with drain, and with safety and check valves between the compressor and the last reservoir tank.

c. Foot control is suspended or treadle type.

d. Air control valves.

e. Air pressure gage, visible to the driver.

f. Low air pressure warning, visible and audible.

g. Service brake stop lamp switch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

h. Automatic moisture ejector on air storage reservoir.

i. Automatic slack adjusters on cam type brakes or internal self-adjusting brakes on wedge and disc type brakes on all axles.

j. Brake dust shields on rear.

k. Spring set parking brake.

2.8.5.2 An air dryer with a replaceable spin on/off desiccant cartridge shall be installed in the air brake system. The dryer shall have the capability of removing not less than 95 percent of the moisture in the air being dried. The dryer shall have a pre-cooler and a filter to screen out oil and solid contaminants. The dryer shall have an automatic self-cleaning cycle and a thermostatically controlled heater to prevent icing of the purge valve. The air dryer shall be in accordance with Technology and Maintenance Council (TMC) RP 637.

2.8.6 Tires and wheels. The Potable Water Truck shall be equipped with single front and single or dual tubeless steel belted radial tires with all season type tread mounted on steel disc wheel assemblies. Tire and wheel assemblies shall be identical at all wheel positions. Tires and wheels shall be in accordance with the *Tire and Rim Association Year Book* requirements for this application. Under no circumstance shall the vehicle maximum governed speed exceed the speed rating of any of the furnished tires.

2.8.6.1 Spare tire and wheel assembly. A spare tire and wheel assembly (the tire mounted on the wheel) shall be mounted on the Potable Water Truck if possible. Otherwise, the assembly shall be shipped along with the Potable Water Truck. The assembly shall be identical to the others provided.

2.9 Engine and related equipment. The Potable Water Truck shall be equipped with a diesel engine that is compliant with the most stringent Environmental Protection Agency (EPA) requirements applicable. When specified (see 6.2d), the Potable Water Truck shall be equipped with an Environmental Protection Agency Tier III diesel engine. This requires a National Security Exemption (NSE) from the Clean Air Act. The engine shall be certified to comply with the most stringent Environmental Protection Agency (EPA) non-road diesel engine emission requirements possible while meeting the requirement to operate on fuels containing over 15 parts per million (ppm) sulfur.

2.9.1 Engine starting system.

2.9.1.1 Starter. The engine shall be equipped with a 12 Volt DC electric starter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2.9.1.2 Engine starting aids. The engine shall start within 15 seconds cranking in any ambient temperature within the required operating range of the Potable Water Truck. Internal engine starting aids, fluid starting aids, and heat from the winterization system (see 2.9.3) may be used prior to and during the start period to facilitate engine starting under the following conditions:

TABLE II. Engine starting aids.

Temperature Range	Starting Aids Permitted
40 through 125 °F	None
0 through 39 °F	Internal engine starting aids and fluid starting aids
-40 through -1 °F	Internal engine starting aids, fluid starting aids, and heat from the winterization system

2.9.2 Engine air intake system. The engine air intake system shall be in accordance with 3.13.1.4.3 of SAE ARP1247. The inlet shall not draw air from directly beneath the Potable Water Truck and shall not be located near the cooling system air outlet nor the engine exhaust outlet. Joints shall be minimized between the air filter outlet and the actual engine air inlet and shall be designed to ensure no leakage of unfiltered air into the engine. A differential pressure air filter service indicator shall be provided.

2.9.3 Engine cooling system. The engine cooling system shall be in accordance with 3.13.1.4.2 of SAE ARP1247. Silicone radiator and heater hoses, constant-torque clamps, a coolant filter, and a coolant recovery system shall be provided. Engine coolant shall be in accordance with A-A-52624, Type I, and of adequate strength to provide protection to -40 °F. The engine out (top of radiator) coolant temperature shall not exceed 210 °F or the engine manufacturer's recommendations at 125 °F. The coolant filter shall be rated for one year or 2,000 hours between replacements, with supplementary coolant additives (SCA) either included in the filter or added separately.

2.9.4 Engine lubrication system. The engine lubrication system shall be designed so that the Potable Water Truck can be operated on a 20 degree longitudinal slope facing both up and down and on an 11.5-degree side slope in each direction (right and left side facing up the slope).

2.9.4.1 Engine oil. The engine shall be compatible with Grade 15W40 of MIL-PRF-2104 from 0 to 125 °F. Oil pre-heat for operation below 0 °F is allowed. The engine shall be compatible with arctic engine oil in accordance with MIL-PRF-46167 from -40 to 60 °F.

2.9.4.1.1 Engine oil operating temperature. The engine oil sump temperature shall not exceed 250 °F or the engine manufacturer's recommendations at 125 °F.

2.9.4.1.2 Engine oil consumption. The engine oil consumption shall not exceed 0.0035 pounds per brake horsepower-hour (lbs/bhp-hr) under any operating condition.

2.9.4.2 Engine oil filter. The engine oil filter shall be in accordance with 3.13.1.4.4 of SAE ARP1247.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2.9.5 Exhaust system. The exhaust system shall be constructed of stainless steel. The muffler(s) shall be constructed of aluminized steel or stainless steel. Exhaust system outlet(s) shall be directed away from personnel accessing any control panel or equipment compartment and the engine air intake and shall not be directed toward the ground.

2.9.6 Engine fuels and fuel system.

2.9.6.1 Engine primary fuels. If an ultra-low-sulfur diesel engine is ordered (see 6.2d), the primary fuel shall be ultra-low-sulfur diesel. Otherwise, the following shall be primary fuels (see 6.3.9):

a. JP-5, in accordance with MIL-DTL-5624, -40 to 125 °F ambient air temperature.

b. JP-8, in accordance with MIL-DTL-83133, -40 to 125 °F ambient air temperature.

c. F-24, in accordance with NATO AFLP-3747, -40 to 125 °F ambient air temperature.

2.9.6.2 Engine emergency fuels. If an ultra-low-sulfur diesel engine is ordered (see 6.2d) this paragraph does not apply. Otherwise, the following shall be emergency fuels (see 6.3.7): Jet A, Jet A1 in accordance with ASTM D1655-05, all ambient temperatures.

Note: Jet A and Jet A1 may contain corrosion inhibitor/lubricity improver and icing inhibitors which shall result in properties equal to JP-8.

2.9.6.3 Fuel system. The fuel system shall be in accordance with 3.13.1.5.1 through 3.13.1.5.11 of SAE ARP1247 except as otherwise specified herein. The fuel system shall be constructed of materials which are compatible with the fuels listed in 2.9.6.1 and 2.9.6.2. Copper shall not be used in the fuel system. The fuel system shall be equipped with a fuel shut-off valve(s) to prevent continuous spillage when fuel lines are disconnected for service.

2.9.6.3.1 Fuel priming pump. The Potable Water Truck shall be equipped with an electric fuel pump in addition to the mechanical fuel pump. The electric pump shall be used as a priming pump capable of re-priming the engine fuel system following fuel exhaustion.

2.9.6.3.2 Fuel filters. Primary and secondary fuel filters and a heated fuel/water separator shall be provided. The fuel/water separator shall include a water coalescer and a drain valve that is readily accessible by an operator or a mechanic. A combination fuel filter and fuel/water separator may be provided. Fuel filter elements shall be easily replaceable by a mechanic using nothing more than common hand tools (see 6.3.5) without loss of engine prime.

2.9.6.3.3 Fuel tank. The fuel tank shall be in accordance with 3.13.1.5.5 through 3.13.1.5.9 of SAE ARP1247. The tank shall be designed so that the Potable water truck can be operated on a 20-degree longitudinal slope facing up and down and on an 11.5 degree side slope in each direction (right and left side facing up the slope). The tank shall be provided with corrosion protection and baffles. A 0.25 to 0.375-inch nominal drain valve shall be provided for emptying fuel and sediment into a container underneath the Potable Water Truck without removal of the tank or any other major component. The fuel tank shall have a fuel fill opening of not less than three inch inside diameter and shall be designed to drain fuel spillage overboard for collection outside the Potable Water Truck. The fuel cap shall be equipped with a retention device to prevent loss and FOD. The fuel fill opening, fuel cap, and fuel cap retention device shall be fabricated from non-sparking material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2.9.7 Engine diagnostic and emergency shutdown systems.

2.9.7.1 Engine diagnostic system. If the engine is equipped with an electronic control module, a diagnostic system shall be provided with a means to indicate engine faults; it shall be equipped with a CAN buss connector. If the Potable Water Truck is equipped with a diagnostic or built-in-test system, the engine diagnostic system shall be integrated with it; if not, it shall be a stand-alone system.

2.9.7.2 Engine emergency shutdown system. The engine shall be equipped with an engine emergency shutdown system consisting of a fuel cutoff solenoid activated by the following conditions:

a. Low oil pressure, less than 10 psi or in accordance with the engine manufacturer's recommendations.

b. Coolant over heat or cylinder head temperature over heat condition in accordance with the engine manufacturer's recommendations.

c. Engine over speed should the engine exceed 110% rated speed. This is required for engines over 100 bhp and optional for engines less than 100 bhp rated horsepower.

2.9.8 Engine operator instruments. The following instruments shall be provided to the engine operator:

a. Tachometer.

b. Coolant temperature gauge.

c. Low coolant level indicator.

d. Oil pressure gauge.

e. Oil temperature gauge.

f. Fuel level gauge.

g. Hour meter.

2.10 Electrical system. The Potable Water Truck shall have a 12 Volt DC, negative ground electrical system in accordance with 3.13.1.2 of SAE ARP1247 except as otherwise specified herein.

2.10.1 Alternator. A single or dual alternator charging system in accordance with 3.13.1.4.9 of SAE ARP1247 shall be provided. The alternator shall be capable of restoring the energy expended during an engine start in less than 15 minutes of engine idle at -40 °F.

2.10.2 Batteries and battery compartment.

2.10.2.1 Batteries. Batteries shall be of the commercial (see 6.3.4) maintenance-free sealed lead acid, starved electrolyte, gas recombination, spiral wrapped, absorbent gas mat (AGM), top post type in accordance with MIL-B-18013/1.

2.10.2.2 Battery compartment. The batteries shall be enclosed in a corrosion-resistant, weatherproof box or compartment and shall be readily accessible.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2.10.2.3 Battery cables. The battery cables shall be sized to handle the system voltage and current levels, be clearly identified with "+" and "-" or red and black markings and shall not be spliced.

2.10.3 Winterization System.

2.10.3.1 Engine winterization system. A winterization system shall be provided for starting in temperatures below 0 °F. The winterization system shall include heaters for engine coolant, engine oil, and the fuel tank, as well as battery warmers. The winterization system shall be designed to operate from an external 110/120 Volt AC, 60 Hz power source utilizing the external electrical connections (see 2.10.3.5). The winterization system shall incorporate high-temperature shutoff switches to prevent overheating of any fluid or component. A labeled indicator light shall be installed on the instrument panel to indicate when the vehicle is connected to external power.

2.10.3.2 Cargo tank winterization system. A standby type winterization kit shall be installed for the Potable Water Truck cargo tank. The heater in the cargo tank shall be controlled to limit the maximum water temperature to 60 °F. The winterization system shall be designed to operate from an external 110/120 Volt AC, 60 Hz power source utilizing the external electrical connections (see 2.10.3.5).

2.10.3.3 Pumping compartment winterization system. A standby type winterization kit shall be installed for the Potable Water Truck pumping compartment. The heater in the pumping compartment shall be controlled to limit the maximum air temperature to 150 °F. The winterization system shall be designed to operate from an external 110/120 Volt AC, 60 Hz power source utilizing the external electrical connections (see 2.10.3.5).

2.10.3.4 Indicator light. An indicator light located inside the cab shall be provided to show that the winterization system is on.

2.10.3.5 Plugs and connectors. All plugs and connectors shall be in accordance with NEMA WD 6. A covered male inlet plug shall be used to hook up the external power cable for the engine winterization system.

2.11 Hydraulic system. If a hydraulic system is utilized, it shall be in accordance with 3.13.1.3 of SAE ARP1247 except as otherwise specified herein. O-ring face seal hydraulic fittings may be used in lieu of flared fittings (see 3.13.1.3.12 of SAE ARP1247). Hydraulic fluid shall be in accordance with MIL-PRF-83282. All hydraulic system components, including the hydraulic tank, shall comply with all corrosion resistance requirements specified herein.

2.12 Technical Data.

2.12.1 Manufacturer publications. The contractor shall provide the following manufacturer's publications in Indexed Portable Document Format (IPDF). All data shall be supplied in accordance with DFARS clause 252.227-7015. All manuals shall be delivered with either unlimited data rights or as a minimum, a Government Purpose License, to allow the Air Force to electronically store, print, distribute and update the manual. Manuals are subject to government review and approval in accordance with MIL-PRF-32216. Any changes or corrections noted by the Air Force shall be corrected and updated pages or manuals shall be submitted. Only one digital copy is required per order regardless of quantity of units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2.12.1.1 Operator's manual. The operator's manual shall include all information required for the safe and efficient operation of the vehicle. The operator's manual shall include at least the following:

a. General description and step-by-step instructions for the operation of the vehicle and its auxiliary equipment.

b. Checklists, lubrication charts, and basic troubleshooting procedures for the daily maintenance inspection and mission readiness checks that the operator is expected to perform.

c. Schedules for required preventative maintenance and required periodic maintenance.

d. Full descriptions and illustrations for the location and function of all controls.

e. List of all checks and adjustments needed in preparation for placing the vehicle into service upon receipt from the contractor.

f. Preparation Instructions for shipment or storage.

g. Warranty information and a list that details the period of the warranty for the complete vehicle and for any component that exceeds the warranty of the complete vehicle. Addresses and telephone numbers shall be provided for all warranty providers listed.

2.12.1.2 Service and repair manuals. Service and repair manuals shall be provided for the chassis, engine, transmission, tanker body, and equipment. The service manuals shall identify any special tools and test equipment required and shall cover troubleshooting and maintenance as well as minor and major repair procedures. The text shall contain performance specifications, tolerances, fluid capacities, current data, voltage data, resistance data, test procedures, and any illustrations or exploded views that may be required to perform proper maintenance by qualified mechanics. The service and repair manuals shall contain an alphabetical subject index as well as a table of contents. The manual shall contain at least the following where applicable:

a. Pneumatic, electrical, and fuel schematics.

b. Schedules for required preventative maintenance and required periodic maintenance.

c. Troubleshooting, servicing, disassembly, repair, and assembly procedures.

2.12.1.3 Illustrated parts breakdown. An illustrated parts breakdown (IPB) manual shall be provided for the chassis, engine, transmission, tanker body, and equipment. IPB manuals shall include illustrations and exploded views as needed to properly identify all parts, assemblies, subassemblies, and special equipment. All components of assemblies shown in illustrations or exploded views shall be identified by reference numbers that correspond to the reference numbers in the parts list. All purchased parts shall be cross-referenced with the original manufacturer's name and part number. The IPB manual shall provide the description and quantity of each item used per vehicle. The size, thread dimensions, torque specifications, and special characteristics shall be provided for all nonstandard nuts, bolts, screws, washers, grease fittings, and similar items. The IPB manuals shall contain a numerical index. The manuals shall contain a list of all the component vendor names, addresses, and telephone numbers referenced in the parts list.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2.12.1.4 Manual delivery. Digital copies shall be provided via digital file transfer such as Department of Defense Secure Access File Exchange (DOD SAFE) and shall be furnished to AFLCMC/WROZ a minimum of 30 days prior to the first hardware delivery. Contact the appropriate Integrated Product Team Equipment Specialist for file delivery instructions.

2.12.2 Service bulletins. The contractor shall prepare service bulletins as required to notify the government of new maintenance problems and/or procedures to be implemented on the contractor's equipment prior to the issuance of permanent changes to the technical manuals. Service bulletins shall also be prepared when the program office has identified a trend of a potential problem or failure that has occurred at field level. The service bulletins shall identify any potential safety hazards and shall be submitted in a Microsoft Office digital format.

2.13 Workmanship. The Potable Water Truck, including all parts and accessories, shall be constructed and finished in a thoroughly workmanlike manner. Workmanship objectives shall include freedom from blemishes, defects, burrs and sharp corners and edges; accuracy of dimensions, surface finish, and radii of fillets; thoroughness of welding, painting, and riveting; marking of parts and assemblies; and proper alignment of parts and tightness of assembly fasteners.

2.13.1 Bolted connections. Bolt holes shall be accurately punched or drilled and shall be deburred. Threaded fasteners shall be tight and shall not work loose during testing or service usage.

2.13.2 Riveted connections. Rivet holes shall be accurately punched or drilled and shall be deburred. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the component.

2.13.3 Gear and lever assemblies. Gear and lever assemblies shall be properly aligned and meshed and shall be operable without interference, tight spots, loose spots, or other irregularities. Where required for accurate adjustment, gear assemblies shall be free of excessive backlash.

2.13.4 Cleaning. The Potable Water Truck shall be thoroughly cleaned. Loose, spattered, or excess solder; welding slag; stray bolts, nuts, and washers; rust; metal particles; pipe compound; and other foreign matter shall be removed during and after final assembly.

3. REGULATORY REQUIREMENTS.

3.1 Recycled, recovered, environmentally preferable, or biobased materials. Recycled, recovered, environmentally preferable, or biobased materials should be used to the maximum extent possible, provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with 23.403 of the Federal Acquisition Regulation (FAR). However, used, rebuilt, or refurbished items shall not be provided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

3.2 Green Procurement Program. Green Procurement Program (GPP) is a mandatory federal acquisition program that focuses on the purchase and use of environmentally preferable products and services. GPP requirements apply to all acquisitions using appropriated funds, including services and new requirements. FAR 23.404(b) applies and states the GPP requires 100% of EPA designated product purchase that are included in the Comprehensive Procurement Guidelines list that contains recovered materials, unless the item cannot be acquired: a) competitively within a reasonable timeframe; b) meet appropriate performance standards, or c) at a reasonable price. The prime contractor is responsible for ensuring that all subcontractors comply with this requirement.

4. PRODUCT CONFORMANCE PROVISIONS.

The products provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace, modified as necessary to comply with the requirements herein. The Government reserves the right to require proof of such conformance.

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First production inspection (see 4.2).

b. Conformance inspection (see 4.3).

4.2 First production inspection. The first production Potable Water Truck shall be subjected to the analyses, examinations, and certifications described in 4.5.1 through 4.5.7. The contractor shall provide or arrange for all test equipment and facilities. Except as otherwise specified, all testing in which the engine is operated shall be performed using JP-8 turbine fuel.

4.3 Conformance inspection. Each production Potable Water Truck shall be subjected to the examination described in 4.5.1.

4.4 Inspection requirements.

4.4.1 General inspection requirements. Apparatus used in conjunction with the inspections specified herein shall be laboratory precision type, calibrated at proper intervals to ensure laboratory accuracy.

4.4.2 Data. During all testing specified herein, at least the following data, unless not applicable, shall be recorded at intervals not to exceed 30 minutes. Additional data or shorter intervals shall be provided as appropriate for any specific test.

a. Date.

b. Time started.

c. Time finished.

d. Ambient temperature.

e. Ambient humidity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

4.4.3 Test rejection criteria. Throughout all tests specified herein, the Potable Water Truck shall be closely observed for the following conditions, which shall be cause for rejection.

a. Failure to conform to design or performance requirements specified herein or in the contractor's technical proposal.

b. Any spillage or leakage of any liquid, including fuel, coolant, lubricant, or hydraulic fluid, under any condition, except as allowed herein.

c. Thermal or structural failure of any component, including permanent deformation, or evidence of impending failure.

d. Evidence of excessive wear. If excessive wear is suspected, the original equipment manufacturers (OEM's) specifications or tolerances shall be utilized for making a determination.

e. Evidence of corrosion or deterioration.

f. Misalignment of components.

g. Conditions that present a safety hazard to personnel during operation, servicing, or maintenance.

h. Interference between the Potable Water Truck components or between the Potable Water Truck, the ground, and all required obstacles, with the exception of normal contact by the tires.

i. Evidence of undesirable mobility characteristics, including instability in handling during cornering, braking, and while traversing all required terrain.

j. Shutdown faults from:

1) Engine cooling system.

2) Engine lubrication system.

3) Engine protective circuits.

4.5 Test methods.

4.5.1 Examination of product. Each Potable Water Truck shall be examined to verify compliance with the requirements herein prior to accomplishing any other demonstrations or tests listed in 4.5. A contractor-generated, Government-approved checklist (part of the test procedure) shall be used to identify each requirement not verified by an analysis, certification, demonstration, or test, and shall be used to document the examination results. Particular attention shall be given to materials, workmanship, dimensions, surface finishes, protective coatings and sealants and their application, welding, fastening, and markings. Proper operation of each Potable Water Truck function shall be verified. Certifications and analyses shall be provided in accordance with Table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

TABLE III. Certifications and analyses.

Paragraph	Required Certifications and Analyses
2.2.5 Electromagnetic Interference (EMI).	Contractor certification that the Potable Water Truck is in accordance with MIL-STD-461: RE 102 and RS 103 to demonstrate compliance with 2.2.5.
2.3.1 Operating temperature range, 2.3.2 Storage temperature range, 2.10.1 Alternator.	Contractor certification that the Potable Water Truck is in accordance with the required temperature ranges as well as meeting the engine starting and alternator charging requirements.
2.3.3.1 Rain.	Contractor certification that the Potable Water Truck is capable of withstanding the rainfall requirements set forth in 2.3.3.1.
2.3.3.2 Snow.	Contractor certification that the snow specifications meet the requirements (see 4.5.4.3.2).
2.3.3.3 Ice.	Contractor certification that the Potable Water Truck is capable of withstanding the ice requirements set forth in 2.3.3.3.
2.3.4 Solar radiation.	Contractor certification that the Potable Water Truck performance is not adversely affected by full time exposure to solar radiation, such as those conditions encountered in desert environments.
2.3.5 Fungus.	Contractor certification that the materials used in construction of the Potable Water Truck are fungus resistant or suitably treated to resist fungus.
2.3.6 Salt fog.	Contractor certification that the materials used in the construction of the Potable Water Truck are capable of withstanding the salt fog requirements set forth in 2.3.6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

TABLE III. Certifications and analyses - Continued.

Paragraph	Required Certifications and Analyses
2.3.7 Sand and dust.	Contractor certification that the Potable Water Truck is capable of withstanding the sand and dust requirements set forth in 2.3.7.
2.2.4.5 Noise.	Contractor certification that the Potable Water Truck meets the noise requirements set forth in 2.2.4.5.
2.5.1 Surface transportability.	Contractor surface transportability analysis (see 4.5.6.1.1) and certification that the Potable Water Truck is transportable via all modes of surface shipment (highway, rail, and water) in accordance with MIL-STD-1366 and shall be capable of withstanding the mechanical shock and vibration characteristics of highway, rail, and water transport.
2.5.2 Tie downs.	Contractor tie down provision analysis (see 4.5.6.2.1).
2.8 Mobility.	Contractor certification that the Potable water Truck meets all requirements set forth in 2.8 parts a - j.
2.9 Engine and related equipment, 2.9.3 Engine cooling system, 2.9.4 Engine lubrication system, 2.9.6.1 Engine primary fuels, 2.9.6.2 Engine alternate fuels, and 2.9.6.3 Engine emergency fuels.	Engine manufacturer certification that the engine is in accordance with all applicable requirements, including exhaust emissions standards and fuels. Engine manufacturer application approval for the engine and its installation, including cooling system, lubrication system, and mounting system.

4.5.2 Noise test. Certification for noise requirements are acceptable in lieu of testing (See Table III).

4.5.3 Electromagnetic interference test. Certification for EMI requirements are acceptable in lieu of testing (See Table III).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

4.5.4 Environmental testing. Certifications for environmental requirements are acceptable in lieu of testing (See Table III).

4.5.4.1 High temperature storage and operation test. Certifications for high temperature storage and operation shall be acceptable in lieu of testing (See Table III).

4.5.4.2 Low temperature storage and operation test. Certifications for low temperature storage and operation requirements are acceptable in lieu of testing (See Table III).

4.5.4.3 Precipitation.

4.5.4.3.1 Rain test. Certifications for rain requirements are acceptable in lieu of testing (See Table III).

4.5.4.3.2 Snow load test. Certification for snow testing shall be acceptable in lieu of a first article test (See Table III).

4.5.4.3.3 Ice accretion test. Certifications for ice accretion requirements are acceptable in lieu of testing (See Table III).

4.5.4.4 Salt fog test. Certifications for salt fog requirements are acceptable in lieu of testing (See Table III).

4.5.4.5 Sand and dust test. Certifications for sand and dust requirements are acceptable in lieu of testing (See Table III).

4.5.5 Weight and dimension tests.

4.5.5.1 Weight and center of gravity test. The weight and center of gravity of a first production Potable Water Truck shall be measured to demonstrate compliance with the weight requirement of 2.4.

4.5.5.2 Dimension measurement. A first production Potable Water Truck shall be measured to demonstrate compliance with the dimensional requirements of 2.4.

4.5.6 Transportability verification.

4.5.6.1 Surface transportability verification.

4.5.6.1.1 Surface transportability analysis. An engineering analysis shall be performed to demonstrate compliance with 2.5.1. The engineering analysis shall utilize the data for road transportation in accordance with MIL-STD-810, Method 514.7, Table 514.7C-II.

4.5.6.2 Tie down provision verification.

4.5.6.2.1 Tie down provision analysis. An engineering analysis shall be performed to demonstrate compliance with the tie down provision requirements of 2.5.2.

4.5.7 Performance test. A first production Potable Water Truck shall be tested to demonstrate compliance with the performance provision requirements of 2.7.

4.5.8 Mobility tests. Certifications for mobility requirements shall be acceptable in lieu of testing (See Table III).

5. PACKAGING. Preservation, packing, and marking shall be as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

6. NOTES.

6.1 Source of documents.

6.1.1 Government Documents. Copies of Military Specifications, Standards, and Handbooks are available online at https://quicksearch.dla.mil.

6.1.2 Air Force Instructions (AFI). Copies of AFIs are available online at https://www.e-publishing.af.mil.

6.1.3 Code of Federal regulations (CFR). Copies of the CFR are available online at https://www.ecfr.gov.

6.1.4 Advancing Standards Transforming Markets (ASTM). Copies of the ASTM are available online at https://www.astm.org.

6.1.5 Society of Automotive Engineers (SAE). Copies of the SAE may be obtained from https://www.sae.org.

6.1.6 Technology and Maintenance Council (TMC). Copies of the TMC may be obtained from https://www.trucking.org.

6.1.7 Federal Acquisition Regulation (FAR). Copies of the FAR are available online at https://www.acquisition.gov.

6.1.8 Federal Motor Vehicle Safety Standard (FMVSS). Copies of the FMVSS are available online at https://www.ecfr.gov.

6.1.9 Environmental Protection Agency (EPA). Copies of the EPA are available online at https://www.epa.gov.

6.1.10 Tire and Rim Association Year Book. Copies of the Tire and Rim Association Year Book are available online at https://www.us-tra.org.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this CID.

b. Finish color required (Semi-gloss green or tan (see 2.2.1.2)).

c. If an EPA Tier III diesel engine is required (see 2.9).

d. Packaging requirements (see section 5).

6.3 Definitions.

6.3.1 Alternate fuel. A fuel that can be used in place of the primary fuel with a possible loss of efficiency, engine adjustments may be necessary. The use of an alternate fuel may result in a change of maintenance or overhaul cost.

6.3.2 Belgian-block. A Belgian-block course consists of a very rough, undulating, hard surface unaffected by changes in climatic conditions. The standard is found at Aberdeen Proving Grounds, Maryland.

6.3.3 Cobblestone. A naturally rounded stone larger than a pebble and smaller than a boulder; *especially*: such a stone used in paving a street or in construction.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

6.3.4 Commercial item.

a. Any item, other than real property, that is of a type customarily used by the general public or by non-Governmental entities for purposes other than Governmental purposes, and:

1) Has been sold, leased, or licensed to the general public; or

2) Has been offered for sale, lease, or license to the general public.

b. Any item that evolved from an item described in paragraph (a) of this definition through advances in technology or performance and that is not yet available in the commercial marketplace but will be available in the commercial marketplace in time to satisfy the delivery requirements under a Government solicitation.

c. Any item that would satisfy a criterion expressed in paragraphs (a) or (b) of this definition, but for:

1) Modifications of a type customarily available in the commercial marketplace; or

2) Minor modifications of a type not customarily available in the commercial marketplace made to meet Federal Government requirements. Minor modifications means modifications that do not significantly alter the non-Governmental function or essential physical characteristics of an item or component or change the purpose of a process. Factors to be considered in determining whether a modification is minor include the value and size of the modification and the comparative value and size of the final product. Dollar values and percentages may be used as guideposts but are not conclusive evidence that a modification is minor.

d. Any combination of items meeting the requirements of paragraphs (a), (b), (c), or (e) of this definition that are of a type customarily combined and sold in combination to the general public.

e. Installation services, maintenance services, repair services, training services, and other services if:

1) Such services are procured for support of an item referred to in paragraph (a), (b), (c), or (d) of this definition, regardless of whether such services are provided by the same source or at the same time as the item; and

2) The source of such services provides similar services contemporaneously to the general public under terms and conditions similar to those offered to the Federal Government.

f. Services of a type offered and sold competitively in substantial quantities in the commercial marketplace based on established catalog or market prices for specific tasks performed or specific outcomes to be achieved and under standard commercial terms and conditions. For purposes of these services:

1) “Catalog price” means a price included in a catalog, price list, schedule, or other form that is regularly maintained by the manufacturer or vendor, is either published or otherwise available for inspection by customers, and states prices at which sales are currently, or were last, made to a significant number of buyers constituting the general public; and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

2) "Market prices" means current prices that are established in the course of ordinary trade between buyers and sellers free to bargain and that can be substantiated through competition or from sources independent of the offerors.

g. Any item, combination of items, or service referred to in paragraphs (a) through (f) of this definition, notwithstanding the fact that the item, combination of items, or service is transferred between or among separate divisions, subsidiaries, or affiliates of a contractor; or

h. A non-developmental item, if the procuring agency determines the item was developed exclusively at private expense and sold in substantial quantities, on a competitive basis, to multiple State and local Government. (Reference the Federal Acquisition Regulation (FAR) 2.101)

6.3.5 Common hand tool. A non-powered tool that is likely to be found in a typical mechanic's toolbox. Common hand tools include open end, boxed end, combination, socket (both 6 and 12-point in both standard and deep-well), and hex key wrenches, in SAE sizes up to and including 1-inch and metric sizes up to and including 25mm; ratchet handles, extensions, and swivels; slotted and Phillips-head screwdrivers; regular and snap-ring pliers; and a ball-peen hammer.

6.3.6 Cross-country terrain. Cross-country terrain consists of unimproved open fields, broken ground, loose sand, and gravel road encountered by tactical vehicles supporting an army in the field.

6.3.7 Emergency fuel. A fuel that can be used when the primary and alternate fuels are not available. This fuel is not for use on a continuing basis but is to be only when the primary and alternate fuel and equipment fuels are unobtainable and operation is mission essential. Engine life could be severely impacted.

6.3.8 Gravel road. A gravel road is a level or rolling gravel trail.

6.3.9 Primary fuel. The fuel or fuels used during tests to demonstrate system performance (contract compliance). Substitutions are presented as Alternate and Emergency fuels.

6.3.10 Special tool. A tool that is not commercially and readily available from a source other than the Potable Water Truck contractor.

6.4 Key words.

Airplane water
Drinking water
Elastomers
Engine
Welds

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

MILITARY INTEREST

Custodian:
Air Force - 184

Preparing activity:
Air Force - 184

(Project 1730-2026-008)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.