INCH-POUND
A-A-60094
06 August 2026

COMMERCIAL ITEM DESCRIPTION

PULLEY, MINI PRUSIK

The General Services Administration has authorized the use of this Commercial Item Description (CID) by all federal agencies.

1. SCOPE. This CID covers the requirements for the pulley, mini prusik that enable the user to put the rope in the pulley without having to thread the rope through the pulley.

2. CLASSIFICATION. The pulley, mini prusik shall be offered in a single type and size only.

3. SALIENT CHARACTERISTICS.

3.1 Design and construction. The pulley, mini prusik shall have split halves that enable the user to put the rope in the pulley without having to thread the rope through the pulley. The pulley sides and wheel shall be fabricated from aluminum. The center bolt shall have a shaft fabricated from steel. The pulley wheel shall have sealed roller bearings and be large enough to accommodate a 7mm to 11mm diameter rope. The snap link hole shall be large enough to accommodate two snap links. Minimum breaking strength shall be 5170 pounds (23Kn). Maximum weight shall be 0.2 pounds (80 Grams). Maximum working load shall be 562 pounds x 2=1124 pounds (2.5 kN x 2 = 5 kN). The manufacturer's identification symbol and Working Load Limit (WLL), shall be stamped on each pulley assembly.

3.2 Certification. The contractor shall certify, and maintain substantiating evidence, that the product offered meets the salient characteristics and requirements of this CID, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices, as well as CE EN 12278 https://www.satra.com/ppe/EN12278.php and NFPA 2500 https://www.nfpa.org/product/nfpa-2500-standard. The Government reserves the right to request proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Beneficial comments, recommendations, additions, deletions, clarifications, and any other data that may improve this document should be sent to trpsptctstandardiz@dla.mil.

AMSC N/A FSC 3020

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

3.3 Barcode hang tag. Each pulley, shall have a barcode label/hangtag conforming to Type VIII, Class 18 of MIL-DTL-32075. The bar coding element shall be a 13-digit National Stock Number (NSN). There shall be a 12-digit Universal Product Code (UPC) number assigned for all NSNs by the contracting activity. The initials "UPC" must appear beneath the code. The barcode for NSN and UPC type shall be a medium to high density.

4. REGULATORY REQUIREMENTS. Unless otherwise specified, the offeror/contractor is encouraged to use recovered, recycled, bio based, and environmentally preferable materials to the maximum extent practicable, in accordance with paragraph 23.403, 23.404(b) of the Federal Acquisition Regulation (FAR), or the sustainable acquisition of EO 13834; as applicable. (see 7.1.2 and 7.1.3).

5. PRODUCT CONFORMANCE PROVISIONS.

5.1 Product conformance. The pulley, mini prusik shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance.

5.2 Market acceptability. The finished pulley offered must have been sold to the government or commercial market.

5.3 Inspection procedures. Sampling for inspection shall be conducted in accordance with ASQ/ANSI Z1.4 - Sampling Procedures and Tables for Inspection of Attributes (see 7.2.1)

5.3.1 Visual examination. Each lot of pulleys shall be inspected in accordance with ASQ/ANSI Z1.4 The lot size shall be expressed in units of pulleys. The sample unit shall be one (1) pulley. Each finished pulley, mini prusik shall be examined for the defects listed in Table I as defined in ASTM D3990.

THIS SPACE LEFT INTENTIONALLY BLANK

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual examination.

Examine	Defect Description
Construction	Not free of burrs, rough spots, slivers, flat areas or projections. Any component loose, missing or not specified type Any component fractured, slit, punctured, dented, bowed, malformed or damaged. Marking etched or indented, contains rough or sharp edges.
Labels/barcoding/instruction slip (if applicable)	Incorrect, illegible, omitted or misplaced.
Finish	Not smooth and adherent; not free of burrs, rough spots, sharp edges. slivers, flat areas or projections; any component missing or not specified type; any component fractured, spilt, dented, bowed, malformed, damaged or loose; shaft nut turns freely on the bolt; all other parts do not rotate freely through 360 degrees rotation; markings in wrong location, incomplete, illegible, or not as specified.
Marking	Omitted, missing information or illegible.

5.3.2 Dimensional examination. The finished pulley, mini prusik shall conform to the dimensions specified. Any dimension that is not within the established tolerance shall be classified as a defect. The sample unit shall be one (1) pulley, mini prusik.

5.4 Acceptance criteria. Acceptance criteria shall be specified in the contract or procurement documents (see 7.5).

6. PACKAGING. The preservation, packing and marking shall be as specified in the contract or order (see 7.5).

7. NOTES

7.1 Sources of Government documents:

7.1.1 Copies of Government documents are available online at https://quicksearch.dla.mil.

7.1.2 Federal Acquisition Regulations (FAR) are available online at https://aquisition.gov.

7.1.3 EPA information is available online at https://www.epa.gov and EO 13834 information is available online at https://www.fedcenter.gov/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

7.2 Source of non-Government documents.

7.2.1 ASQ/ANSI Z1.4 – Sampling Procedures are available online at https://asq.org.

7.2.2 ASTM Standards are available for purchase online at https://www.astm.org.

7.2.3 CE EN 12278 for purchase online at https://www.satra.com/ppe/EN12278.php and NFPA 2500 https://www.nfpa.org/product/nfpa-2500-standard.

7.3 Intended use. The pulley, mini prusik is intended to be used for climbing during mountaineering rescue missions.

7.4 Certificate of compliance. The contracting activity may select to accept a certificate of compliance for a stated requirement.

7.5 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this CID.
b. Design and construction. (3.1)
c. Product conformance (see 5.1).
d. Acceptance criteria (see 5.4).
e. Packaging requirements (see 6.).

7.6 Key words.

Climbing
Mountaineering
Rescue

MILITARY INTERESTS:

Custodians:
Army - GL
Navy - NU
Air Force - 11

Review activities:
Navy - MC

CIVIL AGENCY COORDINATING ACTIVITY
GSA-FAS

Preparing activity:
DLA-CT

(Project: 3020-2026-001)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.