DATA ITEM DESCRIPTION

Title: TEST REQUIREMENTS DOCUMENT (TRD)

Number: DI-ATTS-80041B
Approval Date: 20230929
AMSC Number: F7229
Limitation: N/A
DTIC Applicable: No
GIDEP Applicable: No
Preparing Activity: 11 (AFLCMC/WNA)
Project Number: ATTS-2023-001
Applicable Forms: N/A

Use/Relationship:

This Data Item Description (DID) contains the format, content, and intended use information for the data deliverable resulting from the work task described in the solicitation.

This DID is applicable to engineering (developmental), preliminary qualification, qualification, and acceptance testing.

This DID supersedes DI-ATTS-80041A.

Requirements:

1. Reference documents. The applicable issue of the documents cited herein, including their approval dates and dates of any applicable amendments, notices, and revisions, shall be as specified in the contract.

2. Format. Contractor format is acceptable.

3. Content. The TRD shall include four parts for each item being tested. All test parameters and test conditions shall be independent of any specific test equipment's. The TRD shall include the following information.

3.1 Part A – A detailed description of the performance characteristics of each system, subsystem, unit, and subassembly (referred to as Units-Under-Test (UUT)) and a summary of the total testing requirements including input conditions, outputs measurements, and test points.

a. Functional name of the UUT and supplier's part numbers.

b. All inputs and their range and tolerance.

c. All outputs in terms of their range, accuracy, and relationship to the input conditions.

d. All test points identified by test connector, pin designator, function, and signal (input and output) conditions. This will include the specific parameters that can be measured at the test point and the value(s) expected.

3.2 Part B – The performance tests required to complete exercise the UUT in various modes of operation to reveal any degradation in performance characteristics.

3.3 Part C – The diagnostic tests and support equipment required to isolate and diagnose a fault(s) detected during the UUT performance testing. Fault isolation will be to the lowest component part possible.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.

3.4 Part D – The Automatic Test Markup Language (ATML) for the Part B performance tests and the Part C diagnostic tests in accordance with Institute of Electrical and Electronic Engineers Standards 1671.1 and 1671.3. (Copies of these standards are available online at https://www.ieee.org/.)

End of DI-ATTS-80041B

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:33Z
Check the source to verify that this is the current version before use.