MIL-I-81548(AS)
26 July 1967
Superseding
WS 4376
24 February 1965

MILITARY SPECIFICATION

IGNITION ELEMENT, ELECTRIC, MARK 22 MOD 0

This specification has been approved by the Naval Air Systems Command, Department of the Navy.

1. SCOPE

1.1 This document governs the manufacture, assembly and preparation for delivery of the MARK 22 MOD 0 electric ignition element and the methods of inspection and tests upon which product acceptance will be based.

2. APPLICABLE DOCUMENTS

2.1 The following specifications, standards, drawings and publications, of the issue in effect on date of invitation for bids, form a part of this document to the extent specified herein.

SPECIFICATIONS

Military

MIL-D-21625	Design and Evaluation of Cartridges for Cartridge Actuated Devices
MIL-P-116	Preservation, Methods of

STANDARDS

Military

MIL-STD-414	Sampling Procedures and Tables for Inspection by Variables for Percent Defective
MIL-STD-129	Marking for Shipment and Storage

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:35Z
Check the source to verify that this is the current version before use.

DRAWINGS

Bureau of Naval Weapons

DL 2518291	Ignition Element, Electric MARK 22 MOD 0

PUBLICATIONS

BUSANDA Instruction 4030.17	Preservation, Packaging, Packing and Marking; Navy Policy for

Bureau of Naval Weapons

WR-43	Preparation of Quality Assurance Provisions

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.2 Other publications. The following document forms a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

CODE OF FEDERAL REGULATIONS

49 CFR 71-78	Transportation, Interstate Commerce Commission, Explosives and Other Dangerous Articles

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D. C. 20402. Orders for the above publication should cite the latest edition and supplements thereto.)

3. REQUIREMENTS

3.1 General.

3.1.1 The MARK 22 MOD 0 electric ignition element covered by this specification shall be manufactured in accordance with DL 2518291 and all documents listed thereon.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:35Z
Check the source to verify that this is the current version before use.

3.2 Material. All materials used in the manufacture of the ignition elements shall conform strictly with the specifications referred to on the respective Bureau of Naval Weapons drawings unless specific approval in writing covering a departure therefrom has been obtained from the Navy design activity prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

3.2.1 Preproduction sample. Unless otherwise specified by the procuring activity, a preproduction sample of 76 MARK 22 MOD 0 electric ignition elements shall be manufactured using the same methods and procedures proposed for the production lot. The sample shall be tested as specified in 4.3.2 and is for the purpose of determining that the contractor, prior to starting production, is capable of producing items which comply with the technical requirements of the contract.

3.3 Primary components. For the purpose of this specification, the primer mix and pellet sustainer (Bureau of Naval Weapons Drawings 2406487 and 2518300, respectively, of DL 2518291) are defined as primary components. See 4.3.3.

3.4 Test equipment and facilities. The supplier shall furnish and maintain all necessary test equipment, gages, facilities and personnel for the performance of all tests, where required. The test equipment shall be adequate in quantity and of sufficient accuracy and quality to permit satisfactory performance of the required tests.

3.5 Insulation resistance. Prior to the assembly of the bridgewire, the insulation resistance shall not be less than 50 megohms at a relative humidity of less than 80 percent when measured with a 500 volt megohmmeter. See 4.7.1.

3.6 Bridgewire. The bridgewire shall be resistance welded to the three electrodes. The welding process shall be as specified on the applicable drawing.

3.7 Primer composition and loading. The primer mix, for the prime and main charges, shall be compounded and loaded in accordance with Bureau of Naval Weapons Drawings 2406487 and 2518291, respectively, of DL 2518291. All charges shall be determined by weight rather than by volume measurements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:35Z
Check the source to verify that this is the current version before use.

3.8 Sustainer pellet. The sustainer pellet shall be compounded and loaded in accordance with Bureau of Naval Weapons Drawings 2518300 and 2518291, respectively, of DL 2518291.

3.9 Electric ignition element inspection.

3.9.1 Visual inspection. The complete ignition element shall be free of the visible defects noted in 4.7.2

3.9.2 Bridge circuit resistance. The resistance of each bridge circuit in each completely assembled ignition element manufactured, when measured electrically as specified in 4.7.3, shall be not less than 0.9 ohm or more than 1.1 ohms.

3.9.3 Leakage. There shall be no leakage of air in the completed ignition element. See 4.7.4.

3.9.4 X-ray. All ignition elements shall pass X-ray examination of 4.7.5.

3.10 Ballistic requirements. Electric ignition elements from each production lot, selected in accordance with 4.7.6, shall meet the requirements listed below when subjected to the tests prescribed in 4.7.6.

3.10.1 Maximum chamber pressure. The upper (U) and lower (L) limits of maximum chamber pressure shall be 2275 psi and 1475 psi, respectively.

3.10.2 Misfire. There shall be no misfires. See 4.7.6.2.

3.10.3 Hangfire. There shall be no hangfires. See 4.7.6.3.

3.11 Workmanship. Electric ignition elements shall be constructed and finished in a manner to assure compliance with all requirements of this specification. Particular attention should be directed to dimensions, finishes and coatings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:35Z
Check the source to verify that this is the current version before use.

4.2 Sampling. Unless otherwise specified, and when applicable the sampling plans and procedures used in the determination of the acceptability of products submitted by a supplier shall be in accordance with the provisions of MIL-STD-414. Unless otherwise specified in the contract, order or requisition, all samples for test purposes shall be provided at the expense of the contractor.

4.3 Lots.

4.3.1 Inspection lots. Inspection lot definition, formation and size shall be in accordance with MIL-STD-414.

4.3.2 Preproduction sample. Before entering into quantity production, an acceptable preproduction sample of 76 MARK 22 MOD 0 electric ignition elements shall be prepared. A preproduction sample acceptable for environmental and ballistic testing shall be defined as a sample which has met the requirements of paragraphs 3.1 through 3.9.4 of this specification. The contractor shall deliver the ignition elements to the activity designated by the contracting agency for test. Listed below are the environmental tests to be performed on the preproduction sample followed by the number of ignition elements required for each test: 15 "g" shock (6), vibration (6), temperature and humidity cycling (18). These ignition elements, subsequent to exposure to the environmental tests described in MIL-D-21625, are to be conditioned for 12 hours at +70°F ± 5°F together with 12 additional ignition elements and fired in accordance with paragraph 4.7.6 of this document. In addition, 12 ignition elements each shall be conditioned for 12 hours at -65°F ± 5°F and +160°F ± 5°F and fired as prescribed in 4.7.6 to check temperature sensitivity. No ignition element shall produce results outside the limits of 3.10.1. There shall be no misfires or hangfires. Remaining ignition elements, as required, will be used for investigative purposes. Any quantity production prior to notification by the contracting agency of preproduction sample acceptability shall be at the contractor's risk. The preproduction ignition elements will not be applied as part of the quantity specified for delivery by the contract. Electric ignition elements shall be prepared for delivery in accordance with Section 5 of this document.

4.3.3 Production lot. The suggested production lot size is 111 minimum and 300 maximum electric ignition elements. Ignition elements required for all test purposes are selected from the production lot and will not be applied as a part of the quantity specified for delivery by the contract. Only primary components from a single lot shall be used in a production lot of electric

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:35Z
Check the source to verify that this is the current version before use.

ignition elements, but one primary component production lot may be used in more than one ignition element production lot. Electric ignition elements selected for the ballistic test shall be delivered to the activity designated by the contracting agency.

4.4 Gages. The contractor shall provide gages as necessary to insure that the material to which this specification applies will meet the dimensional requirements shown on the applicable drawings.

4.5 Classification of characteristics. The characteristics verified by the tests and examinations herein are classified as Critical, Major or Minor in accordance with WR-43. Tests and examinations that verify critical characteristics are identified by the symbol (C) and major characteristics by the symbol (M). The number following the classification symbol indicates the serial number of test or examination. Tests and examinations which are not annotated with a classification code are classified minor.

4.6 Production and acceptance inspection. Production and acceptance inspection shall consist of verification of the characteristics classified on the drawings of DL 2518291 and the following tests and examinations.

Item	Nature of Test	Requirement	Test	Classification (WR-43)
Primary Component	Single Lot Verification	3.3	4.3.3	(M101)
Pins and Body Assembly	Insulation Resistance	3.5	4.7.1	(M102)
Bridgewire	Welding Verification	3.6	---	(M103)
Prime and Main Charges	Compounding and Loading Verification	3.7	---	(M104)
Sustainer Pellet	Compounding and Loading Verification	3.8	---	(M105)
Ignition Element	Visual Inspection	3.9.1	4.7.2	(M106)
Ignition Element	Bridge Circuit Resistance	3.9.2	4.7.3	(C5)
Ignition Element	Leakage	3.9.3	4.7.4	(C6)
Ignition Element	X-ray	3.9.4	4.7.5	(C7)
Ignition Element	Ballistic Requirements	3.10	4.7.6	(C8)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:35Z
Check the source to verify that this is the current version before use.

4.6.1 Packing, packaging and markings. (M107) The inspector shall ascertain that the packing and packaging of the electric ignition elements and the container markings conform to Section 5 of this specification.

4.7 Tests.

4.7.1 Insulation resistance. Prior to assembly of the bridgewire in the bridgewire cavity, the insulation resistance shall be checked with a 500 volt megohmmeter. Units with a resistance of less than 50 megohms shall be rejected.

4.7.2 Visual inspection. Examine each electric ignition element produced under a contract and reject for dents, deep scratches, damaged or incomplete threads, torn or perforated closure discs, sharp edges, burrs, etc.

4.7.3 Bridge circuit resistance. Conformance with the bridge circuit resistance of 3.9.2 shall be ascertained by means of a test circuit which limits the bridge current to 50 milliamperes, maximum. A safety chamber with an interlock switch shall be used to protect the operator during the application of the current. A suitable bridge which is known to be accurate within 0.005 ohm in the range of resistance specified shall be used to determine whether or not the requirement is being met. Units which conform to the requirements of 3.9.2 shall be acceptable.

4.7.4 Leakage. Each electric ignition element in the preproduction sample or ballistic sample will be leak tested in a dry gas leak tester. Ignition elements which exhibit a leak rate in excess of 10^{-5} cc/sec air at a pressure differential of one atmosphere shall be considered defective. If one or more ignition elements of the ballistic sample leak, then a leak test of each ignition element purchased under contract for the lot being tested shall be required. If a 100% leak test of the lot is required it shall be at the expense of the contractor. Ignition elements which exhibit a leak rate in excess of that specified above shall be rejected.

4.7.5 X-ray examination. Examine all ignition elements by X-ray and any observable imperfections in assembly shall be cause for rejection. X-ray plates may be destroyed after ballistic acceptance of ignition elements.

4.7.6 Ballistic tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:35Z
Check the source to verify that this is the current version before use.

4.7.6.1 The number of electric ignition elements selected from each production lot for the ballistic tests shall be in accordance with the requirements of Table A-2 of MIL-STD-414, Inspection Level IV and an AQL of 0.04. Ten additional ignition elements shall be furnished. These will be retained by the test activity for investigative purposes. The ignition elements shall be conditioned for 24 hours at +70°F ± 5°F and fired in a 31.8 cubic centimeter closed chamber having a length to diameter ratio of approximately one. Firing current shall be 5.0 ± 0.3 amperes DC.

4.7.6.1.1 Maximum chamber pressure. The instrumentation used shall record the chamber pressure within an accuracy of 2.0 percent. Ignition elements which meet the requirements of 3.10.1 at an AQL of 0.04 shall be acceptable.

4.7.6.2 Misfire. The failure of any electric ignition element to fire shall result in rejection of the lot represented, unless such failure is plainly attributable to faulty test equipment or procedure.

4.7.6.3 Hangfire. One or more hangfires shall result in rejection of the lot represented. If the time lapse from application of current to first indication of pressure exceeds 0.050 second, the ignition element shall be considered defective and the sample lot considered unacceptable. Time measurement shall be recorded for each ignition element firing.

4.8 Retest. There shall be no retests.

4.8.1 Test failure. If test failure is attributable to an assignable cause, excluding the ignition elements, original test results should be discarded and the complete test reconducted.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. For definitions of packaging levels, see 6.4.

5.1.1 Level A. Level A packaging shall be used for packaging of all production lots for service use. Two electric ignition elements shall be packaged in an inner container in accordance with Bureau of Naval Weapons Drawing 2518304 of DL 2518291.

5.1.2 Level B. Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:35Z
Check the source to verify that this is the current version before use.

5.1.3 Level C. When directed by the procuring activity, those ignition elements which are intended for expenditure in preproduction sample testing and for production lot acceptance tests shall be packaged in accordance with Method III of MIL-P-116, and with the Code of Federal Regulations 49 CFR 71-78.

5.2 Packing. For definitions of packing levels, see 6.4.

5.2.1 Level A. Level A packing shall be used for packing of all production lots for service use. Six inner containers as described in 5.1.1 shall be packed in accordance with Bureau of Naval Weapons Drawing 2518303 of DL 2518291.

5.2.2 Level B. Not applicable.

5.2.3 Level C. When directed by the procuring activity, those ignition elements which are intended for expenditure in preproduction sample testing and for production lot acceptance tests and are packaged in accordance with 5.1.3 shall be packed to afford protection against damage during direct shipment from the supply source to the first receiving activity for immediate use. Shipping containers shall be in accordance with the Code of Federal Regulations 49 CFR 71-78.

5.3 Markings.

5.3.1 Special markings. Marking of exterior containers shall be in accordance with the Code of Federal Regulations 49 CFR 71-78.

5.3.2 Normal markings. In addition to the markings required by contract or order, and as specified on Bureau of Naval Weapons Drawing 2518303 and 2518304 of DL 2518291, unit packages and shipping containers shall be marked in accordance with the requirements of MIL-STD-129.

6. NOTES

6.1 Intended use. The MARK 22 MOD 0 electric ignition element is required to ignite the propellant in a gas generator which inflates the flotation bags of a helicopter.

6.2 Ordering information. Procurement documents should specify the following:

a. title, number and date of this specification;

b. whether preproduction inspection is required and if so, specify the test activity;

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:35Z
Check the source to verify that this is the current version before use.

c. production lot size and test activity (see 4.3.3);

d. items of data required for each preproduction and production lot (see 6.3).

6.3 Data. For the information of Contractors and Contracting Officers, any of the data specified in (a) subparagraphs below, (b) applicable documents listed in Section 2 of this specification or (c) referenced lower-tier documents need not be prepared for the Government and shall not be furnished to the Government unless specified in the contract or order. The data to be furnished shall be listed on DD Form 1423 (Contractor Data Requirements List), which shall be attached to and made a part of the contract or order. NAVWEPS Form 4200/15 (Drawings, Lists, and Specifications Required) shall be attached where applicable.

6.3.1 Test report. Results of ballistic tests shall be forwarded to the Naval Air Systems Command and the procuring activity.

6.3.2 Data cards. The contract or order should state the format, quantity and destination of data cards.

6.4 Definitions. The definitions of Levels A and C packaging and packing given below were extracted from BUSANDA Instruction 4030.17.

6.4.1 Level A packaging. The degree of preservation and packaging which will afford adequate protection against corrosion, deterioration and physical damage during handling, shipment, indeterminate storage and world-wide redistribution.

6.4.1.1 Level C packaging. The degree of preservation and packaging which will afford adequate protection against corrosion, deterioration and physical damage during shipment from supply source to the first receiving activity, for immediate use. This level may conform to supplier's commercial practice when such meets the requirements of this level.

6.4.2 Level A packing. The degree of packing which will afford adequate protection during shipment, handling, indeterminate storage and world-wide redistribution.

6.4.2.1 Level C packing. The degree of packing which will afford protection against damage during direct domestic shipment from the supply source to the first receiving activity for immediate

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:35Z
Check the source to verify that this is the current version before use.

use. This level in general will conform to applicable carrier rules and regulations, and may be the supplier's commercial practice when such meets the requirements of this level.

6.5 Explosives safety precautions.

6.5.1 Applicability. The loading, assembly and handling of the explosives, subassemblies and the finished items covered by this specification involve hazardous operations and therefore require suitable explosive safety precautions. At plants of the Naval Air Systems Command, Department of the Navy, and other Government plants where the Government is responsible for safety, the precautions listed below are mandatory. These same minimum provisions are recommended for observance by a contractor or manufacturer that explosively loads the item covered in this specification in order to fulfill his own safety responsibility. Other warnings and precautions, pertaining to the operational effectiveness or safety of the specified item during its use (for example, during its handling, launching or firing), are included in the detailed technical requirements of the specification. Use of this specification shall not be construed to replace other safety regulations of governmental agencies or to relieve the contractor or manufacturer of responsibility for the safety of his operations.

6.5.2 Personnel and equipment. Proper care must be exercised at all times to protect personnel from accidents, fires or explosions and to limit damage to equipment and loading areas. In connection with the above, the precautionary measures in the following paragraphs should be observed. (See also paragraph 6.5.4, Static and electrical and other applicable parts of these safety precautions.)

6.5.2.1 Explosives operations shall be kept under strict supervision. Periodic inspections shall be employed to assure compliance with established safety regulations.

6.5.2.2 Safe equipment and methods should be utilized for handling and transporting explosives and loaded parts.

6.5.2.3 Where required, remote control-barricaded-handling equipment shall be used for explosives operations such as mixing, pouring, weighing, charging, sifting, drying, pressing, casting, crimping, etc.

6.5.2.4 Employ properly proportioned and properly located protective barricades, screens or shields at all required points.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:35Z
Check the source to verify that this is the current version before use.

6.5.2.5 Maintain equipment such as presses, dies, crimpers, blenders, mixers, sifters, conveyors, and the like in safe operating condition.

6.5.2.6 Enforce, where necessary, the wearing of suitable safety footwear, gloves, goggles, respirators, and impregnated garments to protect personnel against burns, poisoning and associated industrial hazards.

6.5.2.7 During static tests, propulsion units such as rocket motors shall be restrained against full thrust to prevent flight if ignited, for example, during test of igniter circuit. Also, means shall be provided to harmlessly vent flames and exhaust gases.

6.5.3 Operating procedures. All loading operations shall be conducted in full accordance with a formalized operating procedure which shall include the following:

6.5.3.1 Keep only minimum, limited quantities of explosives and completed or partially loaded parts present at each stage of operation.

6.5.3.2 Allow no fires, exposed electrical or other sparking equipment, and little or no flammable material to be present in loading, handling and storage spaces. Enforce proper "Match" and "No Smoking" rules where necessary.

6.5.3.3 Appropriate safety instructions for specific operations shall be posted and personnel instructed as to the hazards present and precautions involved.

6.5.3.4 The number of working personnel and transients permitted in each work space shall be established and posted in such areas. The numbers shall be the minimum number required to accomplish necessary operations.

6.5.3.5 All loading operations should be conducted in a neat and orderly manner.

6.5.3.6 Enforce good housekeeping and maintain effective policing, inspection and supervisory methods throughout the loading area and surroundings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:35Z
Check the source to verify that this is the current version before use.

6.5.3.7 Employ effective cleaning methods periodically to minimize the accumulation of explosives or explosive dust and other contamination upon, and assure its removal from, floors, walls, ceiling, ledges, tables, benches, piping, and equipment or the items loaded. Clean up any spilled material immediately.

6.5.3.8 The exposure of explosive materials and related parts should be so controlled as to minimize the absorption of moisture from the atmosphere or other sources during loading and handling operations.

6.5.3.9 Personnel handling detonators, primers, delay elements, lead-ins, boosters, and related parts which affect functioning should, insofar as practicable, avoid using bare fingers or improper equipment in order to prevent damage, corrosion, or deterioration from perspiration or other contaminating deposits.

6.5.3.10 Keep explosives and explosive parts in approved covered receptacles with covers in place when material is not being taken out or put into the receptacles. Where necessary, receptacles should be conductive to ground electrostatic charges. (See paragraph 6.5.4.)

6.5.4 Static and electrical.

6.5.4.1 Protect operations from electrostatic charges by effectively grounding all machinery, equipment, and fixtures; and, where necessary, employ suitable grounded conductive coverings for floors, work benches and tables, and workers' conductive shoes. Workers' clothing of a type to minimize the accumulation of static charges shall be employed. Fabrics, such as silk and nylon, which promote static generation shall be avoided. Additional grounding devices such as grounded bracelets for workers should be employed where operations are conducted with items which are unusually sensitive to initiation by static electricity. Such items include initiating explosives, tracer mixtures, and low energy type of electric primers, detonators and squibs. The latter types of items shall have the free ends of lead wires bared and twisted together, and be packed in relatively small groups wrapped in bare non-insulated aluminum foil or other uncoated metal foil. During assembly and processing operations, such sensitive electric items should be short circuited by clips or other devices until installed with safety shunt in the final device. Additional precautions for these items should include mechanical shielding to contain or deflect fragments and blast; also electrical shielding from induced electric currents originated by sources such as lightning, static,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:35Z
Check the source to verify that this is the current version before use.

electromagnetic radiations, etc. Where necessary for safety, humidity of work rooms should be appropriately increased, as required to lessen electrostatic effects, but without inducing excessive moisture absorption by any of the components of the item being processed.

6.5.4.2 Protect all explosive operations from effects of electric current originating in equipment (such as soldering irons or guns, heaters, switches, wiring, motors, lights, test instruments, etc.) by suitable insulation, grounding, separation or shielding. Such electric sources may initiate explosives by heat, sparks, arcs, or by completing an electric circuit through an electric primer, detonator or squib. For example, circuits may be inadvertently completed from a defective electric soldering iron through a grounded contact. All electric type of primers, detonators or squibs provided with wire leads shall have the free ends of the wires bared and twisted together to short circuit each unit, except when in process of assembly into a finished item. Removable short circuiting clips or other devices should be employed during manufacturing operations involving items such as electric primers, detonators or squibs.

6.5.4.3 Where necessary, protect personnel and operations from electromagnetic energy. In certain work with very sensitive explosives or items, a shielded environment free from significant electromagnetic energy should be provided.

6.5.5 Operating facility and storage regulations.

6.5.5.1 All explosives including partially loaded items should be stored in suitable storage magazines located in accordance with the minimum distances prescribed in the American Table of Distances (ATD). While the explosive or loaded items are in process, stored in loading rooms, or in ready or service magazines, they should be located in accordance with Intraplant Distances set forth in the ATD. For Navy managed or contractor managed-Navy owned-explosives loading plants, the Armed Services Explosives Safety Board standards approved by the Department of Defense, the Secretary of the Navy and the Naval Air Systems Command covering quantity-distance regulations for explosives apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:35Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION
MIL-I-81548(AS) IGNITION ELEMENT, ELECTRIC, MARK 22 MOD 0

ORGANIZATION *(Of submitter)*	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 APR 63 1426

C-8878

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:35Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
Naval Air Systems Command
Washington, D.C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

NAVAL AIR SYSTEMS COMMAND (AIR-52021)
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:35Z
Check the source to verify that this is the current version before use.