INCH-POUND

MIL-P-70697A(AR)
21 June 1994
SUPERSEDING
MIL-P-70697 (AR)
10 July 1988

MILITARY SPECIFICATION

PURSUIT DETERRENT MUNITION, HAND EMPLACED MINE (PDM), M86 MOLDED ASSEMBLY FOR

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements, examinations and tests for the fabrication of parts, assembling and packing for the Molded Assembly used in the Pursuit Deterrent Munition (PDM) M86. (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation. (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document, should be addressed to: Commander U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 1320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

MILITARY

MIL-S-19500	- Semiconductor Device General Specification For.
MIL-G-45204	- Gold Plating, Electrode Deposited.
MIL-S-45743	- Soldering, Hand Type, High Reliability Electrical, Electronic, Instrument, Communications, and Radar for Aerospace, and Control Systems, Procedures For.
MIL-S-46844	- Solder Bath Soldering of Printed Wiring Assemblies, Automatic Machine Type.
MIL-A-48078	- Ammunition, General Quality Assurance Provisions, General Specification For.
MIL-M-48245	- Molding Compound, Housing and Plug.
MIL-I-48331	- Integrated Circuit, Digital, CMOS Time Base and Special Purpose Function Generator, Monolithic, Silicon.
MIL-R-63993	- Resistor, Thick Film, Fixed and Trimmable.
MIL-B-70731	- Battery, Primary Reserve, Ammonia Milliampere Capacity For Mine PDM, M86.

STANDARDS

FEDERAL

FED-STD-595	- Color (Requirements for individual color chips).

MILITARY

MIL-STD-109	- Quality Assurance Terms and Definitions.
MIL-STD-202	- Test Methods for Electronic and Electrical Component Parts.
MIL-STD-453	- Inspection, Radiographic.
MIL-STD-750	- Test Methods for Semiconductor Devices.
MIL-STD-883	- Test Methods and Procedures for Microelectronics.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the DODSSP - Customer Service, Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:30Z
Check the source to verify that this is the current version before use.

DRAWINGS (see 6.8)

U.S. ARMY ARMAMENT, RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT AND PACKAGING DRAWINGS

9366661	- Molded Assembly PDM
9366700	- Mine Assembly M86
9366705	- Mine, STM
12598601	- Packing and Marking for Box, Fiberboard for Molded Assembly for M86 or Housing Timing and Fuzing Type 1/Type 2

(Copies of other Government documents, drawings, and publications required by contractor in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity).

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D-695-(69)	- Compressive Properties of Rigid Plastics
ASTM A-743	- Specification for Castings, Iron Chromium, Iron-Chromium-Nickel, and Nickel Base Corrosion Resistant For General Application

2.3 Order of precedence. In the event of conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained. (see contract provisions for additional precedence criteria).

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

3.1.1 Radiographic examination of cam. When the alternate material (cast stainless steel, Grade CF-8, ASTM A743 (except para. 9)) is used as per dwg. 12579582, Note 4 the cams shall be inspected for voids as per 4.4.3.11.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:30Z
Check the source to verify that this is the current version before use.

3.2 Molded assembly. The PDM molded assembly shall comply with all requirements specified on Dwg. 9366705 and 9366661, all associated drawings, and with all requirements in applicable specifications and standards.

3.3 S&A assembly. (Dwg. 9366668).

3.3.1 Presence of slider assembly and piston actuator in S&A assembly. The S&A assembly shall have the slider assembly and the piston actuator present and properly positioned and assembled.

3.3.2 Qualification test of electric detonator, transfer lead assembly and lead cup assembly lots. The electric detonator serial lot, transfer lead assembly serial lot to be used in the housing lot (see 4.4.1) shall perform satisfactorily as evidenced by high order functioning or the lead cup assembly when subjected to the qualification test specified in 4.5.3.

3.4 Function of sensor assembly. (Dwg. 9298569).

3.4.1 Release. The Sensor Assembly when subjected to a pressure of 250 + 25 psig for 1 second maximum while at a temperature of 75°F + 10°F shall release the ejection spring, sleeve, cap and bobbin with the thread remaining unbroken and attached to the bobbin and post with the breakwire maintaining continuity when tested as specified in 4.5.4.1.

3.4.2 Tripline deployment. When the Sensor Assembly functions in 3.4.1, the tripline shall deploy a minimum of 16 feet when tested in accordance with 4.5.4.2.

3.4.3 Breakwire function. When the pressure is released and the line pulled, the breakwire shall break at a force of 140 grams, minimum, and 500 grams, maximum, when tested in accordance with 4.5.4.3.

3.4.4. Post retention and thread breaking strength. Following the breakwire function, the post must be retained within the sensor case and the thread must not break when a 540 gram minimum dislodging force is applied in accordance with 4.5.4.4.

3.4.5 Molding material intrusion test. After molding into a test brick, the sensor assembly when subjected to 250 + 25 psig for 1 second maximum and while at a temperature of 75°F ± 10°F shall release the cap, sleeve and bobbin assembly when tested as specified in 4.5.4.6.

3.5 Functioning of electronic circuitry. After molding into the Molded Assembly, the electronic circuitry of the Molded Assembly shall be tested as specified in Appendix A.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:30Z
Check the source to verify that this is the current version before use.

3.6 Mine loading. All special test mines shall be loaded and packed for lot acceptance testing specified in the contract.

3.7 Temperature control during molding and cure of molded assemblies. The Molded Assemblies shall not have been subjected to temperatures exceeding 165°F at any time when examined as specified in 4.5.8.

3.8 Soldered electrical connections. Soldered electrical connections on the following assemblies shall comply with MIL-S-46844 or MIL-S-45743.

Piston Actuator & Clip Assy	(Dwg. 9366697)
Printed Wiring Board Assembly	(Dwg. 9366692)
Printed Wiring Board Assembly Interconnect	(Dwg. 9298620)
Preform and Sensor Assembly	(Dwg. 9298540)
Preform Assembly	(Dwg. 9366662)
Molded Assembly	(Dwg. 9366661)
Switch Assembly (Terminals)	(Dwg. 9298512)

3.9 Void criteria for molded assembly. Void with dimension larger then 1/8 inch across by 1/16 inch deep are not allowed except within the large cavity below 1/4 inch from the open end. Within this cavity, voids with dimensions greater then 1/4 inch across by 1/4 inch deep are not allowed. In addition, voids in the S&A and penthouse area of ball cavity are allowed to a maximum dimension of 1/8 inch across by 1/8 inch deep, except the booster pocket must be intact.

Comparison photographs or visual standards may be used to establish visual accept/reject criteria for voids approved by the Contracting Officer.

3.10 Color. The color of the molding compound in the molded assembly shall be within the range of the colors bounded by colors numbered 34079 through 334102, inclusive of FED-STD-595.

3.11 Mine functions.

3.11.1 Anti-disturbance functioning. The mine shall function in the anti-disturbance mode as the mine is disturbed by two (2) different movements to two (2) different sides.

3.11.2 Breakwire functioning. The mine shall function in the breakwire mode when any deployed tripline is pulled with a minimum force of one hundred and forty gram (140 g) to max force of six hundred grams (600 g).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

3.11.3 Self-destruct functioning. The mine shall be capable of self-destructing itself within the self-destruct time but no earlier than 80% of the allowable maximum time.

3.11.4 Early functioning. The mine shall not self-destruct itself by any internal mode within 80% of the self-destruct time.

3.11.5 Tripline deployment. The mine after ground impact and with unobstructed field, shall deploy a minimum of three (3) triplines with at least one (1) deployed tripline attaining a minimum deployed length of thread of ten (10) feet and two (2) others providing additional length to total sixteen (16) feet for three (3) triplines.

3.11.6 Premature arming. The mine shall be deploy sensors, fire the piston actuator or position the slider in line prior to 25 seconds.

3.11.7 Piston actuator. The piston actuator or the gas generator shall not function in less than 25 seconds after the battery ball is depressed at temperatures of -25°F to +125°F.

3.12 Duds.

3.12.1 Safe dud. The mine, if not functioning by any external or internal mode, shall not function after the maximum self-destruct time has elapsed.

3.12.2 Hazardous dud. All safe duds when tested as specified in 4.5, shall not be capable of functioning after the maximum self-destruct time has elapsed.

3.13 Test temperatures and conditioning. The loaded munitions, shall be temperature conditioned for a minimum of twenty-four (24) hours prior to testing. Temperature conditioning temperatures are as follows:

a. -25°F, -5°F

b. +70°F ± 10°F

c. +145°F, +5°F

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:30Z
Check the source to verify that this is the current version before use.

3.14 Munition arming. Arming of test units will be accomplished by removal of the arming lever which results in battery initiation, rupture of the shorting bar and removal of the S&A safety pin. The Arming Assembly, PDM shall comply with the requirements of Dwg. 12579595.

3.15 Qualification testing of electrical components. The components of the electronics assembly (P/N 9366692) that require qualification by electrical and mechanical testing are as follows:

9366695	Piston Actuator
9366704	Transition, Q3
9298496	Resistor Network
9298507/MIL-I-48331	Integrated Circuit (CMOS)
9298509	Capacitor C3
9298658	Capacitor C1 and C2
9298555	Transistors, NPN, Q1, Q2
9366694	Capacitor C7 and C8
9366695	Piston actuator
9366691	Printed Wiring Board
9298665	Capacitor, C4
9298666	Capacitor, C5

Components that were qualified in previous contracts for the Molded Assembly do not require requalification except as specified in 3.15.1.

3.15.1 Qualification of components. Qualification of the components listed above shall be accomplished by the following. The method of qualification shall be recommended by contractor for approval.

3.15.2 Pass/fail criteria. Pass/fail criteria for qualification components will be as follows:

(a) Electrical and mechanical laboratory tests - The components must pass all test to the specified sampling plan for qualification as defined on the applicable component drawings and specification, otherwise the qualification sample shall be rejected.

3.16 Data requirements. The contractor shall generate data in accordance with the requirements of the data item descriptions cited in 4.4.2.1 through 4.4.2.52, as applicable.

3.17 First article. When specified in the contract or purchase order (see 6.3), a sample shall be subjected to First Article Inspection in accordance with the technical provisions herein (see 4.3).

Source: https://assist.dla.mil -- Downloaded: 20260-26T04:30Z
Check the source to verify that this is the current version before use.

3.18 Workmanship.

3.18.1 Workmanship - molded assembly. The Molded Assembly shall be free of dirt, grease, chips, gouges, cracks, and any other defects which would make the item unsuitable for its indended use.

3.18.2 Workmanship - parts and assemblies. Parts and assemblies shall be free from chips, direct, grease, and other foreign matter that may impair proper functioning. Cleaning methods used shall not be injurious to any of the parts nor shall the parts be contaminated.

3.18.3 Workmanship - packaging, packing and marking. Packaging and packing materials shall not be water-damaged or contain excessive moisture. They shall not be torn, broken or otherwise damaged, and shall be suitable for the intended use. All marking shall be neat, accurate and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examination and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of Sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:30Z
Check the source to verify that this is the current version before use.

4.1.2 General provisions. Unless otherwise specified herein, the provisions of MIL-A-48078 apply and form a part of this specification. Reference shall be made to MIL-STD-109 to define quality assurance terms used herein.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the assemblies, components and test specimens listed below in the quantities as indicated below:

a. Certification that each molding compound batch (see 4.5.7.1) used to manufacture the Housing in (c) below complies with the requirements in MIL-M-48425 for compressive modules, flexural strength, flexural modules and area under the flexural strength, curve.

b. Fifty (50) S&A assemblies (Dwg. 9366668) less detonator, acceptor lead, transfer lead assembly, lead cup assembly, sleeve, and sealing washers.

c. Thirty-two (32) molded assemblies (Dwg. 9366661) prior to molding over test pads.

d. Housings from (c) above finished as specified on Dwg. 9366705 (after completion of inspections listed in 4.3.2.c).

e. Ninety-six (96) sliders (Dwg. 9366684) tested as per 4.5.14.

f. Thirty (30) piston actuators and clip assembly (Dwg. 9366696).

g. Twenty-five (25) printed wiring board assemblies electronics (Dwg. 9366692).

h. Thirty (30) detonator side plates (Dwg. 9366666).

i. Twenty-five (25) sensor assemblies (Dwg. 9298476).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:30Z
Check the source to verify that this is the currentversion before use.

j. Twenty-five (25) anti-disturbance switches (Dwg. 9298512).

k. One (1) test bar (0.50 x 0.50 x 1.0 inches or 0.50 inch diameter x 1.0 inches long) from each molding compound batch (see 4.5.7.1) used to manufacture the Housing in g. below. A second test bar shall be made available for the use in the event the first bar fails the test 4.3.2 due to a void. Tolerances on specimen dimensions shall be ± .01 inches.

l. Thirty (30) printed wiring board assemblies (Dwg. 9366692) electronic boards.

4.3.2 Inspections to be performed. The First Article parts submitted in accordance with 4.3.2 will be subjected by the Government to any or all the requirements of the applicable drawings and to the examinations, inspections, and tests specified herein.

a. The test bars for 4.3.1 (2) shall be tested for compressive strength as specified in 4.5.7.2.

b. Fifty (50) of the S&A assemblies from 4.3.1.b shall be subjected to the following after being loaded into molded test blocks (design or test blocks requires approval of Government agency).

(1) Thirty (30) S&A assemblies shall have the piston actuator fired with the safety pin in place. The actuator must fire (as evidenced by bent pin) without letting the slider move in line. This will be better verified by firing the detonator. If the slider goes in line or propagates from the detonator, it shall be considered a critical failure (see 4.5.2).

(2) Fifty (50) S&A assemblies shall have the piston actuator fired with the safety pin removed (4.5.1).

c. The molded assemblies (Dwg. 9366661) from 4.3.1.c shall be subjected the following:

(1) Upon completion of the tests specified in 4.4.2.27, the bridge between V_C and T terminals shall be removed, mold over the test pads and the assembly shall then be subjected to the examinations of 4.4.2.28.

(2) The assemblies shall be finished to comply with Dwg. 9366705 for Special Test Mines and shall be subjected to the criteria of 4.4.3.1 through 4.4.3.6.

Source: https://assist.dla.mil -- Downloaded: 20260-26T04:30Z
Check the source to verify that this is the current version before use.

d. Fifty (50) slider pins (Dwg. 9366684) tested as per 4.5.14.

e. Functioning of mines shall be performed on the seventy-two (72) mines as per 4.4.3.1 Assembly of Arming Assembly (Dwg. 12579595) is required.

4.3.3 Rejection. The first article quantity shall be rejected if any of the following occurs:

a. Any S&A assembly fails the arm/fire or non-arm test or any S&A assembly fails any of the examinations specified in 4.4.2.17 and 4.5.1.

b. The sensor assemblies subjected to the functioning tests exceed the reject criteria specified in 4.4.2.5.

c. Any anti-disturbance switch fails any of the examinations or tests specified in 4.4.2.7.

d. Any molded assembly fails to comply with any of the electrical tests or examinations specified in 4.4.2.28 and 4.4.2.56.

e. The sample exceeds the allowable defects (4.4.3.1 through 4.4.3.6).

NOTE: The Government reserves the right to terminate its inspection when any failure of an assembly, component, or test specimen in the sample causes rejection per the accept/reject criteria for that examination or test.

TABLE I. First article testing

	Cold ($-25^{o}F + 5^{o}F$)	Ambient ($70^{o}F \pm 5^{o}F$)	Hot ($145^{o}F \pm 5^{o}F$)
Breakwire	8	8	8
Anti-disturbance	8	8	8
Self-destruct	8	8	8
	24	24	24

TOTAL 72

First article and productions - (sample size of 72 special test mines (STM). The lot shall be rejected if four (4) or more test mines fail to comply with any of the requirements specified in 3.4 and 3.11 (72-3-4). There shall be no more than two (2) failures at test temperature.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:30Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. Inspection lots of Molded Assemblies shall contain:

a. Electrical detonators (Dwg. 9245691) of one lot interfix number from one manufacturer (see 4.5.3).

b. Lead cup, transfer lead, acceptor lead assemblies (Dwg. 9298456) of one lot interfix number from one manufacturer (see 4.5.3).

c. Battery assembly (MIL-B-70731) from one manufacturer.

d. Gas generator (Dwg. 9298507) of one lot interfix number from one manufacturer.

e. Integrated circuits (Dwg. 9298507) from one manufacturer.

f. Thick film resistor network (Dwg. 9298496) from one manufacturer.

g. Piston actuator (Dwg. 9366695) from one lot interfix number from one manufacturer.

h. Darlington transistor (Dwg. 9366704) from one lot interfix number from one manufacturer.

4.4.2 Examination and tests.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified herein. Where cited herein, attributes sampling inspection shall be conducted in accordance with Table II below, using the inspection levels stated in Classification of Characteristics paragraphs.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:30Z
Check the source to verify that this is the current version before use.

TABLE II. Attributes sampling inspection

Lot Size	Inspection Levels I	II	III	IV	V	VI
2 to 8	*	*	*	*	5	3
9 to 15	*	*	*	13	5	3
16 to 25	*	*	*	13	5	3
26 to 50	*	*	32	13	5	3
51 to 90	*	*	32	13	13	5
91 to 150	*	125	32	13	13	5
151 to 280	*	125	32	32	20	6
281 to 500	*	125	32	32	20	8
501 to 1200	*	125	80	50	20	13
1201 to 3200	1250	125	80	50	32	13
3201 to 10000	1250	125	125	50	32	13
10001 to 35000	1250	315	125	80	50	13
35001 to 150000	1250	315	125	80	50	13

Numbers under inspection levels indicate sample size; asterisks indicates one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

TABLE III. Special inspection levels

Lot Size	S-I	S-II	S-III	S-IV	S-V	S-VI
2 to 15	*	*	*	13	5	3
15 to 50	*	*	32	13	5	3
51 to 150	*	125	32	13	5	3
151 to 500	*	125	32	13	5	3
501 to 3200	1250	125	32	13	13	5
3201 to 35000	1250	125	32	13	13	5
35001 to 500000	1250	125	32	32	20	8
500001 and over	1250	125	32	32	20	8

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

b. Alternative quality conformance provisions. Unless otherwise specified herein or provided for in the contract, alternative quality conformance procedures, methods, or equipment, such as statistical process control, tool control, other types of sampling plans, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions herein. Prior to applying such alternative procedures, methods or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation (see 6.4). When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the specified quality assurance provision(s) herein. In case of dispute as to whether the contractor's proposed alternative(s) provides equivalent assurance, the provisions of this specification shall apply. All approved alternative provisions shall be specifically incorporated into the contractor's quality program or inspection system, as applicable.

c. Examination. See MIL-A-48078.

4.4.3.3 Lot acceptance testing. Shall be performed as per 4.4.3.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Printed Wiring Board, Electronics	1 OF 1	9366691
			NEXT HIGHER ASSEMBLY: 9366692

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Red board	Level II	3.2 1/	Visual
102	Printed wiring board material		3.1 1/	Certification
Minor				
201	Poor workmanship	Level III	3.18	Visual

NOTES: 1/ Sample in accordance with Inspection Level II. Acceptance of the lot is contingent upon finding zero (0) defects in the sample.

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Manifold Assembly, Center	1 OF 1	9298547
			NEXT HIGHER ASSEMBLY 9298540

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Any passage blocked	Level II	3.2	Test
102	Tubing punctured, cut, loose or improperly assembled	Level II	3.2	Visual
103	Ball missing or loose	Level II	3.2	Visual
Minor				
201	Poor workmanship	Level III	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Manifold Assembly, Side	1 OF 1	9298543
			NEXT HIGHER ASSEMBLY: 9298540

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Any passage blocked	Level II	3.2	Test
102	Ball missing or loose	Level II	3.2	Visual
103	Tubing punctured, cut, loose or improperly assembled	Level II	3.2	Visual
Minor				
201	Poor workmanship	Level III	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Diaphragm	1 OF 1	9298598
			NEXT HIGHER ASSEMBLY 9298598

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Presence of tears or cracks after mandrel test	Level II	3.2	Visual
102	Material		1/	Certification
Minor				
201	Poor workmanship	Level III	3.18	Visual

NOTES: 1/ Certification of compliance for material shall include the 100% virgin material requirement.

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Sensor Assembly	1 OF 1	9298569
			NEXT HIGHER ASSEMBLY: 9298540

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	Functioning Tests 1/			
101	Non-release 2/	Level II		
102	Release and thread security	80-7-8	3.4.1	4.5.4.1
103	Tripline deployment	80-3-4	3.4.2	4.5.4.2
104	Breakwire functioning	80-5-6	3.4.3	4.5.4.3
105	Post retention and thread breaking strength	80-7-8	3.4.4	4.5.4.4
106	Solder connections improper		3.8	3.8
107	Post locking ball missing 2/	Level II	3.2	X-ray
108	Sensor intrusion test	80-4-5	3.4.5	4.5.4.6
Minor				
201	Poor workmanship	Level III	3.18	Visual

NOTES:

1/ The tests shall be performed in the order listed. The sample units for each test shall have been tested on all preceding tests in this sequence. However, acceptance or rejection on one test shall not constitute acceptance or rejection on the other tests. The sample sizes specified are applicable to each test and shall not be amended by fallout from previous tests.

2/ This test to be performed prior to assembly of the breakwire, breakwire retaining ring switch post cover and epoxy. The testing may be conducted as a normal production operation with an inspector verifying the operation.

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Can, Switch	1 OF 1	9298515
			NEXT HIGHER ASSEMBLY: 9298524

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Plating	5 per batch	3.2	4.5.5.3
Minor 201	Poor workmanship	Level III	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026[illegible]T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Switch Assembly	1 OF 1	9298512
			NEXT HIGHER ASSEMBLY: 9366692

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Switch function seven (7) contact closures minimum each direction	Level II	3.2	4.5.5.1
102	Contact closure duration 0.60 seconds maximum	Level II	3.2	4.5.5.1
103	Insulation resistance	Level II	3.2	4.5.5.2
104	Assembly damaged, distorted or incomplete	Level II	3.2	Visual
105	Ribbon improperly welded to can	Level II	3.2	Visual
106	Epoxy seal missing or incomplete	Level II	3.2	Visual
107	Solderability, 2 leads		3.8	Visual
Minor				
201	Poor workmanship	Level III	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Printed Wire Board Assembly Interconnect	1 OF 1	9298620
			NEXT HIGHER ASSEMBLY 9298451

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Natural color board without hole in shorting bar	Level II	3.2	Visual
102	Ribbons not welded to battery	Level II	3.2	Visual
103	Shorting bar missing	Level II	3.2	Visual
104	Ribbons not soldered to printed wiring board	Level II	3.2	Visual
105	Battery or battery flange missing	Level II	3.2	Visual
106	Soldering workmanship	Level II	3.8	Visual
107	Weld pull test			4.5.6
108	Printed wiring board material		3.1	Certification
Minor				
201	Poor workmanship	Level III	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026[illegible]T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Dual Transistor, NPN Darlingtom	1 OF 1	9298555
			NEXT HIGHER ASSEMBLY 9366692

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	Temperature Cycling 1/			
101	Forward-current transfer, ratio, HFE at 85°C	Level II	3.2	MIL-STD-883/ Method 1010/ Condition C
102	Collector-emitter cut off current, Ices at 85°C	Level II	3.2	MIL-STD-750/ Method 3076
103	Base-emitter voltage, VBEF at 85°C	Level II	3.2	MIL-STD-750/ Method 3041
104	Collector-emitter saturation voltage, VCES at 85°C			MIL-STD-750/; Method 3066
Minor				
201	Poor workmanship	Level III	3.18	Visual

NOTES: 1/ Test to be perfored at 85°C after subjecting the components to twenty-five (25) cycles of temperature shock.

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Capacitor, Fixed, Tantalum Solid, Polarized	1 OF 1	9298665
			NEXT HIGHER ASSEMBLY: 9366692

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	Thermal Shock 1/			
101	Capacitance	Level II	3.2	Note 1A/Dwg. 9298665
102	Dissipation factor	Level II	3.2	Note 1C/Dwg. 9298665
103	DC leakage (ambient temperature)	Level II	3.2	Note 1D1/Dwg. 9298665
104	DC leakage (plus 85°C)	Level II	3.2	Note 1D2/Dwg. 9298665
Minor				
201	Poor workmanship	Level III	3.18	Visual

NOTES: 1/ Tests to be performed after subjecting components to five (5) cycles of thermal shock in accordance with Note 3A of Dwg. 9298665.

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.11	Capacitor, Fixed, Tantalum, Solid Polarized	1 OF 1	9298509
			NEXT HIGHER ASSEMBLY 9366692

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	Thermal Shock 1/			Method 107, Cond. A, MIL-STD-202
101	Capacitance	Level II	3.2	Method 305/ MIL-STD-202
102	Dissipation factor	Level II	3.2	Method 306/ MIL-STD-202
103	DC leakage at 6VDC (4 US maximum)	Level II	3.2	Method 306/ MIL-STD-202
Minor				
201	Poor workmanship	Level III	3.18	Visual

NOTES: 1/ Tests to be performed after subjecting components to five (5) cycles of thermal shock in accordance with Method 107, Test Condition A of MIL-STD-202.

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.12	Capacitor, Fixed Plastic Dielectric	1 OF 1	9298658
			NEXT HIGHER ASSEMBLY 9366692

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	Thermal Shock 1/			NOTE 3b/Dwg. 9298510
101	Capacitance	Level II	3.2	NOTE 1a/Dwg. 9298510
102	Dissipation factor	Level II	3.2	NOTE 1c/Dwg. 9298510
103	Insulation resistance (Ambient Temp)	Level II	3.2	NOTE 1d/Dwg. 9298510
104	Insulation resistance (Plus 85°C)	Level II	3.2	NOTE 1d/Dwg. 9298510
Minor				
201	Poor workmanship	Level III	3.18	Visual

NOTES: 1/ Tests to be performed after subjecting components to five (5) cycles of thermal shock in accordance with NOTE 4b of Dwg. 9298658.

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.13	Resistor, Network, Thickfilm	1 OF 1	9298496
			NEXT HIGHER ASSEMBLY
			9366692

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Contractor shall furnish evidence of having satisfactorily met inspection requirements of MIL-R-63993		3.2	Certification
Minor 201	None defined			

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.14	Integrated Circuit, Control and Timing Base CMOS	1 OF 1	MIL-I-48331/9298507
			NEXT HIGHER ASSEMBLY 9366692

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Contractor shall furnish evidence of having satisfactorily met inspection requirement of MIL-I-48331		3.2	Certification
Minor 201	None defined			

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.15	Printed Wiring Board Assembly		9366692
			NEXT HIGHER ASSEMBLY 9366693

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Solder workmanship	Level II	3.2	Visual
102	Land paths broken, raised or bridged with solder	Level II	3.2	Visual
103	Printed wiring board cracked or broken	Level II	3.2	Visual
104	Components damaged or missing	Level II	3.2	Visual
105	Components mounted with wrong polarity	Level II	3.2	Visual
Minor				
201	Maximum height	Level III	3.2	Gage
202	Poor workmanship	Level III	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.16	S&A and Laminate Assembly	1 OF 1	9366685-1
			NEXT HIGHER ASSEMBLY: 9366662-1

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Lead cup assembly inverted	Level II	3.2	Visual
102	Sealant or foreign material on exposed surface of lead cup assembly	Level II	3.2	Visual
103	Shorting washer missing	Level II	3.2	Visual
Minor				
201	Poor workmanship	Level III	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-04-20T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.17	S&A Assembly, PDM	1 OF 1	9366668-1
			NEXT HIGHER ASSEMBLY 9366685-1

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Special 1	Presense of shorting device	SII		Visual
Major 101	Presence of parts			
	a. Sleeve, S&A 9366683 per NOTE 6	Level II		Visual
	b. Lead cup assembly, green end exposed	Level II		Visual
	c. Seal, washer 9298459-1 per NOTE 2	Level II		Visual
	d. Piston actuator and clip assembly with wires 9366697 per NOTE 5	Level II		Visual
	e. Gasket - 9366667	Level II		Visual
	f. Seal, washer 9298459-2	Level II		Visual
	g. Clip, terminal	Level II		Visual
	h. Det., electric, M100 9245691	Level II		Visual
	i. NOTE 5 adhesive/sealant	Level II		Visual
	j. Slider assembly 9366684	Level II		Visual
	k. Piston actuator short to case	Level II		Gage
102	Lead cup assembly over .005" above flush with dovetail slot	Level II	3.2	Gage
Minor 201	Poor workmanship	Level IV	3.18	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.18	Sleeve, S&A	1 OF 1	9366683
			NEXT HIGHER ASSEMBLY 9366668

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material verification	Level II		Lab testing
102	Thickness, minimum	Level II		Gage
Minor				
201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-04-20T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.19	Plate, Side, Detonator	1 OF 1	9366666
			NEXT HIGHER ASSEMBLY: 9366668

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Special				
1	Presence and workmanship of boss	SII		Visual
2	Width of boss	SII		Gage
Major				
101	True position of small detonator hole	Level II		Gage
102	True position of larger detonator hole	Level II	3.2	Gage
103	Non-destructive shear test of boss	Level II		Gage
104	Destructive shear test of boss		3.2	Gage
Minor				
201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.20	Slider, Assembly	1 OF 1	9366684
			NEXT HIGHER ASSEMBLY: 9366668-1

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical				
1	Slider integrity	100%	3.1	4.5.14
Major				
101	Staking of transfer lead assembly	Level II	3.3	Visual/Centrifuge
102	Transfer lead assy 9366678 with blue end	Level II	3.3	Visual
103	Staking of acceptor lead	Level II	3.3	Visual/Centrifuge
Minor				
201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-04-20T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.21	Slider	1 OF 1	9366664
			NEXT HIGHER ASSEMBLY: 9366668-2

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Radius of boss relief		3.3	Gage
102	Height and angle of slider edge		3.3	Gage
103	Height of slider body	Level II	3.3	Gage
104	Diameter of detonator hole	Level II	3.3	Gage
105	True position of detonator hole		3.3	Gage
106	Width of slider arm	Level II	3.3	Gage
107	Depth of piston actuator hole	Level II	3.3	Gage
108	Diameter of transfer lead output hole	Level II	3.3	Gage
109	True position of transfer lead output hole		3.3	Gage
110	Integrity test	Level III	3.18	Visual
Minor				
201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.22	Transfer Lead Assembly	1 OF 1	9366678
			NEXT HIGHER ASSEMBLY
			9366684

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Conformance to NOTE 2	each lot		Certification
102	Conformance to NOTE 3	each lot		Certification
103	Source inspection	20-0-1		Gage/Equipment
Minor				
201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-28T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.23	Wire, Housing	1 OF 1	9366686
			NEXT HIGHER ASSEMBLY 9366674

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Material verification	1-0-1		Lab testing
Minor 201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.24	Preform Assembly	1 OF 1	9366662-1
			NEXT HIGHER ASSEMBLY 9366661-1

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Soldered connections improper or unsoldered	Level II	3.2	Visual
102	Retainer and ball assembly not seated on battery	Level II	3.2	Visual
103	Any components or assembly not secured to preform	Level II	3.2	Visual
104	Kinked, broken, loose or flattened sensor tubing	Level II	3.2	Visual
105	Any unconnected sensor tubing	Level II	3.2	Visual
106	Shorting washer present	Level II	3.2	Visual
107	Presence of solder bridge	Level II	3.2	Visual 1/
108	Gas generator assembly missing	Level II	3.2	Visual
Minor				
201	Poor workmanship	Level III	3.18	Visual

NOTES: 1/ For safety purposes, soldering bridge must be present on part from time detonator leads are connected until just prior to soldering flex circuit to detonator leads and conducing detonator resistance test (see 4.5.12).

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026[illegible]
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.25	Molded Assembly (Prior to Molding Over Conductor Test Pads)	1 OF 1	9366661-1
			NEXT HIGHER ASSEMBLY: 9366700 or 9366705

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical				
1	Temporary safety delay (less than 25 seconds)	100%	3.2	Gage
Major				
101	Check EUD's (pads) not shorted	Level II	3.2	Visual
102	Solder connections improper	Level II	3.8	Visual
103	Temperature control during cure and cure time	1/	3.7	4.5.8
104	Resin/Hardener weight ratio of molding compound	Level II	3.2	4.5.7.2
105	Shelf life of molding compound expired	Level II	3.2	Visual
106	Functional testing of electronic circuitry	Level II	3.5	4.5.9
107	Removal of solder bridge between V_C and T			
Minor				
201	Mounting plate insulator improperly installed	Level III	3.2	Visual
202	Poor workmanship	Level III	3.18	Visual

NOTES: 1/ Cure temperature and cure time shall be monitored for each molding compound batch of housings.

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.26	Molded Assembly	1 OF 3	9366661-1
			NEXT HIGHER ASSEMBLY: 9366700 or 9366705

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical				
1	Temporary safety pin or safety pin assembly missing or defective	100%	3.2	Visual
Special				
1	Shorting bar broken or damaged	SI	3.2	Visual or Approved Gages
2	Safety delay (less than 25 seconds)	SI	3.2	Gage
Major				
101	Presence of bare (uninsulated) or broken wire in cavity	Level II	3.2	Visual
102	Voids in excess of specified	Level II	3.9	Visual
103	Detonator sleeve missing or loose	Level II	3.2	Visual
104	Any sensor locating plug missing (7 places)	Level II	3.2	Visual
105	Molding material or other foreign material on exposed surface of lead cup assembly over 0.005	Level II	3.18	Visual
106	Incomplete fill in test pad area	Level II	3.2	Visual
107	Temperature control during cure minimum cure time	1/	3.7	1/
108	Weight ratio of molding compound	1/	3.7	1/

NOTES: 1/ Cure temperature, cure time and weight ratio shall be monitored for each batch housings.

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-04-20T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.26	Molded Assembly (Cont'd)	2 OF 3	9366661-1
			NEXT HIGHER ASSEMBLY: 9366700 or 9366705

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Major				
109	Distance from base of largest cavity diameter to apex gaging surface maximum	Level II	3.2	Gage
110	Color incorrect	Level II	3.10	Visual
111	Distance from end face to forward edge of shorting bar	Level II	3.2	Gage
112	Height or bare battery ball above apex radius	Level II	3.2	Gage
113	Height of shorting bar above apex radius	Level II	3.2	Gage
114	Max distance from arc face (center area) to apex gaging radius	Level II	3.2	Gage
115	Battery ball free of potting material over designaged area	Level II	3.2	Visual
116	Short bar clip missing	Level II	3.2	Visual
117	Safety pin seal missing	Level II	3.2	Visual
118	Tape missing or improper	Level II	3.2	Visual
119	Note 17 requirement	Level II	3.2	Gage
120	Insulation missing	Level II	3.2	Visual
121	Screw torque incorrect	Level II	3.2	Gage
122	Shelf life of molding compound expired	Level II	3.2	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.26	Molded Assembly (Cont'd)	3 OF 3	9366661-1
			NEXT HIGHER ASSEMBLY: 9366700 or 9366705

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Minor				
201	Plug under shorting bar removed	Level IV	3.2	Gage
202	Molding material in dovetail of S&A or booster slot	Level IV	3.2	Gage
203	Loose end face laminates	Level IV	3.2	Visual/Manual
204	Any exposed tubing which is twisted, kinked, punctured or broken	Level IV	3.2	Visual
205	Surface preparation of largest diameter of cavity missing or incomplete	Level IV	3.2	Visual
206	Any markings missing, incorrect or incomplete	Level IV	3.2	Visual
207	Molding material or other foreign material on exposed surface of lead cup assembly equal to less than .005	Level IV	3.2	Visual
208	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026[illegible]T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.27	Packaging and Packing Material	1 OF 1	TBD
			NEXT HIGHER ASSEMBLY: TBD

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Presence of foreign material	Level I	3.18	Visual
102	Material damaged (broken, torn, punctured, etc.)	Level I	3.18	Visual
Minor				
201	Poor workmanship	Level III	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.28	Packaging and Packing Housings	1 OF 1	TBD
			NEXT HIGHER ASSEMBLY: TBD

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Housing(s) incorrectly positioned	Level I	3.18	Visual
Minor 201	Poor workmanship	Level III	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.29	Packaging and Marking for Box, Fiberboard for Molded Assembly	1 OF 1	TBD
			NEXT HIGHER ASSEMBLY: TBD

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Box damaged	Level II	3.18	Visual
102	Markings missing, illegible, incorrect or incomplete	Level II	5.3	Visual
Minor				
201	Poor workmanship	Level III	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.30	Mine, Assembly Demonstrator, PDM	1 OF 1	9366698
			NEXT HIGHER ASSEMBLY: ---

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Presence of parts			
	a. Arming assembly 12579595	Level II		Visual
	b. 2-Screw, panhead-MS51957-14	Level II		Visual
	c. Screw, tapping, panhead-MS24630-12	Level II		Visual
	d. Hook, shorting bar 12579585	Level II		Visual
	e. Clip, shorting bar 12579586	Level II		Visual
102	Adhesive	Level II		Visual
103	Screw torque	Level II		Torque wrench
104	Insulator placement per NOTE 10	Level II		Visual
Minor				
201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.31	Mine, Assembly Training, PDM	1 OF 1	9366675
			NEXT HIGHER ASSEMBLY: ---

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Presence of parts			
	a. Arming assembly 12579595	Level II		Visual
	b. 2-Screw, panhead-MS24630-11	Level II		Visual
	c. Screw, tapping, panhead-			
102	Adhesive	Level II		Visual
103	Screw torque	Level II		Torque wrench
Minor				
201	Poor workmanship	Level III	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.3.32	Housing Assembly, Timing and Fuzing Training Units	1 OF 1	9366674
			NEXT HIGHER ASSEMBLY: ---

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Insert, housing 9366676	Level II		Visual
102	2-Wire, housing 9366686	Level II		Visual
Minor				
201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS. MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.33	Plate, Mounting	1 OF 1	12579584
			NEXT HIGHER ASSEMBLY 12579581

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material	Each lot	3.1	Certification
102	Length from datum B to theoretical nose point	Level II	3.15	Gage
103	Size of lever rivet hole	Level II	3.15	Gage
104	Position of lever rivet hole	Level II	3.15	Gage
105	Position of two radiused sensor cutouts	Level II	3.15	Gage
Minor				
201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 12579583
4.4.2.34	Stiffener, Plate		NEXT HIGHER ASSEMBLY 12579581

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor 201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026[illegible]T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.35	Mounting Plate and Stiffener Assembly	1 OF 1	12579581
			NEXT HIGHER ASSEMBLY: 12579595

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Presence of all parts	Level II	3.15	Visual/Print
Minor 201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.36	Ring, Hookup	1 OF 1	12579591
			NEXT HIGHER ASSEMBLY 12579595

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Material per print	Each lot	3.1	Certification
Minor 201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026[illegible]T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.37	Clip, Safety	1 OF 1	12579590
			NEXT HIGHER ASSEMBLY
			12579595

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Material per print	Each lot	3.1	Certification
Minor 201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.38	Safety Clip Assembly	1	1	12579598

NEXT HIGHER ASSEMBLY: 12579595

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Presence of all parts	Level II	3.15	Visual/Print
Minor 201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.39	CAM	1 OF 1	12579582
			NEXT HIGHER ASSEMBLY: 12579595

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material per print	Each lot	3.1	Certification
102	Radius of CAM lobe to horizontal centerline of slot	Level II	3.15	Gage
103	True position of CAM lobe radius	Level II	3.15	Gage
104	Thickness of lobe at outside edge	Level II	3.15	Gage
105	True position of thickness of lobe	Level II	3.15	Gage
106	Width of slot	Level II	3.15	Gage
107	True position of slot	Level II	3.15	Gage
108	Size of hole at end opposite lobe	Level II	3.15	Gage
109	True position of hole at end opposite lobe	Level II	3.15	Gage
110	Hardness	Level II	3.15	
111	Radiographic	Level II	3.15.1	X-Ray
Minor				
201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.40	Sleeve, Lever	1 OF 1	12579587
			NEXT HIGHER ASSEMBLY: 12579595

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Overall length	Level II	3.15	Certification
Minor 201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.41	Rivet, Lever	1 OF 1	12579588
			NEXT HIGHER ASSEMBLY: 12579595

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material per print	Each lot	3.1	Certification
102	Length of shank	Level II	3.15	Gage
Minor				
201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.42	Pin, Safety	1 OF 1	12579589
			NEXT HIGHER ASSEMBLY: 12579595

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Special				
1	OD of pin shaft with flat	SI	3.15	Gage
2	OD of pin shaft	SI	3.15	Gage
3	OD of pin head collar	SI	3.15	Gage
4	Material	Each lot	3.1	Lab verification
Major				
101	Distance across slots	Level II	3.15	Gage
102	True position of slots	Level II	3.15	Gage
103	Width of slot	Level II	3.15	Gage
104	Height from slots to end of head	Level II	3.15	Gage
Minor				
201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.43	Insulator Mounting Plate	1 OF 1	12579594
			NEXT HIGHER ASSEMBLY: 12579595

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material per print	Each lot	3.1	Certification
102	Profile of surface with respect to datums a and b	Level II	3.15	Optical comparator
Minor				
201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.44	Lever, Arming	1 OF 1	12579580
			NEXT HIGHER ASSEMBLY: 12579595

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material per print	Each lot	3.1	Certification
102	Width of slot	Level II	3.15	Gage
103	True position of slot	Level II	3.15	Gage
104	Distance between outside faces of drilled ears, wide end	Level II	3.15	Gage
105	Size of hole in small end (2)	Level II	3.15	Gage
106	True position of holes in small end (2)	Level II	3.15	Gage
107	Lever embrittlement test		3.2	4.5.4.7
Minor				
201	Poor workmanship	Level III	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026[illegible]T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.45	Arming Assembly, PDM	1 OF 1	12579595
			NEXT HIGHER ASSEMBLY: 12579601

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Presence of all parts	Level II	3.15	Visual
102	Coated ring properly seated in arming lever	Level II	3.15	Visual
103	Pull force per Dwg. 9366705	Level II	3.15	Force Gage/Set Up
104	Rivet peening complete (2 places)	100%	3.2	Visual
Minor				
201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.46	Pin, Safety, Temporary	1 OF 1	12579592
			NEXT HIGHER ASSEMBLY: 12579596

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Special				
1	Material per print	Each lot	3.1	Lab verification
2	Length of major diameter	Level II		Gage
3	Diameter of flat section	Level II		Gage
Major	None defined			
Minor 201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T04:30Z
Check the source to verify that this is the current version before use.

MIL-P-70697A(AR)

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.47	Plate, Safety, Temporary	1	1	12579593

NEXT HIGHER ASSEMBLY: 12579596

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Material per print	Each lot	3.1	Certification
Minor 201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.48	Safety Pin Assembly, Temporary	1 OF 1	12579596
			NEXT HIGHER ASSEMBLY: 12579601

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Pull for verification (destructive test)	Level II		Force Gage/Set Up
102	Presence of all parts	Level II		Visual
Minor				
201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.49	Hook, Shorting Bar	1 OF 1	12579585
			NEXT HIGHER ASSEMBLY 12579601

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Material per print	Each lot	3.1	Certification
102	Diameter of wire	Level II	3.15	Gage
103	Distance between vertical shanks at hook end	Level II	3.15	Gage
104	Height of hook shank at hook end	Level II	3.15	Gage
105	Length of tang on hook end	Level II	3.15	Gage
106	Overall length of shorting bar hook	Level II	3.15	Gage
Minor				
201	Poor workmanship	Level III	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.50	Clip, Shorting Bar	1 OF 1	12579586
			NEXT HIGHER ASSEMBLY 12579601

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Size of hole	Level II	3.15	Gage
102	True position of hole	Level II	3.15	Gage
103	Overall width	Level II	3.15	Gage
104	Depth of slot formed by bend radius	Level II	3.15	Gage
105	Width of slot formed by bend radius	Level II	3.15	Gage
106	Diameter of slot aligned with hole	Level II	3.15	Gage
107	True position of slot aligned with hole	Level II	3.15	Gage
Minor				
201	Poor workmanship	Level III	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.51	Seal, Safety Pin	1 OF 1	12579274
			NEXT HIGHER ASSEMBLY: 12579601

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor 201	Poor workmanship	Level IV	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.52	Special Test Mine	1 OF 2	9366705
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical				
1	Shorting bar broken or damaged	100%	3.2	DOD-702-3
2	Safety pin properly installed	100%	3.2	DOD-702-3
3	Safety clip properly installed	100%	3.2	DOD-702-3
4	Hazardous dud (AT)	100%	3.13.2	DOD-702-3
Special				
5	Mounting plate insulator properly installed	SI	3.2	Visual
Major				
101	Arming mechanism functioning (LAT)	Level II	3.15	
102	Anti-disturbance functioning (LAT)	Level II	3.11.1	4.4.3.4/4.5.12.1
103	Breakwire functioning (LAT)	Level II	3.11.2	4.4.3.5/4.5.12.2
104	Tripline deployment (LAT)	Level II	3.12	4.4.3.6/4.5.13
105	Safe duds (LAT)	Level II	3.13.1	4.5.14
106	Early functioning (LAT)	Level II	3.11.4	4.4.3.3/4.5.12.3

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.52	Special Test Mine	2 OF 2	9366705
			NEXT HIGHER ASSEMBLY: ---

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Major	Cont'd			
107	Self-destruct functioning (LAT)	Level II	3.11.3	4.4.3.3/4.5.12.3
108	Distance between battery ball and CAM	Level II	3.2	STD. Gage
109	Any sensor restricted (cap not removed or molding compound/flash over sensor cutout)	Level II	3.2	Visual
110	Any sensor prematurely deployed	Level II	3.2	Visual
111	Mounting screws properly torqued	Level II	3.2	Torque Wrench
112	Shorting bar hook attached per print	Level II	3.2	Visual
113	Shorting bar clip attached per print	Level II	3.2	Visual
Minor				
201	Test pads exposed	Level III	3.2	Visual
202	Poor workmanship	Level III	3.18	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.53	Transistor, Darlington, NPN	1 OF 1	9366704
			NEXT HIGHER ASSEMBLY 9366691

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Table II of MIL-S-19500 Testing	Level II	3.2	Certification and witnessed by DCAS
102	Forward - current transfer ration, HFE at 85°C	Level II	3.2	MIL-STD-883/Method 1010, Condition C
103	Collector - emitter cut off current ICES at 85°C	Level II	3.2	MIL-STD-750/ Method 3076
104	Base - emitter voltage, VBEF at 85°C	Level II	3.2	MIL-STD-750/ Method 3041
105	Collector - emitter saturation voltage VCES at 85°C	Level II	3.2	MIL-STD-750/ method 3066
Minor				
201	Poor workmanship	Level III	3.18	Visual

NOTES: Test to be performed at 85°C after subjecting the transistors to twenty-five (25) cycles of temperature shock.

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026[illegible]T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-70697A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.54	Actuator, Piston	1 OF 1	9366695
			NEXT HIGHER ASSEMBLY 9366696

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Resistance of bridgewire	Level II	3.2	Gage
102	Current requirements	Level II	3.2	Gage
103	Minimum force 1/	Level II	3.2	Gage
104	Incorrect part number	Level II	3.2	Visual
105	Firing requirements 1/	Level II	3.2	Gage
106	Length(s) incorrect	Level II	3.2	Gage
107	Diameter(s) incorrect	Level II	3.2	Gage
Minor				
201	Poor workmanship	Level IV	3.2	Visual

NOTES 1/ The units will be functioned in a test fixture, destructive test 50-1-2.

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.3.1 Lot acceptance testing. Seventy-two (72) STM mines (9366705) per lot shall be used for lot acceptance testing. The rounds shall be conditioned and tested as follows:

Temperature	Quantity
-25°F - 5°F	24
+70°F + 10°F	24
+145°F + 5°F	24

4.4.3.2 Mine test distribution. Each test lot of munitions shall be divided so that approximately one-third (1/3) of the mines are tested for anti-disturbance, one-third (1/3) of the mines are tested for breakwire and one-third (1/3) of the mines are tested for self-destruct.

4.4.3.3 Self-destruct functioning. The lot shall be rejected if any of the self-destruct functions exceed any of the defect quantities as follows:

Safe duds (3%)
Early outs: (3%)

4.4.3.4 Anti-disturbance functioning. Mines designated for anti-disturbance testing shall be tested for the specified criteria in accordance with 4.5.11.1. Also, mine failing to function during the first breakwire function attempt in accordance with 4.5.11.2 and subsequently tested for anti-disturbance functioning test should be scored providing the sample is not classed as a safe dud. The results of mines undergoing a second breakwire function attempt shall be for information only and not included in lot acceptance.

The lot shall be rejected if more than 6% of the mines tested for anti-disturbance functioning are classed defective.

4.4.3.5 Breakwire functioning. Mines designated for breakwire testing shall be tested for the specified breakwire criteria in accordance with 4.5.11.2. Also, mines failing to function in the anti-disturbance mode in accordance with 4.5.11.1 shall be tested for breakwire functioning in accordance with 4.5.11.2. Mines which fail to deploy any triplines are to be scored as a no test for breakwire mode and deleted from the sample.

Mines either functioning or failing to function on the first breakwire attempt shall be included in the number of breakwire functioning test observed providing the sample is not classed as a safe dud.

The results of mines undergoing a second breakwire attempt shall be recorded for informational purposes only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

The lot shall be rejected if more than six percent (6%) of the mines tested for breakwire functioning is classed defective.

Mines failing to function on the first breakwire attempt shall be tested for anti-disturbance functioning in accordance with 4.5.11.1 as noted in 4.4.3.4.

4.4.3.6 Tripline deployment. All mines shall be visually examined for triplines deployed and, where required, for length of lead deployed. The results of the above shall be recorded. The lot shall be rejected if more than six percent (6%) of all mines conditioned to +70°F are classed defective. Tripline deployment for mines conditioned at the temperature extremes shall be recorded.

4.4.3.7 Premature functioning. All functioning mines shall be tested for premature functioning. Depressing the battery ball with the Cam determines the initiation of the arming cycle. The requirement is that no functioning (i.e. firing of the piston actuator, gas generator or detonator) for a minimum of 25 seconds after initiation of the arming cycle.

4.4.3.8 Data acquisition. All data pertaining to mine testing shall be recorded.

Included with lot acceptance criteria, records shall be maintained of the number of special test mines which function early or are complete duds as well as approximate time of early functioning.

4.4.3.9 Sensor intrusion test. Each lot of sensors shall be tested for the epoxy intrusion requirement (defined by 3.4.5 and 4.5.4.6) to determine if there is any epoxy intrusion. Testing for this requirement shall be completed prior to lot acceptance testing for sensor functional requirements (as defined in 3.4.1 through 3.4.4). The sampling plan used for the intrusion test defined in 3.4.5 shall be 80-8-9. Any lot failing to comply with the sampling shall be rejected.

4.4.3.10 Sensor wire continuity. As an alternate to inspecting a sample of the parts, the contractor may perform an inspection to verify the effectiveness of a 100% production screen for continuity of the sensor circuits. The inspection must verify that the test equipment and production operator are making the correct decision during the 100% screening operation. The plan for this verification must be documented and forwarded to the Technical Agency for approval.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:30Z
Check the source to verify that this is the current version before use.

4.4.3.11 Radiograph examination of cam. The cam shall be raidographed with the cam resting on its side. Units which fail to meet the requirement of 3.1.1 shall be classed defective and removed from the lot. This test is non-destructive. Radiographic equipment operations and procedures shall be qualified in accordance with MIL-STD-453. In addition, it will be classed as the defective void criteria. The sensitivity of radiographic techniques shall be at least two (2) percent, and the photographic density of the film used shall be of a quality which will produce a sharp definition of internal structure.

4.4.4 Inspection equipment. The inspection equipment required to perform the inspections specified herein is identified in the "Inspection Method Reference" column of the Classification of Characteristics listings starting with 4.4.2.1. Contractor inspection equipment designs shall be submitted for Government approval as specified in the contract. Designs which provide variable measurements instead of attributes data are preferred in order to facilitate the use of statistical process control. See MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection.

4.5.1 Arming of S&A assembly. After removing the safety pin from forty (40) of the S&A assemblies, the piston actuator shall be initiated. Standard safety practices shall be employed. Success will be measured by evidence of function of the lead cup assembly.

4.5.2 Non-arming of S&A assembly. Thirty (30) S&A assemblies shall be tested for non-arming by initiating the piston actuator. The safety pin must remain intact, blocking movement of the slider. Standard safety practices shall be employed. The S&A assemblies in 4.5.1 and 4.5.2 shall be molded in test blocks. The design of the test blocks shall be approved by the Government prior to testing.

4.5.3 Qualification test of electric detonator, transfer lead assembly and acceptor cup lead cup assembly lots. This qualification test shall be performed for the combination of detonator serial lot, transfer lead assembly serial lot, lead cup assembly serial lot and acceptor cup serial lot. The components to be used for this test shall be randomly selected from the respective lots. All detonators selected for this test shall remain shorted, (leads twisted) until immediately prior to firing. The components shall be assembled into S&A's comprised of housing, slider assembly, gasket and detonator side plate. (Piston actuators are not required.) The S&A's shall meet applicable drawing requirements, including those affecting the gaps between the detonator, transfer lead assembly and lead cup assembly. Detonating cord assemblies from an accepted lot shall be suitably attached next to the lead cup assembly with a .020 inch minimum spacing between the two assemblies. The short shall then be removed and the detonators shall be initiated from behind an approved barricade using a suitable power source (a 100 microfarad capacitor charged to 1.6 volts). Quantity of 50 shall be used for each part.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:30Z
Check the source to verify that this is the current version before use.

Observation shall be made for failure to initiate the detonating cord assembly. Approved barricades shall be used for assembling and testing these components. If the number of assemblies failing to initiate the detonating cord exceeds the specified acceptance criteria, that lot combination of detonators, transfer lead assemblies and lead cup assemblies shall be rejected for use in the molded assembly.

4.5.4 Sensor assembly.

4.5.4.1 Release and thread security of sensor assembly. The breakwire resistance shall be checked for continuity. Units which have resistance greater than 1,000 ohms shall not be subjected to this test. The units to be tested shall be placed in a suitable fixture and the pressure specified in 3.4.1 shall be applied. A unit shall be classified defective if any of the following occur:

a. Fails to release when initially pressurized as evidenced by the bobbin core being retained within the sensor case.

b. The breakwire continuity is broken as evidenced by a resistance greater than 1,000 ohms across the exposed ends for the breakwire.

c. The thread does not remain attached to the bobbin and post.

d. The thread breaks during release.

e. Any unit that does not release when initially pressurized, but releases when the pressure is reapplied, shall be classed defective. This test is destructive. Those units capable of meeting the requirements of the test specified in 4.5.4.2 shall be used for that test even if they failed to meet the requirements for this test.

4.5.4.2 Tripline deployment of sensor assembly. After the sensor assembly has been tested in accordance with 4.5.4.1, and with the sensor remaining in the test fixture, observation shall be made to assure that the bobbin core, with tripline attached, is deployed over a vertical barrier as follows:

a. The barrier location shall be 16 feet, minimum, measured horizontally from the sensor.

b. Barrier height shall be 7 inches, minimum, above the top of the sensor. A bobbin core that impacts ground level before the barrier or impacts the barrier shall be considered defective. This test is destructive.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

4.5.4.3 Breakwire function of sensor assembly. After the sensor assembly is tested in accordance with 4.5.4.1, 4.5.4.2 and with the unit remaining in the test fixture, a suitable force gage shall be attached to the tripline at a point just above the barrier. A pull force shall be applied along the axis of the bobbin post and the breaking force shall be noted. The breaking force is that force at which the resistance across the exposed ends meets the requirements specified in 3.4.3. Any unit that fails the pull force test, as specified in this paragraph, shall be classified defective. This test is destructive. Those units that are capable of meeting the requirements of the test specified in 4.5.4.4 shall be used for that test even if they failed to meet the requirements of this test. The rate of pull shall be a person walking at a normal rate.

4.5.4.4 Post retention and thread breaking strength. After the sensor assembly is tested in accordance with 4.5.4.1, 4.5.4.2, 4.5.4.3 and with the unit remaining in the test fixture, the specified force shall be applied at rate of 4 inches/second minimum to the tripline along the axis of the bobbin post. Any unit that releases the bobbin post or on which the tripline breaks shall be classed defective. This test is destructive. Units so tested shall not be returned to the lot. The rate of pull shall be a person walking at a normal rate.

4.5.4.5 Soldered electrical connections of sensor assembly. The electrical connections of the breakwire to the breakwire terminals shall be tested for electrical continuity using a suitable ohmmeter. The soldered connections shall have a smooth, bright appearance with metallic luster and shall not have a chalky, gritty surface, nor exhibit points (peaks), pits, scars, or fractures. The connections shall be completely covered by solder to the extent that no base metal is visible, with the exception that exposed copper is permissable on the end of the cut wires. Accept/reject criteria is as follows:

All examinations will be performed using a minimum 5X diopter lens. Suspected connections may be examined using 10X magnification to determine acceptability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

4.5.4.6 Molding material intrusion test. The sensor assembly will be placed into a test brick mold with twelve (12) sensors per mold. Shrink tubing will be assembled to the sensor nozzles and exit the mold. Sensor plugs will be assembled to the cap end. The mold will be closed and subjected to the normal ADAM wedge molding process. The test brick cure will be for a minimum of 16 hours at 155°F + 10°F cure temperature. The sensor caps shall be removed and the test brick assembled to an approved test fixture. The pressure specified in 3.4.5 shall be applied to the protruding end of the shrink tubing. This is a destructive test. Units may not be returned to the lot.

4.5.4.7 Level embrittlement test. The end of the lever shall be held in a fixture and a two (2) pound minimum weight shall be applied to the slotted portion of the sample. The weight shall be held in place for a minimum of twenty-four (24) hours. After removal of the weight, the lever shall be examined under a 10 power microscope for cracking. If one or more of the samples are classed defective, the heat treat batch shall be classed defective (Destructive Test).

4.5.5 Anti-disturbance switch.

4.5.5.1 Anti-disturbance switch function and closure time duration. The switch assembly shall be placed in an approved fixture. The fixture shall be capable of rotating the switch assembly through 360° on its cylindrical axis, while this axis is held at 15° + 2° referenced to the horizontal, for both clockwise and count-clockwise directions of rotation. The functional requirements of drawing 9298512 shall be met.

This is a non-destructive test and acceptable parts may be returned to the lot.

4.5.5.2 Insulation resistance of anti-disturbance switch. The switch assembly, when mounted in a suitable fixture, shall be measured for insulation resistance in the rest position using an approved megohmmeter. The megohmmeter reading shall meet the requirements of drawing 9298512. This is a non-destructive test and acceptance parts may be returned to the lot.

4.5.5.3 Plating of anti-disturbance switch components. Five (5) components shall be randomly selected from each plating batch. The specimens shall be checked in accordance with MIL-G-45204. If any sample fails to comply with the plating requirements, the sample shall be classed defective (Destructive test).

Source: https://assist.dla.mil -- Downloaded: 20260-26T04:30Z
Check the source to verify that this is the current version before use.

4.5.6 Weld test of printed wiring board assembly, interconnect. A sample of one (1) part from the first ten (10) welded shall be tested to qualify the welding equipment for use in production. In addition, one (1) sample shall be tested after production of one each 100 welded parts as a control of welding equipment during production. The units shall be placed in a fixture capable of applying the force specified on the applicable drawing. Any assembly in which the weld cracks or breaks when the specified force is applied shall be classed defective.

If any defective parts are found during qualification of welding equipment, the equipment producing the defective assembly shall not be used in production.

If any defective assembly is found when inspection is performed for control of the welding equipment, the equipment producing the defective weld shall be removed from production. Further, that portion of production since the last weld control check shall be returned to the contractor for corrective action.

If welding is stopped for one (1) hour or longer, the equipment shall be subjected to the qualification test prior to use in production.

All welding equipment removed from production because of some fault may, after reworking, be returned to production, providing it passes the qualification test above.

The contractor may use coupons of the same material and thickness as the parts being welded subject to approval of the Contracting Officer.

4.5.7 Quality controls for each molding compound batch for housing or plug.

4.5.7.1 Resin/hardener weight ratio control. At the beginning of production and at least once each four hours of production, or portion thereof, the inspector shall draw two (2) test shots with the mixer set to expel the hardener and resin separately. The hardener and resin of each shot shall be weighed individually to verify that the ratio is between 1.8/1 and 2.2/1. If either shot fails to meet the requirement, all items filled since the last acceptable check shall be rejected. Further, the mixer shall be corrected and shall pass the above test before being returned to use.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:30Z
Check the source to verify that this is the current version before use.

4.5.7.2 Mixing and cure control. One (1) test bar from each batch of molding compound (see 4.5.7.1) shall be molded at the same time the batch is used to mold housings or plugs, or bond plugs to housing for lot acceptance testing. Vibration and evacuation as necessary may be used to mold the bar. The mix ratio limits shall be 2.0/1 + 10% (1.8/1 to 2.2/1). The test bar shall be processed with the items molded from the batch of molding compound which the bar represents; i.e., the bar shall be cured in the same ovens and subjected to the same temperatures for the same periods as the time it represents. After completion of the cure, the bar shall be tested for ultimate compressive strength, as specified in ASTM-D-695(69) except that the specimen dimensions shall be 0.5 inch by 0.5 inch by 1.0 inch or 0.5 inch diameter by 1.0 inch long. The ends shall be flat and parallel to within .003 inch, and shall be perpendicular to the long axis of the specimen. Speed of testing shall be as specified in the ASTM.

4.5.8 Temperature control during molding/cure operations. Whenever the preform assembly, the housing, or the munition is subjected to heating in ovens, temperature records shall be maintained and reviewed to assure that the minimum temperature has been reached and that the maximum temperature has not been exceeded. If any units have been subjected to temperatures beyond the maximum limit at anytime, regardless of duration, they shall be rejected. Temperature measuring instruments shall be approved and calibrated in accordance with 4.4.4.

4.5.9 Functioning of the electronic circuitry of the housing, timing and fuzing. The electronic circuitry of each housing in the lot shall be tested after molding and prior to filling the test conductor areas. Each housing shall be subjected to the tests listed below. All housings containing any defect shall be removed from the lot.

Test	Paragraph	Limits
Detonator and Gas Generator Logic	40.2.4	Improper
Preliminary Oscillator Frequency	40.2.1	a) Less than 97% of nominal. b) More than 104% of nominal. c) Equal to or greater than 97% and less than 99% of nominal or greater than 102% but less than or equal to 104% of nominal.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:30Z
Check the source to verify that this is the current version before use.

Barrier Oscillator Frequency	40.2.1	a) Less than 97% of nominal. b) More than 104% of nominal. c) Equal to or greater than 97% and less than 99% or nominal or greater than 102% but less than or equal to 104% of nominal.
System Operating Current	40.2.2	Greater than 1.8 milliamps but less than 2.40 milliamps.
Self-Destruct Time Out	40.2.3	a) Greater than 100.1% of nominal.
Low Voltage	40.2.5 At TA=+25°C +5°C (+77° ± ±10°)	a) Type I: Non-functioning, or functioning less than. b) Type I: Equal to or greater than 3.2 volts but less than 3.4 volts.
Detonator Resistance	40.2.9 (see note)	Less than 2.9 ohms greater than 9.5 ohms.

NOTE: This test shall be 100% performed on Part #9298451 prior to molding, and precaution should be taken to assure that the solder bridge is present to prevent inadvertent functioning of the detonator during handling prior to test. Assurance shall be provided that the solder bridge is removed immediately prior to the resistance test so as not to invalidate test results.

Test	Paragraph	Limits
Output Capacitor Voltage	40.2.6	Improper
Continuity	40.2.12	a) Both circuits open. b) One circuit open.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:30Z
Check the source to verify that this is the current version before use.

Anti-disturbance Switch Operation	40.2.12	

The following tests shall be performed after adding the permanent detonator short.

Detonator Short	40.2.11	Absence of Short
Gas Generator	40.2.10	a) Equal to or less than 1.1. ohms or equal to or greater than 2.9 ohms. b) Greater than 4.0 ohms but less than 8.0 ohms.

4.5.10 Pull test. The sample shall be fixtured and the ribbon lead shall be pulled in the specified direction to meet the specified minimum force. The sample shall not indicate failure of the weld during the test. Any sample failing to comply with all of the specified requirements shall be classed defective (Destructive test).

4.5.11 Mine functioning.

4.5.11.1 Anti-disturbance functioning. The sample selected for anti-disturbance functioning shall be tested in the following manner:

a. The sample under test shall be tested as follows:

(1) If the mine is resting on an end face, rotate it to an adjacent slant face or arc face.

(2) If the mine fails to function on the first movement, it shall be moved a second time to an adjacent face. If the mine is currently resting on a slant face, it can be moved to either the other slant face or end face not previously encountered in the first movement.

If the mine is resting on the arc face, it shall be rotated to the end face not encountered during the first movement.

b. All data shall be recorded.

c. If the mine fails to function it shall be tested for breakwire activation in accordance with 4.5.11.1a) through 4.5.11.2e).

d. If the mine fails to funciton, another tripline from the adjacent breakwire circuit shall be randomly selected and tested in accordance with 4.5.11.2a through 4.5.11.2e for infomational purposes only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

4.5.11.2 Breakwire functioning. The sample selected for breakwire functioning shall be tested in the following manner:

a. The sample to be tested shall be restricted from any movement.

b. Any tripline from either breakwire cricuit shall be selected for an activation attempt.

c. A digital readout force gage shall be attached to the lead and an axial force shall then be applied to the device under test.

d. The tripline, with gage attached, shall be pulled until either the mine functions or the tripline fails to function within the specified limits.

e. All data shall be recorded. The mine shall be classed defective if it fails to function with the specified force criteria for breakwire functioning.

f. The mine shall be tested for anti-disturbance functioning in accordance with the procedures of 4.5.11.1 and the requirements of 3.11.1 and shall be scored.

g. If the mine fails to function in the anti-disturbance mode, another tripline from the adjacent breakwire circuit shall be tested for breakwire functioning and shall be scored.

h. If the mine fails to function in the second breakwire attempt, it shall be left to time out for self-destruct functioning.

i. If the mine fails to function self-destruct, it shall be tested in accordance with 4.5.14 for the hazardous dud requirements of 3.13.2 (Destructive test).

4.5.11.3 Self-destruct function. The mines selected for self-destruct functioning shall be flagged and monitored for detonation times. All times of detonator, early or normal, shall be recorded (Destructive test).

4.5.12 Tripline deployment. All samples shall be visually examined and measured when required for the tripline deployment criteria of 3.12. Any mine failing to meet the specified criteria shall be classed defective.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:30Z
Check the source to verify that this is the current version before use.

4.5.13 Hazardous dud evaluation procedure. (Special test mine) Any mine which has failed to function in the breakwire mode, anti-disturbance mode or failed to function self-destruct after the maximum time out has elapsed shall be subjected to the following inputs to determine if the detonator can be fired:

a. One additional tripline, on the item, shall be pulled. All other triplines shall be cut so as not to activate the remaining breakwires.

b. The item shall be tipped about the arc face, to the slant face, to the apex and to the opposite slant face.

c. Repeat b.

The inputs shall be applied in the order listed above. If the detonator functions when any of these inputs is applied, the unit shall be classed as a hazardous dud. If the detonator does not fire after all these inputs are applied, it shall be classed as a non-hazardous dud.

4.5.14 Slider integrity. The contractor shall submit to the Government a test plan for testing the integrity of each sintered slider lot. As a minimum three temperatures must be used for testing (-45°+5°F, 70+5°, 145+5°F). A portion of the test plan must include testing the loaded slider P/N 9366684 at all three temperatures with an M100 firing directly into the wall of the loaded slider. The test quantity shall be no less than 10 pieces at each temperature (30 at cold temp) for a total of 50 loaded sliders being fired on. A failure (critical) will be assumed if evidence of any cracking or spalling of the slider takes place or an initiation of the loaded slider occurs. Submission of the test procedure shall be submitted to the Government for approval prior to testing.

5. PACKAGING

5.1 Packaging, packing, and marking requirements for arming assemblies. The Arming Assemblies (12579595) shall be preserved, packaged, packed and marked in accordance with the requirements of Special Packaging Instruction (SPI) P12579595.

5.2 Packaging requirements for molded assembly (molded assembly - 9366661-1.

5.2.1 Packaging.

5.2.1.1 Level A. Level A packaging not applicable.

5.2.1.2 Level B. Level B packaging not applicable.

5.2.1.3 Level C. Packaging shall be in accordance with Dwg. 12598601.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

5.2.2 Packing.

5.2.2.1 Level A. Level A packing not applicable.

5.2.2.2 Level B. Level B packing not applicable.

5.2.2.3 Level C. Level C packing shall be in accordance with Dwg. 12598601.

5.2.3 Marking.

5.2.3.1 Level A. Level A marking not applicable.

5.2.3.2 Level B. Level B marking not applicable.

5.2.3.3 Level C. Level C marking shall be in accordance with Dwg. 12598601.

5.3 Shipping. When shipments of units from more than one lot are made at one time, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory).

6.1 Intended use. The Molded Assembly covered by this specification is intended for use in the Pursuit Deterrent Munition/Hand Emplaced Mine M86.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of indivisual documents referenced (see 2.1.2).

c. Requirements for submission of first article sample.

6.3 Submissions of contractor inspection equipment designs for approval. Submit copies of designs as required, to: Commander, ARDEC, ATTN: SMCAR-QAT-I, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:30Z
Check the source to verify that this is the current version before use.

6.4 Submission of alternative quality conformance provisions. Unless otherwise specified in the contract, proposed alternative quality conformance provisions will be submitted by the contractor for evaluation by the technical activity responsible for the preparation of this specification.

6.5 Data requirements. Deliverable data required by this specification is cited in paragraphs listed below. The form DD 1423 should include distribution to SMCAR-QAT-M (D).

Paragraph	Data Requirements	Applicable DID
4.4.2.1 through 4.4.2.61 as applicable	Quality Deficiency Reports	DI-QCIC-80736

6.6 Molding compound batch definition. A batch of molding compound is herein defined as that quantity of compound mixed at one time using base resin and hardener of one lot number from one manufacturer to mold housings of plugs in one continuous, unchanged process. When a continuous type mixing process is used, a batch is that quantity of molding compound mixed and dispensed in one continuous, unchanged process during a one (1) hour period or portion thereof using base resin and hardener of one lot number from one manufacturer.

6.7 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament, Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as U.S. Army Armament, Research and Development Command (ARRADCOM), Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under cognizance of ARDEC.

6.8 Subject term (key word) listing.
Anti-personnel
Arming assembly
Slider assembly
Acceptor lead assembly

6.9 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1320-A520)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-P-70697A (AR)	940621

3. DOCUMENT TITLE PURSUIT DETERRENT MUNITION, HAND EMPLACED MINE (PDM), M86 MOLDED ASSEMBLY FOR

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
U.S. ARMY ARDEC STANDARDIZATION OFFICE	(1) Commercial 201-724-6675	(2) AUTOVON DSN-880-6675
c. ADDRESS (Include Zip Code) ATTN: SMCAR-BAC-S PICATINNY ARSENAL, NJ 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 *Previous editions are obsolete.* 198/290

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:30Z
Check the source to verify that this is the current version before use.