MIL-A-27582A(USAF)
26 August 1963
Superseding
MIL-A-27582(USAF)
17 May 1963

MILITARY SPECIFICATION

ADAPTER, TEST MX-6050/PSM-6

1. SCOPE. This specification covers the requirements for one type of test adapter designated as the MX-6050/PSM-6 hereafter referred to as the adapter. The adapter is designed to check arming control monitor circuits of fighter and bomber aircraft.

2. APPLICABLE DOCUMENTS. The following documents of the issue in effect on the date of invitation for bids form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

PPP-B-566	Boxes, Folding, Paperboard
PPP-B-601	Boxes, Wood, Cleated-Plywood
PPP-B-621	Boxes, Wood, Nailed and Lock Corner

Military

JAN-P-100	Packaging and Packing for Overseas Shipment, General Specification
MIL-P-116	Preservation, Methods Of

STANDARDS

Military

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-130	Identification Marking of U. S. Military Property

DRAWINGS

Air Force

63D13071	Adapter, Test MX-6050/PSM-6, Assembly Of

(Copies of documents required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 6625

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:25Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 DESIGN AND CONSTRUCTION. The adapter shall be designed and constructed in accordance with drawing number 63D13071 and subsidiary drawings.

3.2 PERFORMANCE. Performance requirements of the adapter shall consist of the capability to detect existence or absence of voltage on the critical bomb arming control monitor circuits of fighter and bomber aircraft when used with the AN/PSM-6 Multimeter and mated to appropriate aircraft circuits.

3.3 IDENTIFICATION OF PRODUCT. The adapter, parts and assemblies shall be marked for identification in accordance with MIL-STD-130.

3.4 WORKMANSHIP. The adapter and parts shall be fabricated in a manner such that the criteria of appearance, fit, and adherence to specified tolerances are observed. Particular attention shall be given to neatness of marking, soldering and screw assemblage. All components shall be free of burrs or sharp edges which might mar adjacent equipment or injure operating personnel.

4. QUALITY ASSURANCE PROVISIONS

4.1 CLASSIFICATION OF TESTS. Inspection and testing of the adapter shall consist of the following individual tests:

a. Examination of Product

b. Conformance to Drawings

c. Electrical Tests

4.2 REJECTION AND RETEST. When an item fails to meet the specified tests, no item still on hand or later produced shall be accepted until the extent and cause of failure are determined and corrected.

4.3 DEFECTS IN ITEMS ALREADY ACCEPTED. The investigation of a test failure could indicate that defects may exist in items already accepted. If so, the contractor shall fully advise the procuring activity of all defects likely to be found and methods of correcting them.

4.4 TEST CONDITIONS. Unless otherwise specified for specific tests all tests shall be conducted under ambient conditions.

4.5 TEST METHODS

4.5.1 EXAMINATION OF PRODUCT. Each adapter shall be examined visually to determine compliance with the requirements of this specification for which tests are not specified. Failure to satisfy these requirements shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:25Z
Check the source to verify that this is the current version before use.

4.5.2 CONFORMANCE TO DRAWINGS. Each adapter shall be inspected to determine strict conformance to the engineering drawings and to all specifications and standards referenced therein. Failure to conform to the above criteria shall be cause for rejection.

4.5.3 ELECTRICAL TEST. Using a suitable ohmmeter or resistance bridge and by reference to the schematic shown on drawing number 63D13071, the following resistance measurements shall be made:

FROM-TO	MEASURED RESISTANCE (OHMS)
Pin C to D	Less than 0.1
Pin C to N	Less than 0.1
Pin C to I	Less than 0.1
Pin C to a	Less than 0.1
Pin C to g	Less than 0.1
Pin C to Red Jack (with switch in ARM position)	Less than 0.1
Pin A to F	Less than 0.1
Pin A to B	Less than 0.1
Pin A to Red Jack (with switch in SAFE position)	Less than 0.1
Pin E to H	Less than 0.1
Pin E to f	Less than 0.1
Pin E to O	Less than 0.1
Pin S to b	Less than 0.1
Pin K to Red Jack	Less than 0.1
Pin L to k	Less than 0.1
Pin L to Black Jack	Less than 0.1
Red Jack to Black Jack	500 $\pm$ 100

Measured resistance not meeting these requirements shall be cause for rejection. Each pin not listed above shall be checked for absence of inadvertent interconnection. Any indication of continuity between these pins and any other pin shall be cause for rejection.

5. PREPARATION FOR DELIVERY

5.1 PRESERVATION, LEVELS A AND B. Preservation for all shipping and storage shall be in accordance with Method 1A8, MIL-P-116.

5.2 PACKAGING, LEVELS A AND B. Each adapter, preserved as specified in 5.1 shall be packaged in a box conforming to PPP-B-566, Style I, Type A, Class b.

5.3 PRESERVATION AND PACKAGING, LEVEL C. Adapters shall be preserved and packaged to afford adequate protection against corrosion, deterioration and physical damage during shipment from supply source to first domestic receiving activity for immediate use. This preservation and packaging may be in accordance with the supplier's commercial practices when such meets the above requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:25Z
Check the source to verify that this is the current version before use.

5.4 PACKING, ALL LEVELS. A number of adapters specified by the procuring activity shall be prepared in accordance with 5.1 and 5.2 or 5.3 and packed in a box conforming to PPP-B-601 or PPP-B-621. Physical protection shall be in accordance with JAN-P-100.

5.5 MARKING. Interior and exterior containers shall be marked in accordance with MIL-STD-129. Nomenclature shall be:

ADAPTER, TEST MX-6050/PSM-6

6. NOTES

6.1 INTENDED USE. The adapter, used with the AN/PSM-6 Multimeter, is intended for use in determining the existence or absence of voltage on critical bomb arming control monitor circuits of fighter and bomber aircraft. This use obviates the use of multimeter probes in checking connections which are inaccessible in varying degrees.

6.2 ORDERING DATA. Procurement documents should specify the following:

a. Title, number and date of this specification.

b. Levels of preservation, packaging and packing.

NOTICE: When Government drawings, specifications or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

WLDC-3
MHJ/pfg

GPO 804-149

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:25Z
Check the source to verify that this is the current version before use.