MILITARY SPECIFICATION

ADAPTER, TEST MX-6050/PSM-6

This amendment forms a part of Military Specification MIL-A-27582A(USAF), dated 26 August 1963.

Page 3, paragraph 4.5.3: Delete and substitute:

"4.5.3 ELECTRICAL TEST. Using a suitable ohmmeter or resistance bridge and by reference to the schematic shown on Drawing Number 63D13071, the following resistance measurements shall be made:

FROM-TO	MEASURED RESISTANCE (OHMS)
Pin C to g	Less than 0.1
Pin C to I	Less than 0.1
Pin C to a	Less than 0.1
Pin C to D	Less than 0.1
Pin C to N	Less than 0.1
Pin C to O	Less than 0.1
Pin C to U	Less than 0.1
Pin C to V	Less than 0.1
Pin C to Red Jack (with switch in ARM position)	Less than 0.1
Pin A to Red Jack (with switch in SAFE position)	Less than 0.1
Pin h to Black Jack	Less than 0.1
Pin E to K	Less than 0.1
Pin L to S	Less than 0.1
Pin G to j	Less than 0.1
Red Jack to Black Jack	500 ± 100

Measured resistance not meeting these requirements shall be cause for rejection. Each pin not listed above shall be checked for absence of inadvertent interconnection. Any indication of continuity between these pins and any other pin shall be cause for rejection.

FSC 6625

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:25Z
Check the source to verify that this is the current version before use.

Custodian:

Air Force - 67

Reviewer:

Air Force - 67

Preparing Activity:

Air Force - 67

Review/user information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:25Z
Check the source to verify that this is the current version before use.