MILITARY SPECIFICATION

DUMMY WARHEAD, MISSILE MDU-8/A

1. SCOPE. This specification covers one type of equipment designated as Dummy Warhead, Missile MDU-8/A, hereafter referred to as the dummy warhead, for use in crew training in the handling and loading of warheads and will permit training in the types of missiles which are intended as carriers of the parent weapon. This item is non-expendable and is not normally fired with the missile.

2. APPLICABLE DOCUMENTS. The following documents, of the issue in effect on the date of invitation for bids, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

TT-T-266	Thinner; Dope and Lacquer (Cellulose-Nitrate)
PPP-B-601	Boxes, Wood, Cleated, Plywood
PPP-B-621	Boxes, Wood, Nailed and Locked Corners

Military

JAN-P-100	Packaging and Packing for Overseas Shipping, General Specification
MIL-P-116	Preservation: Methods Of
MIL-E-4970	Environmental Testing, Ground Support Equipment, General Specification For
MIL-L-7178	Lacquer, Cellulose Nitrate, Gloss, for Aircraft Use
MIL-T-9107	Test Reports, Preparation Of
MIL-B-13239	Barrier Material, Waterproof Flexible, All Temperatures
MIL-B-27000	Bomb, Practice, General Specification For
MIL-D-70327	Drawings, Engineering and Associated Lists

STANDARDS

Federal

FED-STD-595	Colors

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:24Z
Check the source to verify that this is the current version before use.

Military

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-130	Identification Marking of U. S. Military Property

DRAWINGS

Air Force

61J14150	Dummy Warhead MDU-8/A
61E14152	Forward Section
61D14153	Aft Section

(Copies of documents required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 PREPRODUCTION TESTING. This specification makes provisions for preproduction testing.

3.2 COMPONENTS

3.2.1 The dummy warhead shall consist of the following major components:

ITEM	DRAWING NUMBER	QUANTITY
Forward Section	61E14152	1
Aft Section	61D14153	1

3.3 GENERAL SPECIFICATIONS. The requirements of MIL-B-27000 apply as requirements of this specification with the exceptions and additions called out herein. When the two specifications conflict, this specification shall govern.

3.4 DESIGN AND CONSTRUCTION. Design and construction of the dummy warhead shall be in accordance with drawing 61J14150 and all subsidiary detail drawings.

3.4.1 FORWARD SECTION. The forward section shall be designed and constructed in conformance to drawing 61E14152.

3.4.2 AFT SECTION. The aft section shall be designed and constructed in conformance to drawing 61D14153.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:24Z
Check the source to verify that this is the current version before use.

3.4.3 INTERCHANGEABILITY. The warhead shall be interchangeable from one RVU-8/E Dummy Re-Entry Vehicle to another. Parts functionally and dimensionally interchangeable shall be identified by the same part number. When parts are not interchangeable, the criteria listed in MIL-D-70327 shall apply and new drawings shall be prepared as required.

3.4.4 FINISH PROCESS. The Dummy Warhead shall be finished in accordance with the finish requirements of MIL-B-27000.

3.4.4.1 FINISH COAT ON EXTERNAL SURFACES. The external surface shall be given a finish coat in accordance with the following:

a. Lacquer, Gloss, MIL-L-7178 or equivalent, color aluminum; two coats.

b. Lacquer, Gloss, MIL-L-7178 or equivalent, clear; two coats.

c. The lacquer shall be thinned by one volume of lacquer thinner, TT-T-266 to two volumes of lacquer.

d. The lacquer shall be applied by spraying on a coat 0.5 to 1.0 Mil in thickness.

e. Parts shall be allowed to air dry for a minimum of one hour prior to handling.

3.5 PERFORMANCE

3.5.1 FUNCTIONAL. Satisfactory functional performance of the dummy warhead shall be interpreted as proper attachment of forward ring and support base to the operational hardware or master gages of these attachment points and simulation of electrical checkouts of the parent warhead.

3.5.2 STATIC LOADS. The dummy warhead shall be capable of withstanding the static loads imposed by handling and suspension.

3.5.3 ENVIRONMENTAL CONDITIONS. The dummy warhead shall be capable of satisfactory performance during or after, as applicable, subjection to the following environmental conditions:

a. High temperature to +160°F.

b. Low temperature to -65°F.

c. Salt-fog, likely to be encountered during storage, use or transportation near a large body of salt water.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:24Z
Check the source to verify that this is the current version before use.

d. Sunshine, such as encountered in dry, hot climates.

e. Sand and dust likely to be encountered in desert areas.

f. Vibration likely to be experienced during transportation and handling.

g. Shock likely to be experienced during transportation and handling.

3.6 IDENTIFICATION OF PRODUCT. Equipment, assemblies, and parts shall be marked for identification in accordance with MIL-STD-130.

3.7 GOVERNMENT LOANED PROPERTY. When so stated in the contract, the following item shall be furnished to the contractor as Government loaned property for the purpose of testing the warhead:

ITEM NUMBER	ITEM DESCRIPTION	DRAWING NUMBER	QUANTITY
1	Dummy Re-Entry Vehicle Group RVU-8/E	61J15765	1

3.8 WORKMANSHIP. Workmanship requirements shall be in accordance with MIL-B-27000.

4. QUALITY ASSURANCE PROVISIONS

4.1 CLASSIFICATION OF TESTS. The inspection and testing of the dummy warhead shall be classified as follows:

a. Preproduction Testing

b. Acceptance Test

4.2 PREPRODUCTION TESTING

4.2.1 PREPRODUCTION TEST SAMPLES. The preproduction test units, prepared by the contractor shall be representative of the production equipment. They shall be tested at a laboratory designated by the procuring activity, or when so stated in the contract, at the contractor's plant under the supervision of the procuring activity.

4.2.1.1 PREPRODUCTION TEST REPORTS. In the event that preproduction testing is performed at the contractor's plant, the contractor shall, after completion of the preproduction test, prepare a preproduction test report according to MIL-T-9107, and furnish three complete copies of the report to the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:24Z
Check the source to verify that this is the current version before use.

4.2.2 PREPRODUCTION TESTS. Preproduction tests shall consist of all tests described in "4.5 TEST METHODS" of this specification, and shall be arranged in the same order.

4.3 ACCEPTANCE TESTS. Acceptance tests shall consist of the following individual tests as described under "4.5 TEST METHODS" of this specification:

a. Examination of Product

b. Conformance to Drawings

c. Functional Test

4.4 TEST CONDITIONS. The test conditions are described under the test methods to which they apply.

4.5 TEST METHODS

4.5.1 EXAMINATION OF PRODUCT. Each dummy warhead shall be given a complete visual examination to determine compliance with the requirements of this specification for which tests are not specified, including workmanship. Failure to pass this inspection shall be cause for rejection.

4.5.2 CONFORMANCE TO DRAWINGS. Each dummy warhead shall be inspected for strict conformance to the engineering drawings and all specifications and standards referenced therein. Failure to conform to these criteria shall be cause for rejection.

4.5.3 FUNCTIONAL TEST. The following operations shall be checked by any suitable means. Failure to obtain the required fit or response shall be cause for rejection:

a. Fit of forward section to aft section.

b. Fit of skirt to warhead.

c. Fit of warhead to handling sling.

d. Electrical continuity.

4.5.4 TRANSPORTATION AND HANDLING LOAD TEST. With the dummy warhead mounted on its most common transportation media, loads shall be applied, (either positive or negative), through the c.g. of the warhead. Direction and magnitude of loads shall be:

a.	Lateral	1000 pounds
b.	Vertical	4125 pounds
c.	Longitudinal	4125 pounds

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:24Z
Check the source to verify that this is the current version before use.

4.5.5 SHOCK TEST. The dummy warhead, when fully assembled, shall be subjected to the shock test specified in MIL-B-27000 with the following exception: 30 inch suspension system and sway brace simulation shall not apply. Permanent deformation or failure of any part shall be cause for rejection.

4.5.6 ENVIRONMENTAL TESTS. The dummy warhead shall be subjected to the following test in accordance with the indicated procedures of MIL-E-4970:

TEST	PROCEDURE
a. High temperature	I
b. Low temperature	I
c. Salt-fog	I
d. Sunshine	I
e. Sand and dust	I
f. Vibration	VI

5. PREPARATION FOR DELIVERY

5.1 LEVELS OF PRESERVATION

5.1.1 LEVEL A, B, AND C. The dummy warhead shall be preserved in accordance with MIL-P-116, method III for all levels. Unit quantities shall be one each.

5.2 LEVELS OF PACKING

5.2.1 LEVELS A AND B. The dummy warhead shall be packaged in exterior type shipping containers meeting PPP-B-601, style A with skids added or PPP-B-621, style 2 with skids added as far as practicable, exterior container shall be of uniform shape and size, be of minimum cube and tare consistent with protection required. Containers shall be closed and strapped in accordance with the applicable container specifications or appendix thereto. Containers shall be provided with a case liner conforming to MIL-B-13239 and shall be sealed in accordance with the appendix thereto.

5.2.2 LEVEL C. Packages which require overpackaging for acceptance by the carrier shall be packed in exterior type shipping containers in a manner that will insure safe transportation at the lowest rate to the point of delivery. Containers shall meet consolidated freight classification rules or regulations of other common carriers as applicable to the mode of transportation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:24Z
Check the source to verify that this is the current version before use.

5.2.3 PHYSICAL PROTECTION. Cushioning, blocking, bracing, bolting, and testing to determine adequacy as required shall be in accordance with JAN-P-100. The drop tests of MIL-P-116 are not required when the level of packing is Level C.

5.3 MARKING. Interior and exterior containers shall be marked in accordance with MIL-STD-129. The nomenclature shall be as follows:

DUMMY WARHEAD, MISSILE MDU-8/A

6. NOTES

6.1 INTENDED USE. The dummy warhead is intended to be used by ground crews to gain practice in ground handling and loading of the parent weapon. This item is non-expendable and is not normally fired with the carrying missile.

6.2 ORDERING DATA. Procurement documents should specify the following:

a. Title, number and date of this specification.

b. Conditions under which Government loaned property will be made available to the contractor.

c. Whether preproduction tests will be conducted by the procuring activity.

d. Levels of preservation, packaging and packing.

6.2.1 PREPRODUCTION TEST SAMPLES. It is expected that the contract or purchase order will specify that two units representative of the production dummy warhead will be submitted to the procuring activity for test and evaluation. The invitation for bids, and the contract or purchase order, should specify the point of inspection for these tests.

6.3 PRODUCTION DELIVERY. No production items should be delivered prior to approval of the preproduction samples.

6.4 SOURCES. When requesting publications, refer to both title and number.

6.5 DEFINITIONS

a. PREPRODUCTION TEST. Preproduction tests are those tests performed prior to production on representative samples of the production equipment to demonstrate that the equipment meets the requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:24Z
Check the source to verify that this is the current version before use.

b. ACCEPTANCE TEST. Acceptance tests are those tests accomplished on representative samples of equipment submitted for acceptance under a contract to determine conformance to the requirements of this specification, and to determine that the equipment is equivalent in performance and construction to the approved preproduction samples.

NOTICE: When Government drawings, specifications or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

SWVSC
MHJ/pfg

GPO 821769

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:24Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-014-1802

☆ U.S. GOVERNMENT PRINTING OFFICE: 1973—714-866/3983 2-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:24Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

San Antonio Air Logistics Center
Standardization
Directorate of Special Weapons
San Antonio ALC (SWRCS)
Kelly AFB TX 78241

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:24Z
Check the source to verify that this is the current version before use.