27 January 1989

MILITARY SPECIFICATION
HEATER, DUCT TYPE, PORTABLE, TRAILER MOUNTED, HDU-13/M

This amendment forms a part of MIL-H-27507C (USAF) dated 31 October 1983, and is approved for use within the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

Page 1

1.2 Classification. CHANGE:

Class 2 - "200" to "208"

Add the following:

Class 3 - Equipped with a 380 volt, 50 hertz electric motor and other components compatible with this power source.

Class 4 - Equipped with a 230/460 volt, 50/60 hertz electric motor and other components compatible with this power source.

2.1.1 Specifications and standards. Add the following:

MIL-E-16298	Electric Machines having Rotating Parts and Associated Repair Parts: Packaging of
MIL-P-116	Preservation, Methods of
FED-STD-H28	Screw Thread Standards for Federal Services.
MIL-STD-143	Standards and Specifications, Order of Precedence for the Selection of

Delete the Following:

MIL-T-704	Treatment and Painting of Materiel
MIL-C-5541	Chemical Conversion Coating on Aluminum and Aluminum Alloys
MIL-A-8625	Anodic Coatings, for Aluminum and Aluminum Alloys

FSC 4520

AMSC N/A

Distribution Statement A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:14Z
Check the source to verify that this is the current version before use.

MIL-P-19834	Plates, Identification or Instruction, Metal Foil Adhesive Backed General Specification for
DOD-STD-100	Engineering Drawing Practices
MIL-STD-831	Test Reports, Preparation of

Page 3

2.1.2 Other Government documents, drawings and publications. Delete: "National Bureau of Standards Handbook H-28" and associated references.

Page 5

3.1 Preproduction. Add to the end of the sentence:
"(see 4.2, 4.4 and 6.2)"

Page 8

3.7.2.1 Secondary fluid system. Change:
"Diethylene glycol" to "Diethylene-Monobutyl-Glycol-Ether" in first sentence.
"explosion" to "expansion" in the last sentence.

Page 9

3.7.6 Power Package. Sub Paragraph b. change:
"200" to "208"

Add the following subparagraphs:

c. Class 3 Heater. 380 volt, 50 hertz. The total current draw of the heater shall not exceed 62 amps.

d. Class 4 Heater. 230/460 volt, 50/60 hertz. The total current draw of the heater shall not exceed 104 amps for 230 volt operation and 52 amps for 460 volt operation. When delivered, the unit shall be connected for 230 volt operation. The heater shall be capable of operation with all possible combinations of volts and hertz.

3.7.6.1 Electric Motor. Subparagraph a, delete reference to:
Federal Specification CC-M-1807.

Replace with NEMA Standard MG-1.

Subparagraph b, change:

"220" to "208" and "440" to "400"

Add the following subparagraph:

c. Class 3 and Class 4 Heater. The electric motor shall be compatible with the power package and shall allow the heater to comply with all requirements herein.

Page 10

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:14Z
Check the source to verify that this is the current version before use.

3.7.7.6 Power cable. Change the first sentence to read:

For all classes of heaters (1,2,3 and 4), the power lead-in cable shall be a 50 foot long, extra flexible, six conductor, 600 volt cable conforming to MIL-C-5756.

Subparagraph a, delete second sentence and add:

"A connector reflecting the pin arrangement and dimensional characteristics of MS 27265 shall be molded to the connector."

Page 12

3.14.2 Warning plate. Delete and substitute:

For Class 1 and Class 4 heaters, a reversible warning plate shall be fastened to the outside of the cable compartment door indicating appropriate voltage at which the unit is to be operated. One side of the plate shall contain a wiring diagram representing one of the voltages along with instructions for changeover to the alternate voltage for that class heater. The reverse side of the plate shall contain a wiring diagram representing the alternate voltage with instructions for changeover back to the original voltage.

Page 24

6.2 Ordering data. Add the following requirement:

"d. Definitive military specification part number required (see 1.2.1 and 6.5)".

Page 25

6.5.1 Class designator. Table III, class II change:

"220" to "208"

Table III, add:

III	Equipped with a 380 volt, 50 hertz, electric motor.
IV	Equipped with a 230/460 volt, 50/60 hertz electric motor.

Custodian:
Air Force - 99

Preparing Activity:
Air Force - 84

Reviewer:
DLA - CS

Project No: 4520-F319

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:14Z
Check the source to verify that this is the current version before use.