MIL-O-27525(USAF)
AMENDMENT 2
15 April 1969

SUPERSEDING
AMENDMENT 1
21 October 1968

MILITARY SPECIFICATION

OVERCOAT, SURVIVAL, ARCTIC SRU-6/P

This amendment forms a part of Military Specification MIL-O-27525(USAF) dated 16 January 1962.

Page 1

2.1: Under SPECIFICATIONS, Federal add:

"V-T-295 Thread, Nylon"

2.1: Under SPECIFICATIONS, Military delete:

"MIL-T-7807 Thread, Nylon"

2.1: Under SPECIFICATIONS, DRAWINGS, Air Force add:

"61K4027 Patterns - Arctic Survival Overcoat"

Page 4

3.1.8: Delete and substitute:

"3.1.8 Tape for neck, front and rear closures. The tape used for the neck, front and rear closures shall be made of nylon fastener tape conforming to type II closure of MIL-F-21840. The tape shall be 1 inch wide, and the color of the tape shall be white for the neck closure. The tape for the front and rear closures shall match the basic material color."

3.1.10, second line: Delete "MIL-T-7807" and substitute "V-T-295."

3.4, third line: After "Drawing 61B4026" add "and sheets 1 and 2 of Drawing 61K4027."

FSC 8415

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:16Z
Check the source to verify that this is the current version before use.

Page 6

TABLE II - SEWING OPERATIONS: After No. 6c add the following:

No.	Description of Operation	Stitch Type	Seam and Stitching Type	Stitches Per Inch
6.	d. Tape for front closure.	301	SSa-1	10-12
	(1) Place between each stud portion of the snap fastener, 24 each, on the outside of the right front outer shell panel a piece of pile nylon fastener tape conforming to Type II closure of MIL-F-21840. The tape shall be 1 inch wide and located no closer than 1/2 inch ±1/16 inch to the snap fastener stud. The tape shall be fastened with a single row of stitching 1/16 inch from each edge.			
	(2) Place between each female portion of the snap fastener, 12 each, on the outside of the left front inner shell panel a piece of hook nylon fastener tape conforming to Type II closure of MIL-F-21840. The tape shall be 1 inch wide and located no closer than 1/2 inch ±1/16 inch to the snap fastener button and aligned to lock into the pile on the right front outer shell panel. The tape shall be fastened with a single row of stitching 1/16 inch from each edge.	301	SSa-1	10-12

Page 18

TABLE II - SEWING OPERATIONS: Change "No. 27" to "No. 28" and add the following new paragraph as "No. 27."

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:16Z
Check the source to verify that this is the current version before use.

No.	Description of Operation	Stitch Type	Seam and Stitching Type	Stitches Per Inch
27.	Tape for back slit closure. a. Place between each stud portion of the snap fastener, 5 each, on the outside of the left facing at slit on back of coat a piece of pile nylon fastener tape conforming to Type II closure of MIL-F-21840. The tape shall be 1 inch wide and located no closer than 1/2 inch ±1/16 inch to the snap fastener stud, the tape shall be fastened with a single row of stitching 1/16 inch from each edge.	301	SSa-1	10-12
	b. Place between each female portion of the snap fastener, 5 each, on the inside of the right facing, at the slit on the back of the coat, to match the pile nylon fastener on the outside of the left facing, a piece of hook nylon fastener tape conforming to Type II closure of MIL-F-21840. The tape shall be 1 inch wide and located no closer than 1/2 inch ±1/16 inch to the snap fastener button. The tape shall be fastened with a single row of stitching 1/16 inch from each edge.	301	SSa-1	10-12

Delete "NOTICE" in its entirety and substitute the following concluding material:

Custodian:
Air Force - 82

Preparing Activity:
Air Force - 82

Review Activity:
Air Force - 82

Project No. 8415-F539

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:16Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:16Z
Check the source to verify that this is the current version before use.