MILITARY SPECIFICATION

TRAILER, DUMMY BOMB MHU-47/E

1. SCOPE. This specification covers the requirements for one type of trailer designated as the MHU-47/E, hereafter referred to as the trailer, for use in transportation, storage, and loading crew training for the BDU-15/E and BDU-16/E Loading Practice Bombs.

2. APPLICABLE DOCUMENTS. The following documents of the issue in effect on the date of invitation for bids, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Federal

TT-T-291	Thinner; Paint, Volatile Mineral Spirits (Petroleum-Spirits)
TT-E-485	Enamel, Semi-Gloss, Rust Inhibiting

Military

JAN-P-100	Packaging and Packing for Overseas Shipment, General Specification
MIL-C-104	Crates, Wood, Lumber and Plywood Sheathed, Nailed and Bolted
MIL-M-8090	Mobility Requirements, Ground Support Equipment, General Specification For
MIL-A-8421	Air Transportability Requirements, General Specification For
MIL-T-9107	Test Reports, Preparation Of
MIL-P-26915	Primer Coating, Zinc Dust Pigmented, For Steel Surfaces
MIL-D-70327	Drawings, Engineering and Associated Lists

STANDARDS

Federal

595	Colors

FSC 1190

AF Hooven-Dayton Co., 18 May 1962 1400

Source: https://assist.dla.mil -- Downloaded: 20260-20T12:23Z
Check the source to verify that this is the current version before use.

Military

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-130	Identification Marking of U. S. Military Property

DRAWINGS

Air Force

61J15345	Trailer, Dummy Bomb MHU-47/E

(Copies of documents required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 PREPRODUCTION. This specification makes provisions for preproduction testing.

3.2 DESIGN AND CONSTRUCTION. The trailer shall be designed and constructed in conformance to drawing 61J15345 and subsidiary drawings.

3.2.1 INTERCHANGEABILITY. Parts functionally and dimensionally interchangeable shall be identified by the same part number. When parts are not interchangeable, the criteria listed in MIL-D-70327 shall apply and new drawings shall be prepared as required.

3.2.2 FINISH. The trailer shall be finished in the following manner:

a. After cleaning and pretreating, two spray coats of primer conforming to Type I, MIL-P-26915 shall be applied to all surfaces not machined or plated.

b. FINAL FINISH COAT. After second coat of primer has dried for a minimum of one hour, two spray coats of enamel conforming to Type II, TT-E-485, color 24087 Federal Standard 595, shall be applied. Enamel shall be thinned by adding one volume of thinner conforming to TT-T-291. Drying time shall be in accordance with TT-E-485.

3.3 PERFORMANCE. Performance of the trailer shall consist of supporting the BDU-15/E or BDU-16/E Bomb, Loading Practice during storage, transportation and loading operations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:23Z
Check the source to verify that this is the current version before use.

3.4 MOBILITY. The trailer, supporting the applicable practice weapon shall be capable of Type I, Group C, Class 2 mobility as specified in MIL-M-8090.

3.5 AIR TRANSPORTABILITY. The trailer, with design load, shall be air transportable as specified in MIL-A-8421.

3.6 COMPATIBILITY. The trailer shall provide proper fit, and tie down facilities for the BDU-15/E or BDU-16/E Bomb, Loading Practice, provide for attachment of the ADU-2/E Adapter and mate properly to the Type MF-1 Bomb Trailer.

3.7 IDENTIFICATION OF PRODUCT. The trailer, parts and assemblies shall be marked for identification in accordance with MIL-STD-130.

3.8 WORKMANSHIP. The trailer shall be fabricated and finished in a manner that will insure that the criteria of appearance, fit and adherence to specified tolerances are observed. These criteria shall apply to all accessories and to all non-functional parts. Particular attention shall be given to neatness and thoroughness of marking of parts and assemblies, plating, painting, machine screw assemblage, welding, and freedom of parts from burrs and sharp edges which might mar associated equipment or cause injury to operating personnel.

4. QUALITY ASSURANCE PROVISIONS

4.1 CLASSIFICATION OF TESTS. Inspection and testing of the trailer shall be classified as follows:

a. Preproduction tests

b. Acceptance tests

4.2 PREPRODUCTION TESTING

4.2.1 PREPRODUCTION TEST SAMPLES. The preproduction test samples shall consist of models representative of the production trailers. They shall be tested at a laboratory designated by the procuring activity, or, when so stated in the contract, at the contractor's plant under the supervision of the procuring activity, except that the fit test shall be conducted at a military establishment.

4.2.2 PREPRODUCTION TEST REPORTS. In the event that preproduction testing is performed at the contractor's plant, the contractor shall, after completion of the preproduction tests, prepare a preproduction test report conforming to MIL-T-9107 and furnish three complete copies of the report to the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:23Z
Check the source to verify that this is the current version before use.

4.2.3 PREPRODUCTION TESTS. Preproduction tests shall consist of all tests described in "4.5 TEST METHODS."

4.3 ACCEPTANCE TESTS. Acceptance tests shall consist of the following individual tests:

a. Examination of Product

b. Conformance to Drawings

4.4 TEST CONDITIONS. Test conditions shall be as required for each specific test.

4.5 TEST METHODS

4.5.1 EXAMINATION OF PRODUCT. Each trailer shall be visually examined to determine compliance with the requirements of this specification for which tests are not specified, including materials and workmanship. Failure to satisfy this examination shall be cause for rejection.

4.5.2 CONFORMANCE TO DRAWINGS. Each trailer shall be inspected to determine strict compliance with engineering and subsidiary drawings and specifications and standards specified therein. Non-compliance to this criteria shall be cause for rejection.

4.5.3 MOBILITY. The trailer, with full service load, shall be tested for Type I, Group C, Class 2 Mobility in accordance with MIL-M-8090. The rejection criteria of MIL-M-8090 shall apply.

4.5.4 AIR TRANSPORTABILITY

4.5.4.1 RAMP TEST. With a test load simulating the weight and exterior shape of the applicable practice bomb installed, the trailer shall be subjected to the ramp test described in MIL-M-8090. Failure to satisfy the requirements of this test shall be cause for rejection.

4.5.4.2 FLIGHT AND TAXIING LOAD TEST. With a test load simulating the applicable practice bomb installed, the trailer shall be subjected to the flight and taxiing load test specified in MIL-A-8421.

4.5.4.3 EMERGENCY LANDING LOAD TEST. With a test load simulating the applicable practice bomb installed, the trailer shall be subjected to the emergency landing loads test specified in MIL-A-8421.

Source: https://assist.dla.mil -- Downloaded: 202640-20T12:23Z
Check the source to verify that this is the currentversion before use.

4.5.5 FIT TEST. The trailer shall be subjected to a fit test which shall be performed at a military installation. The test shall be performed in the following steps:

a. Install and secure a BDU-15/E or BDU-16/E or suitable substitute Loading Practice Bomb in service configuration.

b. While in the configuration described in step a., install the trailer on a Type MF-1 trailer in transport configuration.

Interference in making the above installations, clearances in excess of drawing requirements or binding or failure to mate properly with any piece of associated equipment shall be cause for rejection.

5. PREPARATION FOR DELIVERY

5.1 PRESERVATION. Preservation for all levels of shipment and storage shall consist of normal lubrication of all moving parts.

5.2 PACKAGING AND PACKING, ALL LEVELS

5.2.1 When the trailer is shipped or stored with a practice bomb installed, the trailer/bomb combination shall constitute unit package and exterior packing.

5.2.2 When the trailer is shipped or stored separately, it shall be packed in an exterior container conforming to MIL-C-104. Physical protection shall be in accordance with JAN-P-100.

5.3 MARKING. Shipment and storage marking shall be in accordance with MIL-STD-129. The nomenclature shall be:

TRAILER, DUMMY BOMB MHU-47/E

6. NOTES

6.1 INTENDED USE. The Trailer, Dummy Bomb MHU-47/E is intended for use in transportation and storage of the BDU-15/E and BDU-16/E Bombs, Loading Practice and loading and handling training of loading crews.

6.2 ORDERING DATA. Procurement documents should specify the following:

a. Title, number and date of this specification.

b. Whether preproduction tests will be conducted by the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 202610-20T12:23Z
Check the source to verify that this is the currentversion before use.

6.2.1 PREPRODUCTION TEST SAMPLES. It is expected that the contract or purchase order will specify that two units representative of the production trailer will be submitted to the procuring activity for test and evaluation. The invitation for bids and the contract or purchase order, should specify the point of inspection for these tests.

6.3 PRODUCTION DELIVERY. No production items should be delivered prior to approval of the preproduction samples.

6.4 DEFINITIONS

a. PREPRODUCTION TESTING. Preproduction tests are those tests made on samples which have been submitted by a contractor on a production contract or purchase order, to prove, prior to his starting production, that the equipment meets the requirements of this specification.

b. ACCEPTANCE TESTS. Acceptance tests are those tests accomplished on equipment submitted under a contract to determine that the units are equivalent in performance and construction to the approved preproduction samples.

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

SWVSC
MHJ/pfg

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:23Z
Check the source to verify that this is the current version before use.