INCH-POUND

MIL-B-49430C(ER)
AMENDMENT 1
21 January 1992

MILITARY SPECIFICATION

BATTERIES, NON-RECHARGEABLE, LITHIUM SULFUR DIOXIDE

This amendment forms a part of MIL-B-49430C(ER), dated 1 August 1991, and is approved for use by the Laboratory Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

Paragraph 3.5.1, first line - Delete the first sentence and replace with:

"Intercell connections shall be spot welded in accordance with the contractor's established procedures. These procedures shall be developed by the contractor as part of the quality program requirements of the contract and shall use MIL-W-8939 as guidance."

PAGE 19

Table VII - Delete in its entirety and substitute:

Table VII - Group C Inspection.

Inspection Lot Size	Sample Size	Acceptance No. 4.7.1.3.2 a,b,c	Acceptance No. 4.7.1.3.2 d
500 or less	13	1	0
501-1,200	20	2	0
1,201-10,000	32	3	0
10,001-35,000	50	5	0
35,001 or more	80	7	0

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:05Z
Check the source to verify that this is the current version before use.

Table VIII, delete in its entirety and substitute:

TABLE VIII - Group D inspection.

Storage and Capacity Test	Requirement Paragraph	Method of Test Paragraph
Subgroup I (see 4.7.1.4.3.1) Capacity T & TP (where applicable)	3.7	4.8.9.1.7
Subgroup II (see 4.7.1.4.3.2) Capacity D	3.7	4.8.9.1.8

Paragraph 4.7.1.4.1, delete in its entirety and substitute:

"4.7.1.4.1 Sampling Plan. A sample of n_s batteries shall be selected at random from production for each shipment lot in amounts determined from the following formula, and rounded off in the case of fractions to an adjacent integer (up or down for each shipment lot), so that exactly n batteries have been assigned to both T combined with TP (where applicable) capacity test when the sample for the final shipment of the contract lot has been drawn.

$$n_s = a + N_s \frac{n}{N}$$

where:
a = five batteries for D capacity test
n_s = total number of sample batteries to be taken from each shipment lot
N_s = number of batteries in the shipment lot
N = number of batteries in the contract lot (see Table IX)
n = number of batteries to be taken from the contract lot for each of the two capacity tests, T combined with TP (where applicable) in accordance with Table IX (total number of T selected is n)."

Paragraph 4.7.1.4.1.1, delete in its entirety and substitute:

"4.7.1.4.1.1 Allocation of sample batteries for Group D inspection. The number of batteries n_s selected from a shipment lot shall be assigned at random at the Government test facility so that five batteries shall be scheduled for the D capacity test and the remainder for the T and TP (where applicable) test. Such assignment shall result in the allocation of exactly n batteries to both T combined with TP (where applicable) capacity tests after the final shipment on the contract lot is made. If necessary, the sample size n_s taken from the last shipment lot of a contract lot shall be adjusted so that this result is achieved."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:05Z
Check the source to verify that this is the current version before use.

PAGE 21

Table IX, delete in its entirety and substitute:

TABLE IX - Sample size and allowable failures for T capacity test. 1/

Contract lot Size "N"	Sample size "n" for T tests 1/ from contract lot	Acceptance No. for T tests 2/
0 to 110	5 3/	-- 3/
111 to 500	15	3
501 to 800	25	5
801 to 1,300	35	7
1,301 to 3,200	50	9
3,201 to 8,000	75	13
8,001 to 22,000	110	18
22,001 to 110,000	150	24
over 110,000	225	34

1/ Test is combined with TP (where applicable).

2/ When the number of capacity values falling below the minimum requirements specified (see 3.1) for a given test is equal to or less than the associated acceptance number, the contract lot from which the sample was drawn has met the requirements of that test.

3/ Determination of compliance specified in 4.7.1.4.2 shall not apply to contract lot sizes of less than 111."

PAGE 29

Paragraph 4.8.16.1 - Delete in its entirety and substitute:

"4.8.16.1 Sample Size. Sample size shall be twenty each for each shipment lot. No failures allowed."

Paragraph 4.8.16.2 - Delete in its entirety.

Paragraph 4.8.18.1 - Delete in its entirety and substitute:

"4.8.18.1 Sample Size. Sample size shall be twenty each for each shipment lot. No failures allowed."

Custodian:
Army-ER

Preparing Activity:
Army-ER

(Project 6135-A245)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:05Z
Check the source to verify that this is the current version before use.