MIL-C-48087A (AR)
AMENDMENT 4
12 March 1987
SUPERSEDING
AMENDMENT 3
30 October 1985

MILITARY SPECIFICATION

CARTRIDGE, 4.2 INCH, HE, M329A2
W/SUPPLEMENTARY CHARGE
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-C-48087A (AR), dated 17 June 1982, and is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.2, Add the following: "12624505 - Packing and marking for box, fiberboard for obturator assembly"

PAGE 7

* Table II, Delete in its entirety and substitute the new paragraph, Page 7 included.

PAGE 12

* 4.4.2.4, Delete in its entirety and substitute the new paragraph, Page 12 included.

PAGE 16

* 4.4.2.8, Under Critical defect 3, delete in its entirety and add the following:

"Special a, Metal parts separation (proving ground) ... 80/50 ... 3.5.6 ... 4.4.3.1.2/4.5.2"



AMSC N/A FSC 1315

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

PAGE 22

* 4.4.2.14, Delete in its entirety and substitute the new paragraph, Page 22A included.

* 4.4.2.15, Delete in its entirety and substitute the new paragraph, Page 22B included.

4.4.2.16, Add new paragraph, Page 22C included.

* 4.4.2.17, Add new paragraph, Page 22D included.

PAGE 23

* 4.4.3.1.2.2, Change "Critical, Metal parts seperation 0 1 0 1" to "Special, Metal parts separation 0 1 0 1"

PAGE 26

5.1 Delete in its entirety and substitute the following:

"5.1 Packaging requirements.

a. Packaging for 4.2 Inch Mortar Ammunition shall be as specified on drawing 9272389.

b. Packaging for obturator assembly shall be as specified on drawing 12624505."

5.2 Delete in its entirety and substitute the following:

"5.2 Packing and marking.

a. Packing and marking for 4.2 Inch Mortar Ammunition shall be as specified in drawing 9243973.

b. Packing and marking for obturator assembly shall be as specified in drawing 12624505."



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

TABLE II First article inspection

## CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48087A (AR)
AMENDMENT 4

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER / NEXT HIGHER ASSEMBLY |
|---|---|---|---|---|---|
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| | Cartridge Assembly | | | | |
| | Examination for Defects | 80 | 100% | 3.2 | 4.4.2.8 |
| | Proving Ground | 80 | 100% | 3.5 | 4.4.3.1/4.5.2 |
| | Obturator | | | | |
| | Examination for Defects | 25 | 100% | 3.2 | 4.4.2.4 |
| | Obturator Assembly | | | | |
| | Examination for Defects | 50 | 100% | 3.2 | 4.4.2.14 |
| | Bristle, Strip | | | | |
| | Examination for Defects | 25 | 100% | 3.2 | 4.4.2.15 |

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48087A (AR)
AMENDMENT 4

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.4.2.4 | Obturator | | | | 9391032 |
| | | | | | NEXT HIGHER ASSEMBLY 9391030 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major | | | | | |
| 101 | Diameter of strip bristle well | | 0.40% | 3.2 | Gage |
| 102 | Width of strip bristle well | | 0.40% | 3.2 | Gage/Caliber |
| 103 | Thickness at front face (Large) (Four measurements, 90° apart) | | 0.40% | 3.2 | Gage/Caliber |
| 104 | Thickness at rear face (Small) (Four measurements, 90° apart) | | 0.40% | 3.2 | Gage |
| 105 | Distance from front face to strip bristle well | | 0.40% | 3.2 | Gage/Caliber |
| 106 | Separator cut(s) missing | | 0.40% | 3.2 | Visual |
| 107 | Forward inside diameter | | 0.40% | 3.2 | Gage |
| 108 | Overall width of obturator | | 0.40% | 3.2 | Gage |
| 109 | Depth of separator cut | | 0.40% | 3.2 | Gage |
| 110 | Concentricity of strip bristle well | | 0.40% | 3.2 | Gage |
| 111 | Evidence of contaminants (foreign materials) in bristle strip well considered capable of interfacing with adhesion | | 0.40% | 3.2 | Visual |
| Minor | | | | | |
| 201 | Angle at rear obturator | | 0.65% | 3.2 | Visual |
| 202 | Radii missing | | 0.65% | 3.2 | Visual |
| 203 | Evidence of poor workmanship | | 0.65% | 3.7 | Visual |

NOTES:



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS



| PARAGRAPH | TITLE | | SHEET 1 OF 2 | | DRAWING NUMBER 9391030 |
|---|---|---|---|---|---|
| 4.4.2.14 | Obturator Assembly | | | | NEXT HIGHER ASSEMBLY 9235654 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Special | | | | | |
| A | Improper orientation of bristle strips | | 100% | 3.2 | Visual/manual Note A |
| B | Evidence of no adhesive across full width of bristle strip ends | | 100% | 3.2 | Visual/ Note B |
| C | Evidence of separation between bristle strip ends and the base obturator | | 100% | 3.2 | Visual/ Note C |
| D | Bristle assembly outside diameter | | 100% | 3.2 | Gage |

(A) When the obturator assembly is positined with thick side of obturator facing to the inspector, the bristle strip shall be lightly rubbed in the counter clockwise direction. Resistance to manual touch indicates improper assembly.

(B) The inspector shall not bend or distort the obturator assembly out of its normal circular form during the inspection.

(C) The obturator assembly shall be positioned on a cylindrical plug with outside diameter of 3.77 inches. The obturator assembly shall be slipped on the plug from the forward edge. The obturator assembly shall be inspected visually for any separation between the ends of bristle strips and the base obturator. Any failures shall be classed defective and removed from the lot.

NOTES:



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS



| PARAGRAPH | TITLE | SHEET | DRAWING NUMBER |
|---|---|---|---|
| 4.4.2.14 | Obturator Assembly (continued) | 2 OF 2 | 9391030 |
| | | | NEXT HIGHER ASSEMBLY: 9235654 |

| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
|---|---|---|---|---|---|
| Major | | | | | |
| 101 | Separator cuts to be between ends of bristle strips | | 0.40% | 3.2 | Visual |
| 102 | Backing material of bristle strip exceeded 0.01 inches above flush of obturator (2 places, 108° apart) | | 0.40% | 3.2 | Gage |
| 103 | Evidence of excessive adhesive around the bristle strip | | 0.40% | 3.2 | Visual |
| Minor | | | | | |
| 201 | Evidence of poor workmanship | | 0.65% | 3.7 | Visual |

NOTES:



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

# CLASSIFICATION OF DEFECTS & TESTS



| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER 9391031 |
|---|---|---|---|---|---|
| 4.4.2.15 | Bristle, Strip | | | | NEXT HIGHER ASSEMBLY 9391030 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major | | | | | |
| 101 | Width of strip | | 0.40% | 3.2 | Gage |
| 102 | Length of strip | | 0.40% | 3.2 | Gage |
| 103 | Overall height of strip | | 0.40% | 3.2 | Gage |
| 104 | Height from the bottom of bristle to the top of backing | | 0.40% | 3.2 | Gage |
| 105 | Evidence of contaminants (foreign materials) on rear of bristle strips considered capable of interfering with adhesion | | 0.40% | 3.2 | Visual |
| 106 | Angle of wire bristles | | 0.40 | 3.2 | Gage/Visual Note A |
| Minor | | | | | |
| 201 | Evidence of poor workmanship | | 0.65% | 3.7 | Visual |

NOTES: A. Each bristle strip shall have minimum 75% of the wires meeting the angle requirement.



Source: https://assist.dla.mil - Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48087A (AR)
AMENDMENT 4

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.4.2.16 | Packing and Marking for Box, Fiberboard for Obturator Assembly | | | | 12624505 |
| | | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major | None defined | | | | |
| Minor | | | | | |
| 201 | Lot number missing | | 0.65% | 5.1/5.2 | Visual |
| 202 | National stock number missing | | 0.65% | 5.1/5.2 | Visual |
| 203 | Item nomenclature/part number missing or incorrect | | 0.65% | 5.1/5.2 | Visual |

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS



| PARAGRAPH | TITLE | | SHEET | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.4.2.17 | Obturator During Assembly | | 1 OF 1 | | 9391030 |
| | | | | | NEXT HIGHER ASSEMBLY 9235654 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major 101 | Adhesive missing, or not fully applied (360°) around the strip bristle well | | Note A | 3.2 | Visual |
| Minor | None defined | | | | |

NOTES: A Ten samples shall be inspected at beginning of 8 hour shift, ten samples shall be inspected at midway of 8 hour shift and ten samples shall be inspected at end of 8 hour shift.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army-AR

Preparing activity:
Army-AR

(Project 1315-A886)



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.