MILITARY SPECIFICATION

ROCKET, HE, 66MM, ANTITANK, M72A2, W/COUPLER OR M72A3, LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-R-50431A(MI), dated 14 November 1974, and is approved for use within the U.S. Army Missile Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

* The attached insertable pages listed below are replacements for stipulated pages. When the new pages have been entered in the document, insert the amendment as the cover sheet to the specification.

Replacement page	Page replaced
1, 1A	1
2, 2A	2
3, 3A	3
4	4
5	Reprinted without change

PAGE 5

* 3.12, following "9271631", add "(M72A2) or 13012530 (M72A3)".

* 3.13, following "9210200", add "(M72A2) or 13012560 (M72A3)".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:24Z
Check the source to verify that this is the current version before use.

PAGE 6

* Add:

"3.18 Serial numbers. Blocks of serial numbers applicable to weapons being procured will be assigned to the contractor for each contract (see 6.1). When a serial number is not assigned by the procuring agency, the manufacturers serial number shall be entered, if the manufacturer employs a serial number system. Application of serial numbers to the M72 Launchers will be in accordance with MIL-STD-130."

PAGE 7

* 4.3.1, line 7, following "M72A2" add "or M72A3".

PAGE 12

* 4.4.2.1, following "9220248" add "(M72A2), or dwg 13012546 covering a detail of dwg 13012547 (M72A3))".

* 4.4.2.2, following "9220248" add "(M72A2) or dwg 13012549 covering a detail of dwg 13012547 (M72A3))".

PAGE 13

* 4.4.2.3, following "9235663" add "(M72A2) or 13012547 covering a detail of 13012550 (M72A3))".

* 4.4.2.4, following "9235663" add "(M72A2) or dwg 13012547 covering a detail of dwg 13012550 (M72A3))".

* 4.4.2.5, following, "9235663" add "(M72A2) of dwg 13012553 covering a detail of dwg 13012550 (M72A3))".

PAGE 14

4.4.2.6, following, "9235663" add "(M72A2) or dwg 13012558 covering a detail of dwg 13012550 (M72A3))".

Under "categories, critical," delete and substitute:

"Critical 100% Inspection

1. Holes in lid or parts loose to the extent that the explosive charge may leak out or draw moisture ---------- Visual 06001"

* 4.4.2.7, following "9235663" add "(M72A2) or dwg 13012551 covering a detail of dwg 13012550 (M72A3))".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:24Z
Check the source to verify that this is the current version before use.

PAGE 15

* 4.4.2.10, following "9244054" add "(M72A2) or dwg 13012550 covering a detail of dwg 13012530 (M72A3))".

PAGE 16

* 4.4.2.11, following "9244054" add "or Rocket HE, 66mm, Anti-tank: M72A3 (see dwg 13012530)".

Under "Categories, Major" add:
"106. Serial number missing ---------- Visual"

PAGE 19

* 4.4.3.6, following "9220248" add "(M72A2) or dwg 13012547 (M72A3))".

* 4.4.3.10, following "9235663" add "(M72A2) or dwg 13012550 (M72A3))".

* 4.4.4.1, delete entire paragraph and substitute:

PAGE 20

4.4.4.1 Test to be performed. For all lots, a sample of fifty weapons shall be randomly selected and tested for compliance with the requirements of section 3. A listing of tests to be performed, the quantities allotted to each type of test and defects considered with each type of test are indicated in Table II. It is required that the 70°F flight test and waterproof/penetration test be performed prior to the 140°F flight test. When the plus 70°F conditioned light test is conducted using a thirty (30) round sample size, replacements shall be selected from the plus 140°F test sample only if less that 27 sample accuracy results are obtained. Every fifth (5th) lot, the 70°F conditioned flight test shall be conducted using a twenty (20) round sample size and ten (10) rounds used for the waterproof/penetration test. Replacement rounds taken from the 140°F flight test shall assume twenty (20) 70°F sample accuracy results and ten (10) penetration sample results. High temperature (140°F) tests shall be conducted using the balance of the samples available for that test. If a penetration test fails, continue penetration test sampling until two (2) consecutive lots satisfy the penetration requirements.

PAGE 21

4.4.4.3, delete last sentence of paragraph.

PAGE 22

Table II, in "Quantity in Test", above "Waterproof Penetration" column; delete "10" and substitute "**".

In "Quality in Test", above "+70°F accuracy" column; delete "20" and substitute "30".

For "Defect code 17007", in "Waterproof Penetration" column, delete "***" and substitute "X".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:24Z
Check the source to verify that this is the current version before use.

PAGE 24

4.5.1.4, delete the "WARNING" note in its entirety.

PAGE 26

4.5.2, following "64.6 miles for the -40°F" add: "(nonvented propellant)".

Add to "Temperature" column:
"62.0 mils for the -40°F (vented propellant)".

PAGE 28

* 6.1, add:

"c. Block of serial numbers when required (see 3.18)".

PAGE 29

* 6.3.1, in "b", following "as defined in "delete "MIL-STD-100" and substitute "DOD-STD-100".

in "c", following "as defined in "delete "MIL-STD-100" and substitute "DOD-STD-100".

PAGE 30

* 6.3.3, line 3, following "for approval to" delete Picatinny Arsenal, ATTN: SARPA-QA-A-R-, Dover, New Jersey 07801" and substitute: "Commander, U.S. Army Armament Research and Development Center, ATTN: AMSMC-QAT-B, Dover, NJ 07801-5001".

* 6.6, line 4, delete "Picatinny Arsenal" and substitute "U.S. Army Armament Research and Development Center".

Following "inquiries should be forwarded to" delete address and substitute:
"Commander
U.S. Army Armament Research and Development Center
ATTN: AMSMC-QAT-B
Dover, NJ 07801-5001"

PAGE 31

* Delete: "Custodian: Army-MI".

* Under "Review Activity: Army", delete "PA" and substitute "AR."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:24Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-MI

Review Activity:
Army-AR

Preparing Activity:
Army-MI

Project No. 1340-A702

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:24Z
Check the source to verify that this is the current version before use.