MILITARY SPECIFICATION

WRENCH, FUZING, ANTI-PERSONNEL MINE, M25

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the M25 Wrench for Fuzing the M16A1, and M16A2 Anti-Personnel Mines.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests for
MIL-STD-1169 - Packaging, Packing, and Marking for Shipment of Inert Ammunition Components

FSC: 1345

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:39Z
Check the source to verify that this is the current version before use.

DRAWINGS

U.S. ARMY PICATINNY ARSENAL

9214053 - Wrench, Fuzing, Anti-Personnel Mine, M25

(Copies of specifications, standards, and drawings required by contractors In connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

3. REQUIREMENTS

3.1 Material. - Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Wrench. - The wrench shall comply with all requirements specified on drawing (Dwg.) 9214053 and with all requirements specified on applicable specifications.

3.3 Protective finish. - There shall be no evidence of rust or corrosion of metals due to salt deposits when the wrenches are subjected to salt fog per MIL-STD-331, Test 107.1.

3.4; Workmanship. - All parts shall be fabricated and finished In a thorough workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. They shall be clean and free of burrs, sharp edges, unblended radii , surface defects, chips, dirt, grease and oil (except where specifically required). The cleaning method used shall not be Injurious to any part or assembly nor shall they be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined. Required packing shall be dry.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection and Standard Quality Assurance Provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspection. - The following type of inspection shall be conducted on this item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:39Z
Check the source to verify that this is the current version before use.

a. Quality Conformance Inspection

4.3 First Article Inspection. - There are no first article provisions for this item.

4.4 Quality Conformance Inspection

4.4.1 Inspection lot formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078. Each inspection lot of wrenches shall contain parts from one manufacturer.

4.4.2 Examination. - (See MIL-A-48078). Unless otherwise specified in the classification of defects and test tables, sampling plans for major and minor defects shall be In accordance with MIL-STD-105, Inspection Level II. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:39Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-48763 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9214053
4.4.2.1	Wrench, Fuzing, Anti-Personnel Mine, M25				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major B					
131	Inside width of hex (three places)		0.40%	3.2	Gage
132	Outside radius of hex end		0.40%	3.2	Gage
133	Distance between inside parallel surfaces at open end		0.40%	3.2	Gage
134	Length of inside parallel surfaces at open end		0.40%	3.2	Gage
135	Width at midsection		0.40%	3.2	Gage
136	Total length, max.		0.40%	3.2	Gage
Minor					
201	Wrench thickness		0.65%	3.2	Gage
202	Marking missing, misleading or unidentifiable		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:39Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Protective finish (see 3.3) - Major A defect - A sample of ten (10) wrenches shall be selected from each lot for this test. If any wrench fails to comply with the requirements specified the lot shall be rejected. The test shall be as specified in 4.5.1.

4.4.4 Inspection Equipment. - The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/ Inspection Method' column in the table of paragraph 4.4.2.1 and the test method paragraph (see 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and Section 6.2 herein.

4.5 Test Methods and Procedure

4.5.1 Protective finish. - The wrenches shall be subjected to the salt fog specified in MIL-STD-331, Method 107.1 except that exposure test time shall be 24 hours minimum (min.).

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging

5.1.1 Level C. - The wrenches shall be packaged in accordance with MI-STD-1169 in such a manner that no damage will occur during shipment.

5.2 Packing

5.2.1 Level C. - The wrenches shall be packed in accordance with MIL-STD-1169.

5.3 Marking. - Unit, intermediate and exterior containers shall be marked in accordance with MIL-STD-1169 requirements.

6. NOTES

6.1 Intended Use. - The wrench covered by this specification is intended for use with the M605 fuze and the M16A1 or A2 antipersonnel mine.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:39Z
Check the source to verify that this is the current version before use.

6.2 Ordering Data. - Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. provisions of MIL-A-48078.

6.3 Submission of Inspection Equipment Designs for Approval (See MIL-A-46078). Submit equipment designs as required, to Commander, Picatinny Arsenal, ATTN: SARPA-QA-T-T, Dover; New Jersey 07801.

6.4 Distribution of' ammunition data cards. - Distribution of' data cards shall include the following: Commander, Picatinny Arsenal, ATTN: SARPA-QA-A-M, Dover, New Jersey 07801.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1345-A-123

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:39Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-A
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:39Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3 IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4 REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:39Z
Check the source to verify that this is the current version before use.