ADOPTION NOTICE

SAE- AS1035, “Fitting, Tee, Standard and Reducer, Flared", was adopted on 20 July 1984 for use by the Department of Defense (DoD). Proposed changes by DoD activities must be submitted to the DoD Adopting Activity: DLA Land and Maritime, ATTN: VAI, 3990 East Broad Street, Columbus, OH 43218-3990 or fluidflow@.dla.mil. Copies of these documents are available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or 724-776-4970 (outside USA), www.sae.org.
.

SAE-AS1035 should be used instead of the following cancelled flared fitting standards listed with their cross reference Part or Identifying Number (PIN) tables below:

Cancelled	Document Name	Table
AN824 Rev 7	Tee - Flared Tube	See table I
MS24402D	Tee, Tube, Precision Type	See table II

CAUTION: The supersession information is valid as of the date of this notice and may be superseded by subsequent revisions of the superseding document.

CONCLUDING MATERIAL

Custodians:
Army - AV
Navy - AS
Air Force - 99
DLA - CC

Preparing activity:
DLA - CC

(Project 4730-2010-151)

Review activities:
Army – CR4
Navy - MC, SA
Air Force – 11, 71

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T16:27Z
Check the source to verify that this is the current version before use.

TABLE I. AN824 Rev 7 to SAE-AS1035, cross-reference data.

Cancelled AN PIN	Tube Size	Replacement AS PIN	New Design	Cancelled AN PIN	Tube Size	Replacement AS PIN	New Design
AN824-2	.125	AS1035-020202		AN824-10	.625	AS1035-101010	
AN824-2D	.125	AS1035 D020202	AS1035 W020202	AN824-10D	.625	AS1035 D101010	AS1035 W101010
AN824-2J	.125	AS1035 J020202		AN824-10J	.625	AS1035 J101010	
AN824-2K	.125	AS1035 K020202		AN824-10K	.625	AS1035 K101010	
AN824-2S	.125	AS1035 S020202	AS1035 R020202	AN824-10S	.625	AS1035 S101010	AS1035 R101010
AN824-2T	.125	AS1035 T020202		AN824-10T	.625	AS1035 T101010	
AN824-2W	.125	AS1035 W020202		AN824-10W	.625	AS1035 W101010	
AN824-3	.188	AS1035-030303		AN824-12	.750	AS1035-121212	
AN824-3D	.188	AS1035 D030303	AS1035 W030303	AN824-12D	.750	AS1035 D121212	AS1035 W121212
AN824-3J	.188	AS1035 J030303		AN824-12J	.750	AS1035 J121212	
AN824-3K	.188	AS1035 K030303		AN824-12K	.750	AS1035 K121212	
AN824-3S	.188	AS1035 S030303	AS1035 R030303	AN824-12S	.750	AS1035 S121212	AS1035 R121212
AN824-3T	.188	AS1035 T030303		AN824-12T	.750	AS1035 T121212	
AN824-3W	.188	AS1035 W030303		AN824-12W	.750	AS1035 W121212	
AN824-4	.250	AS1035-040404		AN824-16	1.000	AS1035-161616	
AN824-4D	.250	AS1035 D040404	AS1035 W040404	AN824-16D	1.000	AS1035 D161616	AS1035 W161616
AN824-4J	.250	AS1035 J040404		AN824-16J	1.000	AS1035 J161616	
AN824-4K	.250	AS1035 K040404		AN824-16K	1.000	AS1035 K161616	
AN824-4S	.250	AS1035 S040404	AS1035 R040404	AN824-16S	1.000	AS1035 S161616	AS1035 R161616
AN824-4T	.250	AS1035 T040404		AN824-16T	1.000	AS1035 T161616	
AN824-4W	.250	AS1035 W040404		AN824-16W	1.000	AS1035 W161616	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T16:27Z
Check the source to verify that this is the current version before use.

TABLE I. AN824 Rev 7 to SAE-AS1035, cross-reference data – Continued.

Cancelled AN PIN	Tube Size	Replacement AS PIN	New Design	Cancelled AN PIN	Tube Size	Replacement AS PIN	New Design
AN824-5	.312	AS1035-050505		AN824-20	1.250	AS1035-202020	
AN824-5D	.312	AS1035 D050505	AS1035 W050505	AN824-20D	1.250	AS1035 D202020	AS1035 W202020
AN824-5J	.312	AS1035 J050505		AN824-20J	1.250	AS1035 J202020	
AN824-5K	.312	AS1035 K050505		AN824-20K	1.250	AS1035 K202020	
AN824-5S	.312	AS1035 S050505	AS1035 R050505	AN824-20S	1.250	AS1035 S202020	AS1035 R202020
AN824-5T	.312	AS1035 T050505		AN824-20T	1.250	AS1035 T202020	
AN824-5W	.312	AS1035 W050505		AN824-20W	1.250	AS1035 W202020	
AN824-6	.375	AS1035-060606		AN824-24	1.500	AS1035-242424	
AN824-6D	.375	AS1035 D060606	AS1035 W060606	AN824-24D	1.500	AS1035 D242424	AS1035 W242424
AN824-6J	.375	AS1035 J060606		AN824-24J	1.500	AS1035 J242424	
AN824-6K	.375	AS1035 K060606		AN824-24K	1.500	AS1035 K242424	
AN824-6S	.375	AS1035 S060606	AS1035 R060606	AN824-24S	1.500	AS1035 S242424	AS1035 R242424
AN824-6T	.375	AS1035 T060606		AN824-24T	1.500	AS1035 T242424	
AN824-6W	.375	AS1035 W060606		AN824-24W	1.500	AS1035 W242424	
AN824-8	.500	AS1035-080808		AN824-28	1.750	AS1035-282828	
AN824-8D	.500	AS1035 D080808	AS1035 W080808	AN824-28D	1.750	AS1035 D282828	AS1035 W282828
AN824-8J	.500	AS1035 J080808		AN824-28J	1.750	AS1035 J282828	
AN824-8K	.500	AS1035 K080808		AN824-28K	1.750	AS1035 K282828	
AN824-8S	.500	AS1035 S080808	AS1035 R080808	AN824-28S	1.750	AS1035 S282828	AS1035 R282828
AN824-8T	.500	AS1035 T080808		AN824-28T	1.750	AS1035 T282828	
AN824-8W	.500	AS1035 W080808		AN824-28W	1.750	AS1035 W282828	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T16:27Z
Check the source to verify that this is the current version before use.

TABLE I. AN824 Rev 7 to SAE-AS1035, cross-reference data – Continued.

Cancelled AN PIN	Tube Size	Replacement AS PIN	New Design
AN824-32	2.000	AS1035-323232	
AN824-32D	2.000	AS1035 D323232	AS1035 W323232
AN824-32J	2.000	AS1035 J323232	
AN824-32K	2.000	AS1035 K323232	
AN824-32S	2.000	AS1035 S323232	AS1035 R323232
AN824-32T	2.000	AS1035 T323232	
AN824-32W	2.000	AS1035 W323232	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T16:27Z
Check the source to verify that this is the current version before use.

TABLE II. MS24402D to SAE-AS1035, cross-reference data.

Cancelled MS PIN	Tube Size	Replacement AS PIN	New Design	Cancelled MS PIN	Tube Size	Replacement AS PIN	New Design
MS24402-2	.125	AS1035-020202		MS24402-10	.625	AS1035-101010	
MS24402D2	.125	AS1035 D020202	AS1035 W020202	MS24402D10	.625	AS1035 D101010	AS1035 W101010
MS24402J2	.125	AS1035 J020202		MS24402J10	.625	AS1035 J101010	
MS24402K2	.125	AS1035 K020202		MS24402K10	.625	AS1035 K101010	
MS24402S2	.125	AS1035 S020202	AS1035 R020202	MS24402S10	.625	AS1035 S101010	AS1035 R101010
MS24402T2	.125	AS1035 T020202		MS24402T10	.625	AS1035 T101010	
MS24402W2	.125	AS1035 W020202		MS24402W10	.625	AS1035 W101010	
MS24402-3	.188	AS1035-030303		MS24402-12	.750	AS1035-121212	
MS24402D3	.188	AS1035 D030303	AS1035 W030303	MS24402D12	.750	AS1035 D121212	AS1035 W121212
MS24402J3	.188	AS1035 J030303		MS24402J12	.750	AS1035 J121212	
MS24402K3	.188	AS1035 K030303		MS24402K12	.750	AS1035 K121212	
MS24402S3	.188	AS1035 S030303	AS1035 R030303	MS24402S12	.750	AS1035 S121212	AS1035 R121212
MS24402T3	.188	AS1035 T030303		MS24402T12	.750	AS1035 T121212	
MS24402W3	.188	AS1035 W030303		MS24402W12	.750	AS1035 W121212	
MS24402-4	.250	AS1035-040404		MS24402-16	1.000	AS1035-161616	
MS24402D4	.250	AS1035 D040404	AS1035 W040404	MS24402D16	1.000	AS1035 D161616	AS1035 W161616
MS24402J4	.250	AS1035 J040404		MS24402J16	1.000	AS1035 J161616	
MS24402K4	.250	AS1035 K040404		MS24402K16	1.000	AS1035 K161616	
MS24402S4	.250	AS1035 S040404	AS1035 R040404	MS24402S16	1.000	AS1035 S161616	AS1035 R161616
MS24402T4	.250	AS1035 T040404		MS24402T16	1.000	AS1035 T161616	
MS24402W4	.250	AS1035 W040404		MS24402W16	1.000	AS1035 W161616	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T16:27Z
Check the source to verify that this is the current version before use.

TABLE II. MS24402D to SAE-AS1035, cross-reference data – Continued.

Cancelled MS PIN	Tube Size	Replacement AS PIN	New Design	Cancelled MS PIN	Tube Size	Replacement AS PIN	New Design
MS24402-5	.312	AS1035-050505		MS24402-20	1.250	AS1035-202020	
MS24402D5	.312	AS1035 D050505	AS1035 W050505	MS24402D20	1.250	AS1035 D202020	AS1035 W202020
MS24402J5	.312	AS1035 J050505		MS24402J20	1.250	AS1035 J202020	
MS24402K5	.312	AS1035 K050505		MS24402K20	1.250	AS1035 K202020	
MS24402S5	.312	AS1035 S050505	AS1035 R050505	MS24402S20	1.250	AS1035 S202020	AS1035 R202020
MS24402T5	.312	AS1035 T050505		MS24402T20	1.250	AS1035 T202020	
MS24402W5	.312	AS1035 W050505		MS24402W20	1.250	AS1035 W202020	
MS24402-6	.375	AS1035-060606		MS24402-24	1.500	AS1035-242424	
MS24402D6	.375	AS1035 D060606	AS1035 W060606	MS24402D24	1.500	AS1035 D242424	AS1035 W242424
MS24402J6	.375	AS1035 J060606		MS24402J24	1.500	AS1035 J242424	
MS24402K6	.375	AS1035 K060606		MS24402K24	1.500	AS1035 K242424	
MS24402S6	.375	AS1035 S060606	AS1035 R060606	MS24402S24	1.500	AS1035 S242424	AS1035 R242424
MS24402T6	.375	AS1035 T060606		MS24402T24	1.500	AS1035 T242424	
MS24402W6	.375	AS1035 W060606		MS24402W24	1.500	AS1035 W242424	
MS24402-8	.500	AS1035-080808		MS24402-28	1.750	AS1035-282828	
MS24402D8	.500	AS1035 D080808	AS1035 W080808	MS24402D28	1.750	AS1035 D282828	AS1035 W282828
MS24402J8	.500	AS1035 J080808		MS24402J28	1.750	AS1035 J282828	
MS24402K8	.500	AS1035 K080808		MS24402K28	1.750	AS1035 K282828	
MS24402S8	.500	AS1035 S080808	AS1035 R080808	MS24402S28	1.750	AS1035 S282828	AS1035 R282828
MS24402T8	.500	AS1035 T080808		MS24402T28	1.750	AS1035 T282828	
MS24402W8	.500	AS1035 W080808		MS24402W28	1.750	AS1035 W282828	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T16:27Z
Check the source to verify that this is the current version before use.

TABLE II. MS24402D to SAE-AS1035, cross-reference data – Continued.

Cancelled MS PIN	Tube Size	Replacement AS PIN	New Design
MS24402-32	2.000	AS1035-323232	
MS24402D32	2.000	AS1035 D323232	AS1035 W323232
MS24402J32	2.000	AS1035 J323232	
MS24402K32	2.000	AS1035 K323232	
MS24402S32	2.000	AS1035 S323232	AS1035 R323232
MS24402T32	2.000	AS1035 T323232	
MS24402W32	2.000	AS1035 W323232	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T16:27Z
Check the source to verify that this is the current version before use.