INCH-POUND

MIL-PRF-19500/391D
Amendment 2
18 August 1999
SUPERSEDING
Amendment 1
22 July 1999

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, TRANSISTOR, NPN, SILICON, LOW-POWER
TYPES 2N3019, 2N3019S, 2N3057A, 2N3700, AND 2N3700UB
JAN, JANTX, JANTXV, AND JANS

This amendment forms a part of MIL-PRF-19500/391D, dated 9 December 1997 and is approved for use by all Departments and Agencies of the Department of Defense.

Page 1

1.2 Delete and substitute: 'Physical dimensions. 'See figure 1, 2N3019 (TO-5), 2N3019S (similar to TO-39), figure 3 2N3057(TO-46), figure 4 2N3700 (TO-18), and 6 (surface mount).'

Page 2

FIGURE 1. Delete and substitute new title: 'Physical dimensions for device types 2N3019 (TO-5) and 2N3019S (TO-39).'

Page 4

Physical dimensions table, delete in its entirety and substitute:

Symbol	Dimensions				Note
	Inches		Millimeters		
	Min	Max	Min	Max	
CD	.178	.195	4.52	4.95	
CH	.065	.085	1.65	2.16	
HD	.209	.230	5.31	5.84	
LC	.100 TP		2.54 TP		6
LD	.016	.021	0.41	0.53	7
LL	.500	1.750	12.70	44.45	7
LU	.016	.019	0.41	0.48	7
L1	---	.050	---	1.27	7
L2	.250	---	6.35	---	7
Q	---	.040	---	1.02	4
TL	.028	.048	0.71	1.22	4
TW	.036	.046	0.91	1.17	3
r	---	.007	---	0.18	10, 11
α	45° TP		45° TP		6

FIGURE 3. Delete and substitute new title: 'Physical dimensions for 2N3057A (TO-46).'

Page 5

FIGURE 4. Delete and substitute new title: 'Physical dimensions for type 2N3700 (TO-18).'

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:20Z
Check the source to verify that this is the current version before use.

Page 8

3.3 Delete and substitute: ‘Interface requirements and physical dimensions. The Interface requirements and physical dimensions shall be as specified in MIL-PRF-19500, and figure 1 (2N3019, TO-5, 2N3019S, TO-39), figure 3 (2N3700, TO-18), figure 4 (2N3057, TO-46), and figure 6 (2N3700UB, surface mount) herein.’

Page 12

TABLE I. Group A inspection, Subgroup 1, Inspection column, delete ‘Solderability 1/, 2/’ ,and substitute ‘Solderability 1/, 2/, 4/’

Page 18

* Figure 8. Maximium safe operating graph (DC), Y-Axis, I_C COLLECTOR CURRENT legend, delete ‘(MICROAMPERES)’ and substitute ‘(MILLIAMPERES)’.

The margin of this amendment is marked with an asterisk to indicate where a change from the previous amendment was made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous amendment.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Navy - AS, CG, MC
Army - AR, AV, MI, SM
Air Force - 13, 19, 99

Preparing activity:
DLA - CC

(Project 5961-2197)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:20Z
Check the source to verify that this is the current version before use.