The documentation and process conversion measures necessary to comply with this amendment shall be completed by 1 June 2000.

INCH-POUND

MIL-PRF-19500/391D
AMENDMENT 3
1 March 2000
SUPERSEDING
Amendment 2
18 August 1999

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, TRANSISTOR, NPN, SILICON, LOW-POWER
TYPES 2N3019, 2N3019S, 2N3057A, 2N3700, AND 2N3700UB
JAN, JANTX, JANTXV, AND JANS

This amendment forms a part of MIL-PRF-19500/391D, dated 9 December 1997 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2, delete and substitute: "1.2 Physical dimensions. See figure 1, 2N3019 (TO-5), 2N3019S (similar to TO-39), figure 3 2N3057(TO-46), figure 4 2N3700 (TO-18), and figure 6 (surface mount).'

PAGE 2

FIGURE 1, title, delete and substitute: "FIGURE 1. Physical dimensions for device types 2N3019 (TO-5) and 2N3019S (TO-39)."

PAGE 4

Physical dimensions table, delete and substitute:

"

Symbol	Dimensions				Note
	Inches		Millimeters		
	Min	Max	Min	Max	
CD	.178	.195	4.52	4.95	
CH	.065	.085	1.65	2.16	
HD	.209	.230	5.31	5.84	
LC	.100 TP		2.54 TP		6
LD	.016	.021	0.41	0.53	7
LL	.500	1.750	12.70	44.45	7
LU	.016	.019	0.41	0.48	7
L1	---	.050	---	1.27	7
L2	.250	---	6.35	---	7
Q	---	.040	---	1.02	4
TL	.028	.048	0.71	1.22	4
TW	.036	.046	0.91	1.17	3
r	---	.007	---	0.18	10, 11
α	45° TP		45° TP		6

"

FIGURE 3, title,.delete and substitute: "FIGURE 3. Physical dimensions for 2N3057A (TO-46)."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:20Z
Check the source to verify that this is the current version before use.

PAGE 5

FIGURE 4, title, delete and substitute: "FIGURE 4. Physical dimensions for type 2N3700 (TO-18)."

PAGE 8

3.3, delete and substitute:

"3.3 Interface requirements and physical dimensions. The interface requirements and physical dimensions shall be as specified in MIL-PRF-19500, and figure 1 (2N3019, TO-5, 2N3019S, TO-39), figure 3 (2N3700, TO-18), figure 4 (2N3057, TO-46), and figure 6 (2N3700UB, surface mount) herein."

PAGE 12

TABLE I. inspection column, subgroup 1, delete "Solderability 1/ 2/", and substitute "Solderability 1/ 2/ 4/".

* TABLE I, inspection column, subgroup 2, delete:

"

Collector to base breakdown voltage	3001	Bias condition D; I_C = 100 µA dc.	$V_{(BR)CBO}$	140		V dc	
Emitter to base breakdown voltage	3026	Bias condition D; I_C = 100 µA dc.	$V_{(BR)EBO}$	7		V dc	

"

and substitute

"

Collector to base cutoff current	3036	Bias condition D; V_{CB} = 140 Vdc.	I_{CBO1}		10	µA dc	
Emitter to base cutoff current	3061	Bias condition D; V_{EB} = 7 Vdc.	I_{EBO1}		10	µA dc	

"

* TABLE I, subgroup 2, the new second emitter to base cutoff current test, symbol column; delete "I_{EBO}" and substitute "I_{EBO2}".

PAGE 18

FIGURE 8, Y-Axis, I_C collector current legend, delete "(MICROAMPERES)" and substitute "(MILLIAMPERES)".

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:20Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Navy - AS, CG, MC
Army - AR, AV, MI, SM
Air Force - 13, 19, 99

Preparing activity:
DLA - CC

(Project 5961-2256)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:20Z
Check the source to verify that this is the current version before use.