INCH-POUND
MIL-PRF-24308/5J
28 September 1998
SUPERSEDING
MIL-PRF-24308/5H
2 December 1996

MILITARY PERFORMANCE SPECIFICATION

CONNECTORS, ELECTRIC, RECTANGULAR, MINIATURE, POLARIZED SHELL, RACK AND PANEL, RECEPTACLE, SOCKET CONTACTS, NONMAGNETIC, CLASS M AND N, SOLDER TYPE

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-24308.

REQUIREMENTS:

The connectors shall conform to the design standards (MS standards) indicated in table I.

TABLE I. Design standards. 1/

Part or Identifying Number (PIN) Class N	PIN Class M	Shell size	Shell MS number	Insert arrangement MS number	Contact PIN
M24308/5-1	M24308/5-34	1	MS18269-1	MS18273-1	MS18281-1
M24308/5-2	M24308/5-35	2	MS18269-2	MS18274-1	MS18281-1
M24308/5-3	M24308/5-36	3	MS18269-3	MS18275-1	MS18281-1
M24308/5-4	M24308/5-37	4	MS18269-4	MS18276-1	MS18281-1
M24308/5-5	M24308/5-38	5	MS18269-5	MS18277-1	MS18281-1
2/ M24308/5-12	2/ M24308/5-45	1	MS18269-7	MS18273-1	MS18281-1
M24308/5-13	M24308/5-46	2	MS18269-8	MS18274-1	MS18281-1
M24308/5-14	M24308/5-47	3	MS18269-9	MS18275-1	MS18281-1
M24308/5-15	M24308/5-48	4	MS18269-10	MS18276-1	MS18281-1
M24308/5-16	M24308/5-49	5	MS18269-11	MS18277-1	MS18281-1
M24308/5-23	M24308/5-56	1	MS18269-13	MS18273-1	MS18281-1
M24308/5-24	M24308/5-57	2	MS18269-14	MS18274-1	MS18281-1
M24308/5-25	M24308/5-58	3	MS18269-15	MS18275-1	MS18281-1
M24308/5-26	M24308/5-59	4	MS18269-16	MS18276-1	MS18281-1
M24308/5-27	M24308/5-60	5	MS18269-17	MS18277-1	MS18281-1

1/ These connectors mate with connectors specified in MIL-PRF-24308/7, MIL-PRF-24308/8, MIL-PRF-24308/9, and MIL-PRF-24308/24.

2/ PINs M24308/5-12 through M24308/5-16 and M24308/5-45 through M24308/5-49 are inactive for new design, use M24308/5-23 through M24308/5-27 and M24308/5-56 through M24308/5-60.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:05Z
Check the source to verify that this is the current version before use.

PIN: Consists of the letter M, the basic number of the specification sheet, and a dash number compiled from the code.

PIN example: M24308/5 -36 F

Specification sheet number

Data sheet number from table I

Finish: For class N:

F = Cadmium.
P = Passivated stainless steel
No suffix = Cadmium or zinc

For class M:

Class M connectors have a gold finish, no suffix is required.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AV, MI, AT, CR-4
Navy - AS, CG, MC, SH
Air Force - 99

Preparing activity:
DLA - CC

(Project: 5935-4170)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:05Z
Check the source to verify that this is the current version before use.