INCH-POUND
MIL-PRF-24308/7F
2 December 1996
SUPERSEDING
MIL-C-24308/7E
26 January 1989

MILITARY PERFORMANCE SPECIFICATION

CONNECTORS, ELECTRIC, RECTANGULAR, MINIATURE, POLARIZED SHELL, RACK AND PANEL, PIN CONTACTS, NONMAGNETIC, CLASS M AND N, SOLDER TYPE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-PRF-24308 listed in that issue of the Department of Defense Index of Specification and Standards (DoDISS).

REQUIREMENTS:

The connectors shall conform to the design standards (MS standards) indicated in table I.

TABLE I. Design standards. 1/

Part of identifying number (PIN) Class N	PIN Class M	Shell size	Shell MS number	Insert arrangement MS number	Contact PIN
M24308/7-1	M24308/7-23	1	MS18268-1	MS18273-1	MS18281-1
M24308/7-2	M24308/7-24	2	MS18268-2	MS18274-1	MS18281-2
M24308/7-3	M24308/7-25	3	MS18268-3	MS18275-1	MS18281-2
M24308/7-4	M24308/7-26	4	MS18268-4	MS18276-1	MS18281-2
M24308/7-5	M24308/7-27	5	MS18268-5	MS18277-1	MS18281-2
M24308/7-12 2/	M24308/7-34 2/	1	MS18268-7	MS18273-1	MS18281-2
M24308/7-13	M24308/7-35	2	MS18268-8	MS18274-1	MS18281-2
M24308/7-14	M24308/7-36	3	MS18268-9	MS18275-1	MS18281-2
M24308/7-15	M24308/7-37	4	MS18268-10	MS18276-1	MS18281-2
M24308/7-16	M24308/7-38	5	MS18268-11	MS18277-1	MS18281-2
M24308/7-17	M24308/7-39	1	MS18268-13	MS18273-1	MS18281-2
M24308/7-18	M24308/7-40	2	MS18268-14	MS18274-1	MS18281-2
M24308/7-19	M24308/7-41	3	MS18268-15	MS18275-1	MS18281-2
M24308/7-20	M24308/7-42	4	MS18268-16	MS18276-1	MS18281-2
M24308/7-21	M24308/7-43	5	MS18268-17	MS18277-1	MS18281-2

1/ These connectors mate with connectors specified in MIL-PRF-24308/5, MIL-PRF-24308/6.
2/ PINs M24308/7-12 through M24308/7-16 and M24308/7-34 through M24308/7-38 are inactive for new design, use M24308/7-17 through M24308/7-21 and M24308/7-39 through M24308/7-43.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:06Z
Check the source to verify that this is the current version before use.

PIN: Consists of the letter M, the basic number of the specification sheet, and a dash number compiled from the code.

PIN example M24308/7- -23 F

Specification sheet number

Data sheet number from table I

Finish: For class M:

F = Cadmium.
P = Passivated stainless steel.
No suffix = Cadmium or zinc.

For class N:

Class N connectors have a gold finish, no suffix is required.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA

Preparing activity:
DLA - ES

Review activities:
Army - AV, MI, AT, ME
Navy - AS, CG, MC, SH
Air Force - 99

(Project: 5935-4075-07)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:06Z
Check the source to verify that this is the current version before use.