NOT MEASUREMENT SENSITIVE


MIL-I-3949/12F
3 June 1991
SUPERSEDING
MIL-I-3949/12E
30 January 1991

MILITARY SPECIFICATION SHEET

INSIGNIA, RANK; LIEUTENANT COLONEL AND MAJOR, ARMY AND AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-I-3949.



MATERIAL:
- -1,-2: Red brass or nickel silver.
- -3,-4: Red brass.
- -5,-6: Red brass or zinc aluminum.

DASH NO:
- -1: Lieutenant Colonel, Regular Size
- -2: Lieutenant Colonel, Miniature Size (AF)
- -3: Major, Regular Size
- -4: Major, Miniature Size (AF)
- -5: Lieutenant Colonel, Subdued
- -6: Major, Subdued

DIMENSIONS:
- HEIGHT (Overall):
  - -1,-3,-5,-6: 1-1/8 inch (2.86 cm) (REF)
  - -2,-4: 23/32 inch (1.83 cm) (REF)
- WIDTH (Overall):
  - -1,-3,-5,-6: 1 inch (2.54 cm) (REF)
  - -2,-4: 11/16 inch (2.75 cm) (REF)
- THICKNESS (Overall):
  - -1,-3,-5,-6: .150 inch ± .010 inch (0.381 cm ± 0.025 cm)
  - -2,-4: .096 inch ± .005 inch (0.243 cm ± 0.012 cm)

FINISH:
- -1,-2: Nickel plated, matte finish, polished highlights.
- -3,-4: Gold plated, matte finish, polished highlights.
- -5: Dull flat black baked enamel finish.
- -6: Dull flat brown baked enamel finish.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:45Z
Check the source to verify that this is the current version before use.

NOTES:

1. The attaching device shall be prong and clutch type. Prongs shall be located on the vertical centerline, equidistance from each end and the following distance apart:

   -1,-3,-5,-6: 7/8 inch ± 1/64 inch (2.22 cm ± 0.04 cm)
   -2,-4: 19/32 inch ± 1/64 inch (1/51 cm ± 0.04 cm)

2. A forcer may be used to bring up the design for Dash No. 2, 3, 5 and 6. There shall be a minimum thickness of .085 inch ± .005 inch (0.215 cm ± 0.012 cm) at the high point of the forced area.
3. The enamel for Dash No. 5 and 6 shall match the chip numbers of FED-STD 595 listed below:

COLOR	CHIP NUMBER
Black	37038
Brown	20095

Custodians:
Army - IH
Air Force - 11

Review activities:
Air Force - 82,99
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0598)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:45Z
Check the source to verify that this is the current version before use.