NOT MEASUREMENT SENSITIVE

MIL-I-3949/27B
20 March 1995
SUPERSEDING
MIL-I-3949/27A
19 October 1990

MILITARY SPECIFICATION SHEET

INSIGNIA, RANK, LIEUTENANT (JG) AND ENSIGN, NAVY LIEUTENANT AND SECOND LIEUTENANT, MARINE CORPS

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-I-3949.



DASH NO.

-1: Lieutenant (JG), Navy and First Lieutenant, Marine Corps, Regular Size
-2: Lieutenant (JG), Navy and First Lieutenant, Marine Corps, Miniature Size
-3: Ensign, Navy and Second Lieutenant, Marine Corps, Regular Size
-4: Ensign, Navy and Second Lieutenant, Marine Corps, Miniature Size

MATERIAL: Red Brass or Nickel Silver

DIMENSIONS:

HEIGHT (Overall):
-1,-3: 3/8 inch (0.95 cm) (REF)
-2,-4: 1/4 inch (0.64 cm) (REF)

WIDTH (Overall):
-1,-3: 1-1/8 inch (2.86 cm) (REF)
-2,-4: 3/4 inch (1.91 cm) (REF)

THICKNESS (At Edge) :
-1,-3: 0.070 inch ± 0.005 inch (0.177 cm ± 0.012 cm)
-2,-4: 0.050 inch ± 0.005 inch (0.127 cm ± 0.012 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:48Z
Check the source to verify that this is the current version before use.

FINISH:
-1,-2: Nickel Plated, Rhodium Plated, Mirror-like Polished.
-3,-4: Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Attaching device shall be prong and clutch type. Prongs shall be located on the vertical center line, equidistant from each end and the following distance apart:

-1,-3: 13/16 inch ± 1/64 inch (2.06 cm ± 0.04 cm)
-2,-4: 9/16 inch ± 1/64 inch (1.43 cm ± 0.04 cm)

3. Dash No. -1 and -3 shall be dapped along a radius of 5 inch ± 1/64 inch (12.80 cm ± 0.04 cm) radius on a horizontal plane.

4. Dash No. -1 and -3 may be made from sterling silver for commercial sale and if so, the thickness dimensions are for reference only. A minimum weight of 70 grains for Dash No. -1 and 25 grains for Dash No. - 2 shall govern. The finish shall be as specified except the nickel plating requirement shall not apply.

Custodians:
Army - IH
Navy - NU

Review activities:
Navy - MC
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0792)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:48Z
Check the source to verify that this is the current version before use.