INCH-POUND

A-A-52143
January 14, 1994

COMMERCIAL ITEM DESCRIPTION

ICE CREAM CABINETS, MECHANICALLY-REFRIGERATED

DISPENSING, MOBILE, SELF-ELEVATING

The General Services Administration has authorized the use of this Commercial Item Description in preference to MIL-I-43385.

1. ABSTRACT

1.1 Abstract. This commercial item description covers self-elevating, mobile, dispensing, mechanically-refrigerated ice cream cabinets in the following sizes:

Size 1 - 450 standard 3-ounce ice cream cups or 4-ounce ice cream slices (minimum capacity)

Size 2 - 900 standard 3-ounce ice cream cups or 4-ounce ice cream slices (minimum capacity)

1.2 CID based part identification number (PIN). A document based PIN to identify sizes of items is included in section 5. This identification numbering procedure is for Government purposes and does not constitute a requirement for the contractor except as information on "Government unique" data nameplates (see 5.4).

2. SALIENT CHARACTERISTICS

2.1 Design and construction. The ice cream cabinets shall consist of an insulated enclosure with insulated top opening lids giving access to a refrigerated storage compartment. The insulated cabinet shall consist of an insulated top, an outer shell, and an inner shell all fabricated from 300

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: Commander, U.S. Army Natick Research, Development, and Engineering Center, ATTN: SATNC-WEE, Natick, MA 01760-5018.

AMSC N/A FSC 4110

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

series stainless steel. The inner liner shall be separated from the outer shell by breaker strips except as required by UL Standard No. 471. Cabinets shall be provided with 4 casters, handles located at both ends, fixed tray rails, and a full perimeter wraparound bumper. Unless otherwise specified, a number of baskets necessary for full capacity operation shall be furnished with the cabinets (see 5.2). Basket lids shall be fabricated from aluminum, stainless steel, or a corrosion-resistant metal. Cabinets shall be either size 1 or size 2 as specified and each cabinet shall be provided with an automatic self-contained refrigeration system. Cabinet storage compartments shall have a manually adjusted, self-leveling mechanism to maintain ice cream containers at a constant top level. All material used in the self-elevating mechanism shall be corrosion resistant.

2.1.1 Cabinet. The cabinet shall form a completely rigid structure to provide support to a full load of ice cream and the refrigerating system. The overall maximum dimensions of the ice cream cabinets shall be as shown in table I.

TABLE I. Overall dimensions. 1/

Size	Width (in. max.)	Length (in. max.)	Height (in. max.)
1	32-1/2	56	37
2	32-1/2	72	37

1/ Overall dimensions include accessories such as casters, bumpers, and handles.

2.1.2 Breaker strips. The breaker strips shall be fabricated of composition board, or styrene plastic, or vinyl-chloride plastic, or any combination of these materials. Where foamed-in-place polyurethane insulation is used, all plastics in direct contact with the insulation shall be ABS (acrylonitrile, butadiene, styrene). The breaker strips shall join and shall make a vapor seal with the inner liner and outer shell. The edges of the breaker strips shall be eased or rounded. All plastics used for breaker strips shall not impart odor or taste to foods.

2.1.3 Lids. The lids shall be fabricated of 300 series stainless steel or molded fiberglass. The lids shall be insulated and shall have gaskets or other provisions to form a tight seal between the lids and the cabinets. When specified, the lids shall be the see-through type fabricated for plastic (see 5.2).

2.1.4 Casters. Four casters of the full swivel type shall be furnished on each cabinet. The casters shall be a minimum of five inches. A minimum of two of the casters shall be equipped with a foot operated braking device which shall hold the cabinet stationary.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

2.2 Insulation. The manufacturer shall use insulation with a "K" factor that will meet the outer shall temperature requirements set in paragraph 2.3.

2.3 Outer shell temperature. The temperature of the outer shell of the cabinets shall not be more than 10°F below the ambient temperature when the refrigeration system is in operation and the temperature in the storage compartment is being held at 0°F.

2.4 Tray rails. A fixed type tray rail fabricated from 300 series stainless steel with supporting hardware shall be supplied with each ice cream cabinet. The tray rail shall extend the full length of the cabinet. The height of the tray rail from the floor shall be adjustable from 34 to 35 inches. The tray rails shall be capable of supporting the weights listed when the weight is equally distributed over the full length of the tray.

Size 1 - 75 pounds

Size 2 - 80 pounds

2.5 Refrigeration system. The refrigeration system and component parts shall be completely installed and connected in the machine compartment; making the fully automatic, self-contained, mechanically cooled ice cream cabinet ready for connection to an external electric power source.

2.5.1 Refrigerant charge. The assembled refrigeration system shall be evacuated, completely dehydrated, and charged with the necessary amount and type of refrigerant and lubricating oil necessary for operation.

2.5.2 Ozone depleting substances. Class I ozone depleting substances, in accordance with section 602(a) of the Clean Air Act Amendments 1990, 42 USC 7671a(a) as implemented by 40 CFR 82, Protection of Stratospheric Ozone, shall not be used for refrigerant gases, or for any other purpose, or employed in any process associated with the manufacture of any component parts for this item. See the 5.6 for additional information.

2.6 Temperature control. The ice cream cabinets shall be equipped with a thermostat to maintain temperature control. The control shall be adjustable to maintain temperatures selected between minus 10°F and minus 15°F. The thermostat shall be adjusted and installed so that the cabinet temperature will not vary more than plus or minus 5°F from the temperature setting when ambient conditions vary from 50°F to 110°F. An external dial type thermometer, calibrated in Fahrenheit and having a temperature scale range which includes the operating range of the cabinet, shall be furnished.

2.7 Performance. The empty ice cream cabinets shall be capable of obtaining an internal temperature of minus 5°F in not more than eight hours in an ambient of 110°F. When fully loaded the ice cream cabinet shall maintain internal temperatures between minus 10°F and minus 15°F with an ambient temperature range of 50°F to 110°F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

2.8 Electrical requirements. Unless otherwise specified, the ice cream cabinets shall be designed for 115 V, singe phase, 60 Hz (see 5.2). All ice cream cabinets shall be completely electrically wired and shall conform to the National Fire Protection Association (NFPA) Standard No. 70. Motors shall be protected against damages from overloads and voltage flucturations when starting or running. A six to ten foot power supply cord shall be furnished as part of the ice cream cabinet. The power supply cord shall be three wire with a three-prong National Electrical Manufacturers Association (NEMA) plug. When a 50 Hz system is specified, equipment and systems shall be specifically designed for operation on that frequency.

2.9 Standard compliance. The ice cream cabinets shall conform to the requirements of American Society of Heating, Refrigeration, and Air Conditioning Engineers (ASHRAE) Standard No. 13, NSF International Standard No. 1, NFPA Standard No. 70, Underwriters Laboratory (UL) Standard No. 471, and NEMA Standards.

2.10 Data nameplate ("Government unique" requirement). The cabinets shall be furnished with a data nameplate in accordance with the applicable requirements of MIL-STD-130 except the requirements for: (a) Methods of applying, (b) Identification tags, (c) Information not required, and (d) Optional marking information shall not apply. The data nameplate shall be made of minimum 20 gauge corrosion-resisting metal and attached to the cabinets by rivets, screws, or welding in such a manner as to meet the applicable NSF International sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved, or applied by photosensitive means:

Contract Number
National Stock Number
Procurement Instrument Identification Number
CID Based Part Identification Number (PIN)
Manufacturer's Name, Address, and Telephone Number
Supplier's Name, Address, and Telephone Number (List Only if Different from Manufacturer)
Manufacturer's Model and Serial Number
Government Approved Manual Number

Each plate shall be placed so that it is readily visible to the operator during normal operating use and so as to not adversely affect the life and utility of the cabinet.

2.11 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified using conversion tables contained in the latest revision of Federal Standard No. 376, and all other requirements of this commercial item description are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

contracting officer to determine if the product is acceptable. The contracting officer has the option of accepting or rejecting the product.

2.12 Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this commercial item description unless otherwise specified.

2.13 Workmanship. The finished cabinets shall be complete, clean, and free of fabrication marks, scratches, dents, sharp edges, sharp corners, burrs, slivers, or visible evidence of rust. Rivets, when used, shall be tight and the rivet heads and peened ends shall be round and concentric and in full contact with the joined metal surfaces. There shall be no empty rivet holes. Welds shall be clean, continuous, sound, and free of flux, pits, buildups, undercuts, and shall be ground so as to blend with the adjacent surfaces. Spot welds shall be free from pits, burn throughs, and flashes.

3. QUALITY ASSURANCE

3.1 Contractor certification. The contractor shall certify that the product offered meets the salient characteristics and requirements of this commercial item description and except for those Government unique requirements specified, conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product offered for sale in the commercial marketplace or that had successfully been delivered to the Government on a previous contract or purchase order. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3.2 Compliance. Prior to approval of the first shipment, the contractor shall submit satisfactory evidence to the contracting officer or his authorized representative that the ice cream cabinet conforms to the requirements of ASHRAE Standard No. 13, NSF International Standard No. 1, NFPA Standard No. 70, UL Standard No. 471, and NEMA Standards, as applicable.

3.2.1 Underwriters Laboratories, Inc. (UL). Acceptable evidence of meeting the requirements of UL Standard No. 471 shall be the UL listing mark, or a certified test report from a recognized independent laboratory acceptable to the Government indicating compliance with the applicable requirements of UL Standard No. 471.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

3.2.2 NSF International. Acceptable evidence of meeting the requirements of NSF International Standard No. 1 shall be a listing in the current edition of the NSF International "Listing of Food Service Equipment" and display of the NSF International mark on the finished product, or a certified test report from a recognized independent laboratory acceptable to the Government indicating compliance with the applicable NSF International requirement(s).

3.2.3 National Fire Protection Association (NFPA). The contractor shall submit to the contracting officer a written certificate of compliance as proof that the ice cream cabinet meets the applicable requirements of the NFPA.

3.2.4 American Society of Heating, Refrigeration, and Air Conditioning Engineers (ASHRAE). The contractor shall submit to the contracting officer a written certificate of compliance as proof that the ice cream cabinets meet the applicable requirements of ASHRAE.

3.2.5 National Electrical Manufacturers Association (NEMA). The contractor shall submit to the contracting officer a written certificate of compliance as proof that the ice cream cabinets meet the applicable requirements of NEMA.

4. PACKAGING

4.1 Packaging and packing. Packaging and packing shall be commercial or export as specified (see 5.2).

4.2 Commercial packaging and packing. Each ice cream cabinet shall be cleaned, preserved, packaged, and packed in accordance with ASTM D 3951.

4.3 Export packaging and packing.

4.3.1 Export packaging. Each ice cream cabinet shall be disassembled to the extent determined by the manufacturer to protect parts susceptible to damage during shipment and storage. Disassembled parts shall be such that special skills or special tools, other than those provided, or both, are not required to place the ice cream cabinet in operation. The ice cream cabinet and disassembled parts shall be preserved and cushioned to provide adequate protection against corrosion, deterioration, and damage during shipment and storage.

4.3.2 Export packing. Each ice cream cabinet shall be packed in a snug-fitting, wood-cleated plywood box conforming to domestic type, style A or B, type 2 load of PPP-B-601 or nailed wood box conforming to class 1, style 2 or 4, type 2 load of PPP-B-621. The cabinet shall be blocked and braced to prevent movement and provide 1 inch clearance between the casters and the bottom of the box. Closure and strapping shall be in accordance with PPP-B-601 or PPP-B-621, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

4.4 Marking. Marking of shipping containers shall be in accordance with MIL-STD-129.

5. NOTES

5.1 Intended use. The ice cream cabinets covered by this commercial item description are intended for use as mobile ice cream dispensers for dining facilities.

5.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this commercial item description.
b. PIN designating size required (see 1.1, 1.2, and 5.4).
c. When number of baskets is other than specified (see 2.1).
d. When see-through lids are required (see 2.1.3).
e. Electrical requirements if other than specified (see 2.8).
f. Government approved manual number to be included on data nameplate (see 2.10).

5.3 Sources for documents.

5.3.1 Sources for non-Government association documents.

ASHRAE Standard No. 13 - Home Freezers, Methods of Rating and Testing

ASHRAE documents are available from:

American Society of Heating, Refrigerating, and
Air Conditioning Engineers, Inc.
United Engineering Center
345 West 47th Street
New York, NY 10017

NEMA documents are available from:

National Electrical Manufacturers Association (NEMA)
2101 L Street, NW
Washington, DC 20037

NFPA Standard No. 70 is available from:

National Fire Protection Association (NFPA)
Batterymarch Park
Quincy, MA 02269

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

NSF International Standard No. 1 - Soda Fountain and Luncheonette Equipment

NSF International documents are available from:

NSF International
3475 Plymouth Road
P.O. Box 130140
Ann Arbor, MI 48113-0140

UL Standard No. 471 - UL Standard for Safety Commercial Refrigerators

UL documents are available from:

Underwriters Laboratories, Inc. (UL)
333 Pfingsten Road
Northbrook, IL 60062

5.3.2 Source for Government documents. Copies of military and federal documents are available from:

Standardization Documents Order Desk
Building 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

5.4 Part identification number (PIN). The PIN's to be used for items required by this CID are created as follows:



5.5 "Government unique" requirements. Whenever a "Government unique" requirement is included in the title of a paragraph under "Salient Characteristics", it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

5.6 Ozone depleting substances. For current information about the status of the Environmental Protection Agency's (EPA) Significant New Alternatives Policy (SNAP) program and specific refrigerant alternatives, call the Stratospheric Ozone Protection Hotline at (800) 296-1996 or the SNAP Coordinator at (202) 233-9195. For published information see the EPA Stratospheric Ozone Protection, Fact Sheet (EPA-430-F-93-004 dated February 1993) Short List of Alternative Refrigerants and Action Guide (EPA-430-F-93-003, dated February 1993) Cooling & Refrigerating without CFCs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians

Army - GL
Navy - YD
Air Force - 99

Review Activities

Army - MD, QM
Navy - MC
Air Force - 50, 82
DLA - GS

User Activity

Army - ME

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project 4110-0474

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
3. DOCUMENT TITLE		

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME U.S. Army Natick RD&E Center	b. TELEPHONE (Include Area Code) (1) Commercial: 508-651-5175 (2) AUTOVON/DSN: 256-5175
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: SATNC-WEE Natick, MA 01760-5018	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil - Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.