MILITARY SPECIFICATION

FUZE, IMPACT, ATOMIC WEAPON: M1131

This amendment forms a part of Military Specification MIL-F-48003A(AR) dated 11 May 1977.

PAGE 1

Standards, Military: Add "MIL-STD-1188 - Commercial Packing of Supplies and Equipment."

PAGE 2

(a) Line 1 (Drawings) and line 12 (Publications): Add "(see 6.4)".
(b) Drawings: Delete drawing 9321236.

PAGE 3

Delete paragraph 3.5 (and Table II) and substitute:

"3.5 Output voltage.- The peak output voltage of the impact fuze, as measured during the initial pulse, shall be a minimum of 0.6 volt from each output circuit (J1 and J2), and it shall be of positive polarity. The impact pulse applied to the fuze shall be 500 ± 25 gravities (g), peak amplitude, which will result in a maximum duration of the initial pulse of 200 microseconds as measured along the zero-voltage (reference) baseline on the measuring oscilloscope. Testing shall be as specified in 4.5.2."

PAGE 4

Delete paragraph 3.7 and substitute:

"3.7 Sensitivity.- The sensitivity of the impact fuze shall be as specified in Table III when subjected to a continuous sinusoidal vibration of 40 g ± 10 percent

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:09Z
Check the source to verify that this is the current version before use.

peak-to-peak at a frequency of 330 ± 20 hertz. In addition, the actual sensitivity value in millivolts (mv), for each fuze output circuit, shall be recorded (see 3.14). Testing shall be as specified in 4.5.4.

TABLE III

Output circuit	Sensitivity (mv, peak-to-peak)	Test identification number (see 3.14) 1/
J1	15 minimum	080001
J2	15 "	080002

1/ Not required during the following tests: high temperature, temperature shock, low temperature, humidity, and vibration."

PAGE 6

Line 6: Delete "3.5".

PAGE 11

Paragraph 4.4.2.1.5, Major defect 101, line 5: Delete "dwg. 9321236" and substitute "MIL-STD-1188".

PAGE 13

(a) Paragraph 4.5.2, line 12: Delete "three times" and substitute "once".

(b) Delete paragraph 4.5.4 and substitute:

"4.5.4 Sensitivity.- The impact fuze shall be mounted to a vibration machine with the fuze cover plate in the upper position. The fuze shall be assembled to the vibration machine using the threaded hole in the narrow end of the fuze. The fuze shall be tightened to the vibration machine with a torque of 19 ± 2 ft-lb. The fuze shall be subjected to the vibrations specified in 3.7 along a vertical axis which is perpendicular to the fuze cover plate. The output of the fuze shall be measured across the fixed load, specified in 4.5.2, using an oscilloscope or other measuring device which has been approved by the Government for this purpose. The measurements from output connectors J1 and J2 do not have to be taken

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:09Z
Check the source to verify that this is the current version before use.

simultaneously, but may be taken separately. The duration of this test is not significant, but it shall be long enough to ensure obtaining valid measurements. The fuze shall comply with the requirements of 3.7 during this test."

PAGE 16

(a) Section 5 (Packaging): Delete references to drawing 9321236 and substitute MIL-STD-1188.
(b) Paragraph 6.1.2, line 1: Delete "3.5".

Custodian:
Army-AR

(Project 1135-A245)

Preparing activity:
Army-AR

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:09Z
Check the source to verify that this is the current version before use.