
28 VOLT DC TWO WIRE
-02 INSERT ARRANGEMENT

QTY	CONTACT	SIZE	SOCKET M39029	PIN M39029
1	A	4/0	49-335	48-327
1	N	4/ON	49-335 SEE NOTE 9	48-328

(E) AC SINGLE PHASE THREE WIRE GROUNDING
-06 INSERT ARRANGEMENT


QTY	CONTACT	SIZE	SOCKET M39029	PIN M39029
2	A,B	4/0	49-335	48-327
1	N	4/ON	49-335 SEE NOTE 9	48-328
3	G1,G2,G3	4G	49-332	48-322



SERVICE D

-02 ICEA 2-NO. 2/0 CONDUCTOR
ROUND TYPE W CABLE 0-600 Volts.

FRONT FACE OF PIN INSERT SHOWN
(SOCKET INSERT OPPOSITE), UNLESS
OTHERWISE SPECIFIED.

(E)


SERVICE D

-06 ICEA 3-NO. 2/0 CONDUCTOR
ROUND TYPE G CABLE 0-600 Volts.

INSERT ARRANGEMENT	CONTACTS		CABLE CONDUCTORS MS90556 & MS90557		CONTACT BUSHINGS REQUIRED	
	QTY	SIZE	QTY	SIZE	QTY	P/N MS3348-
52-02	2	4/0	2	2/0	2	4/0-2/0L
52-06	3 3	4/0 4	3 3	2/0 5(G)	3 3	4/0-2/0L 4-5L

(E) denotes changes.

APPROVED 29 Jan 1973 REVISED (A) 28 Aug 1974 (B) 6 May 1975 (C) 7 FEB 80 (D) 30 Mar 1982 (E) 20 December 1982

User activities: Army - AT, AV, ME
Navy - MC, CG, SH, OS
Air Force -19


Review activities: Army -CR , MI , AS, YD
Navy -
Air Force -17, 11
DLA-ES

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

P.A NAVY - EC Other Cust ARMY - CR AF - 85	International interest	TITLE INSERT ARRANGEMENTS, ELECTRICAL CONNECTOR, SIZE 52, CLASS L, 200 AMPS	MILITARY STANDARD MS 14057
Procurement Specification MIL-C-22992		SUPERSEDES:	PAGE 1 OF 3

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:33Z
Check the source to verify that this is the current version before use.

AC THREE PHASE FOUR WIRE GROUNDING
-12 AND -13 INSERT ARRANGEMENTS



SERVICE D

QTY	CONTACT	SIZE	SOCKET M39029	PIN M39029
3	A,B,C	4/0	49-335	48-327
1	N	4/ON	49-335 SEE NOTE 9	48-328
2	G1,G2,G3,G4	4G	49-332	48-322

-12-CABLE ICEA 4-NO. 4/0 CONDUCTOR ROUND TYPE G 0-600 Volts.
-13-CABLE CO-04 HDE (4/0000-4/4R) 2380 PER MIL-C-3432
52-12 SHALL BE MARKED ON 52-13 INSERT (SEE NOTE 8)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
3. Metric equivalents are in parentheses.
4. Unless otherwise specified, tolerance is ±.002 (.05 mm).
5. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
6. Referenced documents shall be of the issue in effect on date of invitation for bid.
7. Unless otherwise specified, pin insert pattern shown. Socket inserts are the reverse.
8. Trademark and 52-( ) shall appear in available space. Contact identifying letter shall be located so as to identify relative contact.
9. Only the pin contact is lengthened and has the N (neutral) designation. The mating socket contact is the same as the power contact.

REQUIREMENTS:
1. Neutral pin (N) is not connected to shell.
2. Grounding pin (G) is connected to shell.
3. Applicable MS3348 crimp bushings shall be supplied with the contacts for insert arrangements as specified.

ARRANGEMENT NUMBER	INSERT ROTATION (DEGREES FROM NORMAL) NORMAL (SEE FIG. 1) DC or 60 Hz	ALTERNATE (SEE FIG 1) 400 Hz W	X	Y
52-02	0°	---	---	---
52-06	0°	---	---	---
52-12,52-13	0°	300°	---	---

FRONT FACE OF PIN INSERT SHOWN (SOCKET INSERT OPPOSITE), UNLESS OTHERWISE SPECIFIED. (E)

REVISED (E) For changes see pages 1,2, AND 3
APPROVED 29 Jan 1973

User activities: Army - AT, AV, ME
Navy - MC, CG, SH, OS
Air Force -19

Review activities: Army -CR, MI
Navy - AS, YD
Air Force -17, 11
DLA-ES


This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

P.A NAVY - EC	International interest	TITLE	MILITARY STANDARD
Other Cust ARMY - CR AF - 85		INSERT ARRANGEMENTS, ELECTRICAL CONNECTOR, SIZE 52, CLASS L, 200 AMPS	MS14057
Procurement Specification MIL-C-22992		SUPERSEDES:	PAGE 2 OF 3

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:33Z
Check the source to verify that this is the current version before use.


FED. SUP CLASS
5935

INSERT IN NORMAL POSITION
(60 Hz POWER ONLY)




(REF. MS90555******S)
(REF. MS90557******S)
SOCKET CONTACT PATTERN
FRONT FACE OF SOCKET INSERT SHOWN

INSERT IN ALTERNATE POSITION
(400 Hz POWER ONLY)




(REF. MS90555******SW)
(REF. MS90557******SW)
SOCKET CONTACT PATTERN
FRONT FACE OF SOCKET INSERT SHOWN

INSERT IN NORMAL POSITION
(60 Hz POWER ONLY)



(REF. MS90556******P)
(REF. MS90558******P)
SOCKET CONTACT PATTERN
FRONT FACE OF PIN INSERT SHOWN

INSERT IN ALTERNATE POSITION
(400 Hz POWER ONLY)



(REF. MS90556******PW)
(REF. MS90558******PW)
SOCKET CONTACT PATTERN
FRONT FACE OF PIN INSERT SHOWN

Ⓔ FIGURE 1.

APPROVED 29 JAN 1973 REVISED Ⓔ FOR CHANGES SEE PAGES 1,2, AND 3

User activities: Army - AT, AV, ME
Navy - MC, CG, OS, SH
Air Force - 19

Review activities: Army - CR, MI
Navy - AS, YD
Air Force - 17, 80
DLA-ES

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

P.A NAVY - EC Other Cust ARMY - CR AF - 85	International Interest	TITLE INSERT ARRANGEMENTS, ELECTRICAL CONNECTOR, SIZE 52, CLASS L, 200 AMPS	MILITARY STANDARD MS14057
Procurement Specification MIL-C-22992		SUPERSEDES:	PAGE 3 OF 3

DD FORM 1 MAY 73 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

5935-3333-2

☆ U.S. GOVERNMENT PRINTING OFFICE: 1983-605-034/1488

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:33Z
Check the source to verify that this is the current version before use.