


FED SUP CLASS
4730





SECTION A-A



DETAIL B-B
SIZE 8 ONLY

APPROVED 17 Mar 71

NOTE : THE GOVERNMENT HAS A ROYALTY FREE LICENSE UNDER THE FOLLOWING PATENTS FOR THE BENEFIT OF MANUFACTURERS OF THE ITEM EITHER FOR THE GOVERNMENT OR FOR USE IN EQUIPMENT TO BE DELIVERED TO THE GOVERNMENT. (U.S. PATENT NOS. 2,833,567; 3,044,163; 2,955,692)

This standard has been approved by the Department of the Air Force and is mandatory for use by that activity. All other military activities are encouraged to employ this standard where suitable.

P.A. USAF-11 Other Cust	TITLE NIPPLE, FLARED, TUBE TO HOSE-SWIVEL NUT	MILITARY STANDARD MS27626
Procurement Specification	SUPERSEDES	SHEET 1 OF 3

DD FORM 1 SEP 67 672

Source: https://assist.dla.mil -- Downloaded: 202610-23T16:46Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
4730

(a) USE COMMERCIAL STOCK SIZE TOLERANCES

(b) THREAD GAGE MUST ENTER THREAD RELIEF.

(c) ALL DIAMETERS WITHIN "B" DIMENSION SHALL BE CONCENTRIC WITHIN .005 TIR.

(d) THREADS MUST BE ROLLED.

THREADS PER SPECIFICATION MIL-S-7742.

MATERIAL : CORROSION RESISTING STEEL, CLASS 304, CONDITION "B", SPECIFICATION QQ-S-763. MIN YIELD : 70,000 PSI ON -4C, -6C AND -8C AND 60,000 PSI ON -10C

FINISH : PASSIVATE PER MIL-F-83296

DRY-FILM LUBRICATE AREA "X" IN ACCORDANCE WITH MIL-L-8937. DRY-FILM ALLOWED IN AREA "Y". DRY-FILM MUST NOT EXTEND BEYOND AREA "Z".

DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED : RADIUS OR BREAK ALL CORNERS .005, +.005/-.000. REMOVE ALL BURRS AND SLIVERS. SURFACE ROUGHNESS PER ANSI B46.1-1962 NOT TO EXCEED 125 AA . ALL DIAMETERS MUST BE CONCENTRIC WITHIN .010 TIR.

THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.

THIS IS A DESIGN STANDARD FOR MANUFACTURING PURPOSES. THE ITEM IS ONLY PROCURED AS AN INTEGRAL PART OF ADAPTER ASSEMBLIES.

NEXT ASSEMBLY MS27619

APPROVED 17 Mar 71

NOTE : THE GOVERNMENT HAS A ROYALTY FREE LICENSE UNDER THE FOLLOWING PATENTS FOR THE BENEFIT OF MANUFACTURERS OF THE ITEM EITHER FOR THE GOVERNMENT OR FOR USE IN EQUIPMENT TO BE DELIVERED TO THE GOVERNMENT. (U.S. PATENT NOS. 2,833,567; 3,044,163; 3,055,682)

This standard has been approved by the Department of the Air Force and is mandatory for use by that activity. All other military activities are required to employ this standard where suitable.

P.A USAF-11 Other Cust	TITLE NIPPLE, FLARED, TUBE TO HOSE-SWIVEL NUT	MILITARY STANDARD MS27626
Procurement Specification	SUPERSEDES:	SHEET 2 OF 3

DD FORM 1 SEP 67 672 (Limited coordination) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:46Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
4730

MS PART NUMBER	A ±.010	B ±.005	C (a)	D ±.005	E ±.005	F ±.005	G ±.005	H ±.050
MS27626-4C	.428	.929	.750	.379	.110	.544	.041	.100
MS27626-6C	.545	.981	.875	.361	.085	.660	.043	
MS27626-8C	.630	1.137	1.000	.400	.100	.813	—	
MS27626-10C	.735	1.388	1.250	.338	.100	.989	.037	

J +.000 -.005	K ±.005	L ±.005	M ±.010	N ±.005	P ±.02	R ±30′	S ±.005	THREAD "T"
.250	.420	—	—	—	.72	—	.161	5/8-18UNF-3A
.343	.495	—	—	—	.84	—	.271	3/4-16UNF-3A
.445	.610	—	.783	.030	.97	—	.375	7/8-24UNS-3A
.588	.762	.150	—	—	1.22	10°	.465	1 1/16-20UN-3A

PITCH DIAMETER	U ±5°	V ±.005	W ±.005	AA ±.005	AB		AC ±.005
.5889/.5854	45°	—	.825	.069	.625	+.000 -.009	.138
.7094/.7056		—	.962	.092	.750		.185
.8479/.8448	30°	.050	1.100	.095	.875	+.000 -.007	.190
1.0300/1.0266	45°	—	1.375	.125	1.062	+.000 -.008	.250

APPROVED 17 Mar 71

NOTE: THE GOVERNMENT HAS A ROYALTY FREE LICENSE UNDER THE FOLLOWING PATENTS FOR THE BENEFIT OF MANUFACTURERS OF THE ITEM EITHER FOR THE GOVERNMENT OR FOR USE IN EQUIPMENT TO BE DELIVERED TO THE GOVERNMENT. (U.S. PATENT NOS. 2,833,567; 3,044,163; 3,055,682)

This standard has been approved by the Department of the Air Force and is mandatory for use by that activity. All other military activities are required to employ this standard where suitable.

P.A. USAF-11 Other Cust	TITLE NIPPLE, FLARED, TUBE TO HOSE - SWIVEL NUT	MILITARY STANDARD MS27626
Procurement Specification	SUPERSEDES:	SHEET 3 OF 3

DD FORM 1 SEP 67 672 (Limited coordination) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:46Z
Check the source to verify that this is the current version before use.