AA-B-1976/GEN
May 20, 1976
SUPERSEDING
Int. Fed. Spec. AA-B-00790 (GSA-FSS)
April 2, 1965 and
Int. Fed. Spec. AA-B-00800A (GSA-FSS)
August 22, 1967

FEDERAL SPECIFICATION

BULLETIN BOARDS: GENERAL SPECIFICATION FOR

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers interior bulletin boards. Specific requirements are covered by individual specification sheets (see 6.2 and 6.4).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extend specified herein:

Federal Specifications:

C-F-206	-	Felt Sheet: Cloth, Felt, Wool, Pressed
DD-G-451	-	Glass, Plate, Sheet, Figured (Float, Flat, for Glazing, Corrugated, Mirrors and Other Uses)
QQ-C-320	-	Chromium Plating (Electrodeposited)
TT-F-336	-	Filler, Wood, Paste
TT-L-57	-	Lacquer, Rubbing, Cear (For Wood Furniture)
PPP-B-1980	-	Boards; Bulletin and Control; Packaging and Packing Of

Federal Standard:

FED-STD-175	-	Adhesives, Methods of Testing

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.

FSC 7195

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

(Single copies of this specification and other Federal specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications:

MIL-A-8625 - Anodic Coatings, for Aluminum and Aluminum and Aluminum Alloys
MIL-C-15116 - Cork Sheet, Bulletin Board

See Supplement-1 for list of associated specification sheets.

Military Standard:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

Department of Commerce

PS-51 - Hardwood and Decorative Plywood
CS-251 - Hardboard

(Application for copies should be addressed to the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.)

American National Standards Institute (ANSI) Inc.

Z97.1 - Performance Specifications and Methods of Test for Transparent Safety Glazing Material Used in Buildings.

(Application for copies may be addressed to American National Standard Institute, 1430 Broadway, New York, NY 10018.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Specification sheets. The individual item requirements shall be as specified herein and in accordance with the applicable specification sheets.

3.2 Standard product. The bulletin board covered herein shall be a current standard product of the manufacturer, except for any changes necessary to meet specification requirements.

3.3 Materials. Materials shall conform to the applicable specifications, standards and requirements specified herein. Materials not definitely specified shall be of the quality used by the manufacturer in commercial bulletin boards.

3.3.1 Metal binders. Metal binders shall be minimum 0.040 inch thick stainless steel or carbon steel, or minimum 0.060 inch thick temper T4 or T5, compositions 6061 or 6063, aluminum alloy.

3.3.2 Wood. The wood shall be kiln-dried without brashness, case-hardening or honeycombing, to a moisture content of from 5 to 9 percent at time of fabrication. The wood shall be plain or quarter sawn. The wood components shall be free from defects, except: (1) Sound, tight knots not exceeding 1/4 inch in greatest dimension and not less than 10 inches apart, (2) Sap stain or discoloration, provided that no more than two such defects appear in any one table; (3) Not more than two wormholes, 1/16 inch or less in diameter, provided that they are in a concealed surface. Slope of grain shall not exceed 1 inch in 10 inches on any one surface of a part. The wood shall be any of the following species except that only one specie shall be used in the fabrication of any single frame.

Oak	Cherry
Sweet Gum	Swientinia or Khaya Mahogany
Walnut	Maple
Beech	Pecan
Birch	

3.3.3 Plywood. Plywood shall be 5 ply, type II of PS-51, or better. The face plys shall be grade 1 or 2 veneers.

3.3.4 Felt. Felt shall conform to type III of C-F-206.

3.3.5 Cork. The cork shall conform to type I or type II, 1/8 inch thick, tan color of MIL-C-15116.

3.3.6 Hardboard. The hardboard shall conform to tempered or tempered service, 1/8 inch thick of CS-251.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

3.3.7 Glass. Glass shall be 3/16 inch thick, transparent, tempered glass conforming to ANSI Z97.1. The glass shall be marked as specified in ANSI Z97.1.

3.3.8 Locks and keys. Locks shall be of the disk tumbler type. Each lock shall be provided with two keys. Each key shall operate the lock without binding.

3.4 Construction. The bulletin boards shall be as specified in the applicable specification sheet and as specified herein. A tolerance of ± 1/8 inch shall be permitted on overall dimensions. Unless otherwise specified on the applicable specification sheet, each board shall be provided with three hangers.

3.4.1 Posting boards. Posting boards shall be of the type specified in the specification sheet. Unless otherwise specified on the specification sheet, posting board shall be fabricated of one piece of material. Cork posting boards shall consist of the cork sheet specified in 3.3.5 glued to the hardboard specified in 3.3.6. The boards shall not delaminate when tested as specified in 4.2.1.1.

3.4.2 Frames. Frames for posting boards and glass inclosures shall be fabricated of the material specified in the specification sheet. Each side of the frame shall be made of a single piece of material. Frame corners shall be mitered. Gap between sides shall not exceed 0.015 inch. Frames for posting board shall inclose the posting surface. Frames for inclosed boards shall inclose the glass specified in 3.3.7 and shall be provided with a flush mounted lock and keys specified in 3.3.8. The glass inclosures shall not sag or bind.

3.4.2.1 Metal frame. The metal frame shall be fabricated of 1/2 inch wide material specified in 3.3.1. Aluminum frames shall be reinforced at the corners by angles. Steel frames shall be welded or bazed.

3.4.2.2 Wood frame. Wood frames shall be fabricated of 1 1/2 ± 1/16-inch by 3/4-inch thick wood specified in 3.3.2. Frame corners shall be glued and reinforced with corrugated fasteners.

3.5 Finish.

3.5.1 Metal finishes. Stainless steel shall have a No. 4 commercial polish. Carbon steel shall be chromium plated in accordance with class 1, type 1 of QQ-C-320. Aluminum shall have a type 1, class 1 coating in accordance with MIL-A-8625. Hardware shall be finished to resist corrosion.

3.5.2 Wood and plywood finishes.

3.5.2.1 Preparation. Prior to finishing, all exposed surfaces shall have been thoroughly sanded smooth and shall be free of gouges or tool marks. Glue size may be used before sanding. The surface shall be cleaned immediately before application of finish.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

3.5.2.2 Application. Plywood shall be given two coats of white varnish. Oak and sweetgum shall be stained a light oak (see 6.3). Other woods shall be stained a walnut (see 6.3). Filler shall be applied to open grain woods. Clear lacquer shall be applied.

3.6 Marking. The bulletin board shall be legibly and permanently marked with the manufacturer's name, trademark or trade name.

3.7 Workmanship. Sharp corners, burrs, slivers, and splinters shall be removed. The felt shall be clean and free of wrinkles and raw edges. Varnished surfaces shall be dry, uniform, and shall be free of blisters, runs, peels, flakes, cracks, wrinkles, finger marks, scratches, or imbedded foreign matter. Posting boards shall not be loose in the frame.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.2.1.1 Component testing. Prior to assembly, the cork-hardboard laminate shall be tested in accordance with method 2021, procedure A of FED-STD-175. The lot shall be all cork-hardboard laminate manufactured under the same conditions offered for inspection at one time. The sample unit shall be one 6 inch square panel. The inspection level shall be S-1. Any delamination shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

4.2.2 End item inspection The lot shall be all bulletin board of one description offered for inspection at one time. The sample unit shall be one complete bulletin board.

4.2.2.1 Visual examination. Examination shall be made of the bulletin boards for defects set forth in table I. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE I. Visual defects

Examine	Defect	Classification Major	Minor
Finish			
Wood and plywood	Burr, sliver, or splinter		X
	Tacky, blistered, peeling, flaky, sag, run, wrinkle, finger mark, scratch or imbedded foreign matter		X
	Wrong color		X
	Area of thin or no coating		X
	Open grain wood not filled		X
Metal	Not finished as specified	X	
Frames	Not constructed as specified	X	
	More than one species used in a frame (as applicable)		X
Glass inclosure (when applicable)	Binds or sags		X
	Fastener missing	X	
	Loose or uneven joint	X	
	Posting board loose in frame	X	
	Hanger missing (as applicable)	X	
	Not color specified		X
	Raw edge, wrinkle not clean		X
Identification marking	Missing, illegible, incomplete		X

4.2.2.2 Dimensional examination. Examination shall be made of the end item for defects in dimensions. Any dimension not within tolerances specified shall be classified as a defect. The inspection level shall be S-2 and the AQL 4.0, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

4.2.2.3 Inspection of preparation for delivery. Packaging, packing, and marking shall be inspected in accordance with the quality assurance provisions of PPP-B-1980.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking. Bulletin boards shall be packaged, packed and marked for levels A, B, and C in accordance with PPP-B-1980 (see 6.2).

6. NOTES

6.1 Intended use. Bulletin boards covered by this specification are intended to be wall or stand mounted and used for the display of visual materials.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number and date of this specification
(b) Part number required (see specification sheet)
(c) Level of packaging and packing and marking required (see 5.1)

6.3 Standard color panels. Sample panels of the standard colors of wood finish are obtainable without charge from the Business Service Center, Federal Supply Service, General Services Administration.

6.4 Supersession data. Federal specifications AA-B-00790 and AA-B-00800A have been included in this specification and associated specification sheets as follows:

Superseded specification		Part number
AA-B-00790	Type I	AAB1796/2-1A
	Type II	AAB1796/2-1
AA-B-00800	Class 1	
	Size 1	AAB1976/4-1
	Size 2	AAB1976/4-2
	Size 3	AAB1976/4-3
	Class 2	
	Size 1	AAB1976/1-1
	Size 2	AAB1976/1-2
	Size 3	AAB1976/1-3

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

6.5 Definitions. The terms length and width are used for overall dimension in the specification sheets to distinguish two dimensions in a flat plane. Bulletin Boards, without glass enclosures, may be mounted with either the length or width in a vertical position.

Custodians:

Army - GL
Air Force - 84

User activity:

Navy - YD

Preparing activity:

Army - GL

Civil Agency Coordinating Activities:

GSA - FSS

Project No. 7195-0077

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 30 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.