DD-S-50C
April 23, 1973
SUPERSEDING
Int. Fed. Spec. DD-S-0050B(GSA-FSS)
September 23, 1970

FEDERAL SPECIFICATION

SALT AND PEPPER SHAKERS, SUGAR DISPENSERS (MOISTURE RESISTANT)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers moisture-resistant salt and pepper shakers and sugar dispensers with glass bodies and plastic tops.

1.2 Classification. Salt and pepper shakers and sugar dispensers shall be of the following types, as specified (see 6.2):

Type I - Salt and pepper shaker, 3-ounce.

Type II - Dispenser, sugar, 9-ounce.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

EE-S-631 - Spices; Ground and Whole.
SS-S-31 - Salt, Table.
JJJ-S-791 - Sugar, Refined and Brown; Beet or Cane.
PPP-B-636 - Boxes, Shipping, Fiberboard.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.

FSC 7350

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:42Z
Check the source to verify that this is the current version before use.

Laws and Regulations:

21 CFR 121.2501 - Food Additives Resulting From Contact With Containers or Equipment and Food Additives Otherwise Affecting Food; Olefin polymers.

(The Code of Federal Regulations (CFR) and Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal Agency responsible for issuance thereof.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies shall be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N. W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies shall be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Materials.

3.1.1 Glass. The shaker and dispenser bodies shall be made from either a lime, borosilicate, or lead-flint colorless glass.

3.1.2 Plastic. Shaker and dispenser tops made of plastic under this specification shall be certified by the contractor to conform to 21 CFR 121.2501. Plastic tops shall be free from objectionable odor when tested as specified in 4.4.2.

3.3.1 Elastomer. The elastomer material shall be suitable for sealing the shaker against ingress of moisture. (see 3.4 and 4.4.1).

3.2 Design, construction.

3.2.1 Type I. The type I salt and pepper shaker shall be constructed of a glass body and fitted with a plastic top. The body and top shall be threaded so that they may be attached or detached by manual pressure. The top shall be either hinged containing an elastomer seal, or plain containing a moisture control element at the manufacturer's option. The size and number of dispensing holes in the top shall be at the manufacturer's option and the same design top shall be used for dispensing either salt or pepper.

3.2.1.1 Capacity. The capacity of the type I salt and pepper shaker shall be three ounces, plus or minus 1/2 ounce.

3.2.2 Type II. The type II sugar dispenser shall be constructed of a glass body, fitted with a plastic self closing top. The body and top shall be threaded so that they may be attached or detached by manual pressure. The top shall be designed with a handle, a hinge and a stainless steel spring so that the top may be opened with finger pressure and when pressure is released, the top shall return to a closed position completely covering the dispensing hole. The top shall be constructed with two removable elastomer gaskets, one to completely seal the dispensing hole, and the other to completely seal the outer ridge, when the top is in a closed position. The top shall have one dispensing hole, 7/16 $\pm$ 1/16 inch diameter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:42Z
Check the source to verify that this is the current version before use.

3.2.2.1 Capacity. The capacity of the type II dispenser shall be 9 ounces plus or minus 1/2 ounce.

3.3 Color. The salt and pepper and the sugar dispenser top shall be available in two colors, red and white, as specified (see 6.2).

3.4 Moisture resistance. Salt, pepper, and sugar shall pour freely when the shakers and dispensers are tested according to 4.4.1.

3.5 Finish.

3.5.1 Glass. All surfaces and edges shall be smoothly finished.

3.5.2 Plastics. All plastic parts shall be free of mars, blemishes, and rough edges. All holes shall be completely cleaned of flash and fins.

3.6 Workmanship. The glass shakers and dispenser bodies shall be free from cracks, chips, blisters, stones, and sharp edges. All glass, plastic threaded, and push-fit members shall fit properly and shall be capable of being attached and detached with normal pressure. All moving parts shall work freely and smoothly.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Lot. Unless otherwise specified (see 6.2), a lot shall consist of all salt and pepper shakers and sugar dispensers of the same type submitted for inspection at the same time.

4.2.2 Visual examination of end item. Sampling for this examination shall be according to level S-3 in MIL-STD-105. The Acceptable Quality Levels (AQL's) for defects listed in table I shall be 2.5 percent for major defects and 4.0 percent for minor defects, expressed in terms of defects per hundred units.

4.2.3 Sampling for tests. Sampling for tests shall be in accordance with level S-2 in MIL-STD-105. The AQL for tests shall be 6.5 percent, expressed in terms of defects per hundred units.

4.3 Examination.

4.3.1 End item. Salt and pepper shakers and sugar dispensers selected in accordance with 4.2.2 shall be examined for defects listed in table I.

TABLE I. Classification of defects, end item

Defects	Major	Minor
Type not as specified.	X	
Nicks, chips or cracks in glass bodies.	X	
Sharp corners or edges in glass bodies.	X	
Plastic parts with flashes or fins.	X	
Tops bent or deformed; do not fit shaker bodies properly.	X	
Hinged tops do not move freely and smoothly.		X
Damage or defects not affecting function or serviceability.		X
Damage or defects affecting function or serviceability.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:42Z
Check the source to verify that this is the current version before use.

4.3.2 Inspection of preparation for delivery requirements. An inspection shall be made to determine that the packaging, packing and marking comply with the requirements in section 5 of this specification. Defects shall be scored in accordance with table II. For examination of interior packaging the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to the closing operation. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an AQL of 4.0 defects per hundred units.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling. Distortion of container.
Contents (exterior and interior container)	Number per container is more or less than required. Net weight exceeds requirements.

4.4 Tests.

4.4.1 Moisture resistance. Samples shall be tested for resistance to moisture as specified in 4.4.1.1 and 4.4.1.2.

4.4.1.1 Conditioning of samples. Type I shakers shall be filled 3/4 full with table salt conforming to SS-S-31 or 3/4 full of pepper conforming to type II of EE-S-631. The type II dispenser shall be filled 3/4 full of sugar conforming to type Ia of JJJ-S-791. The shakers and dispensers shall then be placed in a vessel, such as a desiccator, kept at 68 ± 2°F., and containing a suitable solution to provide a relative humidity of 90 percent minimum. Samples shall be held in the closed desiccator for four hours.

4.4.1.2 Method of test.

4.4.1.2.1 Type I shakers shall then be shaken manually, in a inverted position for 10 cycles onto paper (colored black for salt, colored white for pepper) to determine compliance with 3.4.

4.4.1.2.2 Type II dispenser shall be manually turned in a semi-inverted position for one cycle onto a piece of paper (colored black) to determine compliance with 3.4.

4.4.2 Odor. Plastic tops of the sample units to be tested shall be placed in a clean, dry glass container approximately 4 to 6 times the volume of the items to be tested. Close the container, place in a circulating air oven, maintaining a temperature of 125° ± 5°F. for 4 ± 1/4 hours. The container shall be then removed from the oven and opened, and immediately checked for odor. The presence of a strong odor or disagreeable chemical odor shall constitute failure of the test (see 3.1.2).

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Salt and pepper shakers. Unless otherwise specified (see 6.2), 72 shakers shall be packaged in a close fitting box conforming to PPP-B-636, class weather resistant, Grade V3C. Each box shall have inserted, sets of slotted partitions so designed as to provide cells for each shaker. The partitions shall be made of the same material used in the construction of the box. Each box shall be closed and waterproof sealed with tape in accordance with the appendix to the box specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:42Z
Check the source to verify that this is the current version before use.

5.1.1.2 Sugar dispensers. Unless otherwise specified (see 6.2), twelve dispensers shall be packaged in a close-fitting box conforming to PPP-B-636 class weather resistant, Grade V3C. Each box shall have inserted, sets of slotted partitions so designed as to provide cells for each dispenser. The partitions shall be made of the same material used in the construction of the box. Each box shall be closed and waterproof sealed with tape in accordance with the appendix of the box specification.

5.1.2 Level B (Civil Agencies). No unit packaging required.

5.1.3 Level C. The shakers and dispensers in quantities as specified (see 6.2) shall be packaged to afford protection against damage and deterioration from the supplier to the initial destination. The supplier may use his commercial practice when it meets the above requirements.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Shakers and dispensers, packaged as specified in 5.1, and in quantities as specified (see 6.2), shall be packed in a close fitting box conforming to PPP-B-636, V3C, style CSSC-L. Each box shall be closed, waterproofed, and reinforced in accordance with the appendix to PPP-B-636.

5.2.2 Level B.

5.2.2.1 Salt and pepper shakers. Seventy-two shakers shall be packed in a close fitting box conforming to PPP-B-636, type CF or SF, class Domestic. Each box shall have inserted, sets of slotted partitions so designed as to provide cells for each shaker. The partitions shall be made of the same material used in the construction of the box. Closure shall be in accordance with the appendix to the box specification.

5.2.2.2 Sugar dispensers. Twelve dispensers shall be packed in a close-fitting box conforming to PPP-B-636, type CF or SF, class Domestic. Each box shall have inserted, sets of slotted partitions so designed as to provide cells for each dispenser. The partition shall be made of the same material used in the construction of the box. Closure shall be in accordance with the appendix to the box specification.

5.2.3 Level C. The shakers or dispensers shall be packed to insure carrier acceptance and safe delivery to destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Marking.

5.3.1 Civil agencies. In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military activities. In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with MIL-STD-129.

5.3.3 Special marking. Each shipping container shall have fragile marking applied in accordance with the applicable standards referenced in 5.3.1 and 5.3.2. In addition, the top of each container shall be plainly marked in capital letters not less than three-quarters of an inch in height as follows:

GLASS
HANDLE WITH CARE

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:42Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The salt and pepper shakers and sugar dispensers are intended for use in dispensing salt, pepper, and sugar in normal and humid environments.

6.2 Ordering data. Purchasers should select the preferred option permitted herein and include the following information in procurement documents:

(a) Title, number and date of this specification.
(b) Type required (see 1.2).
(c) Color of plastic top for type I and type II, as applicable (see 3.3).
(d) Size of lot, if different from 4.2.1.
(e) Selection of applicable level of packaging and packing required (see 5.1 and 5.2).
(f) Quantities to be supplied for level A packaging (see 5.1.1.1 and 5.1.1.2).
(g) Quantities to be supplied for level C packaging (see 5.1.3).
(h) Quantities to be supplied for level A packing (see 5.2.1).

MILITARY CUSTODIANS:

Army - GL
Navy - SA

Review activities:

Army - MD
Navy - MS, MC

User activity:

Navy - CG

Preparing activity:

GSA-FSS

Civil Agency Coordinating Activities:

GSA-FSS
USDA-AFS
VA-DMS

Orders for this publication are to be placed with the General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:42Z
Check the source to verify that this is the current version before use.