INCH POUND

MIL-DTL-12875C
3 March 2026
SUPERSEDING
MIL-S-12875B
4 March 1969

DETAIL SPECIFICATION

SHEET, PERFORATED, METAL

Inactive for new design after 16 June 1997

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers four types of metal perforated sheets.

1.2 Classification. The sheets covered by this specification and the respective base sheet specification may be as specified (see 6.2) and are as follows:

Type I - Brass:
Class A - ASTM-B36/B36M, ASTM-B121/B121M
Class B - QQ-B-639

Type II - Aluminum Alloy:
Class A - Alloy 3003 per ASTM-B209/B209M
Class B - Alloy 5052 per SAE-AMS4015, SAE-AMS4016, SAE-AMS4017, ASTM-B209/B209M

Type VI - Nickel Copper: QQ-N-281

Type VII - Steel, Sheet and Strip, Low Carbon
Class A - Hot rolled: ASTM-A659/A659M, ASTM-A1011/A1011M
Class B - Cold rolled: ASTM-A109/109M, ASTM-A794/A794M, ASTM-A1008/A1008M

2. APPLICABLE DOCUMENTS

2. 1 General. The documents listed in this section are specified in section 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

Comments, suggestions, or questions on this document should be addressed to DLA Troop Support – Construction and Equipment (C&E) (ATTN: Code FCSB), 700 Robbins Avenue Philadelphia, PA 19111-5096 or e-mail to CE_Standardization@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 9515

DISTRIBUTION STATEMENT A. Approved for public release; distribution unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:27Z
Check the source to verify that this is the current version before use.

FEDERAL SPECIFICATIONS

QQ-B-639 - Brass, Naval: Flat Products
QQ-N-281 - Nickel-Copper Alloy Bar, Rod, Plate, Sheet, Strip Wire, Forgings, and Structural And Special Shaped Sections

(Copies of these documents are available online at https://assist.dla.mil.)

2.3 Non-Government publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

AMERICAN SOCIETY FOR QUALITY (ASQ)

ASQ Z1.4 - Sampling Procedures and Tables for Inspection by Attributes

(Copies of this document are available from www.asq.org or the American Society for Quality, 611 East Wisconsin Avenue, Milwaukee, WI 53202.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-A109/A109M - Standard Specification for Steel, Strip, Carbon, (0.25 Maximum Percent, Cold-Rolled
ASTM-A659/A659M - Standard Specification for Commercial Steel (CS), Sheet and Strip, Carbon (0.16 Maximum to 0.25 Maximum Percent), Hot-Rolled
ASTM-A794/A794M - Standard Specification for Commercial (CS), Sheet, Carbon (0.16% Maximum to 0.25% Maximum), Cold-Rolled
ASTM-A1008/A1008M - Standard Specification for Steel, Sheet, Cold-Rolled, Carbon, Structural, High-Strength Low-Alloy, High-Strength Low-Alloy with Improved Formability, Required Hardness, Solution Hardened, and Bake Hardenable
ASTM-A1011/A1011M - Standard Specification for Steel, Sheet and Strip, Hot-Rolled, Carbon, Structural, High-Strength Low-Alloy with Improved Formability, and Ultra-High Strength
ASTM-B36/B36M - Standard Specification for Plate, Brass, Sheet, Strip, and Rolled Bar
ASTM-B121/B121M - Standard Specification for Plate, Leaded Brass, Sheet, Strip, and Rolled Bar
ASTM-B209/B209M - Standard Specification for Aluminum and Aluminum-Alloy Sheet and Plate

(Copies of this document are available from www.astm.org or the American Society for Testing and Materials, 100 Barr Harbor Drive, W. Conshohocken, PA 19428-2959.)

SAE INTERNATIONAL (SAE)

SAE-AMS4015 - Aluminum Alloy, Sheet and Plate 2.5Mg - 0.25Cr (5052-O) Annealed - UNS A95052
SAE-AMS4016 - Aluminum Alloy, Sheet and Plate 2.5Mg - 0.25Cr (5052-H32), Strained Hardened, Quarter Hard, and Stabilized - UNS A95052
SAE-AMS4017 - Aluminum Alloy, Sheet and Plate 2.5Mg - 0.25Cr (5052-H34), Strained Hardened, Half Hard, and Stabilized - UNS A95052

(Copies of these documents are available from www.sae.org or SAE International Customer Service, 400 Commonwealth Drive, Warrendale, PA 15096.)

2.4 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this specification and the references cited herein, the text of this specification takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:27Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material. All material used in the manufacture of the sheets shall conform to the specifications and applicable drawings forming a part of this specification (see 6.2).

3.2 Manufacture. The sheets shall be manufactured as specified on the applicable drawing and procurement document.

3.3 Perforations.

3.3.1 Size and arrangement. The size and arrangement of the perforations shall be as specified on the applicable drawing or procurement document.

3.3.2 Imperfections. The perforated sheets shall be kept in the same condition in which the unperforated sheets were received (see 3.5).

3.4 Unperforated sheet.

3.4.1 Size. The size of the sheets shall be as specified in the material specification (see 2.1) or procurement document. Tolerances in sizes allowed in the material specifications shall apply to the perforated sheets furnished under this specification.

3.4.2 Thickness. The thickness of the unperforated sheet shall be as specified in the material specification and procurement document.

3.5 Workmanship. The perforated sheets shall be free from foreign matter (dirt, oil or grease) and damage such as cracks, or deformation which could affect their use.

4. VERIFICATION

4.1 Conformance inspection.

4.1.1 Lot. A lot shall consist of the perforated sheets produced by one manufacturer, at one plant, from the same materials, under essentially the same manufacturing conditions. Howerver, no more than one lot of unperforated sheets shall be represented in any one lot of finished perforated sheets.

4.1.2 Sampling for examination. Unless otherwise specified, sampling shall be conducted in accordance with ASQ-Z1.4.

4.1.3 Inspection procedure.

4.1.3.1 For examination. Unless otherwise specified, sample perforated sheets shall be examined in accordance with the classification of defects in table I and ASQ-Z1.4.

TABLE I. Classification of defects, sheet, perforated, metal (dwg as specified (see 6.2)).

Categories	Defects
Critical:	None defined
Major:	
101	Perforations missing, incomplete, or wrong size
102	Perforations incorrectly located
103	Sheet size incorrect
104	Sheet thickness incorrect
105	Burrs or rough edges
106	Workmanship (see 3.5)
Minor:	
201	Protective finish missing (when applicable)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:27Z
Check the source to verify that this is the current version before use.

5. PACKAGING.

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from then managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The metal perforated sheets are for use in the manufacture of canisters, grills, strainers and similar items.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of the specification.
b. Title, number and date of the applicable drawing.
c. Size and thickness of unperforated sheet if not on drawing.
d. Type and class sheet required (see 1.2).
e. Packaging requirements (see 5.1).

6.3 Subject term (key word) listing.

Aluminum
Brass
Nickel Copper

6.4 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - EA
Navy - SH
DLA - CQ

Preparing activity:
DLA - CQ

(Project 9515-2026-002)

Review activities:
Army - MI, MR
Navy - AS, OS

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:27Z
Check the source to verify that this is the current version before use.