INCH-POUND


MIL-PRF-12883/10E
28 June 1996
SUPERSEDING
MIL-S-12883/10D
11 January 1972

PERFORMANCE SPECIFICATION SHEET

SOCKETS AND ACCESSORIES FOR PLUG-IN ELECTRONIC COMPONENTS (ELECTRON TUBE, BOTTOM MOUNTING, SADDLE TYPE WITHOUT SHIELD BASE, 7 CONTACT, RADIAL)

This specification is approved for use by all Departments and agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-PRF-12883.



Inches	mm	Inches	mm	Inches	mm	Inches	mm
.002	0.05	.031	.79	.125	3.18	.620	15.75
.005	0.13	.043	1.09	.188	4.78	.750	19.05
.010	0.25	.065	1.65	.375	9.53	.812	20.62
.014	0.36	.094	2.39	.406	10.31	.875	22.23
.016	0.41	.109	2.77	.438	11.13	1.125	28.58

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.016 inch (0.41 mm) and ±1/2° on angles.
4. Seven contact cavities equally spaced throughout 270° of arc, and each cavity located within 1/2° of true position, shall be established along the pin circle.
5. Each contact tab shall have either 1 wire hole of .040 inch (1.02 mm) minimum width and .125 inch (3.18 mm) minimum length, or two holes of .040 inch (1.02 mm) minimum width and .075 inch (1.91 mm) minimum length. The hole or holes, shall lie on the longitudinal centerline of the contact tab within ±.008 inch (0.20 mm).
6. The design of bosses and the shape of barrier, when used, are optional. When present, barriers shall have a maximum height of .062 inch (1.57 mm).
7. Clearance between the cavity wall and the contact, with the contact in any position, shall be no greater than .018 inch (0.46 mm).
8. Marking shall be at any convenient visible location.
9. Material thickness of mounting flange shall be measured in an area where burring or dishing of the mounting hole is not present.

FIGURE 1. Socket configuration.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:31Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configurations: See figure 1, and table I.

Reference material: (see 3.1.1 of MIL-PRF-12883).

Insulating material: Ceramic, SDG-F, GDI-30 or MIL-M-14, type MFE.

Contact cavities: One shape only; D-shaped or circular, at option of the manufacturer.

Float: With a pin of .041 inch (1.04 mm) diameter and .271 inch (6.88 mm) minimum length fully inserted in a socket contact, the contact shall be capable of free movement (float) within the contact cavity.

Saddle: The method of attaching the saddle to the insulator body, and the shape of the saddle where attachment is effected, are optional.

Electrical

Insulation resistance: 1,000 megohms minimum. Test pin diameter: .040 ±.001 inch (1.02 ±.03 mm).

Dielectric withstanding voltage:

Sea level: Test voltage: 2,000 volts root mean square (rms). Test pin diameter: .040 ±.001 inch (1.02 ±.03 mm).

High altitude: Test voltage: 660 volts rms. Test pin diameter: .040 ±.001 inch (1.02 ±.03 mm).

Contact resistance:

Average for all contacts: 0.015 ohm maximum.

Individual contacts: 0.03 ohm maximum.

Continuity test circuit: With the header test-gage(s) inserted into the socket(s) under test, the pins of the test-gage(s) and the contacts of the sockets(s) under test, shall result in a series circuit. The header shall be the one used for electron tube 6AU6WB.

Mechanical

Insertion and withdrawal force:

Initial insertion force: 15 pounds (66.72 newton) maximum.

Average insertion force: 12 pounds (53.38 newton) maximum.

Initial withdrawal force: 4 pounds (17.79 newton) minimum, 12 pounds (53.38 newton) maximum.

Vibration: The test-gage shall be an approved electron-tube type 6AU6WB, in accordance with MIL-E-1/952.

Durability: After the durability test, the withdrawal force shall be 2 pounds (8.90 newton) minimum.

Static load: 40 pounds (177.93 newton).

The part shall be designed to operate at the following conditions:

Environmental

Operating temperature: See table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:31Z
Check the source to verify that this is the current version before use.

TABLE I. Dash number and characteristics.

Dash number	Operating temperature °C	Insulating material	Old type designator 1/
-01	200	Ceramic	TS102C02 (2-way)
-02	100	SDG-F, GDI-30F	TS102P02 (1-way)
-03	100	MIL-M-14, type MFE	TS102P02 (2-way)

1/ 1-way replacement: The new item (designated by military part number) will replace the old item (formerly designated by type designator); however, the old item will not replace the new item.
2-way replacement: The new items are interchangeable; i.e., the new item will replace the old item, and the old item will replace the new item.

Ratings (absolute maximum):

Voltage:
Sea level: 500 volts rms.
50,000 feet (15240 meters): 225 volts rms.

Current: 1 amperes.

Operating temperature: See table I.

Test gage details: See table II and MIL-PRF-12883 appendix.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:31Z
Check the source to verify that this is the current version before use.


TABLE II. Test gage details. 1/ 2/

Inspection	A Pin length (mm)	B Pin dia (mm)	M Test-end dia (mm)	C Pin-circle dia (mm)	N Probe-end dia (mm)	D Gage dia max (mm)	No. of pins	Total weight of gage ounces (grams) (±5%)
Insertion and withdrawal force------	.276 ±.005 (7.01 ±0.13)	.0390 ±.0001 (0.991 ±0.003)	---	.3750 (9.525) basic	---	11/16 (17.46)	7	---
Contact resistance-	.276 ±.005 (7.01 ±0.13)	.0390 ±.0001 (0.991 ±0.003)	---	.3750 (9.525) basic	---	11/16 (17.46)	7	---
Contact retention--	.276 ±.005 (7.01 ±0.13)	--- .0410 ±.0001 (1.041 ±0.003)	.0390 ±.0001 (0.991 ±0.003) ---	---	.0410 ±.0001 (1.041 ±0.003)	---	---	3 (85.05)
Durability---	.276 ±.005 (7.01 ±0.13)			.3750 (9.525) basic	---	11/16 (17.46)	7	---

1/ Dimensions are in inches.
2/ Metric equivalents are given for general information only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:31Z
Check the source to verify that this is the current version before use.

Mating-base dimensions: Sockets shall accommodate plug-in components having mating-base dimensions as shown on figure 2.



Inch	mm
.002	0.05
.005	0.13
.040	1.02
.187	4.75
.281	7.14
.375	9.53

NOTES
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.

FIGURE 2. Mating-base dimensions.

Part or identifying number (PIN): The PIN shall consist of the basic number of this specification sheet and the dash number from table I.

Example



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:31Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodian:
ARMY - CR
Navy - EC
Air Force - 85

Review activity:
Army - AT, AV, ME, MI, AR
Air Force - 17, 19, 70, 80
Navy - AS, CG, OS, MC, SH

Preparing activity:
DLA - ES

(Project 5935-4015-05)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:31Z
Check the source to verify that this is the current version before use.