INCH-POUND


MIL-PRF-12883/40E
28 June 1996
SUPERSEDING
MIL-S-12883/40D
20 December 1989

PERFORMANCE SPECIFICATION SHEET

SOCKETS, PLUG-IN ELECTRONIC COMPONENTS
FOR RELAYS, 4-POLE, 10 AMPERES
(MIL-R-6106, MIL-R-83536, MIL-R-83726, AND MS27709)

This specification is approved for use by all Departments and agencies of the Department of Defense.


The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-PRF-12883.



MATING FACE
-01, -05, -07, -11, -13, -17, -19, and -23


FIGURE 1. Socket configurations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:33Z
Check the source to verify that this is the current version before use.




BOTTOM VIEW


-01, -05, -07, -11, -13, -17, -19, AND -23




MATING FACE
-02, -14
-08, -20



MATING FACE
-03, -15
-09, -21




MATING FACE
-04, -16
-10, -22




MATING FACE
-06, -18
-12, -24

FIGURE 1. Socket configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:33Z
Check the source to verify that this is the current version before use.






Dimensions

Dash number	A (mm)	B max (mm)
-01 thru -12	.140 - .135 (3.56 - 3.43)	1.130 (28.70)
-13 thru -24	.093 (2.36)	.89 (2.26)

FIGURE 1. Socket configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:33Z
Check the source to verify that this is the current version before use.




RECOMMENDED MOUNTING DIMENSIONS

Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
.005	0.13	.09	2.3	.164	4.17	.400	10.16	1.025	26.04
.010	0.25	.093	2.36	.200	5.08	.403	10.24	1.035	26.29
.035	0.89	.100	2.54	.220	5.59	.517	13.13	1.075	27.31
.05	1.3	.112	2.84	.233	5.92	.600	15.24	1.110	28.19
.06	1.5	.135	3.43	.300	7.62	.625	15.88	1.130	28.70
065	1.65	140	3.56	.312	6.92	.89	22.6	1.406	35.71
.078	1.98	.148	3.76	.335	8.51	.100	25.4	1.71	43.4
		.150	3.81	.370	9.40				


NOTES
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified tolerances are ±.005 inch (0.13 mm) for three place decimals and ±.01 inch (0.25 mm) for two place decimals.
4. Point of electrical contact engagement, from mating face of socket insulator to the socket contact.
5. Marking shall be characters which are molded .035 inch (0.89 mm) minimum. Ink marking optional (see MIL-STD-1285).
6. Keyway is shown for loose stud mounting configuration only (see figure 2 detail A).
7. For mating relay (see table I).
8. Configuration mounting (see figures 2, 3, and table I).
9. Shape is optional
10. .370 inch (9.40 mm) min. for -01 through -12 and .233 inch (5.92 mm) min. for -13 through -24.

FIGURE 1. Socket configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:33Z
Check the source to verify that this is the current version before use.




BOTTOM MOUNT (TYP)




TOP MOUNT (TYP)

FIGURE 2. Loose stud mounting (-01 through -06 and -13 through -18).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:33Z
Check the source to verify that this is the current version before use.



LOOSE STUD



DETAIL A

SOCKET BODY MOUNTING
HOLE AND MATING STUD


Inches	mm	Inches	mm	Inches	mm
.003	0.08	.93	2.36	.190	4.83
.005	0.13	.100	2.54	.220	5.59
.006	0.15	.112	2.84	.245	6.22
.010	0.25	.116	2.95	.270	6.86
.030	0.76	.125	3.18	.290	7.37
.032	0.81	.140	3.56	.318	8.08
.038	0.97	.150	3.81	.350	8.89
.085	2.15				

NOTES


1. Dimensions are in inches.
2. Metric equivalents are for general information only.
3. Unless otherwise specified, tolerances are ±.005 inch (0.13 mm) for three place decimals and ±.01 inch (0.25 mm) for two place decimals.
4. The diameter for loose stud mating hole in the socket body shall be:
   for -01 through -06 diameter shall be .125 ±.003 inch (3.18 ±0.08 mm);
   for -13 through -18 diameter shall be .116 ±.003 inch (2.95 ±0.08 mm).
5. .318 ±.010 inch (8.08 ±0.25 mm) from top of socket flange to base of .112-40 UNC-2A thread for -01 through -06 and .290 ±.010 inch (7.37 ±0.25 mm) for -13 through -18.

FIGURE 2. Loose stud mounting (-01 through -06 and -13 through -18) - Continued.


Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:33Z
Check the source to verify that this is the current version before use.



TOP MOUNT (TYP)



BOTTOM MOUNT (TYP)



FIXED STUD

Inches	mm	Inches	mm
.005	0.13	.220	5.59
.010	0.25	.245	6.22
.093	2.36	.270	6.86
.112	2.84	.290	7.37
.125	3.18	.318	8.08
.190	4.83	.350	8.89

NOTES

1. Dimensions are in inches.
2. Metric equivalents are for general information only.
3. Unless otherwise specified, tolerances are ±.005 (0.13 mm) for three place decimals and ±.01 inch (0.25 mm for two place decimals.
4. .318 ±.010 inch (8.08 ±.25 mm) from, top of socket flange to base of .112-40 UNC-2A thread for -07 through -12 and .290 ±.010 inch (7.37 ±0.25 mm) for -19 through -24.

FIGURE 3. Fixed stud mounting (-07 through -12 and -19 through -24).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:33Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction: See figures 1, 2, 3, and table I.

Reference material: (see 3.1.1 of MIL-PRF-12883)

Insulator: Diallyl phthalate, in accordance with MIL-M-14, type SDG-F, any glass filled thermoplastic material in accordance with MIL-P-46179, or an approved equivalent material manufactured to a commonly accepted industry standard.

Color: Material color shall be optional providing that the color provides a contrasting background for the blue sealing grommet or blue color bands indicating rear release contacts.

Grommet: Silicon rubber in accordance with ZZ-R-765.

Mounting hardware: Corrosion resistant steel or steel with cadmium/chromate finish.

Electrical:

Insulation resistance: 1000 megohms minimum. Test pin diameter, size 16, .0620 ±.0010 inch (1.575 ±0.025 mm).

Dielectric withstanding voltage:

Sea level: Test voltage, 1500 V rms. Test pin diameter, size 16, .0620 ±0.0010 inch (1.575 ±0.025 mm).

High altitude (80,000 feet (24,384 meters)): Test voltage, 500 V rms. Test pin diameter, size 16 .0620 ±0.0010 inch (1.575 ±0.025 mm).

Contacts: Contacts shall be removable crimp type in accordance with MIL-C-39029/92, MIL-C-39029/5 (see table I), or approved equivalent contacts manufactured to a commonly accepted industry standard.

TABLE I. Dash numbers and configurations.

Dash number	Mounting style	Contact size		Number of contacts	Contact designation M39029	Mating relay
		Mating end	Wire barrel			
01	Loose stud (figure 2)	16	16	14	/5 - 116	M83536/15-022, /16-022, /16-031, 1/ MIL-R-83726/1, /2, /3, /4, /28, /29, /30, /31, MS27709-2
02	Loose stud (figure 2)	16	16	14	/5 - 116	M83536/17-002, /17-002, /17-005, /17-005
03	Loose stud (figure 2)	16	16	14	/5 - 116	To be determined.
04	Loose stud (figure 2)	16	16	14	/5 - 116	To be determined.
05	Loose stud (figure 2)	16	20 2/	14	/5 - 117	M83536/15-022, /16-022, /16-031, /16-022 1/ MIL-R-83726/1, /2, /3, /4, /28, /29, /30, /31 MS27709-2

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:33Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers and configurations.

Dash number	Mounting style	Contact size		Number of contacts	Contact designation M39029	Mating relay
		Mating end	Wire barrel			
06	Loose stud (figure 2)	16	16	16	/5 - 116	MS27745-2, -4, -5
07	Fixed stud (figure 3)	16	16	14	/5 - 116	M83536/15-022, /16-022, /16-031, /16-022 1/ MIL-R-83726/1, /2, /3, /4, /28, /29, /30, /31 MS27709-2
08	Fixed stud (figure 3)	16	16	14	/5 - 116	M83536/17-002, /17-002, /17-005,
09	Fixed stud (figure 3)	16	16	14	/5 - 116	To be determined.
10	Fixed stud (figure 3)	16	16	14	/5 - 116	To be determined.
11	Fixed stud (figure 3)	16	20 2/	14	/5 - 117	M83536/15-022, /16-022, /16-031, /16-022 1/ MIL-R-83726/1, /2, /3, /4, /28, /29, /30, /31 MS27709-2
12	Fixed stud (figure 3)	16	16	16	/5 - 116	MS27745-2, -4, -5
13	Loose stud (figure 2)	16	16	14	/92 - 533	M83536/15-022, /16-022, /16-031, /16-022 1/ MIL-R-83726/1, /2, /3, /4, /28, /29, /30, 30, /31 MS27709-2
14	Loose stud (figure 2)	16	16	14	/92 - 533	M83536/17-002, /17-002, /17-005
15	Loose stud (figure 2)	16	16	14	/92 - 533	To be determined.
16	Loose stud (figure 2)	16	16	14	/92 - 533	To be determined.
17	Loose stud (figure 2)	16	20 2/	14	/92 - 534	M83536/15-022, /16-022, /16-031, /16-022 1/ MIL-R-83726/1, /2, /3, /4, /28,/29, /30, /31 MS27709-2
18	Loose stud (figure 2)	16	16	16	/92 - 533	MS27745-2, -4, -5

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:33Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers and configurations.

Dash number	Mounting style	Contact size		Number of contacts	Contact designation M39029	Mating relay
		Mating end	Wire barrel			
19	Fixed stud (figure 3)	16	16	14	/92 - 533	M83536/15-022, /16-022, /16-031 1/MIL-R-83726/1, /2, /3, /4, /28, /29, /30, /31 MS27709-2
20	Fixed stud (figure 3)	16	16	14	/92 - 533	M83536/17-002, /17-005.
21	Fixed stud (figure 3)	16	16	14	/92 - 533	To be determined.
22	Fixed stud (figure 3)	16	16	14	/92 - 533	To be determined.
23	Fixed stud (figure 3)	16	20 2/	14	/92 - 534	M83536/15-022, /15-022, /16-022, /16-031 1/ MIL-R-83726/1, /2, /3, /4, /28, /29, /30, /31 MS27709-2
24	Fixed stud (figure 3)	16	16	16	/92 - 533	MS27745-2, -4, -5

1/ Applies to all plug-in type relays of these documents.
2/ CAUTION: Because of the wire barrel size of -05, -11, -17, and -23, current overload may be experienced at 10 amperes.

Environmental:

Temperature range: Operating temperature range -70°C to +125°C.

Wire sealing: A resilient grommet is permanently bonded to the wire entry face of the socket so as to provide moisture sealing capabilities (see figure 1). Wire sealing range shall be as specified in table II.

TABLE II. Wire sealing range.

Contact size	Wire sealing range (mm)
16-20	.040 min to .083 max (1.02 min to 2.11 max)
16-16	.065 min to .109 max (1.65 min to 2.77 max)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:33Z
Check the source to verify that this is the current version before use.

Mechanical:

Vibration (sinusoidal): In accordance with MIL-STD-202, method 204, test condition G, or an equivalent industry standard.

a. Except that the frequency range shall be varied logarithmically between the limits of 10 Hz and 3,000 Hz.

b. Except that the procedure of method 201 of MIL-STD-202 may be applied during 10 Hz to 55 Hz band of the vibration frequency range.

c. Qualified mating relay shall be used as a test gauge.

Vibration (random): In accordance with MIL-STD-1344, method 2005, test condition V, letter G, or an equivalent industry standard, with a test duration 15 minutes. The mating relay shall be used as the test gage.

Shock (mechanical): In accordance with MIL-STD-202, method 213, condition C, or an equivalent industry standard, except peak value shall be 200 g's.

Insertion and withdrawal forces: The insertion and withdrawal forces of the relay and socket shall be as specified as in table III.

TABLE III. Insertion and withdrawal forces.

M12883/40	-01 through -05, -07 through -11 -13 through -17, -19 through -23	-06, 012, -18, and -24
Insertion force (max)	26.25 lbf (116.77 newton)	30.0 lbf (133.45 newton)
Withdrawal force (min)	1.75 lbf (7.78 newton)	2.00 lbf (8.90 newton)
Insertion force (max) after 10 insertions and withdrawals, before vibration	25 lbf (111.21 newton)	30.0 lbf (133.45 newton)
Withdrawal force (min)	1.75 lbf (7.78 newton)	2.00 lbf (8.90 newton)
Insertion force (max) after vibration	14 lbf (62.28 newton)	26 lbf (115.65 newton)
Withdrawal force (min)	1.31 lbf (5.83 newton)	1.5 lbf (6.67 newton)

Mounting hardware: The mounting hardware shall allow mounting the socket above, or below the panel ochassis (see figures 2 and 3), and shall allow mounting and securing the relay to the socket without disturbing the mounted socket or access to the wiring side of the socket. The hardware shall provide the nominal spacing between socket surface and relay mounting flange, regardless of mounting configuration.

Supplied with relay socket:

6 each .112-40 self locking nuts (.206 max dia x .176 max height).

6 each .112 flat washers (.220 max O.D. x .018 max thick).

3 each .190-32 self locking nuts (.330 max dia x .190 max height).

3 each .190 flat washers (.360 max O.D. x.036 max thick).

3 each studs for loose mounting configuration only (see figure 2).

Fixed mounting studs: Studs shall be molded into the mounting flange of the socket and shall be designedo as to prevent rotation of the stud within the flange (see figure 3).

Contact installation tools: see table IV, approved equivalent industry standard tools may also be used where appropriate.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:33Z
Check the source to verify that this is the current version before use.

TABLE IV. Contact installation tools.

Nomenclature	Part or Identifying Number (PIN) (size 16 contacts)
Crimp tool	M22520/1-01, /7-01
Positioner	M22520/1-02, /7-03
Insertion/removal tool Wired Unwired	 M81969/14-03 M81969/30-06, /30-05

Torque: Relay socket and hardware shall be subjected to torque testing as specified in table V. Sockets hall be installed in mounting panel when test torque is applied. No visual evidence of physical damage shall be permitted. Torque shall be maintained for a reasonable period of time to insure stud, socket, and associated hardware have not been damaged (see table V).

TABLE V. Torque requirements (installed in panel conditions).

Thread size	Torque			
	Testing		Installation	
	Inch-pounds	Newton-meter	Inch-pounds	Newton-meter
.112-40	8 + 1 - 0	0.90 + .11 - 0	4 ±1	0.45 ±.11
.190-32	24 + 1 - 0	2.71 + .11 - 0	18 ±1	2.03 ±.11

Weight: Maximum weight of relay, socket, all contacts and all associated hardware shall be as specified in table VI.


TABLE VI. Weight.

Part designations M12883/40	Maximum weight	
	Pounds	Grams
-01 through -12 -13 through -24	.132 .100	60 45

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:33Z
Check the source to verify that this is the current version before use.

PIN: The PIN shall be marked on the socket body as shown in the example (see figure 1). The PIN shall consist of the basic number of this specification sheet and the dash number from table I.

Example



* For future acquisition of these sockets as of the effective date of revision D, 20 December 1989, parts identified with an "S: modifier shall be corrosion resisting steel (CRS), and parts without an "S" modifier shall be cadmium chromate finish. No mixing of hardware types shall be permitted.

Ordering data: Sockets without contacts may be ordered when so indicated in the ordering data (see MIL-PRF-12883). This applies only to original equipment manufacturers (OEM's) and subcontractors. All direct shipments to the government shall include all applicable contacts and mounting hardware. The PIN to be marked on the socket shall be as shown in the PIN example (see figure 1 and table I).

Revision letters are not used to denote changes due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:33Z
Check the source to verify that this is the current version before use.

The Government PIN, specified in table VII, supersedes the following commercial part numbers.

TABLE VII. Supersession and cross reference data.

Active Government PIN	Superseded manufacturers part number		
	CAGE 58982	CAGE 99699	CAGE F7913
M12883/40-01	RSL116079 AND -S	SE410-2001 AND -S	TBD
M12883/40-02	RSL116081 AND -S	SE410-2002 AND -S	TBD
M12883/40-03	RSL116083 AND -S	TBD	TBD
M12883/40-04	RSL116085 AND -S	TBD	TBD
M12883/40-05	RSL116087 AND -S	TBD	TBD
M12883/40-06	RSL116089 AND -S	TBD	TBD
M12883/40-07	RSL116051 AND -S	SE410-1001 AND -S	TBD
M12883/40-08	RSL116053 AND -S	SE410-1002 AND -S	TBD
M12883/40-09	RSL116055 AND -S	TBD	TBD
M12883/40-10	RSL116057 AND -S	TBD	TBD
M12883/40-11	RSL116059 AND -S	TBD	TBD
M12883/40-12	RSL116061 AND -S	TBD	TBD
M12883/40-13	RSE116661 AND -S	SME410-2001 AND -S	001585 301 07 A 1
M12883/40-14	RSE116663 AND -S	SME410-2002 AND -S	001585 302 07 A 1
M12883/40-15	RSE116665 AND -S	TBD	001585 304 07 A 1
M12883/40-16	RSE116667 AND -S	TBD	001585 303 07 A 1
M12883/40-17	RSE116669 AND -S	SME410-2005 AND -S	001585 301 07 A 2
M12883/40-18	RSE116671 AND -S	SME410-2001 AND -S	001585 305 07 A 1
M12883/40-19	RSE116673 AND -S	SME410-1001 AND -S	001585 301 06 A 1
M12883/40-20	RSE116675 AND -S	SME410-1002 AND -S	001585 302 06 A 1
M12883/40-21	RSE116677 AND -S	TBD	001585 304 06 A 1
M12883/40-22	RSE116679 AND -S	TBD	001585 303 06 A 1
M12883/40-23	RSE116681 AND -S	SME410-1005 AND -S	001585 301 06 A 2
M12883/40-24	RSE116683 AND -S	SMEL410-1001 AND -S	001585 305 06 A 1

CONCLUDING MATERIAL

Custodian:
ARMY - CR
NAVY - EC
Air Force - 85

Review activity:
Army - AR, AT, AV, ME
Navy - AS, MC, OS, SH
Air Force - 99

Preparing activity:
DLA - ES

(Project 5935-4015-07)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:33Z
Check the source to verify that this is the current version before use.