INCH-POUND
MIL-PRF-12883/40E
AMENDMENT 2
29 June 2000
SUPERSEDING
AMENDMENT 1
4 August 1999

PERFORMANCE SPECIFICATION SHEET

SOCKETS, PLUG-IN ELECTRONIC COMPONENTS,
FOR RELAYS, 4-POLE, 10 AMPERES
(MIL-R-6106, MIL-R-83536, MIL-R-83726, AND MS27709)

This amendment forms part of MIL-PRF-12883/40E, dated 28 June 1996, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

TITLE: Delete and substitute as shown above.

PAGE 6

Inch/mm table delete .93 and substitute .093.

PAGE 7

FIGURE 3, Fixed stud mounting (-07 through -12 and -19 through -24), Top mount (typ), mounting panel or chassis dimension: Delete ".093 max" and substitute ".125 max".

PAGES 8, 9, and 10

TABLE I: Delete and substitute:

TABLE I. Dash numbers and configurations.

Dash Number	Mounting style	Contact size		Number of contacts	Contact designation M39029	Mating relay
		Mating end	Wire barrel			
01	Loose stud (figure 2)	16	16	14	/5 - 116	M83536/15-022, /16-022, /16-031, 1/ M83726/1, /2, /3, /4, /28, /29, /30, /31, MS27709-2
02	Loose stud (figure 2)	16	16	14	/5 - 116	M83536/17-002, /17-005
03	Loose stud (figure 2)	16	16	14	/5 - 116	To be determined.

See footnotes at end of table.

AMSC N/A
FSG 5935
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:33Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers and configurations - Continued.

Dash Number	Mounting style	Contact size		Number of contacts	Contact designation M39029	Mating relay
		Mating end	Wire barrel			
04	Loose stud (figure 2)	16	16	14	/5 - 116	To be determined.
05	Loose stud (figure 2)	16	20 2/	14	/5 - 117	M83536/15-022, /16-022, /16-031, 1/ M83726/1, /2, /3, /4, /28, /29, /30, /31 MS27709-2
07	Fixed stud (figure 3)	16	16	14	/5 - 116	M83536/15-022, /16-022, /16-031, 1/ M83726/1, /2, /3, /4, /28, /29, /30, /31 MS27709-2
08	Fixed stud (figure 3)	16	16	14	/5 - 116	M83536/17-002, /17-005
09	Fixed stud (figure 3)	16	16	14	/5 - 116	To be determined.
10	Fixed stud (figure 3)	16	16	14	/5 - 116	To be determined.
11	Fixed stud (figure 3)	16	20 2/	14	/5 - 117	M83536/15-022, /16-022, /16-031, 1/ M83726/1, /2, /3, /4, /28, /29, /30, /31 MS27709-2
12	Fixed stud (figure 3)	16	16	16	/5 - 116	MS27745-2, -4, -5
13	Loose stud (figure 2)	16	16	14	/92 - 533	M83536/15-022, /16-022, /16-031, 1/ M83726/1, /2, /3, /4, /28, /29, /30, /31 MS27709-2
14	Loose stud (figure 2)	16	16	14	/92 - 533	M83536/17-002, /17-005
15	Loose stud (figure 2)	16	16	14	/92 - 533	To be determined.
16	Loose stud (figure 2)	16	16	14	/92 - 533	To be determined.
17	Loose stud (figure 2)	16	20 2/	14	/92 - 534	M83536/15-022, /16-022, /16-031, 1/ M83726/1, /2, /3, /4, /28,/29, /30, /31 MS27709-2
18	Loose stud (figure 2)	16	16	16	/92 - 533	MS27745-2, -4, -5
19	Fixed stud (figure 3)	16	16	14	/92 - 533	M83536/15-022, /16-022, /16-031 1/M83726/1, /2, /3, /4, /28, /29, /30, /31 MS27709-2

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:33Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers and configurations - Continued.

Dash Number	Mounting style	Contact size		Number of contacts	Contact designation M39029	Mating relay
		Mating end	Wire barrel			
20	Fixed stud (figure 3)	16	16	14	/92 - 533	M83536/17-002, /17-005
21	Fixed stud (figure 3)	16	16	14	/92 - 533	To be determined.

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:33Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers and configurations - *Continued.*

Dash number	Mounting style	Contact size		Number of contacts	Contact designation M39029	Mating relay
		Mating end	Wire barrel			
22	Fixed stud (figure 3)	16	16	14	/92 - 533	To be determined.
23	Fixed stud (figure 3)	16	20 2/	14	/92 - 534	M83536/15-022, /16-022, /16-031 1/ M83726/1, /2, /3, /4, /28, /29, /30, /31 MS27709-2
24	Fixed stud (figure 3)	16	16	16	/92 - 533	MS27745-2, -4, -5

1/ *Applies to all plug-in type relays of these documents.*
2/ CAUTION: Because of the wire barrel size of -05, -11, -17, and -23, current overload may be experienced at 10 amperes.

PAGE 11

Fixed mounting studs, delete designe~, substitute designated.

PAGE 12

Torque, second sentence, delete hall and substitute shall.

The margins of this amendment are marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AR, AT, AV
Navy - AS, MC, OS, SH
Air Force - 99

Preparing activity:
DLA - CC

(Project 5935-4285)

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:33Z
Check the source to verify that this is the current version before use.