INCH-POUND

MIL-DTL-371G
1 May 2019
SUPERSEDING
MIL-B-371F
15 May 1987

MILITARY SPECIFICATION

BRAID, TEXTILE, TUBULAR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for tubular textile braid and is intended to be used with various clothing items.

1.2 Classification. This specification covers the following braid Types and Classes.

1.2.1 Types.

Type I	- 1/8-inch diameter, with core
Type II	- 5/32-inch diameter, with core
Type III	- 3/16-inch wide, flat
Type IV	- 1/8-inch diameter, solid
Type V	- 3/16-inch diameter, solid
Type VI	- 1/8-inch diameter, solid (heavier weight)
Type VII	- 11/32-inch wide, flat
Type VIII	- 1/8-inch wide, flat
Type IX	- 1/8 to 3/16-inch wide, flat
Type X	- 1/8 to 3/16-inch wide, flat (higher strength)

Comments, suggestions, or questions on this document should be addressed to: ATTN: DLA Troop Support, 700 Robbins Avenue, Philadelphia, PA 19111-5096. Since contact information can change, verify the currency of the address information using Acquisition Streamlining and Standardization Information System (ASSIST) online database https://assist.dla.mil.

AMSC N/A FSC 8315

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:08Z
Check the source to verify that this is the current version before use.

1.2.2 Classes.

Class 1 - No finish
Class 2 - Water repellent treated
Class 3 - Water and mildew resistant treated
Class 4 - Deleted

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specification, standards, and handbooks. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract. The following specifications, standards, and handbooks form a part of this document to the extent specified herein.

2.2.2 Other Government documents, drawings, and specifications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation or contract.

ENVIRONMENTAL PROTECTION AGENCY

Federal Insecticide, Fungicide and Rodenticide Act (FIFRA)
(40 CFR Part 162) State Registration of Pesticide Products

Federal Insecticide, Fungicide and Rodenticide Act (FIFRA)
FIFRA as amended by the Food Quality Protection Act of 1996 and the
Pesticide Registration Improvement Act of 2003

(Copies of these documents are available online at https://www.epa.gov/pesticides.)

FEDERAL TRADE COMMISSION

Rules and Regulations Under the Textile Fiber Products Identification Act

(Copies of this document are available online at https://www.ftc.gov).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:08Z
Check the source to verify that this is the current version before use.

2.3 Non-Government publications. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract. The following documents form a part of this document to the extent specified herein.

AMERICAN ASSOCIATION OF TEXTILE CHEMISTS AND COLORISTS (AATCC)

AATCC Evaluation Procedure 1, Gray Scale for Color Change
AATCC Evaluation Procedure 2, Gray Scale for Staining
AATCC Evaluation Procedure 8, AATCC 9 Step Chromatic Transference Scale
AATCC Evaluation Procedure 9, Visual Assessment of Color Difference of Textiles
AATCC Test Method 8 - Colorfastness to Crocking: AATCC Crockmeter Method
AATCC Test Method 16.3 - Colorfastness to Light: Xenon
AATCC Test Method 20 - Fiber Analysis: Qualitative
AATCC Test Method 30 - Antifungal Activity, Assessment on Textiles Materials: Mildew and Rot Resistance of Textile Materials.
AATCC Test Method 61 - Colorfastness to Laundering: Accelerated
AATCC Test Method 70 - Water Repellency: Tumble Jar Dynamic Absorption Test
AATCC Test Method 132 - Colorfastness to Drycleaning

(Copies of these documents are available online at https://www.aatcc.org)

AMERICAN SOCIETY FOR QUALITY (ASQ)

ANSI/ASQ Z1.4 - Sampling Procedures and Tables for Inspection by Attributes

(Copies of this document are available online at https://asq.org)

ASTM INTERNATIONAL

ASTM D1776/D1776M - Standard Practice for Conditioning and Testing Textiles.
ASTM D3990 - Standard Terminology Relating to Fabric Defects.
ASTM D5430 - Standard Test Method for Visually Inspecting and Grading Fabrics.

(Copies of these documents are available online at https://www.astm.org)

PARACHUTE INDUSTRY ASSOCIATION (PIA)

PIA-Test Method-6016 - Strength and Elongation Breaking of Cordage; Non-Spliced Specimen Method.

(Copies of this document are available online at https://www.pia.com).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:08Z
Check the source to verify that this is the current version before use.

OTHER PUBLICATIONS

SDL ATLAS

Part Number 402985 – Slub/Knot Replica Set

(Replica set is available for purchase from SDL Atlas Customer Service, 1-803-329-2110.)

INFORMA HEALTHCARE

Repeat Insult Patch Test - Modified Draize Procedure –
Principles and Methods of Toxicology, A Wallace Hayes (editor).

(Copies of this document are available online at https://www.crcpress.com.)

2.4 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the reference cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.2.

3.2 Standard sample. Unless otherwise specified, the finished braid shall match the standard sample for shade and appearance, and shall be equal to or better than the standard sample with respect to all characteristics for which the standard sample is referenced (see 6.2).

3.3 Recycled, recovered, environmentally preferable, or biobased materials. Recycled, recovered, environmentally preferable, or biobased materials should be used to the maximum extent possible, provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs.

3.4 Materials.

3.4.1 Cotton yarn (for all types of braid). The cotton used in the fabrication of the yarn shall be twisted into ply yarns to meet the requirements of this document.

3.4.1.1 Polyester yarn (alternate for Types I through VII). The yarn shall be textured polyester of suitable denier to meet the requirements of this document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:08Z
Check the source to verify that this is the current version before use.

3.4.2 Rayon yarn (alternate for Types VIII, IX, and X braid). The yarn shall be multifilament of a suitable denier to meet the requirements of this document.

3.4.3 Polypropylene yarn (alternate for Types III, IV, V, and VII braid). The yarn shall be textured polypropylene of suitable denier to meet the requirements of this document.

3.4.4 Polyester/cotton blend (alternate for Type V, Class 1). The yarn shall be a blend of not more than 65 percent polyester with the remaining percent of cotton twisted into ply yarns to meet the requirements of this document.

3.5 Labile sulfur. Dyes and compounds containing elementary sulfur capable of oxidation to sulfuric acid shall not be used. The dyed braid shall be "Free" of labile sulfur when tested as specified in 4.7.1.

3.6 Color. The color of the braid shall be as specified in the contract or purchase order (see 6.2). The color and appearance of the braid (see 6.2) shall match the standard sample when tested as specified in 4.7.2.

3.6.1 Colorfastness. Unless otherwise specified in the contract or purchase order, the dyed and finished braid referenced in 3.7 shall conform to the colorfastness requirements listed in Table I, when tested as specified in Table V.

TABLE I. Colorfastness requirements

Color Evaluation	Laundering Color Change and Staining (3 cycles) (min.)	Light (after 40 AFU or 170 kJ/(m^2nm)@420 nm) 1/	Crocking Dry/Wet (min.)	Dry Cleaning Dry/Wet (min.)
Class 1 – Types I through VIII	3-4	3-4	3.5	--
Class 1 – Type IX and X	--	--	3.5	3-4
Class 2 - all Types	3-4	3-4	3.5	--
Class 3 - all Types	3-4	3	3.5	--

1/ AFU: AATCC Fading Units

3.7 Finish.

3.7.1 Class 1. No finish.

3.7.2 Class 2. The braid shall be water-repellent treated. The dynamic absorption of the braid shall not be less than 40 percent when tested as specified in Table V.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:08Z
Check the source to verify that this is the current version before use.

3.7.3 Class 3. The braid shall be water repellent treated as specified in 3.7.2 and mildew resistant treated. The braid shall be treated with an EPA approved organic mildew inhibitor and it shall have a rating of no more than "Microscopic Growth" when tested in accordance with Table V.

THIS SECTION IS INTENTIONALLY LEFT BLANK

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:08Z
Check the source to verify that this is the current version before use.

3.7.4 Physical requirements. The physical requirements of the braid shall be as specified in Table II for cotton, polyester, rayon, and polyester/cotton blend yarns and Table III for polypropylene yarns (only) when tested as specified in 4.6 and 4.7.

TABLE II. Physical requirements

Type	Diameter (inches) 1/	Weight per 144 yards (ounces), (min.) 2/	Number of carriers	Ends per carrier	Number of ends in core	Yarn ply		Picks per inch, (min.) 2/	Breaking strength (pounds), (min.) 3/
						Braid	Core		
I	1/8 1/	14.0	16	1	10	2	3	16	60
II	5/32 1/	28.0	8	1	8	2	3	10	75 4/
III	3/16 1/ (width)	16.5	24	2	--	2	--	22	75
IV	1/8 1/	21.0	8	2	--	3	--	10	80
V	3/16 1/	26.0	8	2	--	4	--	8	100
VI	1/8 1/	25.0	8	6	--	2	--	8	100
VII	11/32 1/ (width)	25.0	44	1	--	--	--	22	140 4/
VIII	1/8 1/	--	--	--	--	--	--	--	50
IX	1/8 - 3/16 (width)	--	--	--	--	--	--	--	50
X	1/8 - 3/16 (width)	--	--	--	--	--	--	--	75

1/ (±) 1/32-inch tolerance.
2/ A 10 percent loss in weight and picks per inch will be acceptable for the treated braids for Classes 2 and 3.
3/ A loss in breaking strength, based on the minimum specified for the untreated braid, shall be permitted for the applicable Classes as follows:
- Class 2 up to 15 percent
- Class 3 up to 20 percent

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:08Z
Check the source to verify that this is the current version before use.

4/ When using polyester yarn (see 3.4.1.1), the breaking strength for Type II shall be 140 pounds (min.) and for Type VII it shall be 200 pounds (min.).

TABLE III. Physical requirements for polypropylene braid (only).

Type	Diameter (inches) 1/	Weight per 144 yards (ounces), (min.) 2/	Number of carriers	Ends per carrier	Picks per inch, (min.) 2/	Breaking strength (pounds), (min.) 3/
III	3/16	18	22	2	17	160
IV	1/8	15	8	2	10	180
V	3/16	24	8	3	8	240
VII	11/32	16	44	1	22	180

1/ (±) 1/32-inch tolerance.

2/ A 10 percent loss in weight and picks per inch will be acceptable for the treated braids for Classes 2 and 3.

3/ A loss in breaking strength, based on the minimum specified for the untreated braid, shall be permitted for the applicable Classes as follows:

- Class 2 up to 15 percent
- Class 3 up to 20 percent

THIS SPACE LEFT INTENTIONALLY BLANK

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:08Z
Check the source to verify that this is the current version before use.

3.8 Braid weave. Types I, II, IV, V, and VI shall be braided with a basket type braiding. Types III and VII shall be braided with a plain type braiding. Any braiding type may be used for Types VIII, IX, and X.

3.9 Toxicity. The finished braid shall not present a health hazard and shall show compatibility with prolonged, direct skin contact when tested as specified in 4.7.4. Chemicals recognized by the Environmental Protection Agency (EPA) as human carcinogens shall not be used.

3.9.1 Toxicity documents. All finishing chemical treatments used to process the braid shall be identified and accompanied by the appropriate Material Safety Data Sheet (MSDS) information.

3.10 Length and put-up. Unless otherwise specified (see 6.2) for Government procurements only, the braid shall be put-up on commercial size spools, as follows:

a. Types I, II, IV, V, VI, VIII, and IX – 288 yards minimum (plus 10 percent) to a spool.

b. Types III, VII, and X – 432 yards minimum (plus 10 percent) to a spool.

c. There shall be not more than three (3) lengths per spool for 288-yard spools and not more than four (4) lengths per spool for 432-yard spools. No single length shall be less than 10 yards.

3.11 Marking. Unless otherwise specified (see 6.2), each spool shall have the following information on one end.

Item description
Stock number
Type, Class, and color
Name of contractor
Number and date of contract
Total yards on the spool

3.12 Spool identification. Each spool shall be labeled, ticketed for fiber content in accordance with the Rules and Regulations under the Textile Fiber Products Identification Act.

3.13 Workmanship. The finished braid shall conform to the quality established by this document and the occurrence of defects shall not exceed the applicable acceptable quality levels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:08Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2)
b. Conformance inspection (see 4.3)

4.2 First article inspection. A first article, submitted in accordance with 3.1, shall be inspected, examined for appearance, color and finish defects in 4.4, 4.5 and tested for the characteristics as specified in 4.6 through 4.7.

4.3 Conformance inspection. Conformance inspection shall include the examination of 4.4, 4.5, and the testing in 4.6 through 4.7 as applicable. Sampling for inspection shall be performed in accordance with ANSI/ASQ Z1.4 and with acceptance quality limits as specified in the contract or purchase order, except where otherwise indicated (see 6.2).

4.4 Inspection conditions. Unless otherwise specified in this specification or applicable procurement documents (see 6.2), all inspections shall be performed in accordance with this specification and all the requirements of referenced documents.

4.5 Yard-by-yard examination. Each spool in the sample shall be examined yard-by-yard on the face side only. The fabric defects are as defined in ASTM D3990 and only defects that are clearly noticeable at normal inspection distance (3 feet) shall be scored. The defects are assigned demerit points in accordance with ASTM D5430, Option A, with the exceptions listed below:

a. The defects found shall be counted regardless of their proximity to each other, except where two (2) or more defects represent a single local condition of the braid in which case only the more serious defect shall be counted.

b. Only coarse yarns that exceed twice the normal diameter shall be scored.

c. Mixed filling shall be scored only if attributed to shade bar resulting from wrong ply, wrong twist in the yarn or off shade yarn.

d. The defects specified for each type shall be scored four (4) points for each yard in which they occur.

4.5.1 Four (4) point defects. Table IV is a list of defects to be included for each type of material.

TABLE IV. Braid defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:08Z
Check the source to verify that this is the current version before use.

Defect Description
Any hole (flat braid), cut, tear, abrasion mark.
Edge ravels when pulled outward.
Core not completely covered (Type I and II only).
Broken or missing yarn.
Any spot, stain or streak more than 1-inch in combined directions.
Coarse or light filling bar resulting in noticeable difference in stiffness and thickness and extending for more than 1/4-inch in the length direction.
The braid will not lie flat due to twist or distortion.
Floats and skips that are over 1-inch.
Hitch-back crack; light or heavy places resulting from opening between adjoining picks.
Kinks – more than three (3) kinks in any nine (9) linear inches.
Knots – more than one (1) knot in any nine (9) linear inches.
Uneven width or width not as specified within a tolerance of ± 1/16 inch (flat braid).
Color not a good match to reference.
Any area of poor dye penetration, streak or shade bar that is 9-inches or less. Defective shade areas that are greater than 9-inches constitute a failure.
Objectionable odor.
Any embedded foreign matter or uncleanness.
Edges tolled folded, scalloped or corded, baggy, ridgy or wavy braid.
Label and marking missing or incorrect.
Any piece less than the allowable minimum length of piece.
Any spool containing more than the allowable number of pieces allowed for the type of braid.
Total lengths on the spools are less than the total lengths marked on the spools.

4.6 End item testing. The braid shall be tested for the characteristics listed in Section 3. The methods of testing as specified in Table V shall be followed. Unless otherwise specified, all testing shall be performed under standard conditions in accordance with ASTM D1776/D1776M. All test reports shall contain the individual values utilized in expressing the final results. The sample size shall be in accordance with the following:

Lot size (yards)	Sample size (yards)
800 or less	2
801 up to and including 22,000	3
22,001 and over	5

The lot size shall be expressed in units of one (1) linear yard. Sample yardage shall be apportioned equally among the selected spools. The lot shall be unacceptable if one (1) test fails to meet the requirement specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:08Z
Check the source to verify that this is the current version before use.

TABLE V. End item tests.

Characteristic	Requirement reference	Test method
Fiber analysis	3.4	AATCC 20 (see 6.5)
Labile sulfur	3.5	4.7.1
Visual Shade matching	3.6	4.7.2
Colorfastness:		
Laundering, after 3 cycles	Table I	AATCC 61, Test 3A 1/, 2/, 3/
Light	Table I	AATCC 16.3, Option 3, 4/
Crocking, wet/dry	Table I	AATCC 8, 5/
Drycleaning	Table I	AATCC 132 4/
Dynamic absorption (Class 2 only)	3.7.2	AATCC 70 6/
Organic mildew inhibitor	3.7.3	AATCC 30, Test III
Diameter or width	Table II & III	Caliper/calibrated ruler 7/
Weight	Table II & III	4.7.3
Number of carriers	Table II & III	Visual
Ends per carrier	Table II & III	Visual
Ends per core (Type I and II only)	Table II & III	Visual
Yarn ply	Table II	Visual
Picks per inch	Table II & III	Visual
Breaking strength	Table II & III	PIA-Test Method-6016
Braiding type	3.8	Visual
Toxicity	3.9	4.7.4

1/ Rated using the AATCC Evaluation Procedure 1, Gray Scale for Color Change and AATCC Evaluation Procedure 2, Gray Scale for Staining.
2/ The specimen must be dried after each laundering cycle.
3/ Only the stain on that part of the color transfer cloth of the same fibers of the specimen being tested shall be evaluated for staining (e.g. cotton braid on the cotton portion of the transfer cloth).
4/ Rated using the AATCC Evaluation Procedure 1, Gray Scale for Color Change.
5/ Rated using the AATCC Procedure 8, AATCC 9 Step Chromatic Transference Scale Rating.
6/ Each braid piece shall 20-cm long by full width.
7/ Except that the braid shall be measured under a tension of 3-ounce weight.

4.7 Method of inspection/testing.

4.7.1 Presence of labile sulfur test. In the determination of presence of labile sulfur in textile materials with lead acetate, two (2) 1.50 (± 0.01) gram samples from each material submitted for evaluation shall be tested. Each of the two (2) samples shall be cut into very small pieces and placed into separate test tubes. The samples shall be submersed in a stannous chloride solution that contains 100 grams of stannous chloride crystals ACS in 100 milliliters of hydrochloric acid ACS (35 percent concentration) and 50 milliliters of distilled water. A filter paper wet out with a 5.0 percent lead acetate solution shall be placed over top of the test tube. The lead acetate

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:08Z
Check the source to verify that this is the current version before use.

solution contains 5.0 grams of lead acetate CP reagent grade and enough distilled water to make up a 100 milliliter solution; if the solution is not clear, add a few drops (one at a time) of glacial acetic acid until the solution is clear. The test tube containing the textile sample, stannous chloride and wet filter paper shall be heated over a low flame until the solution is boiling. The solution should not be heated for more than 15 seconds. A brown to black stain on the filter paper should be evaluated as follows:

Free - The filter paper shows no discoloration or staining of any kind.
Slight - The filter paper shows a light tan to light brown discoloration stain.
Moderate - The filter paper shows a dark brown discoloration stain.
Severe - The filter paper shows a black color stain.

4.7.2 Visual shade matching. The color and appearance of the cloth shall match the standard sample when viewed using the AATCC Evaluation Procedure 9, Option A, with sources simulating artificial daylight D75 illuminant with a color temperature of 7500K (±200) illumination of 100 (± 20) foot candles, and shall be a good match to the standard sample under incandescent A illuminant with a color temperature of 2856K (±200).

4.7.3 Weight. Three (3) specimens shall be cut in excess of one (1) yard each. Three specimens of braid in the relaxed state shall be cut to exactly one (1) yard each. While in a standard condition (see 4.6), each yard shall be weighed separately on a balance or scale accurate to 0.01 ounce. The weight of the three (3) specimens shall be averaged and this average value multiplied by 144 to determine the ounces per gross (144) yards.

4.7.4 Toxicity test. When required, (see 6.2), an acute dermal irritation study and a skin sensitization study shall be conducted on laboratory animals. When the results of these studies indicate the braid is not a sensitizer or irritant, a Repeat Insult Patch Test shall be performed in accordance with the Modified Draize Procedure (see 2.3). If the toxicity requirement (see 3.9) can be demonstrated with historical use data, toxicity testing may not be required (see 6.2).

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of material is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Department or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:08Z
Check the source to verify that this is the current version before use.

6.1 Intended use. The braid is intended for use with various items of clothing as tie cords, lacing cords, and hangers.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Type and Class of braid required (see 1.2).
c. The specific issue of individual documents referenced (see 2.2 and 2.3).
d. When first article is required (see 3.1, 4.2 and 6.3).
e. Color required (see 3.6).
f. Length required if other than specified (see 3.10 and 3.11).
g. Conformance inspection acceptance quality limits (AQL) (see 4.3)
h. Inspection conditions (see 4.4).
i. When toxicity testing is required (4.7.4)
j. Packaging requirements (see 5.1).

6.3 First article. When a first article inspection is required (see 3.1), it will be inspected and approved under the appropriate provisions of FAR 52.209-4. The first article should be a pre-production sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Standard sample. For access to samples and pattern drawings, address the contracting activity issuing the invitation for bids or request for proposal.

6.5 Certificate of compliance. The contracting activity may select to accept a certificate of compliance for stated requirement.

6.6 Supersession data . This document supersedes MIL-B-371F, dated 15 May 1987.

6.7 Subject term (key word) listing.

Cord, tie, and lacing
Clothing
Cotton
Hangers
Polypropylene
Polyester
Rayon

6.8 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:08Z
Check the source to verify that this is the current version before use.

Custodians:
Army - GL
Navy - NU
Air Force - 11

Preparing Activity
DLA - CT

Review activities:
Army - MD
Navy - MC

(Project: 8315-2019-005)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:08Z
Check the source to verify that this is the current version before use.