MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, GLASS DIELECTRIC,
(AXIAL-RADIAL WIRE-LEAD TERMINALS), ESTABLISHED RELIABILITY,
STYLE CYR22

This amendment forms a part of MIL-C-23269/7C, dated 30 September 1970, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Following title, insert:


"

FAILURE RATE LEVEL 'L' IS INACTIVE FOR DESIGN AFTER 20 July 1983 .

"

FIGURE 1, delete and substitute:

Inches	mm
.001	0.03
.004	0.10
.015	0.38
.031	0.79
.032	0.81
.037	0.94
.047	1.19
.156	3.96
.219	5.56
.453	11.51
.700	17.78
.781	19.84
1.125	28.58



NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. The lead diameter shall be .032 +.004, -.001 for capacitance values below 1800 pF, and .037 +.004, -.001 for capacitance values above 1600 pF.
4. For any value above 1600 pF this dimension shall be .219 ±.047.
5. See marking requirements.

FIGURE 1. Dimensions and configurations.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:14Z
Check the source to verify that this is the current version before use.

* Below requirements add; "Qualification inspection is not required."

NOTE: The margin of this amendment is marked with an asterisk to indicate where the change (addition) from the previous amendment was made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notation and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Air Force - 17, 99
DLA - ES

User activities:
Navy - AS, CG, MC, OS, SH
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5910-1740)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:14Z
Check the source to verify that this is the current version before use.