
MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, GLASS DIELECTRIC, (RADIAL OR AXIAL WIRE-LEAD TERMINALS), ESTABLISHED RELIABILITY, STYLES CYR41, CYR42, AND CYR43

The complete requirements for procuring the capacitors described herein shall consist of this document and the latest issue of Specification MIL-C-23269.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.



STYLE CYR41, SEE TABLE I

DIMENSIONS				
Style	M	L Max	W Max	T
CYR41	$.025^{+.004}_{-.001}$	.300	.300	See table I

INCHES	MM	INCHES	MM
.001	.03	.025	.64
.004	.13	.031	.79
.010	.25	.200	5.08
.015	.38	.300	7.62
		1.125	28.58

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. See marking requirement.

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:15Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction:
Dimensions and configuration - See figures 1, 2, and 3 and tables I, II, and III.
Case material - Glass (vitreous enamel).
Terminals - Type C of MIL-STD-1276.
Capacitance (Cap.) (nom) - See tables I, II, and III.
Cap. tolerance - See tables I, II, and III.
Rated voltage - See tables I, II, and III.
Failure rate level - L, M, P, R, or S.
Rated temperature - -55° to +125°C.
Temperature coefficient - 0 ± 25 parts/million/°C.
Capacitance drift - 0.1% or 0.1 pF, whichever is greater.
Seal - Hermetic.
Seal
Seal: Test II.

Insulation resistance: 100,000 megohms or 200 ohm-farads min (qualification inspection only at +125°C). 500,000 megohms min (at +25°C).


Dissipation factor (DF): 0.7% max (0.5 thru 4.7 pF); 0.3% max (5.6 thru 27 pF); and 0.1% max (30 pF and up).

Thermal shock and moisture resistance:
DF - Not to exceed initial requirement.

Q; In accordance with MIL-C-23269.

Life:
ΔCap. (240 hr and 2,000 hr) - 1.0% or 0.5 pF, max.
DF (240 hr and 2,000 hr) - Not to exceed initial requirement.

Marking:



Style	Permissible 85°C voltage	Rated 125°C voltage	Capacitance
	(volts, dc)	(volts, dc)	(pF)
CYR41	200	100	All values
CYR42	500	500	0.5 thru 56
	500	300	68 and 82
	200	100	100 thru 220
	100	50	270 and 300
CYR43	500	300	330 and 390
	200	100	470 thru 680
	100	50	820 thru 1,200

Substitutability data: See table IV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:15Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical and physical characteristics and dash numbers.


Cap.	Rated voltage	Capacitance tolerance	Dash number M23269/09- FR level in %/1,000 hrs				
			L (2.0)	M (1.0)	P (0.1)	R (0.01)	S (0.001)
(pF)	(volts, dc)						
0.5	100	±0.25 pF	2001	3001	4001	5001	6001
1.5			2002	3002	4002	5002	6002
2.7			2003	3003	4003	5003	6003
3.3			2004	3004	4004	5004	6004
3.9			2005	3005	4005	5005	6005
4.7			2006	3006	4006	5006	6006
5.6			2007	3007	4007	5007	6007
6.8		±0.25 pF	2008	3008	4008	5008	6008
6.8		±5%	2009	3009	4009	5009	6009
8.2		±0.25 pF	2010	3010	4010	5010	6010
8.2		±5%	2011	3011	4011	5011	6011
10		±0.25 pF	2012	3012	4012	5012	6012
10		±5%	2013	3013	4013	5013	6013
12		±0.25 pF	2014	3014	4014	5014	6014
12		±5%	2015	3015	4015	5015	6015
15		±0.25 pF	2016	3016	4016	5016	6016
15		±2%	2017	3017	4017	5017	6017
15		±5%	2018	3018	4018	5018	6018
18		±0.25 pF	2019	3019	4019	5019	6019
18		±2%	2020	3020	4020	5020	6020
18		±5%	2021	3021	4021	5021	6021
22		±0.25 pF	2022	3022	4022	5022	6022
22		±2%	2023	3023	4023	5023	6023
22		±5%	2024	3024	4024	5024	6024
27		±1%	2025	3025	4025	5025	6025
27		±2%	2026	3026	4026	5026	6026
27		±5%	2027	3027	4027	5027	6027
33		±1%	2028	3028	4028	5028	6028
33		±2%	2029	3029	4029	5029	6029
33		±5%	2030	3030	4030	5030	6030
39		±1%	2031	3031	4031	5031	6031
39		±2%	2032	3032	4032	5032	6032
39		±5%	2033	3033	4033	5033	6033
47		±1%	2034	3034	4034	5034	6034
47		±2%	2035	3035	4035	5035	6035
47		±5%	2036	3036	4036	5036	6036
56		±1%	2037	3037	4037	5037	6037
56		±2%	2038	3038	4038	5038	6038
56		±5%	2039	3039	4039	5039	6039
68		±1%	2040	3040	4040	5040	6040
68		±2%	2041	3041	4041	5041	6041
68		±5%	2042	3042	4042	5042	6042
82		±1%	2043	3043	4043	5043	6043
82		±2%	2044	3044	4044	5044	6044
82		±5%	2045	3045	4045	5045	6045
100		±1%	2046	3046	4046	5046	6046
100		±2%	2047	3047	4047	5047	6047
100		±5%	2048	3048	4048	5048	6048
120		±1%	2049	3049	4049	5049	6049
120		±2%	2050	3050	4050	5050	6050
120	100	±5%	2051	3051	4051	5051	6051

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:15Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical and physical characteristics and dash numbers - Continued

Cap.	Rated voltage	Capacitance tolerance	Dash number M23269/09- FR level in %/1, 000 hrs				
			L (2.0)	M (1.0)	P (0.1)	R (0.01)	S (0.001)
(pF)	(volts, dc)						
150	100	±1%	2052	3052	4052	5052	6052
150		±2%	2053	3053	4053	5053	6053
150		±5%	2054	3054	4054	5054	6054
180		±1%	2055	3055	4055	5055	6055
180		±2%	2056	3056	4056	5056	6056
180		±5%	2057	3057	4057	5057	6057
220		±1%	2058	3058	4058	5058	6058
220		±2%	2059	3059	4059	5059	6059
220		±5%	2060	3060	4060	5060	6060
270		±1%	2061	3061	4061	5061	6061
270		±2%	2062	3062	4062	5062	6062
270		±5%	2063	3063	4063	5063	6063
330		±1%	2064	3064	4064	5064	6064
330		±2%	2065	3065	4065	5065	6065
330		±5%	2066	3066	4066	5066	6066
390		±1%	2067	3067	4067	5067	6067
390		±2%	2068	3068	4068	5068	6068
390		±5%	2069	3069	4069	5069	6069
470		±1%	2070	3070	4070	5070	6070
470		±2%	2071	3071	4071	5071	6071
470		±5%	2072	3072	4072	5072	6072
560		±1%	2073	3073	4073	5073	6073
560		±2%	2074	3074	4074	5074	6074
560		±5%	2075	3075	4075	5075	6075
680		±1%	2076	3076	4076	5076	6076
680		±2%	2077	3077	4077	5077	6077
680		±5%	2078	3078	4078	5078	6078
820		±1%	2079	3079	4079	5079	6079
820		±2%	2080	3080	4080	5080	6080
820		±5%	2081	3081	4081	5081	6081
1, 000		±1%	2082	3082	4082	5082	6082
1, 000		±2%	2083	3083	4083	5083	6083
1, 000	100	±5%	2084	3084	4084	5084	6084

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:15Z
Check the source to verify that this is the current version before use.



DIMENSIONS				
Style	M	L Max	W Max	T
CYR42	$.020^{+.002}_{-.001}$	.390	.200	.109 max

INCHES	MM	INCHES	MM
.001	.03	.109	.79
.002	.05	.200	5.08
.010	.10	.390	9.91
.020	.25	1.125	28.58
.031	.64		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. See marking requirement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:15Z
Check the source to verify that this is the current version before use.

TABLE II. Electrical and physical characteristics and dash numbers.


Cap.	Rated voltage	Capacitance tolerance	Dash number M23269/09- FR level in %/1,000 hrs				
			L (2.0)	M (1.0)	P (0.1)	R (0.01)	S (0.001)
(pF)	(volts, dc)						
0.5	500	±0.25 pF	2101	3101	4101	5101	6101
1.5	↑	±0.25 pF	2102	3102	4102	5102	6102
2.7		±0.25 pF	2103	3103	4103	5103	6103
3.3		±0.25 pF	2104	3104	4104	5104	6104
3.9		±0.25 pF	2105	3105	4105	5105	6105
4.7		±0.25 pF	2106	3106	4106	5106	6106
5.6		±0.25 pF	2107	3107	4107	5107	6107
6.8		±0.25 pF	2108	3108	4108	5108	6108
6.8		±5%	2109	3109	4109	5109	6109
8.2		±0.25 pF	2110	3110	4110	5110	6110
8.2		±5%	2111	3111	4111	5111	6111
10		±0.25 pF	2112	3112	4112	5112	6112
10		±5%	2113	3113	4113	5113	6113
12		±0.25 pF	2114	3114	4114	5114	6114
12		±5%	2115	3115	4115	5115	6115
15		±0.25 pF	2116	3116	4116	5116	6116
15		±2%	2117	3117	4117	5117	6117
15		±5%	2118	3118	4118	5118	6118
18		±0.25 pF	2119	3119	4119	5119	6119
18		±2%	2120	3120	4120	5120	6120
18		±5%	2121	3121	4121	5121	6121
22		±0.25 pF	2122	3122	4122	5122	6122
22		±2%	2123	3123	4123	5123	6123
22		±5%	2124	3124	4124	5124	6124
27		±1%	2125	3125	4125	5125	6125
27		±2%	2126	3126	4126	5126	6126
27		±5%	2127	3127	4127	5127	6127
33		±1%	2128	3128	4128	5128	6128
33		±2%	2129	3129	4129	5129	6129
33		±5%	2130	3130	4130	5130	6130
39		±1%	2131	3131	4131	5131	6131
39		±2%	2132	3132	4132	5132	6132
39		±5%	2133	3133	4133	5133	6133
47		±1%	2134	3134	4134	5134	6134
47		±2%	2135	3135	4135	5135	6135
47		±5%	2136	3136	4136	5136	6136
56		±1%	2137	3137	4137	5137	6137
56	↓	±2%	2138	3138	4138	5138	6138
56	500	±5%	2139	3139	4139	5139	6139
68	300	±1%	2140	3140	4140	5140	6140
68	↑	±2%	2141	3141	4141	5141	6141
68		±5%	2142	3142	4142	5142	6142
82		±1%	2143	3143	4143	5143	6143
82	↓	±2%	2144	3144	4144	5144	6144
82	300	±5%	2145	3145	4145	5145	6145
100	100	±1%	2146	3146	4146	5146	6146
100	↑	±2%	2147	3147	4147	5147	6147
100		±5%	2148	3148	4148	5148	6148
120		±1%	2149	3149	4149	5149	6149
120		±2%	2150	3150	4150	5150	6150
120	↓	±5%	2151	3151	4151	5151	6151
150	100	±1%	2152	3152	4152	5152	6152

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:15Z
Check the source to verify that this is the current version before use.

TABLE II. Electrical and physical characteristics and dash numbers. - Continued

Cap.	Rated voltage	Capacitance tolerance	Dash number M23269/09- FR level in %/1,000 hrs				
			L (2.0)	M (1.0)	P (0.1)	R (0.01)	S (0.001)
(pF)	(volts, dc)						
150	100	±2%	2153	3153	4153	5153	6153
150	↑	±5%	2154	3154	4154	5154	6154
180		±1%	2155	3155	4155	5155	6155
180		±2%	2156	3156	4156	5156	6156
180		±5%	2157	3157	4157	5157	6157
220		±1%	2158	3158	4158	5158	6158
220	↓	±2%	2159	3159	4159	5159	6159
220	100	±5%	2160	3160	4160	5160	6160
270	50	±1%	2161	3161	4161	5161	6161
270	↑	±2%	2162	3162	4162	5162	6162
270		±5%	2163	3163	4163	5163	6163
300		±1%	2164	3164	4164	5164	6164
300	↓	±2%	2165	3165	4165	5165	6165
300	50	±5%	2166	3166	4166	5166	6166

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:15Z
Check the source to verify that this is the current version before use.



DIMENSIONS				
Style	M	L Max	W Max	T
CYR43	$.025^{+.004}_{-.001}$	.515	.295	.155 max

INCHES	MM	INCHES	MM
.001	.03	.155	3.94
.004	.13	.295	7.49
.010	.10	.515	13.08
.025	.51	1.125	28.58
.031	.64		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. See marking requirement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:15Z
Check the source to verify that this is the current version before use.

TABLE III. Electrical and physical characteristics and dash numbers.

Cap.	Rated voltage	Capacitance tolerance	Dash number M23269/09- FR level in %/1,000 hrs				
			L (2.0)	M (1.0)	P (0.1)	R (0.01)	S (0.001)
(pF)	(volts, dc)						
330	300	±1%	2301	3301	4301	5301	6301
330	↑	±2%	2302	3302	4302	5302	6302
330	↑	±5%	2303	3303	4303	5303	6303
390	↑	±1%	2304	3304	4304	5304	6304
390	↑	±2%	2305	3305	4305	5305	6305
390	300	±5%	2306	3306	4306	5306	6306
470	100	±1%	2307	3307	4307	5307	6307
470	↑	±2%	2308	3308	4308	5308	6308
470	↑	±5%	2309	3309	4309	5309	6309
560	↑	±1%	2310	3310	4310	5310	6310
560	↑	±2%	2311	3311	4311	5311	6311
560	↑	±5%	2312	3312	4312	5312	6312
680	↑	±1%	2313	3313	4313	5313	6313
680	↑	±2%	2314	3314	4314	5314	6314
680	100	±5%	2315	3315	4315	5315	6315
820	50	±1%	2316	3316	4316	5316	6316
820	↑	±2%	2317	3317	4317	5317	6317
820	↑	±5%	2318	3318	4318	5318	6318
1,000	↑	±1%	2319	3319	4319	5319	6319
1,000	↑	±2%	2320	3320	4320	5320	6320
1,000	↑	±5%	2321	3321	4321	5321	6321
1,200	↑	±1%	2322	3322	4322	5322	6322
1,200	↓	±2%	2323	3323	4323	5323	6323
1,200	50	±5%	2324	3324	4324	5324	6324

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:15Z
Check the source to verify that this is the current version before use.

TABLE IV. Substitutability data.

Superseded type designation in MIL-C-23269/9	Use dash number M23269/09- in MIL-C-23269/9A FR level in %/1,000 hrs		Superseded type designation in MIL-C-23269/9	Use dash number M23269/09- in MIL-C-23269/9A FR level in %/1,000 hrs	
	L (2.0)	M (1.0)		L (2.0)	M (1.0)
CYR41E0R5C	2001	3001	CYR41E151F	2052	3052
CYR41E1R5C	2002	3002	CYR41E151G	2053	3053
CYR41E2R7C	2003	3003	CYR41E151J	2054	3054
CYR41E3R3C	2004	3004	CYR41E181F	2055	3055
CYR41E3R9C	2005	3005	CYR41E181G	2056	3056
CYR41E4R7C	2006	3006	CYR41E181J	2057	3057
CYR41E5R6C	2007	3007	CYR41E221F	2058	3058
CYR41E6R8C	2008	3008	CYR41E221G	2059	3059
CYR41E6R8J	2009	3009	CYR41E221J	2060	3060
CYR41E8R2C	2010	3010	CYR41E271F	2061	3061
CYR41E8R2J	2011	3011	CYR41E271G	2062	3062
CYR41E100C	2012	3012	CYR41E271J	2063	3063
CYR41E100J	2013	3013	CYR41E331F	2064	3064
CYR41E120C	2014	3014	CYR41E331G	2065	3065
CYR41E120J	2015	3015	CYR41E331J	2066	3066
CYR41E150C	2016	3016	CYR41E391F	2067	3067
CYR41E150G	2017	3017	CYR41E391G	2068	3068
CYR41E150J	2018	3018	CYR41E391J	2069	3069
CYR41E180C	2019	3019	CYR41E471F	2070	3070
CYR41E180G	2020	3020	CYR41E471G	2071	3071
CUR41E180J	2021	3021	CYR41E471J	2072	3072
CYR41E220C	2022	3022	CYR41E561F	2073	3073
CYR41E220G	2023	3023	CYR41E561G	2074	3074
CYR41E220J	2024	3024	CYR41E561J	2075	3075
CYR41E270F	2025	3025	CYR41E681F	2076	3076
CYR41E270G	2026	3026	CYR41E681G	2077	3077
CYR41E270J	2027	3027	CYR41E681J	2078	3078
CYR41E330F	2028	3028	CYR41E821F	2079	3079
CYR41E330G	2029	3029	CYR41E821G	2080	3080
CYR41E330J	2030	3030	CYR41E821J	2081	3081
CYR41E390F	2031	3031	CYR41E102F	2082	3082
CYR41E390G	2032	3032	CYR41E102G	2083	3083
CYR41E390J	2033	3033	CYR41E102J	2084	3084
CYR41E470F	2034	3034			
CYR41E470G	2035	3035	CYR42E0R5C	2101	3101
CYR41E470J	2036	3036	CYR42E1R5C	2102	3102
CYR41E560F	2037	3037	CYR42E2R7C	2103	3103
CYR41E560G	2038	3038	CYR42E3R3C	2104	3104
CYR41E560J	2039	3039	CYR42E3R9C	2105	3105
CYR41E680F	2040	3040	CYR42E4R7C	2106	3106
CYR41E680G	2041	3041	CYR42E5R6C	2107	3107
CYR41E680J	2042	3042	CYR42E6R8C	2108	3108
CYR41E820F	2043	3043	CYR42E6R8J	2109	3109
CYR41E820G	2044	3044	CYR42E8R2C	2110	3110
CYR41E820J	2045	3045	CYR42E8R2J	2111	3111
CYR41E101F	2046	3046	CYR42E100C	2112	3112
CYR41E101G	2047	3047	CYR42E100J	2113	3113
CYR41E101J	2048	3048	CYR42E120C	2114	3114
CYR41E121F	2049	3049	CYR42E120G	2115	3115
CYR41E121G	2050	3050	CYR42E120J	2116	3116
CYR41E121J	2051	3051	CYR42E150C	2117	3117

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:15Z
Check the source to verify that this is the current version before use.

TABLE IV. Substitutability data. - Continued

Superseded type designation in MIL-C-23269/9	Use dash number M23269/09- in MIL-C-23269/9A FR level in %/1,000 hrs		Superseded type designation in MIL-C-23269/9	Use dash number M23269/09- in MIL-C-23269/9A FR level in %/1,000 hrs	
	L (2.0)	M (1.0)		L (2.0)	M (1.0)
CYR42E150G	2118	3118	CYR42E181F	2156	3156
CYR42E150J	2119	3119	CYR42E181G	2157	3157
CYR42E180C	2120	3120	CYR42E181J	2158	3158
CYR42E180G	2121	3121	CYR42E221F	2159	3159
CYR42E180J	2122	3122	CYR42E221G	2160	3160
CYR42E220C	2123	3123	CYR42E221J	2161	3161
CYR42E220G	2124	3124	CYR42E271F	2162	3162
CYR42E220J	2125	3125	CYR42E271G	2163	3163
CYR42E270F	2126	3126	CYR42E271J	2164	3164
CYR42E270G	2127	3127	CYR42E301F	2165	3165
CYR42E270J	2128	3128	CYR42E301G	2166	3166
CYR42E330F	2129	3129	CYR42E301J	2167	3167
CYR42E330G	2130	3130			
CYR42E330J	2131	3131	CYR43E331F	2301	3301
CYR42E390F	2132	3132	CYR43E331G	2302	3302
CYR42E390G	2133	3133	CYR43E331J	2303	3303
CYR42E390J	2134	3134	CYR43E391F	2304	3304
CYR42E470F	2135	3135	CYR43E391G	2305	3305
CYR42E470G	2136	3136	CYR43E391J	2306	3306
CYR42E470J	2137	3137	CYR43E471F	2307	3307
CYR42E560F	2138	3138	CYR43E471G	2308	3308
CYR42E560G	2139	3139	CYR43E471J	2309	3309
CYR42E560J	2140	3140	CYR43E561F	2310	3310
CYR42E680F	2141	3141	CYR43E561G	2311	3311
CYR42E680G	2142	3142	CYR43E561J	2312	3312
CYR42E680J	2143	3143	CYR43E681F	2313	3313
CYR42E820F	2144	3144	CYR43E681G	2314	3314
CYR42E820G	2145	3145	CYR43E681J	2315	3315
CYR42E820J	2146	3146	CYR43E821F	2316	3316
CYR42E101F	2147	3147	CYR43E821G	2317	3317
CYR42E101G	2148	3148	CYR43E821J	2318	3318
CYR42E101J	2149	3149	CYR43E102F	2319	3319
CYR42E121F	2150	3150	CYR43E102G	2320	3320
CYR42E121G	2151	3151	CYR43E102J	2321	3321
CYR42E121J	2152	3152	CYR43E122F	2322	3322
CYR42E151F	2153	3153	CYR43E122G	2323	3323
CYR42E151G	2154	3154	CYR43E122J	2324	3324
CYR42E151J	2155	3155			

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:15Z
Check the source to verify that this is the current version before use.

Custodians:
Army - EL
Navy - EC
Air Force - 17

Review activities:
Army - EL
Navy -
Air Force - 11, 17, 80
DSA - ES

User activities:
Army - None
Navy - MC, CG, AS, OS , SH
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DSA - ES

(Project 5910-1008-9)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:15Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

S/N-0102-014-1801 C-26264

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:15Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D. C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:15Z
Check the source to verify that this is the current version before use.