NOTICE OF CANCELLATION

INCH-POUND
MIL-PRF-23269/4G
NOTICE 3
6 April 2012
SUPERSEDING
NOTICE 2
10 May 2005

PERFORMANCE SPECIFICATION SHEET

CAPACITORS, FIXED, GLASS DIELECTRIC,
(AXIAL WIRE-LEAD TERMINALS), ESTABLISHED RELIABILITY,
STYLE CYR30

MIL-PRF-23269/4G, dated 12 August 1999, is hereby canceled. Possible replacement parts are available in DLA Land and Maritime drawing 09020. Replacement data is shown in table I.

Users are cautioned to evaluate this document for their particular application before citing it as a replacement document. MIL-PRF-23269/4 capacitors have failure rate levels (FRL) established in accordance with MIL-STD-690. DLA Land and Maritime drawing 09020 parts are non-established reliability.

(Copies of DLA Land and Maritime drawing 09020 are available online at http://www.landandmaritime.dla.mil or from DLA Land and Maritime, ATTN: VAT, Post Office Box 3990, Columbus, OH 43218-3990, or by email to capacitorfilter@dla.mil).

TABLE I. Replacement data.

MIL-PRF-23269/4 PIN	DLA Land and Maritime drawing PIN 09020-
-001 through -036 1/	001 through 036
7001 through 7036	101 through 136

1/ The complete MIL-PRF-23269/4 PIN shall include an additional character to indicate failure rate level (3, 4, 5, or 6).

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5910-2012-006)

Review activities:
Navy - AS, MC, OS, SH
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at https://assist.daps.dla.mil/.

AMSC N/A

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:13Z
Check the source to verify that this is the current version before use.