[INCH-POUND]
A-A-55534/5
19 February 1997

COMMERCIAL ITEM DESCRIPTION

RESISTORS, FIXED, WIRE WOUND OR METAL ELEMENT, (POWER TYPE) STYLE VLV7

The General Services Administration has authorized the use of this commercial item description (CID) for all federal agencies.

1. SCOPE. This CID covers the general requirements for style VLV7 wire wound or metal element, power type, fixed resistors. The resistors covered by this CID are intended for commercial/industrial applications.

2. CLASSIFICATION. This CID uses a classification system which is included in the Part Identification Number (PIN). The PIN shall be A5553405- (plus a coded number) as shown in the following example.

A5553405	R010	F
CID number	Resistance value (see 3.2)	Resistance tolerance (see 3.3)

3. SALIENT CHARACTERISTICS

3.1 Design and construction. The resistors supplied to this CID shall be as specified herein (see figure 1).

3.2 Resistance value. The resistance value shall be 0.005 ohm to 0.9 ohm.

3.3 Resistance tolerance. This style resistor is available in resistance tolerances F, H, and J (±1 percent, ±3 percent, and ±5 percent respectively).

3.4 Power rating. The power rating shall be 7.0 watt at +25°C . The power rating shall be linearly derated to zero at 275°C.

3.5 Temperature coefficient. The temperature coefficient of resistance shall not exceed ±350 ppm/°C from -55°C to +275°C.


3.6 Marking. Resistors supplied to this CID shall be marked with the manufacturers standard commercial PIN. Marking of individual small devices (e.g. chips) is not required but is permitted; however, each unit pack supplied to this CID shall be marked with the manufacturer's standard commercial PIN.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: Defense Supply Center, Columbus, ATTN: DSCC-VAM, Post Office Box 3990, Columbus, OH 43216-5000, or telephone (614) 692-0553, or facsimile (FAX) (614) 692-6939.

AMSC N/A FSC 5905

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:51Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm
0.002	0.05	0.312	7.92
0.031	0.79	1.218	30.94
0.040	1.02	1.500	38.10

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. The picturization of the style above is given as representative of the envelope of the item. Slight deviations from the outline shown, which are contained within the envelope and do not alter the functional aspects of the device, are acceptable.

FIGURE 1. Resistors, fixed, wire wound, or metal element (style VLV7).

4. QUALITY ASSURANCE PROVISIONS. Quality assurance provisions shall be as specified in A-A-55534.

5. PACKAGING. Packaging shall be as specified in A-A-55534.

6. NOTES

6.1 PIN. The PIN should be used for Government purposes to buy commercial products to this CID. See section 2 for PIN format.

6.2 CAGE code. For ordering purposes, inventory control, and submission of these instruments to DSCC under the Military Parts Control Advisory Group (MPCAG) evaluation program, CAGE code 58536 should be used.

6.3 Source of documents.

Commercial Item Description

A-A-55534 - Resistor, Fixed, Power type (Very Low Resistance Values), General Requirements For.

(Copies of commercial item descriptions are available from the Defense Printing Service Detachment Office, Building 4D (Customer Service), 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

6.4 Ordering data. Ordering data shall be as specified in A-A-55534.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:51Z
Check the source to verify that this is the current version before use.

6.5 Commercial products. As part of the market analysis and research effort, this CID was coordinated with the following MFGRs of commercial products. At the time of CID preparation and coordination, these MFGRs were known to have commercial products that would meet the requirements of this CID. (NOTE: This information should not be considered as a list of approved MFGRs or be used to restrict procurement to only the MFGRs shown.)

Commercial item description (CID) PIN	Vendor CAGE	Vendor name and address
A5553405***** Resistance values 0.005 ohm to 0.9 ohm, resistance tolerances F, H, and J, derated to zero at 275°C.	15915	TEPRO of Florida, Inc. 2608 Enterprise Rd. Clearwater, FL 34623

6.6 Part number (P/N) supersession data. This CID supersedes the following MFGRs style numbers as shown. This information is being provided to assist in reducing proliferation in the government inventory system.

MFGR's CAGE	MFGR's style 1/
15915	TSM7

1/ The MFGR's P/N shall not be used for procurement to the requirements of this CID. At the time of preparation of this CID, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown.

6.7 Government users. To acquire information on obtaining these resistors from the Government inventory system, contact Defense Supply Center,Columbus, ATTN: DSCC-CPB, 3990 E. Broad St., Columbus, OH 43216-5000, or telephone (614) 692-7707.

MILITARY INTERESTS:

Custodian

Navy - EC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - 7FXE

Preparing Activity:

DLA-CC

Project 5905-1471-05

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:51Z
Check the source to verify that this is the current version before use.