MIL-A-70609A(AR)
31 May 1988
SUPERSEDING
MIL-A-70609(AR)
6 June 1986

MILITARY SPECIFICATION

ADAPTER & FUZE, ASSEMBLY: M624, PARTS FOR

This Specification is approved for use within the U. S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers quality assurance provisions and preparation for delivery for the parts for Adapter & Fuze Assembly: M624.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, listed in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-2550 -	General Specification for Ammunition Except Small Arms Ammunition.
MIL-P-10025-	Packaging, Packing and Marking for Interplant Shipment of Inert Ammunition Components: General Specifications For.
MIL-A-48078 -	Ammunition, Standard Quality Assurance Provisions, General Specification for.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament, Munitions and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A
FSC 1345
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes. (ABC-STD-105)
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-1169- Packaging, Packing and Marking for Shipment of Inert Ammunition Components.
MIL-STD-1235- Continuous Sampling Procedures and Table for Inspection by Attributes.

(Copies of specifications, standards, drawings, publications, and other Government documents required by the suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

12546032 - Adapter & Fuze Assembly- M624

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings, specifications and standards.

3.2 Parts. All parts shall comply with drawings, specifications and standards.

3.3 Metal parts assembly. The metal parts assembly shall comply with all requirements specified on Drawing (Dwg.) 12546032, all associated drawings, and with all requirements specified in applicable specifications and standards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

3.4 X-ray of delay assembly. Delay assemblies shall be x-rayed in accordance with 4.5.1 to confirm proper loading.

3.5 Delay time. The delay assemblies shall comply with the delay time requirement of Drawing (Dwg.) 12554910 when tested in accordance with 4.5.2.

3.6 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.7 Workmanship. All parts and assemblies shall be fabricated and assembled in thorough, workmanlike manner. They shall be free of burrs, chips, weld spatter, sharp edges, chipped edges, gouges, cracks, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agents. All required markings shall be neat and sharply defined. External threads shall be full, complete and undamaged for their entire length. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection.

b. Quality conformance inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated below and Table I.

Part Description	Drawings	Quantities
Cap	12554906	10
Cap Assembly	12554908	10
Rod, Forward	12546028	10
Rod, Middle	12546029	10
Rod, End	12546030	10
Rod, Extension Assembly	12546027	10
Spring, Compression	12554909	10
Gasket	12546026	10
Holder, Delay	12546039	10
Holder, Primer	8831358	10
Cup, Relay	8831361	10
Delay Assembly	12554910	25
Adapter	12546031	10
Fuze, Mine, AT, M607 Loaded Assembly	8833783	10.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein. If any items fail to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3.3 Rejection. See MIL-A-48078. If any items fail to comply with any of the applicable requirements, the first article sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-A-70609A(AR)

PARAGRAPH	TITLE: Adapter & Fuze, Assembly: M624		SHEET 1 OF 3		DRAWING NUMBER: See below
					NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cap (Dwg. 12554906) Examination for Defects	10		3.2	4.4.2.1
	Cap, Assembly (Dwg. 12554908) Examination for Defects	10		3.3	4.4.2.2
	Rod, Forward (Dwg. 12546028) Examination for Defects	10		3.2	4.4.2.3
	Rod, Middle (Dwg. 12546029) Examination for Defects	10		3.2	4.4.2.4
	Rod, End (Dwg. 12546030) Examination for Defects	10		3.2	4.4.2.5
	Rod, Extension Assembly (Dwg. 1246027) Examination for defects	10		3.3	4.4.2.6

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609A(AR)

PARAGRAPH CATEGORY	TITLE: Adapter & Fuze, Assembly,: M624		SHEET 2 OF 3		DRAWING NUMBER: See Below NEXT HIGHER ASSEMBLY: --
	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Spring Compression (Dwg. 12554909) Examination for Defects	10		3.2	4.4.2.7
	Gasket (Dwg. 12546026) Examination for Defects	10		3.2	4.4.2.8
	Holder Delay (Dwg. 12546039) Examination for Defects	10		3.2	4.4.2.9
	Holder, Primer (Dwg. 8831358) Examination for Defects	10		3.2	4.4.2.10
	Cup, Relay (Dwg. 8831361) Examination for Defects	10		3.2	4.4.2.11
	Delay Assembly (Dwg. 12554910) Examination for Defects X-ray Delay Time	25 25 25		3.2 3.4 3.5	4.4.2.12 4.5.1 4.5.2

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609A(AR)

PARAGRAPH	TITLE: Adapter & Fuze, Assembly: M624		SHEET 3 OF 3		DRAWING NUMBER: See Below NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Adapter (Dwg. 12546031) Examination for Defects	10		3.2	4.4.2.13
	Fuze, Mine, AT, M607, Loaded Assembly (Dwg. 8833783) Examination for Defects	10		3.2	4.4.2.14
NOTES:					

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Tests Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Cap	1 OF 1	12554906
			NEXT HIGHER ASSEMBLY 12554908

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Pitch diameter of inside thread		0.40%	3.2	Gage
102	Minor diameter of inside thread		0.40%	3.2	Gage
103	Minimum depth of full inside thread		0.40%	3.2	Gage
104	Internal depth		0.40%	3.2	Gage
105	Pitch diameter of screw hole		0.40%	3.2	Gage
106	Minor diameter of screw hole		0.40%	3.2	Gage
107	Height of spacer		0.40%	3.2	Gage
108	Diameter of spacer		0.40%	3.2	Gage
109	True position of spacer		0.40%	3.2	Gage
Minor					
201	Overall height		0.65%	3.2	Gage
202	Protective coating inadequate, damaged or improper		0.65%	3.2	Visual
203	Workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609A(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.2	Cap Assembly	1	1	12554908
				NEXT HIGHER ASSEMBLY 12546032

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Presence of nylon screw		0.40%	3.2	Visual
Minor					
201	Workmanship		1.0%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Rod, Forward	1 OF 1	12546028
			NEXT HIGHER ASSEMBLY: 12546027

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of external thread, full		0.40%	3.2	Gage
102	Major diameter of external thread, full		0.40%	3.2	Gage
103	Length of external thread, full		0.40%	3.2	Gage
104	Pitch diameter of internal thread, full		0.40%	3.2	Gage
105	Minor diameter of internal thread, full		0.40%	3.2	Gage
106	Minimum depth of internal thread, full		0.40%	3.2	Gage
107	True position of internal thread		0.40%	3.2	Gage
108	Depth of pilot hole		0.40%	3.2	Gage
109	Perpendicularity of base		0.40%	3.2	Gage
110	Straightness		0.40%	3.2	Gage
111	Deep cuts or grooves		0.40%	3.2	Visual
Minor					
201	Length, total		0.65%	3.2	Gage
202	Outside rod diameter		0.65%	3.2	Gage
203	Protective coating inadequate, damaged or improper		0.65%	3.2	Visual
204	Workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Rod, Middle		12546029
			NEXT HIGHER ASSEMBLY
			12546027

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Pitch diameter of external thread		0.40%	3.2	Gage
102	Major diameter of external thread		0.40%	3.2	Gage
103	True position of external thread		0.40%	3.2	Gage
104	Diameter of undercut		0.40%	3.2	Gage
105	Shoulder length		0.40%	3.2	Gage
106	Width of undercut		0.40%	3.2	Gage
107	Pitch diameter of internal thread, full		0.40%	3.2	Gage
108	Minor diameter of internal thread, full		0.40%	3.2	Gage
109	Minimum depth of internal thread, full		0.40%	3.2	Gage
110	True position of internal thread		0.40%	3.2	Gage
111	Depth of pilot hole		0.40%	3.2	Gage
112	Perpendicularity of undercut below external threads		0.40%	3.2	Gage
113	Perpendicularity of base		0.40%	3.2	Gage
114	Straightness		0.40%	3.2	Gage
115	Deep cuts or grooves		0.40%	3.2	Visual
Minor					
201	Length, total		0.65%	3.2	Gage
202	Outside rod diameter		0.65%	3.2	Gage
203	Protective coating inadequate, damaged, or improper		0.65%	3.2	Visual
204	Workmanship		1.0%	3.7	Visual

NOTES:

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609A(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.5	Rod, End	1	1	12546030
				NEXT HIGHER ASSEMBLY: 12546027

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of thread		0.40%	3.2	Gage
102	Major diameter of thread		0.40%	3.2	Gage
103	Diameter of undercut		0.40%	3.2	Gage
104	Shoulder length		0.40%	3.2	Gage
105	Width of undercut		0.40%	3.2	Gage
106	Perpendicularity of undercut at external threads		0.40%	3.2	Gage
107	True position of outside diameter		0.40%	3.2	Gage
108	Straightness		0.40%	3.2	Gage
Minor					
201	Length, total		0.65%	3.2	Gage
202	Outside rod diameter		0.65%	3.2	Gage
203	Protective coating inadequate, damaged, or improper		0.65%	3.2	Visual
204	Workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Rod, Extension Assembly	1 OF 1	12546027
			NEXT HIGHER ASSEMBLY 12546032

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Overall length, max	315-3-4		3.2	Gage
Minor					
201	Workmanship		1.0%	3.7	Gage

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Spring, Compression	1 OF 1	12554909
			NEXT HIGHER ASSEMBLY: 12546032

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Free length		0.40%	3.2	Gage
102	Outside diameter		0.40%	3.2	Gage
Minor					
201	Diameter of wire		0.65%	3.2	Gage
202	Poor workmanship		1.0%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Gasket	1 OF 1	12546026
			NEXT HIGHER ASSEMBLY 12546032

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Outside diameter		0.65%	3.2	Gage
202	Inside diameter		0.65%	3.2	Gage
203	Thickness		0.65%	3.2	Gage
204	Poor workmanship		1.0%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Holder, Delay				12546039
					NEXT HIGHER ASSEMBLY 12554910
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Pitch diameter of threads		0.40%	3.2	Gage
102	Major diameter of threads		0.40%	3.2	Gage
103	Length of thread		0.40%	3.2	Gage
104	Distance from bottom to start of thread		0.40%	3.2	Gage
105	Diameter of blast exit hole		0.40%	3.2	Gage
106	True position of blast exit hole		0.40%	3.2	Gage
107	Depth of blast exit hole		0.40%	3.2	Gage
108	Diameter of relay assembly hole		0.40%	3.2	Gage
109	Diameter of top counterbore		0.40%	3.2	Gage
110	Concentricity of counterbore		0.40%	3.2	Gage
111	Depth from step to bottom of counterbore		0.40%	3.2	Gage
112	Outside diameter		0.40%	3.2	Gage
113	Concentricity of outside diameter		0.40%	3.2	Gage
114	Step wall thickness		0.40%	3.2	Gage
115	Depth of step		0.40%	3.2	Gage
116	Length from step to base		0.40%	3.2	Gage
Minor					
201	Workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Holder, Primer	1 OF 1	8831358
			NEXT HIGHER ASSEMBLY: 12554910

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Diameter of primer hole		0.40%	3.2	Gage
102	Depth of primer hole		0.40%	3.2	Gage
103	Diameter of lead hole		0.40%	3.2	Gage
104	Major outside diameter		0.40%	3.2	Gage
105	Minor outside diameter		0.40%	3.2	Gage
106	Length from bottom to crimping seat		0.40%	3.2	Gage
107	Length of crimping seat		0.40%	3.2	Gage
Minor					
201	Height of detonator stake		0.65%	3.2	Gage
202	Face angle (inside)		0.65%	3.2	Gage
203	Face angle (outside)		0.65%	3.2	Gage
204	Stake outside diameter		0.65%	3.2	Gage
205	Protective coating inadequate, damaged or improper		0.65%	3.2	Visual
206	Workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609A(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.11	Cup, Relay	1	1	8831361

NEXT HIGHER ASSEMBLY: 12554910

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Inside diameter		0.40%	3.2	Gage
103	Overall length		0.40%	3.2	Gage
104	Base thickness		0.40%	3.2	Gage
105	Radius at base		0.40%	3.2	Gage
106	Radius at fill end		0.40%	3.2	Visual
Minor					
201	Protective coating inadequate, damaged or improper		0.65%	3.2	Visual
202	Workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609A(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.12	Delay Assembly	1	1	12554910
				NEXT HIGHER ASSEMBLY 12546032

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Presence of M42 percussion primer		0.40%	3.2	Visual
102	Evidence of crimping		0.40%	3.2	Visual
103	X-ray		0.40%	3.4	4.5.1
104	Delay time		0.405	3.2	4.5.2
Minor					
201	Overall height		0.65%	3.2	Gage
202	Poor workmanship		1.0%	3.7	Visual

NOTES:

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 4		DRAWING NUMBER
4.4.2.13	Adapter				12546031
					NEXT HIGHER ASSEMBLY 12546032
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None define				
Major					
101	Major diameter of external thread at discharge end		0.40%	3.2	Gage
102	Pitch diameter of external thread at discharge end		0.40%	3.2	Gage
103	True position of external thread at discharge end		0.40%	3.2	Gage
104	Minor diameter of internal thread at discharge end		0.40%	3.2	Gage
105	Pitch diameter of internal thread at discharge end		0.40%	3.2	Gage
106	True position of internal thread at discharge end		0.40%	3.2	Gage
107	Major diameter of large external thread		0.40%	3.2	Gage
108	Pitch diameter of large external thread		0.40%	3.2	Gage
109	True position of large external thread		0.40%	3.2	Gage
110	Minor diameter of internal thread at fuze end		0.40%	3.2	Gage
111	Pitch diameter of internal thread at fuze end		0.40%	3.2	Gage
112	True position of internal thread at fuze end		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609A(AR)

PARAGRAPH	TITLE		SHEET 2 OF 4		DRAWING NUMBER
4.4.2.13	Adapter				12546031
					NEXT HIGHER ASSEMBLY 12546032
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
113	Largest outside diameter after knurling (max.)		0.40%	3.2	Gage
114	Second largest outside diameter		0.40%	3.2	Gage
115	Third largest outside diameter		0.40%	3.2	Gage
116	Smallest outside diameter		0.40%	3.2	Gage
117	True position of third largest outside diameter		0.40%	3.2	Gage
118	Diameter of large counterbore on fuze end		0.40%	3.2	Gage
119	True position of large counterbore on fuze end		0.40%	3.2	Gage
120	Diameter of small counterbore on fuze end		0.40%	3.2	Gage
121	True position of small counterbore on fuze end		0.40%	3.2	Gage
122	Diameter of undercuts (2 places)		0.40%	3.2	Gage
123	Diameter of Datum A		0.40%	3.2	Gage
124	Overall height		0.40%	3.2	Gage
125	Distance from face of discharge end to largest outside diameter		0.40%	3.2	Gage
126	Length of second largest outside diameter		0.40%	3.2	Gage
127	Length from largest outside diameter to beginning of large external thread		0.40%	3.2	Gage
128	Length from largest outside diameter to end of large external thread		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609A(AR)

PARAGRAPH	TITLE	SHEET 3 OF 4	DRAWING NUMBER
4.4.2.13	Adapter		12546031
			NEXT HIGHER ASSEMBLY 12546032

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
129	Length of external thread at discharge end		0.40%	3.2	Gage
130	Length of full thread at discharge end		0.40%	3.2	Gage
131	Perpendicularity of face at fuze end		0.40%	3.2	Gage
132	Radius at second largest outside diameter		0.40%	3.2	Gage
133	Radius at third largest outside diameter		0.40%	3.2	Gage
134	Depth of large counterbore on fuze end		0.40%	3.2	Gage
135	Full depth of counterbore at fuze end		0.40%	3.2	Gage
136	Perpendicularity of counterbore at fuze end		0.40%	3.2	Gage
137	Depth of undercut at fuze end		0.40%	3.2	Gage
138	Width of undercut at fuze end		0.40%	3.2	Gage
139	Depth of undercut at discharge end		0.40%	3.2	Gage
140	Width of undercut at discharge end		0.40%	3.2	Gage
Minor					
201	Chamfers at fuze end (2 places)		0.65%	3.2	Gage
202	Chamfer at discharge end		0.65%	3.2	Gage
203	Diameter of counterbores on knurled face (4 places)		0.65%	3.2	Gage
204	Depth of counterbores on knurled face (4 places)		0.65%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609A(AR)

PARAGRAPH	TITLE		SHEET 4 OF 4		DRAWING NUMBER
4.4.2.13	Adapter				12546031
					NEXT HIGHER ASSEMBLY 12546032
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
205	True position of counterbores on knurled face (4 places)		0.65%	3.2	Gage
206	Distance from counterbore on knurled face to top of largest outside diameter (4 places)		0.65%	3.2	Gage
207	Protective coating inadequate, damaged or improper		0.65%	3.2	Visual
208	Workmanship		1.0%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.14	Fuze, Mine, AT, M607 Loaded Assembly				8833783
					NEXT HIGHER ASSEMBLY 12546032
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Boxed end pin missing		100%	3.2	Visual
Major					
101	Assembly damaged (dented, deformed, cracked, or punctured)		0.40%	3.2	Visual
Minor					
201	Protective coating damaged (dented, deformed, cracked, or punctured)		0.65	3.2	Visual
202	Marking misleading or unidentifiable		0.65%	3.2	Visual
203	Workmanship		1.0%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.4.3 Inspections to be performed. Each part shall be inspected for all dimensions, except those dimensions that have been machined, and characteristics specified on the applicable detail drawing.

4.4.4 Inspection equipment. The inspection equipment required to perform the examination and tests prescribed in this specification is identified in the "Paragraph Reference/Inspection Method" column in Classification of Defects and Tests forms beginning with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein. All test procedures shall be submitted a minimum of 30 days prior to testing.

4.5 Methods of inspection.

4.5.1 X-ray. The delay assembly shall be x-rayed, in accordance with 4.4.4, for the presence of the delay composition and the relay assembly. The x-ray shall not show the presence of cracks, voids, etc.

4.5.2 Delay time. This test is to be performed by the contractor with the government's technical agency's concurrence as per 4.4.4.

5. PACKAGING

5.1 Preservation and packaging.

5.1.1 Level C. The parts and assemblies for Adapter & Fuze Assembly M624 shall be packed in accordance with MIL-STD-1169 in such a manner that no damage will occur during shipment.

5.2 Packing.

5.2.1 Level C. The parts and assemblies for Adapter & Fuze Assembly M624 shall be packed in accordance with MIL-STD-1169 Separately designated items shall not be packed together.

5.3 Data cards. Data card information shall be as specified in Specification MIL-A-2550.

5.4 Shipping. When component parts from more than one lot are shipped as a carload, each lot shall be kept separate and the division between lots clearly indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

5.5 Marking and labeling. Marking of the cartons shall be in accordance with Standard MIL-STD-129 and Specification MIL-P-10025.

6. NOTES

6.1 Ordering data. See MIL-A-48078.

6.2 Data cards. (See MIL-A-48078). Distribution of data cards shall include the following: Commander, U S ARDEC, ATTN: AMSMC-QAT-M(D), Picatinny Arsenal, New Jersey 07806-5000.

6.3 Submission of inspection equipment designs for approval. (See MIL-A-48078). Equipment designs shall be submitted as required to: Commander, U S ARDEC, ATTN: AMSMC-QAT-I(D), Picatinny Arsenal, New Jersey 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the Contract. Unless otherwise specified DI-R-1714 will apply.

6.4 Drawings. Drawings listed in section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as, US Army Armament Research and Development Command (ARRADCOM), Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities are now under the cognizance of ARDEC.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

6.6 Subject term (key word) listing.
Adapter
Fuze
Parts
Extension Rod Assembly
Compression spring
Adapter Assembly
Delay time

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A521)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-A-70609A (AR)	ADAPTER & FUZE, ASSEMBLY: M624, PARTS FOR

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.