MILITARY SPECIFICATION

CONTAINER, AMMUNITION, METAL, FOR CARTRIDGE 105MM
APFSDS-T, XM833

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the requirements, quality assurance provisions and packaging for one type of metal container used for kinetic energy tank ammunition.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specification and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

TT-C-490	-Cleaning and Preparation of Ferrous and Zinc Coated Surfaces for Organic Protective Coatings

MILITARY

MIL-W-12332	-Welding Resistance, Spot, Seam and Production, for Fabricating Assemblies of Low-Carbon Steel
MIL-A-48078	-Ammunition, Standard Quality Assurance Provisions, General Specification For

FSC 8140

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to Commander, US Army Armament Research and Development Command, Attn DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	-Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-171	-Finishing of Metal and Wood Surfaces
MIL-STD-1188	-Commercial Packaging of Supplies and Equipment
MIL-STD-1261	-Welding Procedures for Constructional Steel

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein."

DRAWINGS (see 6.2)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

9345252	-Container, Ammunition, Metal for Cartridge 105MM, APFSDS-T, XM833

(Copies of specifications, standards, handbooks, drawings and publications required by manufacturers in connections with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer).

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING MATERIALS

ASTM-D412	-Tension Testing of Vulcanized Rubber, Standard Method of
ASTM-D2240	-Indentation Hardness of Rubber and Plastics by Means of a Durometer, Standard Method of Test for
ASTM-E8	-Tension Testing of Metallic Materials, Standard Method of

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING MATERIALS (Cont'd)

ASTM-E18 -Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials, Test for

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Materials. Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Containers. The containers (container assemblies) shall comply with all requirements specified on drawing (dwg.) 9345252 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Welding. The welding shall comply with the requirements of MIL-W-12332 or MIL-STD-1261.

3.3.1 Tensile strength (if applicable). The tensile strength of the longitudinal body weld shall be not less than 65 percent of the tensile strength of body material when tested as specified in 4.5.1.

3.3.1.1 Tensile strength of body material. The tensile strength of the body material shall be not less than 47,000 pounds per square inch (psi) nor greater than 53,000 psi when tested as specified in 4.5.1.

3.4 Painted surface. The painted surfaces of the container shall comply with the requirements of TT-C-490. However, the film thickness and salt spray requirements of TT-C-490 shall not apply to the interior surfaces and the welded spots and sharp corners of the exterior surface of the container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

3.5 Cover assembly. Upon assembly of the cover assembly to the body assembly (body weldment), the cover assembly shall freely engage and rotate within the body assembly. As the cover assembly is rotated with the "Y" handle in the open position, the "Y" handle shaft ends shall freely engage into the respective bayonet slots of the rim. When the "Y" handle is in the closed position (rotated 180°), the spring clip shall engage and lock the handle in place. When the spring clip is disengaged and the handle rotated to the open position, the cover assembly shall disengage from the body assembly.

3.6 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.7 Workmanship.

3.7.1 Containers. The containers shall be regular, smooth, and free from wrinkles, pin holes, cracks, rough spots, burrs, sharp edges and any other defect that might affect the serviceability, durability, safety and appearance of the container.

3.7.2 Paint coating. The paint coating shall be in accordance with applicable drawings and comply with instructions in MIL-STD-171.

3.7.3 Parts. All parts shall be free of chips, dirt, grease, rust and foreign material. The cleaning method used shall not be injurious to any of the parts nor shall any of the parts be contaminated by the cleaning agents used.

3.7.4 Inserts. The inserts shall be regular, smooth and free from any creases, wrinkles, cracks, rips, tears and any other defect which might offset the servicability, durability, safety and appearance of the insert.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of five (5) painted container assemblies, five (5) painted cover assemblies, five (5) unpainted cover assemblies, and ten (10) each of every subassembly and component (unpainted).

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

TABLE I

FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
	Assemblies and components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Container assemblies, painted				
	a. Examination for defects	5		3.2	4.4.2.20
	b. Air pressure	5		3.2	4.5.8.2
	Body assembly (weldment), unpainted				
	a. Examination for defects	5		3.2	4.4.2.19
	b. Air pressure	5		3.2	4.5.8.1
	c. Weld rim to body (see Note)	5		3.2	4.5.2/Dwg. 9344032
	Cover assembly, unpainted				
	a. Examination for defects	5		3.2	4.4.2.12
	b. Air pressure	5		3.2	4.5.8.1
	Cover assembly, painted				
	Examination for defects	5		3.2	4.4.2.13
	Body, unpainted				
	a. Examination for defects	10		3.2	4.4.2.17
	b. Tensile strength (see Note)	5		3.2	4.5.1/Dwg. 9344027
	Spring, unpainted				
	a. Examination for defects	10		3.2	4.4.2.2
	b. Embrittlement (see Note)	3		3.2	4.5.3/Dwg. 9344042

NOTES: The weld security inspections, spring tests and gasket tensile stress test shall be performed after the other inspections have been performed on the applicable samples.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

TABLE I (Cont'd)

FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
	Assemblies and components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	c. Hardness (see Note)	3		3.2	4.5.4/Dwg. 9344042
	d. Deflection load (see Note)	3		3.2	4.5.5/Dwg. 9344042
	Gasket				
	a. Examination for defects	10		3.2	4.4.2.10
	b. Hardness	3		3.2	4.5.7/Dwg. 9344033
	c. Tensile stress (see Note)	3		3.2	4.5.6/Dwg. 9344033
	Remaining subassemblies and components				
	Examination for defects	10		3.2	Applicable subparagraph of 4.4.2

NOTES: The weld security inspections, spring tests and gasket tensile stress test shall be performed after the other inspections have been performed on the applicable samples.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil/ -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of containers shall contain material from lots with the same interfix number from one manufacturer.

4.4.2 Examination - See MIL-A-48078. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Clamp				9344043
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of hole (two places)		0.40%	3.2	Gage
102	Vertical location of holes		0.40%	3.2	Gage
103	Horizontal location of holes		0.40%	3.2	Gage
104	True position of holes		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Spring				9344042
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Spring embrittlement	(a)		3.2	4.5.3
102	Hardness	(a)		3.2	4.5.4
103	Deflection load	(b)		3.2	4.5.5
104	Diameter of hole (two places)		0.40%	3.2	Gage
105	True position of holes		0.40%	3.2	Gage
106	Vertical location of holes		0.40%	3.2	Gage
107	Horizontal location of holes		0.40%	3.2	Gage
108	Radius of bend		0.40%	3.2	Gage
109	Thickness		0.40%	3.2	Gage
110	Length from center of holes to lower edge of bend		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES: (a) Five springs from each heat treatment lot. (b) Ten springs from each heat treatment lot.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Support, shaft		9344035
			NEXT HIGHER ASSEMBLY 9344044

CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of large hole and slot		0.40%	3.2	Gage
102	Diameter of small hole		0.40%	3.2	Gage
103	True position of large hole and slot		0.40%	3.2	Gage
104	Vertical location of large hole and slot		0.40%	3.2	Gage
105	Horizontal location of large hole and slot		0.40%	3.2	Gage
106	True position of small hole		0.40%	3.2	Gage
107	Vertical location of small hole		0.40%	3.2	Gage
108	Horizontal location of small hole		0.40%	3.2	Gage
109	Distance between large hole and slot		0.40%	3.2	Gage
110	Diameter of holes located on side to be assembled with spring and clamp		0.40%	3.2	Gage
111	True position of holes located on side (used for assembly of spring and clamp)		0.40%	3.2	Gage
112	Vertical location of holes on side		0.40%	3.2	Gage
113	Horizontal location of holes on side		0.40%	3.2	Gage
114	Wall thickness		0.40%	3.2	Gage
115	Distance between center line of large hole and slot, and the tab used to assemble the spring and clamp		0.40%	3.2	Gage
Minor					
201	Radius not present on edges of tab		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Shaft support assembly				9344044
					NEXT HIGHER ASSEMBLY 9344040
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Component missing		0.40%	3.2	Visual
102	Rivet missing or improperly applied		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Handle		9344036
			NEXT HIGHER ASSEMBLY 9344031

CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of small hole		0.40%	3.2	Gage
102	True position of small hole		0.40%	3.2	Gage
103	Vertical location of small hole		0.40%	3.2	Gage
104	Horizontal location of small hole		0.40%	3.2	Gage
105	Width of shaft hexhole (three (3) readings 60°apart), 2 places		0.40%	3.2	Gage
106	Vertical location of shaft hexhole, 2 places		0.40%	3.2	Gage
107	Horizontal location of shaft hexhole, 2 places		0.40%	3.2	Gage
108	Largest width of handle		0.40%	3.2	Gage
109	Wall thickness		0.40%	3.2	Gage
110	Distance from center of shaft hexholes to nearer edge of spring slot		0.40%	3.2	Gage
111	Width of spring slot		0.40%	3.2	Gage
Minor					
201	Distance from center of shaft hexhole to outer edge of tabs		0.65%	3.2	Gage
202	Overall length of tabs		0.65%	3.2	Gage
203	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Shaft				9344037
					NEXT HIGHER ASSEMBLY
					9344031
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Width across flats of hexagon segment (three readings, 60° apart)		0.40%	3.2	Gage
102	Length of hexagon segment of shaft		0.40%	3.2	Gage
103	Length of small diameter segment (two places)		0.40%	3.2	Gage
104	Large diameter (two places)		0.40%	3.2	Gage
105	Small diameter (two places)		0.40%	3.2	Gage
106	Total length of large diameters and hexagon segments		0.40%	3.2	Gage
107	Small diameter segment not tangent to large diameter segment and side of hexagon segment		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Washer				9344038
					NEXT HIGHER ASSEMBLY 9344031
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter		0.40%	3.2	Gage
102	Outside diameter		0.40%	3.2	Gage
103	Height		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Retainer, washer				9344041
					NEXT HIGHER ASSEMBLY
					9344031
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of hole		0.40%	3.2	Gage
102	Inside diameter		0.40%	3.2	Gage
103	Wall thickness		0.40%	3.2	Gage
104	Inside depth		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Cover				9344034
					NEXT HIGHER ASSEMBLY
					9344040
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Wall thickness		0.40%	3.2	Gage
103	Depth of groove		0.40%	3.2	Gage
104	Width of groove		0.40%	3.2	Gage
105	Height of cover		0.40%	3.2	Gage
106	Height of threads, minimum		0.40%	3.2	Gage
107	Location of air test hole with rib		0.40%	3.2	Gage
108	Location of ribs to each other		0.40%	3.2	Gage
109	Flatness of bottom surface inside annular ring and surrounding air test hole		0.40%	3.2	Gage
110	Inside depth of annular ring		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil-- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.10	Gasket				9344033
					NEXT HIGHER ASSEMBLY
					9344031
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Tensile stress	5		3.2	4.5.6
102	Hardness	5		3.2	4.5.7
103	Inside diameter, maximum		0.40%	3.2	Gage
104	Large width		0.40%	3.2	Gage
105	Middle width		0.40%	3.2	Gage
106	Small width		0.40%	3.2	Gage
107	Height		0.40%	3.2	Gage
108	Height from top edge of lip		0.40%	3.2	Gage
109	Misalignment of joint		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9344040
4.4.2.11	Cover weldment				NEXT HIGHER ASSEMBLY 9344031
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Component missing		0.40%	3.2	Visual
102	Weld missing, incomplete or visually inadequate		0.40%	3.2	Visual/Manual
103	Location of shaft support slot with respect to cover air hole		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.12	Cover assembly, prior to painting				9344031
					NEXT HIGHER ASSEMBLY
					9345252
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Air pressure		100%	3.2	4.5.8.1/Dwg. 9345252
102	Component missing or inadequately assembled		0.40%	3.2	Visual
103	Gap max remaining after crimping over shaft		0.40%	3.2	Gage
104	Rotating of shaft inadequate after crimping		0.40%	3.2	Manual
Minor					
201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.13	Cover assembly, after painting				9344031
					NEXT HIGHER ASSEMBLY 9344026
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Gasket not secured or secured improperly to cover		0.40%	3.2	Visual
Minor 201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.14	Rim				9344028
					NEXT HIGHER ASSEMBLY 9344032
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Wall thickness		0.40%	3.2	Gage
102	Diameter of larger hole on side of rim		0.40%	3.2	Gage
103	Diameter of smaller hole on side of rim		0.40%	3.2	Gage
104	Location of larger hole		0.40%	3.2	Gage
105	Location of smaller hole		0.40%	3.2	Gage
106	Location of bayonet slot, 4 places		0.40%	3.2	Gage
107	Inside dimension across flats, 2 places		0.40%	3.2	Gage
108	Inside dimension across corner, 2 places		0.40%	3.2	Gage
Minor					
201	Drainage hole missing		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.15	Ring				9344029
					NEXT HIGHER ASSEMBLY 9344032
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Wall thickness		0.40%	3.2	Gage
102	Diameter of larger hole on side on ring		0.40%	3.2	Gage
103	Diameter of smaller hole on side on ring		0.40%	3.2	Gage
104	Location of larger hole with respect to edge of ring		0.40%	3.2	Gage
105	Location of smaller hole with respect to edge of ring		0.40%	3.2	Gage
106	Inside dimensions across flats, 2 places		0.40%	3.2	Gage
Minor					
201	Drainage hole missing		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.16	Bottom				9344030
					NEXT HIGHER ASSEMBLY 9344032
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Wall thickness		0.40%	3.2	Gage
102	Length, minimum		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.17	Body				9344027
					NEXT HIGHER ASSEMBLY 9344032
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Tensile strength	5		3.2	4.5.1
102	Wall thickness		0.40%	3.2	Gage
103	Inside diameter, minimum		0.40%	3.2	Gage
104	Length, minimum		0.40%	3.2	Gage
105	Weld incomplete or missing (if applicable)		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.18	Plug, stacking				9344045
					NEXT HIGHER ASSEMBLY
					9344032
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Plug (smaller) diameter		0.40%	3.2	Gage
102	Knob (larger) diameter		0.40%	3.2	Gage
103	Length of plug		0.40%	3.2	Gage
104	Length of knob		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.19	Body weldment (body assembly), prior to painting		9344032
			NEXT HIGHER ASSEMBLY 9344026

CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Air pressure		100%	3.2	4.5.8.2
102	Weld of rings to body	5		3.2	4.5.2
103	True position of holes of ring, rim and stacking plug		0.40%	3.2	Gage
104	Location of hole in rim relative to holes in inside rings and stacking plugs		0.40%	3.2	Gage
105	Location of hole in rim relative to hole in outside ring and stacking plug		0.40%	3.2	Gage
106	Perpendicularity of ring and rims with Datum-A		0.40%	3.2	Gage
107	Any weld of ring, rim or bottom to body missing, incomplete or visually inadequate		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.20	Container, ammo, metal				9344026
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Cover assembly test		0.40%	3.5	Visual/Manual/4.5.9
102	Air pressure test		0.40%	3.2	4.5.8.2
103	Compression of gasket (Four readings, 90° apart)		0.40%	3.2	Gage
Minor					
201	Protective finish damaged, bare spots exposing metal, etc.		0.65%	3.2	Visual
202	Marking missing, incomplete or illegible (see Dwg. 9344032)		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.21	Support, sabot				9345282
					NEXT HIGHER ASSEMBLY
					9345284
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Total length minimum		1.0%	3.2	Gage
202	Material certification	(a)		3.2	Certification
203	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES

(a) With each lot of material submitted.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.22	Spacer				9345281
					NEXT HIGHER ASSEMBLY
					9345284
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Material certification	(a)		3.2	Certification
202	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES: (a) With each lot of material submitted.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.23	Pad				9345280
					NEXT HIGHER ASSEMBLY 9332584
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Material certification	(a)		3.2	Certification
202	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES (a) With each lot of material submitted.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.24	Cushion				9345278
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Thickness, minimum		1.0%	3.2	Gage
202	Material certification	(a)		3.2	Certification
203	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:
(a) With each lot of material submitted.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.25	Cushion assembly				9332584
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Component missing or damaged		1.0%	3.2	Visual
202	Components improperly adhered		1.0%	3.2	Dwg. 9275690
203	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.26	Cushion				9345279
					NEXT HIGHER ASSEMBLY
					9332584
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Thickness, minimum		1.0%	3.2	Gage
202	Material certification	(a)		3.2	Certification
203	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES: (a) With each lot of material submitted.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.27	Support				9332598
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Length, minimum		1.0%	3.2	Gage
202	Outside, diameter, minimum		1.0%	3.2	Gage
203	Inside diameter, maximum		1.0%	3.2	Gage
204	Material certification	(a)		3.2	Certification
205	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES

(a) With each lot of material submitted.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.28	Lift collar assembly				9345282
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Circumferential tape missing or improper		1.0%	3.2	Visual
202	Strap tape missing or improper		1.0%	3.2	Visual
203	Material certification	(a)		3.2	Certification
204	Tear strip tab missing or improper		1.0%	3.2	Visual
205	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:

(a) With each lot of material submitted.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63521 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.29	Container, ammo, metal, for cartridge 105MM, APFSDS-T, XM833				9345252
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Any component missing or damaged		0.40%	3.2	Visual
Minor 201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First article and Quality conformance inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection.

4.5.1 Tensile strength. The tensile strength shall be determined in accordance with ASTM-E8. Six bodies shall be randomly selected for this test. From each body, three specimens shall be selected at random for determination of body material tensile strength. Also, from each body, four specimens approximately equally spaced along the axis shall be taken at right angles to the weld and the tensile strength of their welds shall be determined. Each of these values shall be compared with the lowest determined value of the body material tensile strength for compliance with the requirement of 3.3.1. If one or more specimens (longitudinal body weld or body material) fail to comply with 3.3.1 or 3.3.1.1, that sample body shall be classed defective. If two or more sample bodies are classed defective, the lot shall be rejected.

4.5.2 Weld of rim to body. The test shall be performed in accordance with ASTM-E8. Five body assemblies shall be randomly selected from each lot and tested. If any sample fails to comply with the applicable requirement, the lot shall be rejected.

4.5.3 Spring embrittlement. Five springs shall be randomly selected from each heat treatment lot for this test. Each spring shall be repeatedly stretched with increasing loads until it does not return to its original free height. That point shall indicate minimum distortion. Any spring which fractures prior to extension to minimum distortion shall be classed defective. If any spring fails to meet the applicable requirement, the heat treatment lot shall be rejected.

4.5.4 Hardness of spring. The hardness of the spring shall be determined in accordance with ASTM-E18. Five springs shall be randomly selected from each heat treatment lot and tested. If any spring fails to meet the applicable requirement, the heat treatment lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

4.5.5 Deflection load of spring. Ten springs shall be randomly selected from each heat treatment lot for this test. Each spring shall be clamped and a load applied in accordance with dwg. 9344042. A measurement shall be made for the required deflection. If any spring fails to meet the applicable requirement, the heat treatment lot shall be rejected.

4.5.6 Tensile stress of gasket. The tensile stress shall be determined in accordance with ASTM-D412. Five gaskets shall be randomly selected from each lot for this test. If any gasket fails to meet the applicable requirement, the lot shall be rejected.

4.5.7 Hardness of gasket.- The hardness shall be determined in accordance with ASTM-D2240. Five gaskets shall be randomly selected from each lot for this test. If any gasket fails to meet the applicable requirement, the lot shall be rejected.

4.5.8 Air pressure test

4.5.8.1 Air pressure of unpainted cover assembly and unpainted body assembly. The core assemblies and body assemblies shall be inspected 100 percent. Subject the cover assembly and container body to the internal air pressure, specified in the applicable container assembly drawing, for one of the test times specified. For the cover assembly, apply the pressure when the cover assembly (equipped with a gasket) is assembled to a master body assembly equipped with a gasket (or its equivalent). For the body assembly, apply the pressure when the body assembly is assembled to a master cover (or equivalent) and gasket. The master cover and the master body assembly shall be provided with satisfactory means for applying and maintaining the pressure during the test and for showing evidence of leakage. Observation shall be made for a pressure drop exceeding the requirement for the corresponding test time (as specified in the applicable drawing). A cover assembly or body assembly which exceeds the requirement, shall be classed defective and removed from the lot.

4.5.8.2 Air pressure of painted container assembly. Subject the container assembly to the internal air pressure, specified in the applicable container assembly drawing, for one of the test times specified. Observation shall be made for a pressure drop exceeding the requirement for the corresponding test time (as specified in the applicable drawing). A container assembly, which exceeds the requirement, shall be classed defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

4.5.9 Cover assembly test. Upon assembly of the body and cover, the cover shall freely engage and rotate within the body. The Y-handle shall engage into the respective bayonet slots of the rim without interference when in the clamping position. The Y-handle when disengaged and in the open position shall disengage the cover from the body. Any assembly which fails to meet this criteria shall be classed defective.

5. PACKAGING

5.1 Packaging requirements. None required.

5.2 Packing. Packing shall be commercial. Metal ammunition containers shall be prepared in accordance with paragraph 2.3.1 of MIL-STD-1188.

5.3 Marking. Shipping marking shall comply with MIL-STD-1188 and the following additional instructions. No shipping marking shall be placed directly on the containers. Commercial shipping tags attached with wire shall be used unless otherwise specified. The following information shall be shown: Item name and model number, part number and revision, contract number, lot number and date, name and address of manufacturer. If containers are bundled, boxed or palletized, the gross weight and quantity shall be included. The above information may be placed on pallets or boxes by labeling or stenciling.

6. NOTES

6.1 Ordering data. See MIL-A-48078.

6.2 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

6.3 Submission of inspection equipment for design approvals - See MIL-A-48078. Submit designs as required to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAT-I, Dover, New Jersey 07801.

Custodian:
Army-AR

Preparing activity:
Army-AR

Project 8140-A543

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARMAMENT RESEARCH & DEVELOPMENT
COMMAND
ATTN: DRDAR-QAT
DOVER. NEW JERSEY 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS This form is provided to solicit beneficial comments which may improve this document and enhance its use DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government Fold on lines on reverse side, staple in corner and send to preparing activity Attach any pertinent data which may be of use in improving this document If there are additional papers, attach to form and place both in an envelope addressed to preparing activity A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed

NOTE This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-63521 Container, Ammunition, Metal For Cartridge 105MM APFSDS-T, XM833

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1 ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDED WORDING CHANGE

C REASON FOR RECOMMENDED CHANGE(S)

2 REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:27Z
Check the source to verify that this is the current version before use.