MIL-C-70618A (AR)
17 October 1988
SUPERSEDING
MIL-C-70618
3 February 1988

MILITARY SPECIFICATION

CIRCUIT CARD ASSEMBLY, GUNFIRE SIMULATOR: 12725086

This Specification is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes requirements for manufacture and acceptance of the circuit card assembly (CCA), used in the Gunfire Simulator (GUFS), also known as the Target Kill Simulator (TKS). (See 6.1).

2. APPLICABLE DOCUMENTS.

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

| | |
|---|---|
| MIL-F-13926 | -Fire Control Material, General Specification Governing the Manufacture and Inspection of |
| MIL-P-14232 | -Parts, Equipment and Tools for Army Materiel, Packaging of |
| MIL-I-45607 | -Inspection Equipment, Acquisition, Maintenance and Disposition of |

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament, Munitions, and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 6920

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

| | |
|---|---|
| MIL-STD-105 | -Sampling Procedures and Tables for Inspection by Attributes |
| MIL-STD-109 | -Quality Assurance Terms and Definitions |
| MIL-STD-454 | -Standard General Requirements for Electronic Equipment |
| MIL-STD-810 | -Environmental Test Methods and Engineering Guidelines |

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extend specified herein. Unless otherwise specified, the issues shall be those in effect on the date of solicitation.

DRAWINGS (See 6.3)

| | |
|---|---|
| 12725085 | -Gunfire Simulator |
| 12725086 | -Circuit Card Assembly, Gunfire Simulator |

SPECIAL PACKAGING INSTRUCTIONS

| | |
|---|---|
| P12725086 | -Special Packaging Instructions for the Circuit Card Assembly, Gunfire Simulator |

(Copies of specifications, standards, handbooks, drawings, publications, and other Government documents required by the contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets or MS standards) the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS.

3.1 General description. The Gunfire Simulator (GUFS) Circuit Card Assembly (CCA) generates the electronic signals necessary to process fire commands to ignite pyrotechnic cartridges (M21 or Smoke) used to simulate gunfire effects.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on Drawing (Dwg) 12725086, all associated drawings, and with all requirements specified in applicable specifications and standards. Where applicable, the CCA shall meet the requirements of MIL-F-13926 as follows:

a. Dimensions and tolerances
b. Inorganic protective surface finishes
c. Part identification and marking
d. Workmanship
e. Soldering electrical connections

3.2.1 Materials. Materials shall be in accordance with applicable drawings and specifications.

3.3 Performance.

3.3.1 Firing command. The CCA upon receipt of a firing command on Pin N (M21) or Pin I or J (Smoke) of the GUFS input connector shall verify that the command is valid before processing the command to the firing circuits. A valid firing command shall satisfy the following conditions:

| | | |
|---|---|---|
| a. | Minimum voltage: | 9.3 VDC |
| b. | Maximum voltage: | 13.6 VDC |
| c. | Minimum pulse width: | 50 milliseconds |
| d. | Maximum duration: | infinite |

3.3.1.1 Firing command interrupt. Once a valid firing command has been detected by the CCA, the firing sequence shall be initiated and all further inputs shall be interrupted until the firing sequence, including the firing pulse lockout period, has been completed.

3.3.1.2 Firing pulse lockout. A minimum delay of two (2) seconds shall be provided between the completion of one firing sequence and initiation of a second firing sequence in response to a valid command. The CCA shall not respond to any input commands sensed during the firing pulse lockout period.

3.3.2 Firing sequence. The CCA shall provide two separate firing modes:

a. Sequential firing of GUFS ports 1 through 20.
b. Partitioned firing of GUFS ports 1 through 15 and ports 16 through 20. Each partitioned segment shall be fired in sequence as commanded.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

3.3.2.1 Sequential mode (M21). Upon receipt of a valid firing command on Pin N a single firing pulse shall be directed to the next firing port in sequence starting with port 1 and continuing through port 20. Each port will be fired once and the circuitry shall retain last port firing sequence until the system is reset and rearmed.

3.3.2.2 Partitioned mode (M21 and smoke). Upon receipt of a valid firing command on Pin I or J of the GUFS, the CCA shall automatically partition itself into two firing sections. Ports 1 through 15 shall fire when commanded by an input pulse on Pin N (M21). Ports 16 through 20 shall fire when commanded by an input on Pins I or J (Smoke). In response to a valid command the ports in each section shall fire a single output in sequence within the designated section. Each port shall be fired once and the circuitry shall retain the last port fired sequence for each section until the system is reset and rearmed.

3.3.2.3 Input-transfer. When the last port is fired in any firing mode for either a sequential or a partitioned GUFS device, the CCA shall automatically transfer the next firing command directly to the input-transfer connector (J4). The firing command transferred shall control any GUFS unit connected to the GUFS input-transfer connector in tandem with the basic device.

3.3.2.4 Last port fired. The CCA shall contain a non-volatile resettable memory for each firing section. The memory circuits shall increment one position each time a valid firing command is detected. Last position commanded per section shall be retained until an automatic reset command is received. Power interruptions or shutdown of the primary power source shall not cause loss, change, or reset of the memory circuits. Memory circuits shall automatically reset when the ARM/SAFE switch is placed in the SAFE position as part of the normal GUFS reloading sequence.

3.3.3 Output command.

3.3.3.1 Output pulse power. The firing circuits shall provide a current regulated output of 2.0 to 2.2 amps for a duration of 110-140 milliseconds at each commanded firing port. This output shall be independent of the load applied to the output port from zero to three ohms.

3.3.3.2 Safety interlock. The CCA shall normally maintain a short circuit across all output lines. Power shall only be directed to the specified port to be fired. The short across the port to be fired is only removed during the firing cycle for that port.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

3.3.4 Input power. The CCA shall automatically monitor the input power lines to prevent inadvertent or false firing commands to be generated when subjected to the following input conditions:

a. Power up transients.
b. Low power condition: Less than 10.5 VDC
c. Overvoltage condition: Greater than 13.6 VDC
d. Reverse voltage.
e. RFI/EMI transients.

3.3.4.1 Power-up interrupt. The CCA firing circuits shall be interrupted for 60 to 75 seconds after initial power up (Arming) of the GUFS. If during the power up lockout period, (60 to 75 seconds) transients, power interruptions, or firing commands are sensed, the power up lockout period will be reset. A minimum of 60 seconds of uninterrupted main power must be sensed before the firing circuits can be energized.

3.3.4.2 Low power interrupt. The CCA firing circuits shall not be energized if the input firing signal is less than 9.3 VDC.

3.3.4.3 Power line protection. The CCA shall include protection against overvoltage and reverse voltage input power conditions. Protection shall also be provided against the effects of both positive and negative power line transient inputs in excess of requirements of 3.3.1.

3.3.5 Input/output interconnections. Input/output connections to the CCA shall be provided by four (4) connector receptacles:

| | | |
|---|---|---|
| a. | Input Receptacle | (J3) |
| b. | Input-transfer Receptacle | (J4) |
| c. | Output Receptacle (Ports 1-10) | (J1) |
| d. | Output Receptacle (Ports 11-20) | (J2) |

Wiring to the respective receptacles will be in accordance with Table I.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

TABLE I. Wiring connections CCA

| RECEPTACLE | J3 | J4 | J1 | J2 |
|---|---|---|---|---|
| FUNCTION | INPUT | INPUT TRANSFER | OUTPUT 1-10 | OUTPUT 11-20 |
| PIN 1 | M21 | +12 VDC | COMMON | COMMON |
| PIN 2 | SMOKE | N/A | PORT 1 | PORT 11 |
| PIN 3 | SMOKE | N/A | PORT 2 | PORT 12 |
| PIN 4 | COMMON | COMMON | PORT 5 | PORT 15 |
| PIN 5 | MEMORY COMMON | SMOKE | PORT 10 | PORT 20 |
| PIN 6 | +12 VDC | M21 | PORT 6 | PORT 16 |
| PIN 7 | N/A | N/A | COMMON | COMMON |
| PIN 8 | N/A | N/A | PORT 3 | PORT 13 |
| PIN 9 | N/A | N/A | PORT 7 | PORT 17 |
| PIN 10 | N/A | N/A | PORT 8 | PORT 18 |
| PIN 11 | N/A | N/A | PORT 4 | PORT 14 |
| PIN 12 | N/A | N/A | PORT 9 | PORT 19 |
| PIN 13 | N/A | N/A | COMMON | COMMON |



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

3.4 Environmental. The CCA shall meet the requirements specified herein unless otherwise specified.

3.4.1 Room ambient temperature. The requirements of this specification shall be met with the CCA stabilized at room ambient temperature of +10°C (50°F) to 32°C (90°F), unless otherwise specified.

3.4.2 Operating temperature. The CCA shall meet the performance requirements in 3.3.2 through 3.3.5, inclusive, when exposed to temperatures from -32°C (-25°F) to +69°C (149°F).

3.4.3 Vibration. The CCA shall meet the requirements of 3.3 after being subjected to Method 514.3 of MIL-STD-810, Procedure II, for 90 minutes of one-inch double amplitude at 5 Hz in the one axis perpendicular to the plane of the PWB and one axis in the plane of the PWB. Testing shall be conducted in a fixture which duplicates the CCA mounting configuration when installed in the GUFS's end application device.

3.4.4 Reliability. Each circuit card assembly shall be subject to a burn-in test to screen out any latent defects which would limit operational reliability in the GUFS. This shall be accomplished by subjecting each board to the burn-in test cycle and verifying performance per 3.3.

3.4.5 Conformal coating. Each CCA, after completion of a burn-in test sequence, shall be conformally coated with a minimum 3 Mil coating.

3.5 First article inspection. When specified in the contract or purchase order, a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.3).

3.6 Workmanship. The workmanship requirements of MIL-F-13926 and applicable requirements of MIL-STD-454 shall apply.

4. QUALITY ASSURANCE PROVISIONS.

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define quality assurance terms used herein.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5 and all applicable drawings. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 General provision. The component and subassembly inspection requirements of MIL-F-13926 and MIL-STD-454 form a part of the Quality Assurance Provisions of this specification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3)

b. Quality conformance inspection (see 4.4)

c. Special sampling inspection (see 4.5).

4.2.1 Inspection conditions. Unless otherwise specified, all examinations and tests shall be conducted at the following standard ambient conditions:

a. Temperature - +50°F to +90°F

b. Relative humidity - 90% RH Max

c. Pressure - 28 to 32 inches of Hg.

4.3 First article inspection.

4.3.1 First article submission. The contractor shall submit a first article sample as designated by the contracting officer consisting of three CCA for inspection in accordance with 4.3.2.

4.3.2 Inspections to be performed. First article assemblies, components and test specimens may be subjected by the Government to any or all of the examinations and tests specified in Table II and Table III herein and to any or all requirements of the applicable drawings.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.3.3 Rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of any CCA to comply with any of the stated requirements.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. The term "inspection lot" is defined as a homogeneous collection of units of product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements. Units of product selected for inspection shall represent only the inspection lot from which they are drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specifications revisions, and complies with the provisions for submission of product as specified in MIL-STD-105. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of inspection procedure which is being applied to determine conformance with requirements.

4.4.2 Examinations and tests.

4.4.2.1 Components, assemblies and subassemblies. All components, assemblies and subassemblies shall be inspected in accordance with the inspection provisions contained in this specification and the Quality Assurance Provisions (QAP) listed in the Technical Data Package (TDP). In the absence of QAPs, the applicable quality assurance provisions of MIL-F-13926 shall apply.

4.4.2.2 Final acceptance inspection. Subsequent to first article approval, examination and tests related to Section 3 herein shall be performed on a single defect (individual characteristic) basis in accordance with MIL-STD-105 and the sampling plans specified in 4.4.2.3 herein. Examination and test for packaging and marking shall be in accordance with MIL-P-14323 and Section 5 herein. The tabulated classification of defects in 4.4.2.3 shall constitute the minimum inspection to be performed by the supplier after first article approval and prior to Government acceptance or rejection by item or lot.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.4.2.3 Functional tests. Each CCA unit will be functionally tested in accordance with the characteristics noted in Table II.

TABLE II. Functional tests

(100% inspection)

| Characteristics | Requirements | Test Procedure |
|---|---|---|
| Critical: None | None | N/A |
| Major: | | |
| 101. Burn in Test | 3.4.4 | 4.7.2 |
| 102. Performance | 3.3 | 4.7.1 |
| 103. Conformal Coating | 3.4.5 | Visual |
| Minor: | | |
| 201. Workmanship | 3.6 | Visual |

4.5 Special sampling. Three circuit card assembly shall be selected at random as a special sample from each lot or each 150 produced, whichever occurs first. The sample shall meet the requirements and tests of Table III below, when installed in a GUFS electronic control assembly 12725088 or equivalent contractor - provided Government approved fixture.

TABLE III. Environmental sampling tests

| Characteristics | Requirements | Test Procedure |
|---|---|---|
| Critical: None | None | N/A |
| Major: | | |
| 104. High Temperature | 3.4.2 | 4.7.3.1 |
| 105. Low Temperature | 3.4.2 | 4.7.3.2 |
| 106. Vibration | 3.4.3 | 4.7.3.3 |
| Minor: | | |
| 202. Workmanship | 3.6 | Visual |



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.6 Inspection equipment.

4.6.1 Government-furnished inspection equipment. Where the contract provides for Government-furnished test equipment, supply and maintenance of test equipment shall be in accordance with the applicable requirements of MIL-I-45607.

4.6.2 Contractor-furnished inspection equipment.

4.6.2.1 Government design. Unless otherwise specified in the contract, all inspection equipment identified by drawing number in specifications or QAPs forming a part of the contract shall be supplied by the contractor in accordance with the design specified. The contractor may, however, propose alternatives to Government designs for approval in accordance with 6.5.

4.6.2.2 Contractor design. The contractor shall design and supply inspection equipment compatible with the "Methods of Inspection" specified in 4.7 of this specification and with the component inspection procedures specified in "Examination" and "Test Facilities" requirements of MIL-F-13926 whenever Government designs are not specified (see 4.6.2.1). Since tolerance of test equipment is normally considered to be within 10 percent of the product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit. Thus, concept, construction, materials, dimensions, and tolerances used in the design of test equipment shall be so selected and controlled as to ensure that the test equipment will reliably indicate acceptability of a product which does not exceed 90 percent of the prescribed tolerance limit and permit positive rejection when non-conforming. Construction shall be such as to facilitate routine calibration of test equipment. Contractor inspection equipment designs shall be submitted for approval in accordance with 6.5.

4.6.2.3 Inspection equipment design requirements.

4.6.2.3.1 Temperature testing. The volume of the test chamber shall conform to the test facilities requirements of MIL-F-13926. The air temperature at the control sensor shall be in accordance with the specified requirements within plus or minus 2.5°F (1.4°C). The temperature gradient across the cross-sectional area occupied by the test item shall not exceed 0.5°F per foot in any direction. The heat source of the test chamber shall be so located that radient heat, if used, will not fall directly on the test item. Thermocouples or equivalent temperature sensors utilized to determine or control the specified chamber temperature shall be centrally located within



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

the test chamber within the supply airstream, or in the return airstream, whichever provides the specified test condition at the item under test and shall be baffled or otherwise protected against radiation effects.

4.6.2.3.2 Fabrication, setup and calibration. Design and fabrication of test equipment shall be such that it incorporates the features of rigidity, stability, and ease of maintenance. Setup and calibration equipment necessary for certification of testing equipment accuracy shall be furnished and will become a part of the testing equipment. Operating and calibration instruction shall be prepared and submitted to the procuring activity.

4.7 Methods of inspection. Unless otherwise specified in the contract, the following procedures shall be utilized to conduct specified tests. If the contractor chooses to use alternate test procedures, a detailed description of the setup and procedure shall be submitted to the Government procuring agency for approval prior to use.

4.7.1 Performance. The performance parameters of 3.3 shall be demonstrated either manually or using a contractor designed, Government-approved, automatic test fixture simulating the conditions and making the measurements or providing a visual indication of a PASS or FAIL condition. Performance tests shall be conducted after completion of burn-in test and after each Table III sample test. The performance test shall verify that each of the following CCA functional characteristics conform to the requirements of 3.3.

a. Shall not respond to signal levels lower than 9.3 VDC.

b. Shall not respond to pulse durations of less than 50 milliseconds.

c. Shall not accept firing commands at a rate greater than 28 commands per minute (2.12 second separation).

d. Commands received on Pin N result in sequential firing of ports 1 through 20.

e. Commands received on Pin I or Pin J result in partitioned firing ports 16-20 in sequence and limiting Pin N commands to sequential firing of ports 1-15.

f. Shall not accept firing commands within 60 to 75 seconds of initial power up.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

g. Shall not accept firing commands with ARM/SAFE-RESET switch in SAFE position.

h. Verify that firing commands will fire designated ports in sequence.

i. Verify that last fired sequence position is retained when system power is removed without disarming the GUFS.

j. Verify that rearming the GUFS (operation of ARM/SAFE switch to SAFE and back to ARM) will cause the firing sequence to reset to position 1.

k. Verify that after the last available position has been fired, in either partitioned or sequential firing modes, that the firing command is transferred to the input-transfer connector.

l. Verify that CCA is protected against overvoltage and reverse voltage input power conditions.

m. Verify that the output power pulse is 2.0 to 2.2 amps. for a duration of 110-140 milliseconds.

n. Verify that the output power is not effected by changes in the output load.

4.7.1 Burn in testing. Each circuit card assembly shall be subjected to a burn-in test to screen out any latent defects which would limit operational reliability in the GUFS. This shall be accomplished by subjecting each board to the burn-test cycle and verifying performance per 3.3 at the end of the test cycle by conducting the performance test 4.7.1. Burn-in test cycle shall be run for two hours continuously at ambient temperature and nominal (12 VDC) power levels using a contractor designed, Government-approved, test fixture. The test fixture will generate firing commands at five-second intervals with 20% of the commands being for the partitioned mode of operation.

4.7.3 Environmental sample testing.

4.7.3.1 High temperature. The device shall be tested in accordance with MIL-STD-810, Method 501.2, Procedure I, with a maximum operating temperature of 65°C (149°F). While operating at the maximum temperature, the device shall successfully complete three trials of the functional test specified in 4.7.1. Following completion of high temperature test, and upon return to ambient condition, the device shall be functionally tested as specified in 4.7 herein to determine compliance with 3.4.2.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.7.3.2 Low temperature. The device shall be tested in accordance with MIL-STD-810, Method 502.2, with a minimum operating temperature of -32°C (-25°F). While operating at the minimum temperatures, the device shall successfully complete three trials of the functional test specified in 4.7. Following completion of the low temperature test, and upon return to ambient condition, the device shall be functionally tested as specified in 4.7.1 herein to determine compliance with 3.4.2.

4.7.3.3. Vibration. The device shall be tested in accordance with MIL-STD-810, Method 514.3, Procedure II. After completion of the vibration test, the device shall be functionally tested three times as specified in 4.7.1 herein to determine compliance with 3.4.3.

5. PACKAGING

5.1 General. Preservation, packaging, packing and marking shall be in accordance with special packaging instructions P12725086.

6. NOTES

6.1 Intended use. The circuit card assembly is intended for use in the GUFS, which is part of the Remote Target System (RETS).

6.2 Ordering data. Procurement documents shall specify the following:

6.2.1 Procurement requirements.

a. Title, number and date of this specification.

b. Applicable stock number.

c. First article sample requirements.

d. Packaging requirements, if other than specified in Section 5.

e. Serialization requirements, if applicable.

f. Certificate of conformance for each lot or shipment of product.

6.2.2 Contract data requirements. When this specification is used in an acquisition and data are to be delivered, the data requirements identified below shall be developed as specified by an approved Data Item Description (DID) (DD Form 1664) and



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

delivered in accordance with the approved Contract Data Requirements List (CDRL) incorporated into the contract. When the provisions of DoD FAR Supplement, Part 27, Sub-part 27.410-6 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification are cited in the following paragraphs.

| Reference Paragraph | DID Title | DID No. | Suggested Tailoring |
|---|---|---|---|
| 4.6 | Quality Engineering Acceptance Inspection Equipment Descriptive Documentation | DI-R-1714 | None |

(Data item descriptions related to this specification, and identified in Section 6, will be approved and listed as such in DoD 5000.19L, Vol. II, AMSDL. Copies of data item descriptions required by contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)

6.3 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament, Research, Development and Engineering Center (ARDEC), may also include drawings prepared by, and identified as, U.S. Army Armament, Research and Development Command (ARRADCOM), Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.4 Definitions.

6.4.1 Trainers. Training device terms are defined in MIL-HDBK-220. Other definitions, if required, will be furnished upon written request to the Procuring Contracting Officer.

6.4.2 Contractor. Unless otherwise specified, the word Contractor used throughout this specification shall mean any supplier or producer of items or material to the Government. This shall include commercial contractors, sub-contractors, Government Owned-Contractor Operated (GOCO), and Government Owned-Government Operated (GOGO) plants.

6.4.3 Technical data package. A technical description of an item adequate for use in procurement. The description defines the required design configuration and assures adequacy of item performance. It consists of all applicable technical data such as plans, drawings, and associated lists, specifications, standards, models, performance requirements, quality assurance provisions and packaging data.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

6.5 Submission of contractor inspection equipment designs for approval. Submit two copies of designs as required to: Commander, U.S. Army AMCCOM, ATTN: AMSMC-QAF-I (D), Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract. Unless otherwise specified, data item DI-R-1714 will apply.

6.6 Keyword listing

a. Gunfire Simulator (GUFS)
b. Target Kill Simulator (TKS)
c. Circuit Card Assembly (CCA)
d. Pyrotech Devices (M21)
e. Remote Target System (RETS)

6.7 Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 6920-A114)



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

*(See Instructions – Reverse Side)*

| 1. DOCUMENT NUMBER | 2. DOCUMENT TITLE |
|---|---|
| MIL-C-70618A | |

| 3a. NAME OF SUBMITTING ORGANIZATION | 4. TYPE OF ORGANIZATION *(Mark one)* |
|---|---|
| | ☐ VENDOR<br>☐ USER<br>☐ MANUFACTURER<br>☐ OTHER *(Specify)*: _____ |
| b. ADDRESS *(Street, City, State, ZIP Code)* | |

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

| 7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional | b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional |
|---|---|
| c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional | 8. DATE OF SUBMISSION *(YYMMDD)* |

*(TO DETACH THIS FORM, CUT ALONG THIS LINE.)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.