INCH-POUND

MIL-C-70618B (AR)
30 September 1993
SUPERSEDING
MIL-C-70618A (AR)
17 October 1988

MILITARY SPECIFICATION

CIRCUIT CARD ASSEMBLY, GUNFIRE SIMULATOR: 12725086

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements, examinations and tests for the Circuit Card Assembly (CCA) Target used in the Gunfire Simulator (GUFS), also known as the Target Kill Simulator (TKS), used as a component of the Remote Target System (RETS) (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document, should be addressed to: Commander, U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 6920

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

MILITARY

MIL-F-13926	- Fire Control Materiel, Manufacture and Inspection, General Specification for
MIL-I-45607	- Inspection Equipment, Acquisition, Maintenance and Disposition of

STANDARDS

MILITARY

MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-454	- Standard General Requirements for Electronic Equipment
MIL-STD-810	- Environmental Test Methods and Engineering Guidelines

HANDBOOKS

MILITARY

MIL-HDBK-220 - Glossary of Training Device Terms

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the DODSSP - Customer Service, Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS (see 6.3)

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

11785556	- Requirements for Soldered Electrical and Electronic Assemblies
12725085	- Gunfire Simulator
12725086	- Circuit Card Assembly, Gunfire Simulator
12725088	- Electronic Control Assembly

SPECIAL PACKAGING INSTRUCTION

PS 12725086	- Special Packaging Instructions for the Circuit Card Assembly, Gunfire Simulator

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

(Copies of other Government documents, drawings, and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained. (See contract provisions for additional precedence criteria.)

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on Drawing 12725086, all associated drawings, and with all requirements specified in applicable specifications and standards. Where applicable, the CCA shall meet the requirements of MIL-F-13926 as follows:

a. Dimensions and tolerances.

b. Inorganic protective surface finishings.

c. Part identification and marking.

d. Workmanship.

3.3 Performance.

3.3.1 Firing command. The CCA upon receipt of a firing command on Pin N (M21) or Pin I or J (Smoke) of the GUFS input connector shall verify that the command is valid before processing the command to the firing circuits. A valid firing command shall satisfy the following conditions:

a. Minimum voltage: 9.3 VDC

b. Maximum voltage: 13.6 VDC

c. Minimum pulse width: 50 milliseconds

d. Maximum duration: infinite

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

3.3.1.1 Firing command interrupt. Once a valid firing command has been detected by the CCA, the firing sequence shall be initiated and all further inputs shall be interrupted until the firing sequence, including the firing pulse lockout period, has been completed.

3.3.1.2 Firing pulse lockout. A minimum delay of two (2) seconds shall be provided between the completion of one firing sequence and initiation of a second firing sequence in response to a valid command. The CCA shall not respond to any input commands sensed during the firing pulse lockout period.

3.3.2 Firing sequence. The CCA shall provide two separate firing modes:

a. Sequential firing of GUFS ports 1 through 20.

b. Partitioned firing of GUFS ports 1 through 15 and ports 16 through 20. Each partitioned segment shall be fired in sequence as commanded.

3.3.2.1 Sequential mode (M21). Upon receipt of a valid firing command on Pin N, a single firing pulse shall be directed to the next firing port in sequence starting with port 1 and continuing through port 20. Each port will be fired once and the circuitry shall retain last port firing sequence until the system is reset and rearmed.

3.3.2.2 Partitioned mode (M21 and smoke). Upon receipt of a valid firing command on Pin I or J of the GUFS, the CCA shall automatically partition itself into two firing sections. Parts 1 through 15 shall fire when commanded by an input pulse on Pin N (M21). Ports 16 through 20 shall fire when commanded by an input on Pins I or J (Smoke). In response to a valid command the ports in each section shall fire a single output in sequence within the designated section. Each port shall be fired once and the circuitry shall retain the last port fired sequence for each section until the system is reset and rearmed.

3.3.2.3 Input-transfer. When the last port is fired in any firing mode for either a sequential or a partitioned GUFS device, the CCA shall automatically transfer the next firing command directly to the input-transfer connector (J4). The firing command transferred shall control any GUFS unit connected to the GUFS input-transfer connector in tandem with the basic device.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

3.3.2.4 Last port fired. The CCA shall contain a non-volatile resetable memory for each firing section. The memory circuits shall increment one position each time a valid firing command is detected. Last position commanded per section shall be retained until an automatic reset command is received. Power interruptions or shutdown of the primary power source shall not cause loss, change, or reset of the memory circuits. Memory circuits shall automatically reset when the ARM/SAFE switch is placed in the SAFE position as part of the normal GUFS reloading sequence.

3.3.3 Output command.

3.3.3.1 Output pulse power. The firing circuits shall provide a current regulated output of 1.7 to 2.2 amps for a duration of 110-140 milliseconds at each commanded firing port. This output shall be independent of the load applied to the output port from 0.5 to 3.0 ohms.

3.3.3.2 Safety interlock. The CCA shall normally maintain a short circuit across all output lines. Power shall only be directed to the specified port to be fired. The short across the port to be fired is only removed during the firing cycle for that port.

3.3.4 Input power. The CCA shall automatically monitor the input power lines to prevent inadvertent or false firing commands to be generated when subjected to the following input conditions:

a. Power up transients.

b. Low power condition: Less than 10.5 VDC

c. Overvoltage condition: Greater than 13.6 VDC

d. Reverse voltage.

e. RFI/EMI transients.

3.3.4.1 Power-up interrupt. The CCA firing circuits shall be interrupted for 60 to 120 seconds after initial power up (Arming) of the GUFS. If during the power up lockout period, (60 to 120 seconds) transients, power interruptions, or firing commands are sensed, the power up lockout period will be reset. A minimum of 60 seconds of uninterrupted main power must be sensed before the firing circuits can be energized.

3.3.4.2 Low power interrupt. The CCA firing circuits shall not be energized if the input firing signal is less than 9.3 VDC.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

3.3.4.3 Power line protection. The CCA shall include protection against overvoltage and reverse voltage input power conditions. Protection shall also be provided against the effects of both positive and negative power line transient inputs in excess of requirements of 3.3.1.

3.3.5 Input/output interconnections. Input/output connections to the CCA shall be provided by four (4) connector receptacles:

a. Input Receptacle (J3)

b. Input-transfer Receptacle (J4)

c. Output Receptacle (Ports 1-10) (J1)

d. Output Receptacle (Ports 11-20) (J2)

Wiring to the respective receptacles will be in accordance with Table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

TABLE I. Wiring connections CCA.

RECEPTACLE	J3	J4	J1	J2
FUNCTION	INPUT	INPUT TRANSFER	OUTPUT 1-10	OUTPUT 11-20
PIN 1	M21	+12 VDC	COMMON	COMMON
PIN 2	SMOKE	N/A	PORT 1	PORT 11
PIN 3	SMOKE	N/A	PORT 2	PORT 12
PIN 4	COMMON	COMMON	PORT 5	PORT 15
PIN 5	MEMORY COMMON	SMOKE	PORT 10	PORT 20
PIN 6	+12 VDC	M21	PORT 6	PORT 16
PIN 7	N/A	N/A	COMMON	COMMON
PIN 8	N/A	N/A	PORT 3	PORT 13
PIN 9	N/A	N/A	PORT 7	PORT 17
PIN 10	N/A	N/A	PORT 8	PORT 18
PIN 11	N/A	N/A	PORT 4	PORT 14
PIN 12	N/A	N/A	PORT 9	PORT 19
PIN 13	N/A	N/A	COMMON	COMMON

3.4 Environmental. The CCA shall meet the requirements specified herein unless otherwise specified.

3.4.1 Room ambient temperature. The requirements of this specification shall be met with the CCA stabilized at room ambient temperature of +10°C (50°F) to 32°C (90°F), unless otherwise specified.

3.4.2 Operating temperature. The CCA shall meet the performance requirements in 3.3.2 through 3.3.5, inclusive, when exposed to temperatures from -32°C (-25°F) to +69°C (149°F).

3.4.3 Vibration. The CCA shall meet the requirements of 3.3 after being subjected to MIL-STD-810, Method 514, Procedure I-3.3.1 using Figure 514.4-1 for one hour of random vibration

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

along the vertical axis. Testing shall be conducted in a fixture which duplicates the CCA mounting configuration when installed in the GUFS end application device.

3.4.4 Reliability. Each circuit card assembly shall be subject to a burn-in test to screen out any latent defects which would limit operational reliability in the GUFS. This shall be accomplished by subjecting each board to the burn-in test cycle and verifying performance per 3.3.

3.4.5 Conformal coating. Each CCA, after completion of a burn-in test sequence, shall be conformally coated with a minimum of 3 Mil coating.

3.5 First article. When specified in the contract or purchase order (see 6.2), a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.3).

3.6 Soldering. All soldering shall be in accordance with the requirements of drawing 11785556, Note 1.

3.7 Workmanship. The workmanship requirements of MIL-F-13926, and applicable requirements of MIL-STD-454 shall apply.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of Sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 General provisions. Unless otherwise specified herein, the provisions of MIL-F-13926 and MIL-STD-454 apply and form a part of this specification. Reference shall be made to MIL-STD-109 to define quality assurance terms used herein.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

c. Special sampling inspection (see 4.5).

4.2.1 Inspection conditions. Unless otherwise specified, all examinations and tests shall be conducted at the following standard ambient conditions:

a.	Temperature	+50°F to +90°F
b.	Relative humidity	90% RH Max.
c.	Pressure	28 to 32 inches Hg

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer consisting of three CCAs for inspection in accordance with provisions of 4.3.2.

4.3.2 Inspections to be performed. As determined by the Government, the first article assemblies, components and test specimens may be subjected to any or all of the examinations and tests specified in Table II and III of this detail specification and be inspected for compliance with any or all requirements of the applicable drawings.

4.3.3 Rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate inspection upon any failure of an assembly, component or test specimen to comply with any of the requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. The term "inspection lot" is defined as a homogeneous collection of units of product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements. Units of product selected for inspection shall represent only the inspection lot from which they are drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of inspection procedure which is being applied to determine conformance with requirements.

4.4.2 Examinations and tests.

4.4.2.1 Components, assemblies and subassemblies.

a. The contractor's quality program or detailed inspection plan shall provide assurance of compliance of all characteristics with the applicable drawings and specifications utilizing as a minimum the conformance criteria specified in this document and the Quality Assurance Provisions (QAP) listed in the Technical Data Package (TDP). In the absence of QAPs, the applicable quality assurance provisions of MIL-F-13926 shall apply.

b. Unless otherwise specified herein or provided for in the contract, alternative quality conformance procedures, methods or equipment, such as statistical process control, tool control, other types of sampling plans, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions herein. Prior to applying such alternative procedures, methods or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation (see 6.3). When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the specified quality conformance provisions(s) herein. In case of dispute as to whether the contractor's proposed alternative(s) provides

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

equivalent assurance, the provisions of this specification shall apply. All approved alternative provisions shall be specifically incorporated into the contractor's quality program or inspection system, as applicable.

4.4.2.2 Final acceptance inspection. Subsequent to first article approval, examinations and tests related to Section 3 shall be performed as specified in 4.4.2.3 and 4.5.

4.4.2.3 Functional tests. Each CCA unit will be functionally tested in accordance with the characteristics noted in Table II.

TABLE II. Functional tests (100 percent inspection).

CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
Critical	None	N/A
Major 101. Burn in test 102. Performance 103. Conformal coating	 3.4.4 3.3 3.4.5	 4.7.2 4.7.1 Visual
Minor 201. Workmanship	 3.6	 Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.5 Special sampling. Three (3) circuit card assemblies shall be selected at random as a special sample from each lot or each 150 produced, whichever occurs first. The sample shall meet the requirements and tests in Table III below, when installed in a GUFS electronic control assembly 12725088 or equivalent contractor-provided Government-approved fixture.

TABLE III. Environmental special sampling.

CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
Critical	None	N/A
Major		
104. High temperature	3.4.2	4.7.3.1
105. Low temperature	3.4.2	4.7.3.2
106. Vibration	3.4.3	4.7.3.3
Minor	None	N/A

4.6 Inspection equipment.

4.6.1 Government-furnished inspection equipment. Where the contract provides for Government-furnished test equipment, supply and maintenance of test equipment shall be in accordance with the applicable requirements of MIL-I-45607.

4.6.2 Contractor-furnished inspection equipment.

4.6.2.1 Government design. Unless otherwise specified in the contract, all inspection equipment identified by drawing number in specifications or QAPs forming a part of the contract shall be supplied by the contractor in accordance with design specified. The contractor may, however, propose alternatives to Government designs for approval in accordance with 6.3.

4.6.2.2 Contractor design. The contractor shall design and supply inspection equipment compatible with the "Methods of Inspection" specified in 4.7 of this specification and with the component inspection procedures specified in "Examination" and "Test Facilities" requirements of MIL-F-13926 wherever Government designs are not specified (see 4.6.2.1). Since tolerance of test equipment is normally considered to be within 10 percent of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit. Thus, concept, construction, materials, dimensions, and tolerances used in the design of test equipment shall be so selected and controlled as to ensure that the test equipment will reliably indicate acceptability of a product which does not exceed 90 percent of the prescribed limit and permit positive rejection when nonconforming. Construction shall be such as to facilitate routine calibration of test equipment. Contractor inspection equipment designs shall be submitted for approval in accordance with 6.5.

4.6.2.3 Inspection equipment design requirements.

4.6.2.3.1 Temperature testing. The volume of the test chamber shall conform to the test facilities requirements of MIL-F-13926. The air temperature at the control sensor shall be in accordance with the specified requirements within ± 2.5°F (1.4°C). The temperature gradient across the cross-sectional area occupied by the test item shall not exceed 0.5°F per foot in any direction. The heat source of the test chamber shall be so located that radiant heat, if used, will not fall directly on the test item. Thermocouples or equivalent temperature sensors utilized to determine or control the specified chamber temperature shall be centrally located within the test chamber within the supply airstream, or in the return airstream, whichever provides the specified test condition at the item under test and shall be baffled or otherwise protected against radiation effects.

4.6.2.3.2 Fabrication, setup and calibration. Design and fabrication of test equipment shall be such that it incorporates the features of rigidity, stability, and ease of maintenance. Setup and calibration equipment necessary for certification of testing equipment accuracy shall be furnished and will become a part of the testing equipment. Operating and calibration instruction shall be prepared and submitted to the procuring activity.

4.7 Methods of inspection. Unless otherwise specified in the contract, the following procedures shall be utilized to conduct specified tests. If the contractor chooses to use alternate test procedures, a detailed description of the setup and procedure shall be submitted to the Government procuring agency for approval prior to use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.7.1 Performance. The performance parameters of 3.3 shall be demonstrated either manually or using a contractor-designed, Government-approved, automatic test fixture simulating the conditions and making the measurements or providing a visual indication of a PASS or FAIL condition. Performance tests shall be conducted after completion of burn-in test and after each Table III sample test. The performance test shall verify that each of the following CCA functional characteristics conform to the requirements of 3.3.

a. Shall not respond to signal levels lower than 9.3 VDC.

b. Shall not respond to pulse durations of less than 50 milliseconds.

c. Shall not accept firing commands at a rate greater than 28 commands per minute (2.12 second separation).

d. Commands received on Pin N result in sequential firing of ports 1 through 20.

e. Commands received on Pin I or Pin J result in partitioned firing ports 16-20 in sequence and limiting Pin N commands to sequential firing of ports 1-15.

f. Shall not accept firing commands within 60 to 75 seconds of initial power up.

g. Shall not accept firing commands with ARM/SAFE-RESET switch in SAFE position.

h. Verify that firing commands will fire designated ports in sequence.

i. Verify that last fired sequence position is retained when system power is removed without disarming the GUFS.

j. Verify that rearming the GUFS (operation of ARM/SAFE switch to SAFE and back to ARM) will cause the firing sequence to reset to position 1.

k. Verify that after the last available position has been fired, in either partitioned or sequential firing modes, that the firing command is transferred to the input-transfer connector.

l. Verify that CCA is protected against overvoltage and reverse voltage input power conditions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

m. Verify that the output power pulse is 2.0 to 2.2 amps for a duration of 110-140 milliseconds.

n. Verify that the output power is not effected by changes in the output load.

4.7.2 Burn-in testing. Each circuit card assembly shall be subjected to a burn-in test to screen out any latent defects which would limit operational reliability in the GUFS. This shall be accomplished by subjecting each board to the burn-test cycle and verifying performance per 3.3 at the end of the test cycle by conducting the performance test 4.7.1. Burn-in test cycle shall be run for two hours continuously at ambient temperature and nominal (12 VDC) power levels using a contractor-designed, Government-approved, test fixture. The test fixture will generate firing commands at five-second intervals with 20% of the commands being for the partitioned mode of operation.

4.7.3 Environmental sample testing.

4.7.3.1 High temperature. The device shall be tested in accordance with MIL-STD-810, Method 501, Procedure I, with a maximum operating temperature of 65°C (149°F). While operating at the maximum temperature, the device shall successfully complete three trials of the functional test specified in 4.7.1. Following completion of high temperature test, and upon return to ambient condition, the device shall be functionally tested as specified in 4.7 herein to determine compliance with 3.4.2.

4.7.3.2 Low temperature. The device shall be tested in accordance with MIL-STD-810, Method 502, with a minimum operating temperature of -32°C (-25°F). While operating at the minimum temperatures, the device shall successfully complete three trials of the functional test specified in 4.7. Following completion of the low temperature test, and upon return to ambient condition, the device shall be functionally tested as specified in 4.7.1 herein to determine compliance with 3.4.2.

4.7.4 Vibration. The device shall be tested in accordance with MIL-STD-810, Method 514, Procedure I-3.3.1, using Figure 514.4-1 for one hour of random vibration along the vertical axis. After completion of the vibration test, the device shall be functionally tested three times as specified in 4.7.1 herein to determine compliance with 3.4.3.

4.8 Soldering. Solering processes shall be inspected to the requirements and acceptance criteria of drawing 11785556 as specified in paragraph 3.7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 General. Preservation, packing and marking shall be in accordance with Special Packaging Instruction PS 12725086.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The Circuit Card Assembly is intended for use in the GUFS, which is part of the Remote Target System (RETS). It generates the electronic signals necessary to process fire commands to ignite pyrotechnic cartridges (M21 or Smoke) used to simulate gunfire effects.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification

b. Issue of DODISS to be cited in the solicitation, and, if required, the specific issue of individual documents referenced (see 2.1.1).

c. Requirements for submission of first article sample.

d. Applicable stock number.

e. Packaging requirements, if other than specified in Section 5.

f. Serialization requirements, if applicable.

g. Certificate of conformance for each lot or shipment of product.

6.3 Submission by the contractor.

a. Inspection equipment designs for approval. Submit two copies of designs as required to: Commander, U.S. Army ARDEC, ATTN: SMCAR-QAF-I, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

b. Alternative quality conformance provisions for approval. Unless otherwise specified in the contract, proposed alternative quality conformance provisions will be submitted by the contractor for evaluation to the technical activity responsible for the preparation of this specification.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament, Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as U.S. Army Armament, Research and Development Command (ARRADCOM), Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under cognizance of ARDEC.

6.5 Definitions.

6.5.1 Trainers. Training device terms are defined in MIL-HDBK-220. Other definitions, if required, will be furnished upon written request to the Procuring Contracting Officer.

6.5.2 Contractor. Unless otherwise specified, the word Contractor used throughout this specification shall mean any supplier or producer of items or material to the Government. This shall include commercial contractors, sub-contractors, Government Owned-Contractor Operated (GOCO), and Government Owned-Government Operated (GOGO) plants.

6.5.3 Technical data packages. A technical description of an item adequate for use in procurement. The description defines the required design configuration and assures adequacy of item performance. It consists of all applicable technical data such as plans, drawings, and associated lists, specifications, standards, models, performance requirements, quality assurance provisions and packaging data.

6.6 Subject term (key word) listing.

Pyrotech Devices (M21)
Remote Target System (RETS)

6.7 Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 6920-0125)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE *(YYMMDD)*
3. DOCUMENT TITLE		
4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*		
5. REASON FOR RECOMMENDATION		

6. SUBMITTER		
a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE *(Include Area Code)* (1) Commercial (2) AUTOVON *(If applicable)*	7. DATE SUBMITTED *(YYMMDD)*
8. PREPARING ACTIVITY		
a. NAME	b. TELEPHONE *(Include Area Code)* (1) Commercial (2) AUTOVON	
c. ADDRESS *(Include Zip Code)*	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 *Previous editions are obsolete.* 198/290

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.