MILITARY SPECIFICATION

CONTAINER, AMMUNITION, METAL, PA117, FOR CARTRIDGE 105MM TANK AMMUNITION

This specification is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements, quality assurance provisions and packaging for one type of metal container used for 105mm tank ammunition.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issues of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

TT-C-490	-Cleaning Methods for Ferrous Surfaces and pretreatments for Organic Coatings.

MILITARY

MIL-W-12332	-Welding Resistance, Spot, Seam and Production, for Fabricating Assemblies of Low-Carbon Steel
MIL-A-48078	-Ammunition, Standard Quality Assurance Provisions, General Specification For

Beneficial comments (recommendations additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to Commander U S Army Armament,Munitions and Chemical Command Attn AMSMC-QA Picatinny Arsenal New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter

AMSC N/A
FSC 8140
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	-Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-171	-Finishing of Metal and Wood Surfaces
MIL-STD-1261	-Welding Procedures for Constructional Steel
MIL-STD-1235	-Single-and-Multi Level Continuous Sampling Procedures and Table for Inspection by Attributes.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS (see 6.2)

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

9378162 - Container, Ammo, Metal, PA117, for Cartridge 105mm

(Copies of specifications, standards, handbooks, drawings and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity).

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-D412	-Rubber Properties in Tension, Test Methods for
ASTM-D2240	-Rubber Property-Durometer Hardness, Test Method for
ASTM-D3951	-Commercial Packaging, Practice for
ASTM-E8	-Tension Testing of Metallic Materials, Standard Method of
ASTM-E18	-Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials, Test for

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Containers. The containers shall comply with all requirements specified on drawing 9378162 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Welding. The welding shall comply with the requirements of MIL-W-12332 or MIL-STD-1261.

3.3.1 Tensile strength. When tested as specified in 4.5.1, the tensile strength of the body material shall be in accordance with drawing 9378177 and the tensile strength of the longitudinal body weld shall be not less than 65 percent of the tensile strength of body material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

3.4 Painted surface. The painted surface of the container shall comply with the requirements of TT-C-490. However, the film thickness and salt spray requirements of TT-C-490 shall not apply to the interior surfaces, welded spots, sharp corners and crevices of the exterior surface of the container. Bare spots permissable on all bearing surfaces.

3.5 Cover assembly. Upon assembly of the cover assembly to the body weldment (body assembly), the cover assembly shall freely engage and rotate within the body weldment. As the cover assembly is rotated with the "Y" handle in the open position, the "Y" handle shaft ends shall freely engage into the respective bayonet slots of the rim. When the "Y" handle is in the closed position (rotated 180°), the spring clip shall engage and lock the handle in place and a 0.06 inch diameter pin shall pass through the handle and shaft support holes. When the spring clip is disengaged and the handle rotated to the open position, the cover assembly shall disengage from the body weldment.

3.6 First article inspection. When specified in the contract or purchase order, a sample shall be subjected to First Article Inspection (see 4.3).

3.7 Workmanship.

3.7.1 Containers. The containers shall be regular, smooth, and free from wrinkles, pin holes, cracks, rough spots, burrs, sharp edges and any other defect that might affect the serviceability, durability, safety or appearance of the container.

3.7.2 Paint coating. The paint coating shall be in accordance with applicable drawings and comply with instructions in MIL-STD-171.

3.7.3 Parts. All parts shall be free of chips, dirt, grease, rust and foreign material. The cleaning method used shall not be injurious to any of the parts nor shall any of the parts be contaminated by the cleaning agents used.

3.7.4 Inserts. The inserts shall be regular, smooth and free from any creases, wrinkles, cracks, rips, tears and any other defect which might offset the serviceability, durability, safety and appearance of the insert.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in this specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First article inspection. (see 4.3)
b. Quality conformance inspection. (see 4.4)

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall be in accordance with Table I.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70630 (AR)

PARAGRAPH	TITLE: Assemblies and components		SH 1 OF 2		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Metal containers (Dwg. 9378166)				
	a. Examination for defects	5		3.2	4.4.2.21
	Body weldment unpainted (Dwg. 9378171)				
	a. Examination for defects	10		3.2	4.4.2.15
	b. Weld of rim to body (see Note)	5		3.2	4.5.2
	Cover assembly (Dwg. 9378170)				
	Examination for defects	5		3.2	4.4.2.10
	Body (Dwg. 9378177)				
	a. Examination for defects	10		3.2	4.4.2.13
	b. Tensile strength (see Note)	5		3.2	4.5.1
	Spring (Dwg. 9344042)				
	a. Examination for defects	10		3.2	4.4.2.1
	b. Embrittlement (see Note)	3		3.2	4.5.3
	c. Hardness (see Note)	3		3.2	4.5.4

NOTE: The weld security inspections, the body tensile strength, spring tests and gasket tensile stress test shall be performed after the other inspections have been performed on the applicable samples.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

Table I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-C-70630 (AR)

PARAGRAPH	TITLE: Assemblies and components		SHT 2 OF 2		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Gasket (Dwg. 9378178)				
	a. Examination for defects	10		3.2	4.4.2.8
	b. Hardness	3		3.2	4.5.6
	c. Tensile stress (see Note)	3		3.2	4.5.5
	Remaining subassemblies and components				
	Examination for defects	10		3.2	Applicable subparagraph of 4.4.2

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of containers shall contain material from lots with the same interfix number from one manufacturer.

4.4.2 Examination. See MIL-A-48078. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Continuously sampling plan in accordance with MIL-STD-1235 may be used if approved by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70630 (AR)

PARAGRAPH	TITLE			SHEET 1 OF 1	DRAWING NUMBER 9344042
4.4.2.1	Spring				NEXT HIGHER ASSEMBLY 9344044
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Spring embrittlement	(a)		3.2	4.5.3
102	Hardness	(a)		3.2	4.5.4
103	Radius of bend		0.40%	3.2	Gage
Minor					
201	Poor workmanship		0.65%	3.7	Visual

NOTES:

(a) Five springs from each heat treatment lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70630 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Support, shaft				9344035
					NEXT HIGHER ASSEMBLY 9344044
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness		0.40%	3.2	Gage
Minor					
201	Radius not present at edges of tab		0.65%	3.2	Visual
202	Poor workmanship		0.65%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70630 (AR)

PARAGRAPH	TITLE		SH 1 OF 1		DRAWING NUMBER
4.4.2.3	Handle				9344036
					NEXT HIGHER ASSEMBLY 9378170
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position of hexholes		0.40%	3.2	Gage
102	Width of hexholes, maximum		0.40%	3.2	Gage
Minor					
201	Poor workmanship		0.65%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70630 (AR)

PARAGRAPH	TITLE		SH 1 OF 1		DRAWING NUMBER
4.4.2.4	Shaft				9378179
					NEXT HIGHER ASSEMBLY 9378170
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length of hexagon segment of shaft, minimum		0.40%	3.2	Gage
102	Small diameter (two places)		0.40%	3.2	Gage
103	Total length of large diameters and hexagon segments		0.40%	3.2	Gage
104	Length of small diameter segment (two places)		0.40%	3.2	Gage
105	Length of large diameter segment		0.40%	3.2	Gage
106	True position of small diameter (two places)		0.40%	3.2	Gage
Minor					
201	Poor workmanship		0.65%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70630 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Washer				9344038
					NEXT HIGHER ASSEMBLY
					9378170
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter		0.40%	3.2	Gage
102	Height, minimum		0.40%	3.2	Gage
103	Outside diameter, minimum		0.40%	3.2	Gage
Minor					
201	Poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70630 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Retainer, washer				9344041
					NEXT HIGHER ASSEMBLY 9378170
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Height of retainer		0.40%	3.2	Gage
Minor 201	Poor workmanship		0.65%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70630 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Cover				9378182
					NEXT HIGHER ASSEMBLY 9378181
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness		0.40%	3.2	Gage
102	Width of groove		0.40%	3.2	Gage
103	Length of threads, minimum		0.40%	3.2	Gage
104	Depth from top of cover to recess		0.40%	3.2	Gage
105	Flatness of area surrounding air test hole		0.40%	3.2	Gage
106	Outside diameter, maximum		0.40%	3.2	Gage
Minor					
201	Poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70630 (AR)

PARAGRAPH	TITLE	SH - 1 OF 1	DRAWING NUMBER
4.4.2.8	Gasket		9378178
			NEXT HIGHER ASSEMBLY 9378170

CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Tensile stress	5		3.2	4.5.5
102	Hardness	(a)		3.2	4.5.6
103	Overall width		0.40%	3.2	Gage
104	Thickness of curved section		0.40%	3.2	Gage
105	Diameter of hole in cross section	5		3.2	Gage
106	Height of rectangular cross section		0.40%	3.2	Gage
107	Misalignment of joint		0.40%	3.2	Visual
108	Location of hole	5		3.2	Gage
Minor					
201	Poor workmanship		0.65%	3.7	Visual

NOTES: (a) One plaque (4 specimens) from each material batch.

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70630 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.9	Cover weldment		9378181
			NEXT HIGHER ASSEMBLY 9378170

CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position of shaft hole and slot		0.40%	3.2	Gage
102	True position of shaft support uprights		0.40%	3.2	Gage
Minor					
201	Spot weld missing or incomplete		0.65%	3.2	Visual
202	Poor workmanship		0.65%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70630 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.10	Cover assembly				9378170
					NEXT HIGHER ASSEMBLY 9378166
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Shaft free to rotate		0.40%	3.2	Manual
102	Primer thickness, minimum		0.40%	3.2	Gage
103	Paint thickness, minimum		0.40%	3.2	Gage
104	Distance from inside gasket groove to top of shaft at small diameter (two places)	(a)	0.40%	3.2	Gage
Minor					
201	Poor workmanship		0.65%	3.7	Visual

NOTES:
(a) Prior to painting and assembly of the gasket.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70630 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.11	Rim				9378175
					NEXT HIGHER ASSEMBLY 9378171
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length of large slot		0.40%	3.2	Gage
102	Width of large slot		0.40%	3.2	Gage
103	Inside dimension across flats, two places (Dim A), minimum		0.40%	3.2	Gage
104	Inside diameter of rim, two places (Dim E)		0.40%	3.2	Gage
105	Radius/chamfer at beginning of locking edge of bayonet slot missing		0.40%	3.2	Visual
Minor					
201	Step at inside of locking edge of bayonet slot missing		0.65%	3.2	Visual
202	Poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70630 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.12	Ring				9378173
					NEXT HIGHER ASSEMBLY 9378171
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length of large slot		0.40%	3.2	Gage
102	Width of large slot		0.40%	3.2	Gage
103	Inside dimensions across flats, 2 places (Dim. A)		0.40%	3.2	Gage
104	Opening of container interlocking grip		0.40%	3.2	Gage
Minor					
201	True position of interlocking cutouts		0.65%	3.2	Gage
202	Poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70630 (AR)

PARAGRAPH	TITLE		SH. 1 OF 1		DRAWING NUMBER
4.4.2.13	Body				9378177
					NEXT HIGHER ASSEMBLY 9378171
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Tensile strength			3.3.1	4.5.1
102	Length		0.40%	3.2	Gage
103	Perpendicularity of ends		0.40%	3.2	Gage
Minor					
201	Poor workmanship		0.65%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70630 (AR)

PARAGRAPH	TITLE			SHEET 1 OF 1	DRAWING NUMBER
4.4.2.14	Plug, stacking				9344045
					NEXT HIGHER ASSEMBLY
					9378171
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length of plug		0.40%	3.2	Gage
102	Width of plug		0.40%	3.2	Gage
Minor					
201	Poor workmanship		0.65%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70630 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.15	Body weldment, prior to painting		9378171
			NEXT HIGHER ASSEMBLY 9378166

CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Weld of rim to body	10		3.2	4.5.2/Gage
102	True position of slots of ring and rim to each other		0.40%	3.2	Gage
103	True position of stacking plugs of ring and rim to each other		0.40%	3.2	Gage
104	Location of lip grip and interlocking slot		0.40%	3.2	Gage
105	Inside diameter, minimum		0.40%	3.2	Gage
106	Perpendicularity of rings with Datum-A		0.40%	3.2	Gage
107	Distance from end of body to top of rim bayonet slot (four places)		0.40%	3.2	Gage
108	Flatness of body end		0.40%	3.2	Gage
Minor					
201	Minimum shear load between stacking plug and rim	10		3.2	Gage
202	Mimimum shear load between stacking plug and ring	10		3.2	Gage
203	Poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70630 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.16	Body Weldment, after painting				9378171
					NEXT HIGHER ASSEMBLY 9378166
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Primer thickness, minimum		0.40%	3.2	Gage
102	Paint thickness, minimum		0.40%	3.2	Gage
103	Marking missing, incomplete or illegible		0.40%	3.2	Visual
Minor					
201	Poor workmanship		0.65%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70630 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.17	Support				9369973
					NEXT HIGHER ASSEMBLY 9378162
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Outside diameter		0.65%	3.2	Gage
202	Length		0.65%	3.2	Gage
203	Inside diameter		0.65%	3.2	Gage
204	Poor workmanship		0.65%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70630 (AR)

PARAGRAPH	TITLE			SHEET 1 OF 1	DRAWING NUMBER
4.4.2.18	Support, Nose				9369970
					NEXT HIGHER ASSEMBLY 9378162
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Overall length		0.65%	3.2	Gage
202	Large inside diameter		0.65%	3.2	Gage
203	Thickness		0.65%	3.2	Gage
204	Outside step (four places)		0.65%	3.2	Gage
205	Length of large inside cavity		0.65%	3.2	Gage
206	Small outside diameter		0.65%	3.2	Gage
207	Poor workmanship		0.65%	3.7	Visual
NOTES:					

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70630 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.19	Cushion, Bottom				9378165
					NEXT HIGHER ASSEMBLY 9378162
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Thickness		0.65%	3.2	Gage
202	Poor workmanship		0.65%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70630 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.20	Cushion		9378164
			NEXT HIGHER ASSEMBLY 9378162

CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Thickness		0.65%	3.2	Gage
203	Poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70630 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.21	Container, ammo, metal, PA117				9378166
					NEXT HIGHER ASSEMBLY 9378162
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Cover assembly test		0.40%	3.5	Visual/Manual/4.5.8
102	Air pressure test		100%	3.2	4.5.7.1
103	Interchangeability test	(a)	0.40%	3.2	4.5.7.2
104	Screw torque test	(b)	0.40%	3.2	4.5.9
105	Marking, missing, incomplete or illegible (see Dwg. 9378171)		0.40%	3.2	Visual
Minor					
201	Protective finish damaged, bare spots exposing metal, etc.		0.65%	3.2	Visual
202	Poor workmanship		0.65%	3.7	Visual
(a) has been	The interchangeability test shall be performed after the air pressure test performed.				
(b) interchangeability test has been performed and the	The screw torque test shall be performed after screw		the air pressure has been	test and reassembled.	

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70630 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.22	Container, ammo, metal, PA117, for cartridge 105mm				9378162
					NEXT HIGHER ASSEMBLY 12561500
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Any component missing or damaged		0.40%	3.2	Visual
Minor 201	Poor workmanship		0.65%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First article and Quality Conformance Inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection.

4.5.1 Tensile strength. The tensile strength shall be determined in accordance with ASTM-E8. Six bodies shall be randomly selected for this test per shift. From each body, three specimens shall be selected at random for determination of body material tensile strength. Also, from each body, four specimens approximately equally spaced along the axis shall be taken at right angles to the weld and the tensile strength of their welds shall be determined. Each of these values shall be compared with the lowest determined value of the body material tensile strength for compliance with the requirement of 3.3.1. If one or more specimens (longitudinal body weld or body material) fail to comply with 3.3.1, that sample body shall be classed defective. If two or more sample bodies are classed defective, the lot shall be rejected.

4.5.2 Weld of rim to body. The test shall be performed in accordance with ASTM-E8. Five body weldments shall be randomly selected from each lot and tested. If any sample fails to comply with the applicable requirement, the lot shall be rejected.

4.5.3 Spring embrittlement. Five springs shall be randomly selected from each heat treatment lot for this test. Each spring shall be repeatedly deflected with increasing loads until it does not return to its original free height. That point shall indicate minimum distortion. Any spring which fractures prior to extension to minimum distortion shall be classed defective. If any spring fails to meet the applicable requirement, the heat treatment lot shall be rejected.

4.5.4 Hardness of spring. The hardness of the spring shall be determined in accordance with ASTM-E18. Five springs shall be randomly selected from each heat treatment lot and tested. If any spring fails to meet the applicable requirement, the heat treatment lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.5.5 Tensile stress of gasket. The tensile stress shall be determined in accordance with ASTM-D412. Five gaskets shall be randomly selected from each lot for this test. If any gasket fails to meet the applicable requirement, the lot shall be rejected.

4.5.6 Hardness of gasket. The hardness shall be determined in accordance with ASTM-D2240. If one specimen fails to meet the applicable requirement, the lot of material shall be rejected.

4.5.7 Air pressure test.

4.5.7.1 Air pressure of painted container assembly. Subject the container assembly to the internal air pressure, specified in the applicable container assembly drawing, for one of the test times specified. Observation shall be made for any evidence of leakage exceeding the requirement for the corresponding test time (as specified in the applicable drawing). A container assembly, which exceeds the requirement, shall be classed defective.

4.5.7.2 Interchangeability of painted container assemblies. Randomly interchange the cover assemblies with container body weldments while positioning the cover assembly in a random orientation and perform the air pressure test per 4.5.7.1. Failure to meet the applicable requirement shall be cause for rejection of the lot.

4.5.8 Cover assembly test. Upon assembly of the body weldment and cover assembly, the cover shall freely engage and rotate within the body weldment. The Y-handle shaft ends shall engage into the respective bayonet slots of the rim without interference and a 0.06 inch diameter pin shall pass through the cover assembly holes when in the clamping position. The spring clip shall engage and lock the handle when in this position. The Y-handle, when disengaged and in the open position, shall disengage the cover from the body. Any assembly which fails to meet this criteria shall be classed defective.

4.5.9 Screw torque test. The minimum applicable torque shall be applied to the screw. Any evidence of motion of the screw before reaching the minimum acceptable torque shall be cause for rejection of the container assembly being tested. Any container assembly which fails the screw torque test may be reworked and returned to the lot after passing the screw torque test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. None required.

5.2 Packing. Packing shall be commercial. Metal ammunition containers and components shall be prepared in accordance with ASTM-D3951.

5.3 Marking. Shipping marking shall comply with ASTM-D3951 and the following additional instructions. No shipping marking shall be placed directly on the containers. Commercial shipping tags attached with wire shall be used on the containers unless otherwise specified. The following information shall be shown: Item name and model number (if applicable), part number and revision, contract number, lot number and date, name and address of manufacturer. If containers or components are bundled, boxed or palletized, the gross weight and quantity shall be included. The above information may be placed on pallets or boxes by labeling or stenciling.

6. NOTES

6.1 Intended use. The metal container is intended for use as the outer shipping and storage packaging for the 105MM Tank Cartridge.

6.2 Ordering data See MIL-A-48078.

6.3 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by and identified as US Army Armament Research and Development Command (ARRADCOM), Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.4 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit designs as required to: Commander, US Army Armament Research, Development and Engineering Center (ARDEC), ATTN: AMSMC-QAT-I, Picatinny Arsenal, New Jersey 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423. Unless otherwise specified,data item DI-R-1714 will apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

6.5 Subject term (key word) listing.

Ammunition
Tank
Cannon
Cartridge
Container
Pallet

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 8140-A753)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
ARDEC
ATTN: AMSMC-QA
PICATINNY ARSENAL, NJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1 DOCUMENT NUMBER	2 DOCUMENT TITLE
MIL-C-70630	CONTAINER, AMMUNITION, METAL, PA117, FOR CARTRIDGE 105MM TANK

3a NAME OF SUBMITTING ORGANIZATION	4 TYPE OF ORGANIZATION *(Mark one)*
AMMUNITION	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)* _____
b ADDRESS *(Street, City, State, ZIP Code)*	

5 PROBLEM AREAS

a. Paragraph Number and Wording

b. Recommended Wording

c. Reason/Rationale for Recommendation

6 REMARKS

7a NAME OF SUBMITTER *(Last First MI)* – Optional	b WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c MAILING ADDRESS *(Street City State ZIP Code)* – Optional	8 DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.