INCH-POUND

MIL-C-70740 (AR)
15 July 1991

MILITARY SPECIFICATION

CONTAINER, AMMUNITION, LIGHTWEIGHT METAL FOR 155MM PROPELLING CHARGE

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers requirements and quality assurance provisions for the manufacture of a family of metal containers used for packing 155MM propelling charges for separate loaded artillery ammunition (see 6.1.).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

TT-C-490	-	Cleaning Methods for Ferrous Surfaces and Pretreatments for Organic Coatings

MILITARY

MIL-W-12332	-	Welding Resistance, Spot, Seam and Projection, for Fabricating Assemblies of Low-Carbon Steel
MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification For

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8140

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

MIL-A-70625 - Automated Acceptance Inspection Equipment for Non-Electronic Components, Design, Testing and Approval of

STANDARDS

MILITARY

MIL-STD-171 - Finishing of Metal and Wood Surfaces
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1261 - Arc Welding Procedures for Constructional Steel

(Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

12910318 - Container, Ammunition, Metal, PA 132
12910319 - Container, Ammunition, Metal, PA 128
12910324 - Container, Ammunition, Metal, PA 131

(Copies of other Government documents, drawings and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM-D2240	-	Rubber Property-Durometer Hardness, Standard Method of Test for (DoD adopted)
ASTM-D3951	-	Commercial Packaging, Practice for (DoD adopted)
ASTM-E8	-	Tension Testing of Metallic Materials, Standard Method of
ASTM-E18	-	Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials, Test for

(Application for copies for ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Containers. The containers (container assemblies) shall comply with all requirements specified on drawings 12910318, 12910319 or 12910324 as applicable and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Welding. The welding shall comply with the requirements of MIL-W-12332 or MIL-STD-1261.

3.3.1 Tensile strength of body weld. The tensile strength of the longitudinal body weld shall not be less than 65 percent of the tensile strength of body material.

3.3.2 Tensile strength of body material. The tensile strength of the body material shall not be less than 50,000 pounds per square inch (psi).

3.4 Painted surface. The painted surfaces of the container shall comply with the requirements of TT-C-490. However, the film thickness and salt spray requirements of TT-C-490 shall not apply to the interior surfaces, exterior surface welded spots and exterior surface sharp corners of the container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

3.5 Cover assembly. Upon assembly of the cover assembly to the body assembly (body weldment), the cover assembly shall freely engage and rotate within the body assembly. As the cover assembly is rotated with the "Y" handle in the open position, the "Y" handle shaft ends shall freely engage into the respective bayonet slots of the rim. When the "Y" handle is rotated toward the closed position, the "Y" handle shall push the spring clip out of the way and snap into place (closed position) and the spring clip shall return to its original position locking the "Y" handle. When the "Y" handle is returned to the open position, it shall push the spring clip out of the way permitting a 180 degree rotation of the "Y" handle to the open position with the spring clip returning to its normal position. Rotation of the cover assembly will permit disengagement from the body assembly.

3.6 Air pressure test.

3.6.1 Air pressure of unpainted cover assembly. The unpainted cover assembly assembly shall withstand an internal air pressure of three psi for five (5) seconds minimum under water, without leakage occurring.

3.6.2 Air pressure of unpainted body assembly. The unpainted body assembly shall withstand an internal air pressure of three psi for five (5) seconds minimum under water, without leakage occurring.

3.7 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.8 Workmanship.

3.8.1 Containers. The containers shall be regular, smooth, and free from wrinkles, pin holes, cracks, rough spots, burrs, sharp edges and any other defect that might affect the serviceability, durability, and safety of the container.

3.8.2 Paint coating. The paint coating shall be in accordance with applicable drawings and comply with instructions in MIL-STD-171.

3.8.3 Parts. All parts shall be free of chips, dirt, grease, rust and foreign material. The cleaning method used shall not be injurious to any of the parts nor shall any of the parts be contaminated by the cleaning agents used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First article inspection (see 4.3)
b. Quality conformance inspection (see 4.4)

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of fifteen (15) painted container assemblies, five (5) painted cover assemblies, five (5) unpainted cover assemblies, and ten (10) each of every subassembly and component (unpainted).

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70740 (AR)

PARAGRAPH	TITLE Assemblies and Components	SHEET 1 OF 2		DRAWING NUMBER See below NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Container assemblies, painted (Dwg. 12910318, 12910319, 12910324, as applicable)			
	a. Examination for defects	5	3.2	4.4.2.18
	b. Air pressure	15	3.6.3	4.5.6.2
	c. Painted surface (see Note)	3	3.4	4.5.7
	Body assembly (weldment), unpainted (Dwg. 12910321)			
	a. Examination for defects	10	3.2	4.4.2.17
	b. Air pressure	5	3.6.2	4.5.6.1
	c. Weld strength of rim to body (see Note)	5	3.2	4.5.2/Dwg.
	Cover assembly, unpainted (Dwg. 9386824) Air pressure	5	3.6.1	4.5.6.1
	Cover assembly, prior to painting (Dwg. 9386824) Examination for defects	5	3.2	4.4.2.10
	Cover assembly (Dwg. 9386824) Examination for defects	5	3.2	4.4.2.11

NOTES:
The weld security inspections , painted surface and spring tests shall be performed after the other inspections have been performed on the applicable samples.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER
	Assemblies and Components		See below
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Body, unpainted (Dwg. 9386828)			
	a. Examination for defects	10	3.2	4.4.2.15
	b. Tensile strength (see Note)	5	3.3.1	4.5.1/Dwg.
	Cover, weldment (Dwg. 9386822)			
	a. Examination for defects	10	3.2	4.4.2.9
	Spring, unpainted (Dwg. 9344042)			
	a. Examination for defects	10	3.2	4.4.2.1
	b. Embrittlement (see Note)	5	3.2	4.5.3/Dwg.
	c. Hardness (see Note)	5	3.2	4.5.4/Dwg.
	Gasket (Dwg. 12910349)			
	a. Examination for defects	10	3.2	4.4.2.8
	b. Hardness	5	3.2	4.5.5/Dwg.
	Remaining subassemblies and components			
	Examination for defects	10	3.2	Applicable subparagraph if 4.4.2

NOTES:
The weld security inspections , painted surface and spring tests shall be performed after the other inspections have been performed on the applicable samples.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of containers shall contain material from lots with the same interfix number from one manufacturer.

4.4.2 Examinations and tests.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified herein. When cited herein, attributes sampling inspection shall be conducted in accordance with Table II below, using the inspection levels stated in the Classification of Characteristics paragraphs.

Table II. Attributes sampling inspection

Lot Size	Inspection Levels					
	I	II	III	IV	V	VI
2 to 8	*	*	*	*	5	3
9 to 15	*	*	*	13	5	3
16 to 25	*	*	*	13	5	3
26 to 50	*	*	32	13	5	3
51 to 90	*	*	32	13	12	4
91 to 150	*	125	32	13	12	5
151 to 280	*	125	32	30	14	6
281 to 500	*	125	32	30	17	7
501 to 1200	*	125	74	35	20	9
1201 to 3200	1250	125	74	43	24	10
3201 to 10000	1250	125	87	50	30	10
10001 to 35000	1250	296	109	61	36	10
35001 to 150000	1250	296	124	74	40	10
150001 to 500000	1250	346	156	91	40	10
500001 to over	1250	431	187	102	40	10

Numbers under inspection levels indicate sample size; asterisk indicates one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

b. Alternative quality conformance provisions. Alternative quality conformance procedures, methods, or equipment, such as statistical process control, tool control, other types of sampling procedures, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions specified herein. Prior to applying such alternative procedures, methods, or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation (see 6.5). When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the specified quality assurance provision(s) herein. In cases of dispute as to whether the contractor's proposed alternative(s) provide equivalent assurance, the provisions of this specification shall apply. All approved alternative provisions shall be specifically incorporated into the contractor's quality program or detailed inspection system, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Spring	1 OF 1	9344042
			NEXT HIGHER ASSEMBLY 9344044-1

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	True position of holes	0-1,Level III	3.2	Gage
102	Radius of bend	0-1,Level III	3.2	Gage
103	Length from end to lower edge of bend	0-1,Level III	3.2	Gage
104	Thickness	0-1,Level III	3.2	Gage
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Support, Shaft	1 OF 1	9344035-1
			NEXT HIGHER ASSEMBLY 9344044-1

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Diameter of large hole, maximum (max.)	0-1,Level III	3.2	Gage
102	True position of large hole	0-1,Level III	3.2	Gage
103	True position of slot	0-1,Level III	3.2	Gage
104	True position of holes located on side (used for assembly of spring and clamp)	0-1,Level III	3.2	Gage
105	Distance between shaft support uprights	0-1,Level III	3.2	Gage
106	Material thickness	0-1, Level IV	3.2	Gage
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70740 (AR)

PARAGRAPH 4.4.2.3	TITLE Handle	SHEET 1 OF 1	DRAWING NUMBER 9344036
			NEXT HIGHER ASSEMBLY 938824-3,-5

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Width of hexhole, max. (three readings, 60° apart)	0-1, Level III	3.2	Gage
102	True position of hexhole	0-1, Level III	3.2	Gage
103	Width of spring slot	0-1, Level III	3.2	Gage
104	Length of spring slot (Dim B)	0-1, Level III	3.2	Gage
105	Material thickness	0-1, Level IV	3.2	Gage
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70740 (AR)

PARAGRAPH 4.4.2.4	TITLE Shaft	SHEET 1 OF 1		DRAWING NUMBER 9344037-1,-5
				NEXT HIGHER ASSEMBLY 9386824-3,-5
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Width across flats of hexagon segment minimum (min.) (three readings, 60° apart)	0-1,Level III	3.2	Gage
102	Length of hexagon segment of shaft	0-1,Level III	3.2	Gage
103	Length of small diameter segment (two places)	0-1,Level III	3.2	Gage
104	Large diameter (two places)	0-1,Level III	3.2	Gage
105	Small diameter (two places)	0-1,Level III	3.2	Gage
106	Total length of large diameters and hexagon segments (Dim B)	0-1,Level III	3.2	Gage
107	Small diameter segment not tangent to large diameter segment and side of hexagon segment	0-1,Level III	3.2	Visual
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Washer	1 OF 1	9344038
			NEXT HIGHER ASSEMBLY 9386824-3,-5

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Inside diameter	0-1,Level III	3.2	Gage
102	Height, min.	0-1,Level III	3.2	Gage
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70740 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Retainer, Washer	1 OF 1	9344041
			NEXT HIGHER ASSEMBLY 9386824-3,-5

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Height	0-1,Level III	3.2	Gage
102	Diameter of hole	0-1,Level III	3.2	Gage
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70740 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Cover	1 OF 1	9386821-3,-5
			NEXT HIGHER ASSEMBLY 9386822-3,-5

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Outside diameter, max.	0-1,Level III	3.2	Gage
102	Width of groove	0-1,Level III	3.2	Gage
103	Depth from top cover to recess	0-1,Level III	3.2	Gage
104	Height of threads, min., when applicable (see Note)	0-1,Level III	3.2	Gage
105	Flatness of bottom surface inner annular ring and surrounding air test hole	0-1,Level III	3.2	Gage
106	Material thickness	0-1, Level IV	3.2	Gage
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES: Threads may be formed on cover (instead of cover assembly).

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70740 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Gasket	1 OF 1	12910349-4,-6
			NEXT HIGHER ASSEMBLY 9386824-3,-5

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Inside diameter, max. (Dim A)	0-1,Level III	3.2	Gage
102	Large width	0-1,Level III	3.2	Gage
103	Middle width	0-1,Level III	3.2	Gage
104	Height of rectangular cross section	0-1,Level III	3.2	Gage
105	Material certification		3.2	Certification
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Cover Weldment	1 OF 1	9386822-3,-5
			NEXT HIGHER ASSEMBLY 9386824-3,-5

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Location of shaft support slot with respect to cover air hole	0-1,Level III	3.2	Gage
102	Weld missing, incomplete or visually inadequate	0-1,Level III	3.2	Visual/Manual
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 . Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70740 (AR)

PARAGRAPH	TITLE	SHEET OF	DRAWING NUMBER
4.4.2.10	Cover assembly, prior to painting	1 1	9386824-3,-5
			NEXT HIGHER ASSEMBLY 12910318, 12910319, 12910324, as app

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	.725 Distance from top of shaft (in closed position) to inside surface of the gasket retainer section of cover	0-1,Level II	3.2	Gage
102	Height of thread (min.), when applicable (see Note)	0-1,Level III	3.2	Gage
103	Component missing or inadequately assembled	0-1,Level III	3.2	Visual
104	Rotating of shaft inadequate after crimping	0-1,Level III	3.2	Manual
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES: Threads may be formed on cover (instead of cover assembly).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.11	Cover Assembly	OF 1 1	9386824-3,-5
			NEXT HIGHER ASSEMBLY 12010318, 12910319, 12910324, as app

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Gasket not secured or secured improperly to cover	0-1,Level III	3.2	Visual/Manual
102	Paint thickness, min.	0-1,Level III	3.2	Gage
103	Height of thread (min) when applicable	0-1,Level III	3.2	Gage
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH 4.4.2.12	TITLE Rim	SHEET 1 OF 1	DRAWING NUMBER 9386827-3,-5
			NEXT HIGHER ASSEMBLY 12910321-2,-3,-4

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Length of larger slot (on side of rim), max.	0-1,Level III	3.2	Gage
102	Width of larger slot (on side of rim), max.	0-1,Level III	3.2	Gage
103	Location of bayonet slot, four places (see note)	0-1,Level III	3.2	Gage
104	Inside diameter of rim, two places (Dim E)	0-1,Level III	3.2	Gage
105	Outside dimension across flats, two places (Dim A)	0-1,Level III	3.2	Gage
106	Outside dimension across corners, two places (Dim D)	0-1,Level III	3.2	Gage
107	Radius at beginning of locking edge of bayonet slot missing (see note)	0-1,Level IV	3.2	Visual
Minor				
201	Drainage hole missing	0-1,Level IV	3.2	Visual
202	Step at inside of locking edge of bayonet slot missing (see note)	0-1,Level IV	3.2	Visual
203	Evidence of poor workmanship	0-1,Level V	3.8	Visual

NOTES: Inspections 103, 107 and 202 may be done on the next higher assembly (Dwg. 12910321 -2, -3, -4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.13	Ring	1 OF 1	12630903-3,-4,-5
			NEXT HIGHER ASSEMBLY: 12910321-2,-3,-4

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Length of larger slot (on side of ring), max.	0-1,Level III	3.2	Gage
102	Width of larger slot (on side of ring), max.	0-1,Level III	3.2	Gage
103	Outside dimension across flats, two places (Dim A)	0-1,Level III	3.2	Gage
Minor				
201	Drainage hole missing	0-1, Level IV	3.2	Visual
202	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70740 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.14	Bottom	1 OF 1	9378172-3,-5
			NEXT HIGHER ASSEMBLY 12910321-2,-3,-4

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Height, minimum (min.)	0-1,Level III	3.2	Gage
102	Material thickness	0-1, Level IV	3.2	Gage
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.15	Body	1	1	9386828-4,-7,-8
				NEXT HIGHER ASSEMBLY: 12910321-2,-3,-4

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Length, min.	0-1,Level III	3.2	Gage
102	Inside diameter, min. (see note)	0-1,Level III	3.2	Gage
103	Flatness of body end (see note)	0-1,Level III	3.2	Gage
104	Material thickness	0-1, Level IV	3.2	Gage
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES: Inspections 102 and 103 may be done on the next higher assembly (Dwg. 12910321 -2, -3, -4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70740 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.16	Plug, Stacking	1 OF 1	9386837
			NEXT HIGHER ASSEMBLY 12910321-2,-3,-4

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Length of plug, min.	0-1,Level III	3.2	Gage
102	Width of plug, min.	0-1,Level III	3.2	Gage
Minor				
201	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.17	Body Assembly (weldment)	1 OF 1	12910321-2,-3,-4
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	.885 Location of bayonet slot of rim with respect to edge of body (four places)	0-1,Level II	3.2	Gage
102	True position of slots of ring(s) and rim to each other	0-1,Level III	3.2	Gage
103	True position of stacking plugs of ring(s) and rim to each other	0-1,Level III	3.2	Gage
104	Perpendicularity of ring(s) and rim with datum A	0-1,Level III	3.2	Gage
105	Inside diameter of body, min.	0-1,Level III	3.2	Gage
106	Body (seam) weld (if applicable) or weld of ring(s), rim or bottom to body missing, incomplete or visually inadequate	0-1,Level III	3.2	Visual
107	Paint thickness, min.	0-1,Level IV	3.2	Gage
108	Shear load min. between stacking plug and rim (see note)	0-1,Level V	3.2	Gage
109	Shear load min. between stacking plug and ring (see note)	0-1,Level V	3.2	Gage
Minor				
201	Marking missing, illegible or incorrect	0-1, Level V	3.2	5.3/Visual
202	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES: These shear load inspections may be performed on the subassembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-70740 (AR)

PARAGRAPH 4.4.2.18	TITLE Container Assembly	SHEET 1 OF 1	DRAWING NUMBER 12910318, 12910319, 12910324
			NEXT HIGHER ASSEMBLY 12913753, 12913754, 12913757

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Cover assembly assembled to body assembly	0-1,Level III	3.5	Visual/Manual
Minor				
201	Protective finish damaged, bare spots exposing metal, etc.	0-1, Level IV	3.2	Visual
202	Evidence of poor workmanship	0-1, Level V	3.8	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Tensile strength of body material and weld (see 3.3), Major defect. During the first half of a production shift and during the last half of a production shift, a body shall be selected for this test. From each body, three (3) specimens shall be selected at random for determination of body material tensile strength. Also from each body, four (4) specimens, approximately equally spaced along the axis, shall be taken at right angles to the weld and the tensile strength of their welds shall be determined. Each of these values shall be compared with the lowest determined value of the body material tensile strength for compliance with the requirement of 3.3.1. If one or more specimens (longitudinal body weld or body material) fail to comply with 3.3.1 or 3.3.2, the quantity of bodies which were welded during this shift and the earlier strength test (if applicable) shall be rejected. A weld strength test shall also be performed whenever an electrode is changed or dressed. The test shall be performed as specified in 4.5.1.

4.4.3.2 Weld strength of rim to body (see Dwg. 12910321), Major defect. During the first half of a production shift and during the last half of a production shift, a body assembly shall be randomly selected for this test. From each body assembly, two (2) specimens of welded rim to body segments shall be taken at random. If any specimen fails to meet the requirement when tested in accordance with 4.5.2, the quantity of body assemblies which were welded during this shift between this weld strength test and the earlier weld strength test and (if applicable) shall be rejected. A weld strength test shall also be performed whenever an electrode is changed or dressed.

4.4.3.3 Spring embrittlement (see Dwg. 9344042), Major defect. Five (5) springs shall be randomly selected from each heat treatment lot for this test. If any spring fails to meet the requirement, the heat treatment lot shall be rejected. The test shall be performed as specified in 4.5.3.

4.4.3.4 Hardness of spring (see Dwg. 9344042), Major defect. Five (5) springs shall be randomly selected from each heat treatment lot for this test. If any spring fails to meet the requirement, the heat treatment lot shall be rejected. The test shall be performed as specified in 4.5.4.

4.4.3.5 Hardness of gasket (see Dwg. 9381614), Major defect. Five (5) gaskets shall be randomly selected from each lot for this test. If any gasket fails to meet the requirement, the lot shall be rejected. The test shall be performed as specified in 4.5.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

4.4.3.6 Air pressure.

4.4.3.6.1 Air pressure of unpainted cover assembly (see 3.6.1), Major defect. The cover assemblies shall be checked 100 percent. If any cover assembly fails to comply with the requirement, the cover assembly shall be rejected. The test shall be performed as specified in 4.5.6.1.

4.4.3.6.2 Air pressure of unpainted body assembly (body weldment) (see 3.6.2), Major defect. The body assemblies shall be checked 100 percent. If the body assembly fails to comply with the requirement, the body assembly shall be rejected. The test shall be performed as specified in 4.5.6.1.

4.4.3.6.3 Air pressure of painted container assembly (see Dwg. 12910318, 12910319 or 12910324 as applicable), Major defect. Container assemblies shall be selected in accordance with MIL-STD-1235, continuous sampling plan CSP-1, using Sample Frequency Code D with a value of i of 135 consecutive units. The test shall be performed as specified in 4.5.6.2.

4.4.3.7 Painted surface (see 3.4), Major defect. Sampling shall be in accordance with TT-C-490 and testing shall be in accordance with 4.5.7.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. and in 4.5. When Automated Acceptance Inspection Equipment is to be used, the provisions of MIL-A-70625 shall apply. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection. (see 6.4)

4.5.1 Tensile strength of body material and weld. The tensile strength shall be determined in accordance with ASTM-E8.

4.5.2 Weld strength of rim to body. The strength of the weld shall be determined in accordance with ASTM-E8.

4.5.3 Spring embrittlement. The spring shall be repeatedly stretched with increasing loads until it does not return to its original free height. That point shall indicate minimum distortion. Any unit which fractures prior to extension to minimum distortion shall be classed defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

4.5.4 Hardness of spring. The hardness of the spring shall be determined in accordance with ASTM-E18.

4.5.5 Hardness of gasket. The hardness shall be determined in accordance with ASTM-D2240.

4.5.6 Air pressure test.

4.5.6.1 Air pressure of unpainted cover assembly and unpainted body assembly. (Water immersion method) Subject the cover assembly and container body to the specified internal air pressure for the test time specified. For the cover assembly, apply the pressure when the cover assembly is assembled to a master body assembly (or its equivalent) equipped with a gasket. For the body assembly, apply the pressure when the body assembly is assembled to master cover (or equivalent) and gasket. The master cover and the master body assembly shall be provided with satisfactory means for applying and maintaining the pressure during the test and for showing evidence of leakage. Observation shall be made for the presence of bubbles. No bubbles (other than surface bubbles) shall be permitted. A cover assembly or body assembly which does not meet the requirements, shall be classed defective.

4.5.6.2 Air pressure of painted container assembly. Subject the painted container assembly to an air pressure test as specified in the applicable container assembly drawing. A container assembly which does not meet the requirement, shall be classed defective. When cover assemblies or body weldments (container bodies) are procured separately, the contractor shall submit for Government approval, the test procedure that will be followed to meet the applicable test requirement.

4.5.7 Painted surface. The painted container assembly shall be tested in accordance with TT-C-490.

5 PACKAGING

5.1 Packaging requirements. None required.

5.2 Packing. Packing shall be commercial. Propelling charge containers shall be prepared in accordance with ASTM-D3951.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

5.3 Marking. Shipping marking shall comply with ASTM-D3951 and the following additional instructions. No shipping marking shall be placed directly on the containers. Commercial shipping tags attached with wire shall be used unless otherwise specified. The following information shall be shown: Item name and model number, part number and revision, contract number, lot number and date, name and address of manufacturer. If containers are bundled, boxed or palletized, the gross weight and quantity shall be included. The above information may be placed on pallets or boxes by labeling or stenciling.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. This lightweight metal ammunition container is used for packing 155MM propelling charges for separate loaded artillery ammunition.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (See 2.1.1 and 2.2).

6.3 Submission of inspection equipment for design approvals. See MIL-A-48078. Submit designs as required to: Commander, U.S. Army Armament Research, Development and Engineering Center, ATTN: AMSMC-QAR-I (D), Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

6.4 Equivalent test methods. Prior approval of the Contracting Officer is required for use of equivalent test methods. A description of the proposed method should be submitted through the Contracting Officer to: Commander, U.S. Army Armament Research Development and Engineering Center, ATTN: AMSMC-QAR-Q (D), Picatinny Arsenal, NJ 07806-5000. This description should include but not be limited to the accuracy and precision of the method, test data demonstrating the accuracy and precision and drawings of any special equipment required.

6.5 Submission of alternative quality conformance provisions. Unless otherwise specified in the contract, proposed alternative quality conformance provisions will be submitted by the contractor for evaluation by the technical activity responsible for the preparation of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

6.6 Subject term (keyword listing).

Artillery
Packing
Pallet

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 8140 - A807)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-C-70740 (AR)	2. DOCUMENT DATE (YYMMDD) 15 July 1991

3. DOCUMENT TITLE
CONTAINER, AMMUNITION, LIGHTWEIGHT METAL FOR 155MM PROPELLING CHARGE

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (if applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME US ARMY ARDEC STANDARDIZATION OFFICE.	b. TELEPHONE (Include Area Code) (1) Commercial: (201) 724-6675 (2) AUTOVON: 880-6675
c. ADDRESS (Include Zip Code) ATTN: SMCAR-BAC-S PICATINNY ARSENAL, NJ 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

DD Form 1426, OCT 89 *Previous editions are obsolete.* 193/290

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.