MILITARY SPECIFICATION

DECELERATOR, RAM AIR PARTS AND CONTAINER ASSEMBLY

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE.

1.1 This specification contains requirements and provides quality assurance provisions for the fabrication of parts and the manufacture, assembly, and packing of the Ram Air Decelerator (RAD) for the M230 and M231 Grenade Fuzes.

2. APPLICABLE DOCUMENTS.

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	Ammunition, Standard Quality Assurance Provisions, General Specification for

FSC 1330

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn. DRSMC-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-331	Fuze and Fuze Components, Environmental and Performance Test for
MIL-STD-1167	Ammunition Data Cards
MIL-STD-1169	Packaging, Packing, and Marking for Shipment of Inert Ammunition Components

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

PRODUCT AND PACKAGE DRAWINGS

9345127	RAD Container Assembly
9345154	RAD Assembly Complete

(Copies of specifications, standards, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.3.1 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS.

3.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

those prescribed on the drawings to insure correct fit, assembly, and operation of the RAD. Any data (E.G., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative. The dimensions shown on the drawing apply at temperatures from 68°F to 70°F.

3.2 First Article. This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.3 Materials. Materials shall be as specified herein and on the applicable drawings.

3.4 RAD assemblies and parts. RAD assemblies and parts shall comply with all requirements specified on Drawings 9345127 and 9345154 and associated drawings and with all requirements specified in applicable specifications and standards.

3.4.1 RAD integrity. The RAD Assembly Complete shall not display any broken threads nor opening of the weave around any stitch greater than 1/8" square after being pressurized from atmospheric to 27 ± 2 psi in 13 ± 1 milliseconds.

3.5 Thermal shock. The RAD shall meet all the functional requirements of this specification after being subjected to Test 113.1 of MIL-STD-331.

3.6 Data requirements. The contractor shall generate data in accordance with the requirements of 4.5.3.

3.7 Workmanship. All parts and assemblies shall be free from burrs, chips, sharp edges, cracks, unblended radii, surface checks, blisters, excess flash, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any part nor shall parts be contaminated by the cleaning agents. Surface coating shall be continuous except for a few slight scratches not exposing base material. The loading and assembly operations shall be performed in a thorough, workmanlike manner consistent with the best practices of the industry. All required markings shall be neat and sharply defined.

Source: https://assist.dla.mil -- Downloaded: 2026Ø-26T04:29Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS.

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the government. The government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are made a part of this specification.

4.2 Classification of inspection. The inspection requirements specified herein are classed as follows:

a. First article inspection

b. Quality conformance inspection

4.3 First Article inspection.

4.3.1 Submission. The contractor shall submit a First Article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The First Article sample shall consist of the following items in sample quantities as indicated:

PART DESCRIPTION	DRAWING	QUANTITY
Plate, RAD	9333813	25
RAD Plate Subassembly	9345151	35
Plate, Lower RAD	9333815	25
Panel, Lower RAD	9345150	25
Panel Subassembly, Lower RAD	9345152	35
Scoop, Rubber	9345147	25
Scoop, Panel	9345146	25
Scoop Assembly	9345148	25
Panel Assembly, Lower RAD	9345153	35
Panel, Upper RAD	9345149	25
RAD Assembly, Complete	9345154	50
Packing Container, RAD	9345155	25
RAD Container Assembly	9345127	25

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 3	DRAWING NUMBER
	Decelerator, Ram Air		Listed below
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE INSPECTION METHOD
	Plate, RAD (Dwg. 9333813) Examination for Defects	25		3.4	4.4.2.1
	RAD Plate Subassembly (Dwg. 9345151) Examination for Defects	35		3.4	4.4.2.2
	Plate, Lower RAD (Dwg. 9333815) Examination for Defects	25		3.4	4.4.2.3
	Panel, Lower RAD (Dwg. 9345150) Examination for Defects	25		3.4	4.4.2.4
	Panel Subassembly, Lower RAD (Dwg. 9345152) Examination for Defects	35		3.4	4.4.2.5
	Scoop, Rubber (Dwg. 9345147) Examination for Defects	25		3.4	4.4.2.6

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

TABLE I. First Article Inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-70430 (AR)

PARAGRAPH	TITLE		SHEET 2 OF 3		DRAWING NUMBER
	Decelerator, Ram Air				Listed below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Scoop Panel (Dwg. 9345146)				
	Examination for Defects	25		3.4	4.4.2.7
	Scoop Assembly Dwg. 9345148)				
	Examination for Defects	25		3.4	4.4.2.8
	Panel Assembly, Lower RAD (Dwg. 9345153)				
	Examination for Defects	35		3.4	4.4.2.9
	Panel, Upper RAD (Dwg. 9345149)				
	Examination for Defects	25		3.4	4.4.2.10
	RAD Assembly, Complete (Dwg. 9345154)				
	Examination for Defects	50		3.4	4.4.2.11
	RAD Integrity	50		3.4.1	4.5.1
	Packing Container, RAD (Dwg. 9345155)				
	Examination for Defects	25		3.4	4.4.2.12

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 3 OF 3	DRAWING NUMBER
	Decelerator, Ram Air		Listed below
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	RAD Container Assembly (Dwg. 9345127)				
	Examination for Defects	25		3.4	4.4.2.13
	Thermal Shock	15		3.5	4.5.2

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078.

Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Plate, RAD		9333813
			NEXT HIGHER ASSEMBLY 9345151

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101	Center Hole Diameter		.40%	3.4	Gage
102	Flatness		.40%	3.4	Gage
103	Major Diameter		.40%	3.4	Gage
104	~~Full~~ Radius on Major Diameter		.40%	3.4	Gage
105	Minimum Flat		.40%	3.4	Gage
Minor					
201	Plate thickness		.65%	3.4	Gage
202	Evidence of Poor Workmanship		.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-70430 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	RAD Plate Subassembly		9345151
			NEXT HIGHER ASSEMBLY 9345152

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Push out load		.40%	3.4	Gage
Minor					
201	Evidence of poor workmanship		.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Plate, Lower RAD				9333815
					NEXT HIGHER ASSEMBLY 9345152
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101	Distance between tabs		.40%	3.4	Gage
102	Major diameter		.40%	3.4	Gage
103	True position between centerline of holes & outside diameter		.40%	3.4	Gage
104	Flatness		.40%	3.4	Gage
105	Presence of notch on radius		.40%	3.4	Visual
Minor					
201	Concentricity of outside diameter to center hole		.65%	3.4	Gage
202	Thickness of plate		.65%	3.4	Gage
203	Inside diameter		.65%	3.4	Gage
204	Poor workmanship		.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-70430 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Panel, Lower RAD				9345150
					NEXT HIGHER ASSEMBLY
					9345152
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101	Port diameter		.40%	3.4	Gage
102	Port location from center		.40%	3.4	Gage
Minor					
201	Lobe radius		.65%	3.4	Gage
202	Lobe length		.65%	3.4	Gage
203	Lobe radius location		.65%	3.4	Gage
204	Inside curvature		.65%	3.4	Gage
205	Poor workmanship		.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Panel Subassembly, Lower RAD		9345152
			NEXT HIGHER ASSEMBLY 9345153

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101	Excessive epoxy on upper plate outside diameter		100%	3.4	Visual
Minor					
201	Evidence of poor workmanship		.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-70430 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.6	Scoop, Rubber		9345147
			NEXT HIGHER ASSEMBLY 9345148

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major	None Defined.				
Minor					
201	Thickness of scoop		.65%	3.4	Gage
202	Width of scoop		.65%	3.4	Gage
203	Height of scoop		.65%	3.4	Gage
204	Evidence of poor workmanship		.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-70430 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Scoop, Panel	1 OF 1	9345146
			NEXT HIGHER ASSEMBLY: 9345148

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE / INSPECTION METHOD
Critical	None Defined.				
Major	None Defined.				
Minor					
201	Scoop length		.65%	3.4	Gage
202	Scoop width		.65%	3.4	Gage
203	Evidence of poor workmanship		.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-70430 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Scoop Assembly	1 OF 1	9345148
			NEXT HIGHER ASSEMBLY 9345153

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101	Thread size		.40%	3.4	Gage
102	Number of stitches per inch		.40%	3.4	Visual
Minor					
201	Wrong seam type		.65%	3.4	Visual
202	Stitch location		.65%	3.4	Visual
203	Poor workmanship		.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Panel Assembly, Lower RAD				9345153
					NEXT HIGHER ASSEMBLY
					9345154
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101	Thread size		.40%	3.4	Gage
102	Number of stitches per inch		.40%	3.4	Visual
Minor					
201	Wrong seam type		.65%	3.4	Visual
202	Poor workmanship		.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-70430 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.10	Panel, Upper RAD		9345149
			NEXT HIGHER ASSEMBLY 9345154

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major	None Defined.				
Minor					
201	Lobe radius		.65%	3.4	Gage
202	Width of lobe		.65%	3.4	Gage
203	Lobe length		.65%	3.4	Gage
204	Diameter of lobe radius center		.65%	3.4	Gage
205	Blend radius		.65%	3.4	Gage
206	Evidence of poor workmanship		.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-Jan-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.11	RAD Assembly, Complete				9345154
					NEXT HIGHER ASSEMBLY 9345127
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101	Wrong stitch type (straight stitch)		.40%	3.4	Visual
102	Number of stitches per inch (straight stitch)		.40%	3.4	Visual
103	Thread size (straight stitch)		.40%	3.4	Gage
104	Wrong stitch type (overlock stitch)		.40%	3.4	Visual
105	Number of stitches per inch (overlock stitch)		.40%	3.4	
106	Thread size (overlock stitch)		.40%	3.4	Gage
107	Location of straight stitch from edge		.40%	3.4	Visual
108	Location of overlock stitch from edge		.40%	3.4	Visual
109	Minimum gap between straight and overlock stitches		.40%	3.4	Visual
110	Excessive stitched pleats on upper RAD panel		.40%	3.4	Visual
111	Missed stitch		.40%	3.4	Visual
112	RAD integrity	32		3.4.1	4.5.1
Minor					
201	Poor workmanship		.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.12	Packing Container, RAD				9345155
					NEXT HIGHER ASSEMBLY
					9345127
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Location of locking projection from inside bottom of cup		.40%	3.4	Gage
102	Inside diameter of locking projections		.40%	3.4	Gage
103	Material thickness of lip		.40%	3.4	Gage
104	Material thickness at bottom of cup		.40%	3.4	Gage
105	Material thickness of locking projection		.40%	3.4	Gage
Minor					
201	Evidence of poor workmanship		.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.13	RAD Container Assembly				9345127
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Thermal Shock	6		3.5	4.5.2
Major					
101	Improper folding	(a)	.40%	3.4	Visual
Minor					
201	Poor workmanship		.65%	3.7	Visual

NOTES:
(a) Special Inspection Level S-3 of MIL-STD-105D.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the Quality Conformance Inspection Tables starting with 4.4.2.1.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in "Paragraph Reference/Inspection Method" column in the tables starting with 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and Section 6.5 herein. The contractor shall submit all inspection equipment designs to the government for evaluation and approval prior to fabrication of such equipment.

4.5 Test methods and procedures.

4.5.1 RAD integrity test. The RAD Assembly Complete shall be brought to an internal pressure of 27.0 ± 2 psi within 13.0 ± 1.0 milliseconds by pressurizing a lecture bottle (having an internal volumn of 27.5 ± 0.5 cu. in.) to 490 ± 10 psi and exhausting through a solenoid valve of sufficient capacity. In preparation for this test, it will be required to machine the center of the Upper RAD Plate (P/N 9349235) of the RAD Assembly Complete in order to accommodate a large input orifice (a 1/8" pipe fitting is sufficient). In addition, provisions shall be made to mount a suitably sensitive pressure transducer to the Lower RAD Panel (P/N 9345150) along the axis of one lobe at a distance of 2.0" ± 0.5" from center to allow for internal pressure measurements.

A sample consisting of 0.1% of a production lot shall be randomly selected and subjected to this test. Any assembly that fails to meet the requirements shall be considered a reject. A single failure shall reject the lot. Any assembly subjected to this test shall not be returned to the production lot.

4.5.2 Thermal shock. A random sample of RAD Container Assemblies shall be selected from each production lot and subjected to the Thermal Shock Test 113 of MIL-STD-331. The RADs shall not require special preparations prior to the test.

Operability of the RAD Container Assembly shall be established by removing the RAD from its container and manually unfolding the packaged assembly to its near final configuration.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:29Z
Check the source to verify that this is the currentversion before use.

Upon complete opening, the RAD shall be visually inspected for stitches, failures, deterioration of fabric and urethane coating, and separation of the upper and lower RAD plates. Separated plates, failed fabric and stitching shall constitute a failure. A single failure shall reject the lot.

4.5.3 Data requirements. The contractor shall submit a quality inspection test demonstration and evaluation report in accordance with Data Item Description DI-R-1721 and DI-R-1724 giving the detailed test results.

5. PACKAGING.

5.1 Packaging and marking. Packaging, packing, and marking shall be in accordance with MIL-STD-1169, Level B. Moisture proofing is required.

5.2 Ammunition data cards. Data card information shall be as specified in MIL-STD-1167.

6. NOTES.

6.1 Intended use. The Ram Air Decelerator (RAD) provides deceleration and stabilization for the grenades used in the 2.75 Inch Rocket Multi-Purpose Submunition (MPSM).

6.2 Ordering data. See MIL-A-48078.

6.3 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL), the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL incorporated into the contract. When the provisions of DAR 7-104.9 (n) (2) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification is cited in the following paragraphs.

Paragraph No.	Data Requirements Title	Applicable DID No.
4.5.3	Quality Inspection Defect Report	DI-R-1721
4.5.3	Quality Inspection Test Demonstration and Evaluation Report	DI-R-1724

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

(Data item descriptions related to this specification, and identified in Section 6, will be approved and listed as such in DoD 5000.19L., Volume II, AMSDL. Copies of data item descriptions required by the contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)

6.4 First Article. When a First Article is required for inspection and approval, see 3.2 and 4.3.

6.5 Submission of inspection equipment for design approvals. See 6.2 of MIL-A-48078. Submit designs as required to Commander, Armament Research and Development Center, U.S. Army Armament Munitions and Chemical Command, ATTN: DRSMC-QAF-I(D), Dover, NJ 07801.

6.6 Source control and specification control drawings. Certification of conformance from the supplier certifying that the item complies with the drawing requirements shall be provided to the government representative.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1330-A189)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:29Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form f submitting comments and suggestions for improvements. All users of military standardization documents are invited t suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAP* mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpret too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are be considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification specification requirements on current contracts. Comments submitted on this form do not constitute or imply author to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARMAMENT RESEARCH & DEVELOPMENT CENTER
ATTN: DRSMC-QA
DOVER, NJ 07801

NO
NEC
IF
IN
UNITE

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-D-70430	DECELERATOR, RAM AIR PARTS AND CONTAINER ASSEMBLY

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:29Z
Check the source to verify that this is the current version before use.